



Weatherford®

**ARRAY INDUCTION
SHALLOW FOCUSED
ELECTRIC LOG**

COMPANY **WHITING PETROLEUM CORP.**
 WELL **CANDELARIO 1928 #101**
 FIELD **WILDCAT**
 PROVINCE/COUNTY **HARDING**
 COUNTRY/STATE **U.S.A. / NEW MEXICO**
 LOCATION **1660' FSL & 1660' FEL**
 PERMIT NUMBER **SEC 10: TWN 19N RNG 28E**

SEC	TWP	RGE	Other Services	
Latitude	35.88815	MPD/MDN	MML	
Longitude	-103.9503417	MSS	SGS	
API Number	30-021-20659	CMI		

Permanent Datum GL, Elevation 5519 feet	Elevations:	feet
Log Measured From KB	KB	5531.00
Drilling Measured From KB @ 12 FEET	DF	5529.00
	GL	5519.00

Date	08-OCT-2014	
Run Number	ONE	
Service Order	7036-99982588	
Depth Driller	2989.00	feet
Depth Logger	2986.00	feet
First Reading	2982.66	feet
Last Reading	772.00	feet
Casing Driller	771.00	feet
Casing Logger	772.00	feet
Bit Size	8.750	inches
Hole Fluid Type	WBM	
Density / Viscosity	8.70 lb/USg	56.00 CP
PH / Fluid Loss	10.00	8.70 ml/30Min
Sample Source	FLOWLINE	
Rm @ Measured Temp	1.61 @ 75.0	ohm-m
Rmf @ Measured Temp	1.29 @ 75.0	ohm-m
Rmc @ Measured Temp	1.93 @ 75.0	ohm-m
Source Rmf / Rmc	CALC	CALC
Rm @ BHT	1.34 @ 91.0	ohm-m
Time Since Circulation	4 HOURS	
Max Recorded Temp	91.00	deg F
Equipment / Base	13096	LIB
Recorded By	DEREK CARTER	
Witnessed By	DAVID ABOIT	MIKE RAINES
JOB #	LB14-309	



Weatherford®

**COMPACT PHOTO DENSITY
COMPENSATED NEUTRON**

COMPANY **WHITING PETROLEUM CORP.**
 WELL **CANDELARIO 1928 #101**
 FIELD **WILDCAT**
 PROVINCE/COUNTY **HARDING**
 COUNTRY/STATE **U.S.A. / NEW MEXICO**
 LOCATION **1660' FSL & 1660' FEL**
 PERMIT NUMBER **SEC 10^c TWN 19N RNG 28E**

SEC	TWP	RGE	Other Services	
Latitude	35.88815		MAI/MFE	MML
Longitude	-103.9503417		MSS	SGS
API Number	30-021-20659		CMI	

Permanent Datum GL, Elevation 5519 feet
 Log Measured From KB
 Drilling Measured From KB @ 12 FEET

Elevations:	feet
KB	5531.00
DF	5529.00
GL	5519.00

Date	08-OCT-2014	
Run Number	ONE	
Service Order	7036-99982588	
Depth Driller	2989.00	feet
Depth Logger	2986.00	feet
First Reading	2931.33	feet
Last Reading	0.00	feet
Casing Driller	771.00	feet
Casing Logger	772.00	feet
Bit Size	8.750	inches
Hole Fluid Type	WBM	
Density / Viscosity	8.70 lb/USg	56.00 CP
PH / Fluid Loss	10.00	8.70 ml/30Min
Sample Source	FLOWLINE	
Rm @ Measured Temp	1.61 @ 75.0	ohm-m
Rmf @ Measured Temp	1.29 @ 75.0	ohm-m
Rmc @ Measured Temp	1.93 @ 75.0	ohm-m
Source Rmf / Rmc	CALC	CALC
Rm @ BHT	1.34 @ 91.0	ohm-m
Time Since Circulation	4 HOURS	
Max Recorded Temp	91.00	deg F
Equipment / Base	13096	LIB
Recorded By	DEREK CARTER	
Witnessed By	DAVID ABBOTT	MIKE RAINES
JOB #	LB14-309	



RADIAL CEMENT BOND GAMMA-RAY/CCL LOG

Company WHITING PETROLEUM CORP.
 Well CANDELARIO 1928#101
 Field WILDCAT
 County HARDING
 State NM

Company WHITING PETROLEUM CORP.

Well CANDELARIO 1928#101

Field WILDCAT

County HARDING State NM

Location: API #: 30-021-20659

1660' FSL & 1660' FEL

SEC 10 TWP 19 N RGE 28E

Other Services

CNL

Elevation

Permanent Datum G.L. Elevation 5519'

Log Measured From K.B.12' ABOVE PERM DATUM

Drilling Measured From K.B.

K.B. 5531'

D.F. 5529'

G.L. 5519'

Date	10-14-14
Run Number	ONE
Depth Driller	2989'
Depth Logger	2938'
Bottom Logged Interval	2924'
Top Log Interval	GL
Open Hole Size	N/A
Type Fluid	WATER
Density / Viscosity	N/A
Max. Recorded Temp.	N/A
Estimated Cement Top	NA
Time Well Ready	ROA
Time Logger on Bottom	9:00 AM
Equipment Number	TRK #49
Location	LEVELLAND TX
Recorded By	R.D. MOTHERAL
Witnessed By	MR. HOLCOMB

Borehole Record

Tubing Record

Run Number	Bit	From	To	Size	Weight	From	To

Casing Record	Size	Wgt/Ft	Top	Bottom
Surface String	9.625"	36#	0'	771'
Prot. String				
Production String	5.5"	15.5#	0'	2989'
Liner				

>>> Fold Here >>>