



FracCAT Treatment Report

Well : Hazen 1928 #24-1
Field : Bravo Dome, west
Formation : Tubb Sand

Well Location :
County : Harding
State : new mexico
Country : United States

Prepared for
Client : Whiting Petroleum Corporation
Client Rep : Robert McNaughton
Proposal No : 1
Date Prepared : 07/04/2014

Prepared by
Name : Claudia Navarro
Division : Schlumberger
Phone : 432-742-5417
Service Point : HOBBS
Fax Number : +1 (575) 393 2132

Comments : Stage1

Disclaimer Notice

This information is presented in good faith, but no warranty is given by and Schlumberger assumes no liability for advice or recommendations made concerning results to be obtained from the use of any product or service. The results given are estimates based on calculations produced by a computer model including various assumptions on the well, reservoir and treatment. The results depend on input data provided by the Operator and estimates as to unknown data and can be no more accurate than the model, the assumptions and such input data. The information presented is Schlumberger's best estimate of the actual results that may be achieved and should be used for comparison purposes rather than absolute values. The quality of input data, and hence results, may be improved through the use of certain tests and procedures which Schlumberger can assist in selecting.

The Operator has superior knowledge of the well, the reservoir, the field and conditions affecting them. If the Operator is aware of any conditions whereby a neighboring well or wells might be affected by the treatment proposed herein it is the Operator's responsibility to notify the owner or owners of the well or wells accordingly.

Prices quoted are estimates only and are good for 30 days from the date of issue. Actual charges may vary depending upon time, equipment, and material ultimately required to perform these services.

Freedom from infringement of patents of Schlumberger or others is not to be inferred.

Section 1: Well Description

Deviated Hole: NO
Treating Down: CASING
Flush Volume to 2934.0 ft is 69.8 bbl

Casing			
OD (in)	Weight (lb/ft)	ID (in)	Depth (ft)
5.500	15.5	4.950	3173.0

Section 2: Perforations

Perforations						
Top MD (ft)	Top TVD (ft)	Bottom MD (ft)	Bottom TVD (ft)	Shot Density (shot/ft)	Number	Diameter (in)
2898.0	2898.0	2912.0	2912.0	6.00	84	0.32
2920.0	2920.0	2926.0	2926.0	6.00	36	0.32
2934.0	2934.0	2942.0	2942.0	6.00	48	0.32

Section 3: Fluid Description

Fluid Name: WF140			
Additive Name	Additive Type	Solid Conc (lb/mgal)	Liquid Conc (gal/mgal)
J580, Gelling Agent	GELLINGAGT	40.0	
J218, Breaker	BREAKER	2.0	
B244B, Microbiocide	BIOCIDE		0.2
L071, Temporary Clay Stabilizer	CLAYSTABILIZ		1.0
L065, Scale Inhibitor	INHIBITORAID		0.5

Fluid Name: WF140 [CO2 65Q]			
Additive Name	Additive Type	Solid Conc (lb/mgal)	Liquid Conc (gal/mgal)
J580, Gelling Agent	GELLINGAGT	40.0	
J218, Breaker	BREAKER	2.0	
F109, Foaming Agent	SURFACTANT		4.0
F112, EZEFL0 Surfactant	SURFACTANT		2.0
B244B, Microbiocide	BIOCIDE		0.2
L071, Temporary Clay Stabilizer	CLAYSTABILIZ		1.0
J475, EB-CLEAN Breaker	BREAKERENCAP	1.0	
L065, Scale Inhibitor	INHIBITORAID		0.5

Section 4: Designed Pump Sched. - Ramp

Designed Pump Schedule Ramp									
Step #	Step Name	Slurry Volume (bbl)	Pump Rate (bbl/min)	Pump Time (min)	Fluid Name	Fluid Volume (gal)	Prop Name	Prop Conc (PPA)	Prop Mass (lb)
1	PrePAD	47.6	30.0	1.6	WF140	2000		0.0	0
2	PAD	45.8	10.5	4.4	WF140 [CO2 65Q]	1925		0.0	0
3	2.0 PPA	20.1	11.8	1.7	WF140 [CO2 65Q]	700	SinterLite Bauxite 16/30	5.7	4000
4	4.0 PPA	29.5	13.0	2.3	WF140 [CO2 65Q]	875	SinterLite Bauxite 16/30	11.4	10000
5	6.0 PPA	51.3	17.7	2.9	WF140 [CO2 65Q]	1500	SinterLite Bauxite 16/30	12.0	18000

Designed Pump Schedule Ramp									
Step #	Step Name	Slurry Volume (bbl)	Pump Rate (bbl/min)	Pump Time (min)	Fluid Name	Fluid Volume (gal)	Prop Name	Prop Conc (PPA)	Prop Mass (lb)
6	8.0 PPA	26.9	21.9	1.2	WF140 [CO2 65Q]	780	SinterLite Bauxite 16/30	12.3	9600
7	Flush	69.8	30.0	2.3	WF140	2933		0.0	0

Designed CO2 Pump Schedule Ramp		
Step #	Step Name	CO2 Rate (bbl/min)
1	PrePAD	0.0
2	PAD	15.7
3	2.0 PPA	14.7
4	4.0 PPA	13.7
5	6.0 PPA	10.3
6	8.0 PPA	7.2
7	Flush	0.0

Designed Ramp Totals				
Slurry (bbl)	Pump Time (min)	Clean Fluid (gal)	Proppant (lb)	CO2 (bbl)
291.0	16.4	10713	41600	163.4

Section 5: As Measured Pump Schedule

As Measured Pump Schedule										
Step #	Step Name	Slurry Volume (bbl)	Slurry Rate (bbl/min)	Pump Time (min)	Fluid Name	Fluid Volume (gal)	Proppant Name	Max Prop Conc (PPA)	Prop Conc (PPA)	Prop Mass (lb)
1	PrePAD	66.4	17.6	4.3	WF140	2785		0.0	0.0	0
2	PAD	45.8	9.9	4.9	WF140 [CO2 65Q]	1933		0.0	0.0	0
3	2.0 PPA	20.1	10.9	1.8	WF140 [CO2 65Q]	717	SinterLite Bauxite 16/30	5.8	2.3	3443
4	4.0 PPA	29.5	12.2	2.4	WF140 [CO2 65Q]	891	SinterLite Bauxite 16/30	11.6	8.9	9464
5	6.0 PPA	51.3	16.4	3.1	WF140 [CO2 65Q]	1511	SinterLite Bauxite 16/30	12.1	3.4	17624
6	8.0 PPA	36.6	19.9	1.8	WF140 [CO2 65Q]	1160	SinterLite Bauxite 16/30	12.4	0.0	10484
7	Flush	68.3	19.9	3.5	WF140	2882	SinterLite Bauxite 16/30	0.0	0.0	19

Stage Pressures & Rates						
Step #	Step Name	Average Slurry Rate (bbl/min)	Maximum Slurry Rate (bbl/min)	Average Treating Pressure (psi)	Maximum Treating Pressure (psi)	Minimum Treating Pressure (psi)
1	PrePAD	17.6	20.0	702	1563	19
2	PAD	9.9	20.0	1098	1214	996
3	2.0 PPA	10.9	12.1	1177	1195	1124
4	4.0 PPA	12.2	15.7	1122	1185	1062
5	6.0 PPA	16.4	17.6	1014	1117	873
6	8.0 PPA	19.9	20.0	890	945	828
7	Flush	19.9	20.0	949	1029	68

As Measured CO2 Pump Schedule				
Step #	Step Name	CO2 Volume (bbl)	CO2 Rate (bbl/min)	Injection Rate (bbl/min)
1	PrePAD	14.0	3.3	20.9

As Measured CO2 Pump Schedule

Step #	Step Name	CO2 Volume (bbl)	CO2 Rate (bbl/min)	Injection Rate (bbl/min)
2	PAD	65.3	13.0	23.0
3	2.0 PPA	25.5	13.9	24.8
4	4.0 PPA	31.0	13.0	25.2
5	6.0 PPA	31.8	10.3	26.6
6	8.0 PPA	12.9	7.0	26.9
7	Flush	16.5	7.0	24.8

As Measured Totals

Slurry (bbl)	Pump Time (min)	Clean Fluid (gal)	Proppant (lb)
317.9	21.8	11878	41034

Average Treating Pressure: 953 psi
 Maximum Treating Pressure: 1563 psi
 Minimum Treating Pressure: 19 psi
 Average Injection Rate: 24.3 bbl/min
 Maximum Injection Rate: 27.4 bbl/min
 Average Horsepower: 368.6 hhp
 Maximum Horsepower: 598.3 hhp
 Maximum Prop Concentration: 12.4 PPA

Section 6: Material Balance

Material Balance	
Material Name	Quantity Pumped
WF140	5667 gal
WF140 [CO2 65Q]	6210 gal
SinterLite Bauxite 16/30	41034 lb
J580, Gelling Agent	0 lb
J218, Breaker	0 lb
B244B, Microbiocide	0 gal
L071, Temporary Clay Stabilizer	0 gal
L065, Scale Inhibitor	0 gal
F109, Foaming Agent	0 gal
F112, EZEFL0 Surfactant	0 gal
J475, EB-CLEAN Breaker	0 lb
CO2	197.1 bbl

Section 7: Job Messages


Message Log							
#	Time	Message	Treating Pressure (psi)	Annulus Pressure (psi)	Total Slurry (bbl)	Slurry Rate (bbl/min)	Prop. Conc. (PPA)
1	17:50:27	Prime Up SPF-37974	111	-3750	0.0	5.1	0.0
2	17:52:35	Prime Up SPF-26339	96	-3750	0.0	4.9	0.0
3	17:55:04	Set Brakes	70	-3750	0.0	3.4	0.0
4	17:55:31	Knock Off Prime Up Hose	69	-3750	0.0	0.0	0.0
5	17:56:40	Area Clear	66	-3750	0.0	0.0	0.0
6	17:57:42	High PSI Test	5347	-3750	0.0	0.0	0.0
7	18:01:13	Leak on Line	8	-3750	0.0	0.0	0.0
8	18:03:23	Low PSI Test	3054	-3750	0.0	1.0	0.0
9	18:04:03	High PSI Test	4497	-3750	0.0	0.0	0.0
10	18:04:25	Pressure Test Lines	4491	-3750	0.0	0.0	0.0
11	18:04:30	Pressure Test Ok	4491	-3750	0.0	0.0	0.0
12	18:05:35	Open Wellhead	439	-3750	0.0	0.0	0.0
13	18:06:48	Start PrePAD Automatically	20	-3750	0.0	17.6	0.0
14	18:06:48	Start Propped Frac Automatically	20	-3750	0.0	17.6	0.0
15	18:06:48	Start Stage 1 Automatically	20	-3750	0.0	17.6	0.0
16	18:06:48	Started Pumping	20	-3750	0.0	17.6	0.0
17	18:07:26	Activated Extend Stage	19	-3750	11.1	17.5	0.0
18	18:11:05	Deactivated Extend Stage	1247	-3750	66.4	19.9	0.0
19	18:11:05	Start PAD Manually	1247	-3750	66.4	19.9	0.0
20	18:11:27	Stage at Perfs: PrePAD	1047	-3750	70.9	9.4	0.0
21	18:14:35	Stage at Perfs: PAD	1099	-3750	99.7	9.1	0.0
22	18:15:58	Start 2.0 PPA Automatically	1133	-3750	112.3	9.1	0.0
23	18:15:58	Started Pumping Prop	1133	-3750	112.3	9.1	0.0
24	18:17:48	Start 4.0 PPA Automatically	1175	-3750	132.4	12.1	5.3
25	18:19:13	Stage at Perfs: 2.0 PPA	1089	-3750	149.5	12.1	11.3
26	18:20:12	Start 6.0 PPA Automatically	1122	-3750	162.0	15.8	9.3
27	18:21:03	Stage at Perfs: 4.0 PPA	1028	-3750	175.9	16.3	11.9
28	18:23:19	Start 8.0 PPA Automatically	951	-3750	213.2	19.0	11.3
29	18:23:23	Activated Extend Stage	936	-3750	214.5	19.6	10.8
30	18:23:40	Stage at Perfs: 6.0 PPA	940	-3750	220.1	19.9	12.2
31	18:25:09	Deactivated Extend Stage	828	-3750	249.7	20.0	-0.0
32	18:25:09	Start Flush Manually	828	-3750	249.7	20.0	-0.0
33	18:26:52	Stage at Perfs: 8.0 PPA	938	-3750	283.9	19.9	-0.0
34	18:28:43	Shutdown - ISIP	796	-3750	317.9	0.0	-0.0
35	18:33:43	5 MIN	730	-3750	317.9	0.0	-0.1
36	18:38:43	10 MIN	706	-3750	317.9	0.0	-0.0
37	18:43:43	15 MIN	690	-3750	317.9	0.0	-0.0
38	18:44:18	Close Wellhead	688	-3750	317.9	0.0	-0.0
39	18:47:56	Bleed Off lines	67	-3750	317.9	0.0	-0.1
40	18:47:59	Stopped Pumping Prop	64	-3750	317.9	0.0	-0.1

FracCAT*

Closure Pressure = 2120 psi
Whiting Petroleum Corporation
Hazen 1928 #24-1
06-03-2014

Nolte Smith Post Job Plot

— Net Pressure



© Schlumberger 1994-2012

Schlumberger

FracCAT*

PRC Post Job Plot

Tr. Press Slurry Rate CO₂ RATE
Prop Con

Whiting Petroleum Corporation
Hazen 1928 #24-1
06-03-2014

