Office District Energy, Minerals and Natural Resources	- F - A- A- A- A- A
1406 N. W 1 P 17 11 N. N. 4 000 40	May 27, 2004
1625 N. French Dr., Hobbs, NM 88240	WELL API NO. 30-007-20693
District II 1301 W. Grand Ave., Artesia, NM 88210 OIL CONSERVATION DIVISION	7. Indicate Type of Lease
District III 1220 South St. Francis Dr	STATE FEE
1000 Rio Brazos Rd., Aztec, NM 87410 District IV Santa FG NM 87505	7. State Oil & Gas Lease No.
1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 2005 APR 27 87505 SUNDRY NOTICES AND REPORTS ON WELLS	
87505 (UND THE TOTAL ON THE CONTROL	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	VPR A
PROPOSALS.)	8. Well Number 247
1. Type of Well: Oil Well Gas Well Other Coalbed Methane	
2. Name of Operator	9. OGRID Number
EL PASO E & P COMPANY, L.P. 3. Address of Operator	10. Pool name or Wildcat
P.O. BOX 190, RATON, NM 87740	10. Foot hame of Wildcat
4. Well Location	
Unit Letter I : 2099 feet from the South line and 334	
Section 23 Township 31N Range 19E NMP	
11. Elevation (Show whether DR, RKB, RT, GR, etc 8,280' (GL)	
8,280' (GL) Pit or Below-grade Tank Application or Closure	
1	
Pit Liner Thickness: mil Below-Grade Tank: Volumebbls; Construction Material	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WOR	
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DR	ILLING OPNS.⊠ PANDA □
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN	IT JOB
	<u> </u>
OTHER: OTHER: OTHER:	nd give pertinent dates including estimated date
13. Describe proposed or completed operations. (Clearly state all pertinent details, as	
 Describe proposed or completed operations. (Clearly state all pertinent details, ar of starting any proposed work). SEE RULE 1103. For Multiple Completions: A 	
 Describe proposed or completed operations. (Clearly state all pertinent details, are of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 04/18/06 Spud @ 7:30 a.m. Drill 11" surface hole to 318'. Run 11 jts. of 8 5/8", 2 	ttach wellbore diagram of proposed completion 24#, J55 ST & C casing at 309'.
 13. Describe proposed or completed operations. (Clearly state all pertinent details, are of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 04/18/06 Spud @ 7:30 a.m. Drill 11" surface hole to 318'. Run 11 jts. of 8 5/8", 2 Halliburton mixed and pumped 100 sx Midcon II cement, 14 ppg, yield 1.4 	ttach wellbore diagram of proposed completion 24#, J55 ST & C casing at 309'.
 Describe proposed or completed operations. (Clearly state all pertinent details, are of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 04/18/06 Spud @ 7:30 a.m. Drill 11" surface hole to 318'. Run 11 jts. of 8 5/8", 2 	ttach wellbore diagram of proposed completion 24#, J55 ST & C casing at 309'.
 13. Describe proposed or completed operations. (Clearly state all pertinent details, are of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 04/18/06 Spud @ 7:30 a.m. Drill 11" surface hole to 318'. Run 11 jts. of 8 5/8", 2 Halliburton mixed and pumped 100 sx Midcon II cement, 14 ppg, yield 1.4 WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes. 	ttach wellbore diagram of proposed completion 24#, J55 ST & C casing at 309'. 66. Circulated 8 bbls of cement to surface.
 13. Describe proposed or completed operations. (Clearly state all pertinent details, at of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 04/18/06 Spud @ 7:30 a.m. Drill 11" surface hole to 318'. Run 11 jts. of 8 5/8", 2 Halliburton mixed and pumped 100 sx Midcon II cement, 14 ppg, yield 1.4 WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes. 04/19/06 Drill 7 7/8" hole from 318' - 2,620'. Reached TD at 2,620' at 11:30 a.m. 	ttach wellbore diagram of proposed completion 24#, J55 ST & C casing at 309'. 66. Circulated 8 bbls of cement to surface.
 13. Describe proposed or completed operations. (Clearly state all pertinent details, are of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 04/18/06 Spud @ 7:30 a.m. Drill 11" surface hole to 318'. Run 11 jts. of 8 5/8", 2 Halliburton mixed and pumped 100 sx Midcon II cement, 14 ppg, yield 1.4 WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes. 04/19/06 Drill 7 7/8" hole from 318' - 2,620'. Reached TD at 2,620' at 11:30 a.m MIRU Patterson and log well. Logger's TD at 2,620'. 	ttach wellbore diagram of proposed completion 24#, J55 ST & C casing at 309'. 66. Circulated 8 bbls of cement to surface.
 13. Describe proposed or completed operations. (Clearly state all pertinent details, are of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 04/18/06 Spud @ 7:30 a.m. Drill 11" surface hole to 318'. Run 11 jts. of 8 5/8", 2 Halliburton mixed and pumped 100 sx Midcon II cement, 14 ppg, yield 1.4 WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes. 04/19/06 Drill 7 7/8" hole from 318' - 2,620'. Reached TD at 2,620' at 11:30 a.m MIRU Patterson and log well. Logger's TD at 2,620'. Run 63 jts 5½", 15.5 #, J-55 LT & C casing at 2,586'. 	ttach wellbore diagram of proposed completion 24#, J55 ST & C casing at 309'. 66. Circulated 8 bbls of cement to surface.
 13. Describe proposed or completed operations. (Clearly state all pertinent details, are of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 04/18/06 Spud @ 7:30 a.m. Drill 11" surface hole to 318'. Run 11 jts. of 8 5/8", 2 Halliburton mixed and pumped 100 sx Midcon II cement, 14 ppg, yield 1.4 WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes. 04/19/06 Drill 7 7/8" hole from 318' - 2,620'. Reached TD at 2,620' at 11:30 a.m MIRU Patterson and log well. Logger's TD at 2,620'. 	ttach wellbore diagram of proposed completion 24#, J55 ST & C casing at 309'. 66. Circulated 8 bbls of cement to surface.
 13. Describe proposed or completed operations. (Clearly state all pertinent details, are of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 04/18/06 Spud @ 7:30 a.m. Drill 11" surface hole to 318'. Run 11 jts. of 8 5/8", 2 Halliburton mixed and pumped 100 sx Midcon II cement, 14 ppg, yield 1.4 WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes. 04/19/06 Drill 7 7/8" hole from 318' - 2,620'. Reached TD at 2,620' at 11:30 a.m MIRU Patterson and log well. Logger's TD at 2,620'. Run 63 jts 5½", 15.5 #, J-55 LT & C casing at 2,586'. 	ttach wellbore diagram of proposed completion 24#, J55 ST & C casing at 309'. 66. Circulated 8 bbls of cement to surface.
 13. Describe proposed or completed operations. (Clearly state all pertinent details, at of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 04/18/06 Spud @ 7:30 a.m. Drill 11" surface hole to 318'. Run 11 jts. of 8 5/8", 2 Halliburton mixed and pumped 100 sx Midcon II cement, 14 ppg, yield 1.4 WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes. 04/19/06 Drill 7 7/8" hole from 318' - 2,620'. Reached TD at 2,620' at 11:30 a.m MIRU Patterson and log well. Logger's TD at 2,620'. Run 63 jts 5½", 15.5 #, J-55 LT & C casing at 2,586'. HES mixed and pumped 458 sks Midcon II cement. Circulated 24 bbls of 	ttach wellbore diagram of proposed completion 24#, J55 ST & C casing at 309'. 66. Circulated 8 bbls of cement to surface.
 13. Describe proposed or completed operations. (Clearly state all pertinent details, are of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 04/18/06 Spud @ 7:30 a.m. Drill 11" surface hole to 318'. Run 11 jts. of 8 5/8", 2 Halliburton mixed and pumped 100 sx Midcon II cement, 14 ppg, yield 1.4 WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes. 04/19/06 Drill 7 7/8" hole from 318' - 2,620'. Reached TD at 2,620' at 11:30 a.m MIRU Patterson and log well. Logger's TD at 2,620'. Run 63 jts 5½", 15.5 #, J-55 LT & C casing at 2,586'. 	24#, J55 ST & C casing at 309'. 56. Circulated 8 bbls of cement to surface. cement to pit.
13. Describe proposed or completed operations. (Clearly state all pertinent details, at of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 04/18/06 Spud @ 7:30 a.m. Drill 11" surface hole to 318'. Run 11 jts. of 8 5/8", 2 Halliburton mixed and pumped 100 sx Midcon II cement, 14 ppg, yield 1.4 WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes. 04/19/06 Drill 7 7/8" hole from 318' - 2,620'. Reached TD at 2,620' at 11:30 a.m MIRU Patterson and log well. Logger's TD at 2,620'. Run 63 jts 5 ½", 15.5 #, J-55 LT & C casing at 2,586'. HES mixed and pumped 458 sks Midcon II cement. Circulated 24 bbls of I hereby certify that the information above is true and complete to the best of my knowledgrade tank has been/will be constructed or closed according to NMOCD guidelines □, a general permit □	ttach wellbore diagram of proposed completion 24#, J55 ST & C casing at 309'. 66. Circulated 8 bbls of cement to surface. cement to pit. ge and belief. I further certify that any pit or below- lor an (attached) alternative OCD-approved plan .
13. Describe proposed or completed operations. (Clearly state all pertinent details, at of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 04/18/06 Spud @ 7:30 a.m. Drill 11" surface hole to 318'. Run 11 jts. of 8 5/8", 2 Halliburton mixed and pumped 100 sx Midcon II cement, 14 ppg, yield 1.4 WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes. 04/19/06 Drill 7 7/8" hole from 318' - 2,620'. Reached TD at 2,620' at 11:30 a.m MIRU Patterson and log well. Logger's TD at 2,620'. Run 63 jts 5 ½", 15.5 #, J-55 LT & C casing at 2,586'. HES mixed and pumped 458 sks Midcon II cement. Circulated 24 bbls of I hereby certify that the information above is true and complete to the best of my knowledgrade tank has been/will be constructed or closed according to NMOCD guidelines □, a general permit □ SIGNATURE	ttach wellbore diagram of proposed completion 24#, J55 ST & C casing at 309'. 66. Circulated 8 bbls of cement to surface. cement to pit. ge and belief. I further certify that any pit or below- lor an (attached) alternative OCD-approved plan . DATE 04/24/2006
13. Describe proposed or completed operations. (Clearly state all pertinent details, at of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 04/18/06 Spud @ 7:30 a.m. Drill 11" surface hole to 318'. Run 11 jts. of 8 5/8", 2 Halliburton mixed and pumped 100 sx Midcon II cement, 14 ppg, yield 1.0 WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes. 04/19/06 Drill 7 7/8" hole from 318' - 2,620'. Reached TD at 2,620' at 11:30 a.m MIRU Patterson and log well. Logger's TD at 2,620'. Run 63 jts 5 ½", 15.5 #, J-55 LT & C casing at 2,586'. HES mixed and pumped 458 sks Midcon II cement. Circulated 24 bbls of I hereby certify that the information above is true and complete to the best of my knowledgrade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit SIGNATURE TITLE Regulatory Analytype or print name Shirley A Mitchell E-mail address: shirley.mitchell@elpa	ttach wellbore diagram of proposed completion 24#, J55 ST & C casing at 309'. 66. Circulated 8 bbls of cement to surface. cement to pit. ge and belief. I further certify that any pit or below- lor an (attached) alternative OCD-approved plan .
13. Describe proposed or completed operations. (Clearly state all pertinent details, at of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 04/18/06 Spud @ 7:30 a.m. Drill 11" surface hole to 318". Run 11 jts. of 8 5/8", 2 Halliburton mixed and pumped 100 sx Midcon II cement, 14 ppg, yield 1.4 WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes. 04/19/06 Drill 7 7/8" hole from 318' - 2,620'. Reached TD at 2,620' at 11:30 a.m. MIRU Patterson and log well. Logger's TD at 2,620'. Run 63 jts 5 ½", 15.5 #, J-55 LT & C casing at 2,586'. HES mixed and pumped 458 sks Midcon II cement. Circulated 24 bbls of I hereby certify that the information above is true and complete to the best of my knowledgrade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit SIGNATURE SIGNATURE TITLE Regulatory Analytic State Use Only E-mail address: shirley.mitchell@elpa	ttach wellbore diagram of proposed completion 24#, J55 ST & C casing at 309'. 66. Circulated 8 bbls of cement to surface. cement to pit. ge and belief. I further certify that any pit or belowdor an (attached) alternative OCD-approved plan . yst DATE
13. Describe proposed or completed operations. (Clearly state all pertinent details, at of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 04/18/06 Spud @ 7:30 a.m. Drill 11" surface hole to 318". Run 11 jts. of 8 5/8", 2 Halliburton mixed and pumped 100 sx Midcon II cement, 14 ppg, yield 1.4 WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes. 04/19/06 Drill 7 7/8" hole from 318' - 2,620'. Reached TD at 2,620' at 11:30 a.m. MIRU Patterson and log well. Logger's TD at 2,620'. Run 63 jts 5 ½", 15.5 #, J-55 LT & C casing at 2,586'. HES mixed and pumped 458 sks Midcon II cement. Circulated 24 bbls of I hereby certify that the information above is true and complete to the best of my knowledgrade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit SIGNATURE SIGNATURE TITLE Regulatory Analytic State Use Only E-mail address: shirley.mitchell@elpa	ttach wellbore diagram of proposed completion 24#, J55 ST & C casing at 309'. 66. Circulated 8 bbls of cement to surface. cement to pit. ge and belief. I further certify that any pit or belowdor an (attached) alternative OCD-approved plan . yst DATE
13. Describe proposed or completed operations. (Clearly state all pertinent details, at of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 04/18/06 Spud @ 7:30 a.m. Drill 11" surface hole to 318". Run 11 jts. of 8 5/8", 2 Halliburton mixed and pumped 100 sx Midcon II cement, 14 ppg, yield 1.4 WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes. 04/19/06 Drill 7 7/8" hole from 318' - 2,620'. Reached TD at 2,620' at 11:30 a.m. MIRU Patterson and log well. Logger's TD at 2,620'. Run 63 jts 5 ½", 15.5 #, J-55 LT & C casing at 2,586'. HES mixed and pumped 458 sks Midcon II cement. Circulated 24 bbls of I hereby certify that the information above is true and complete to the best of my knowledgrade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit SIGNATURE SIGNATURE TITLE Regulatory Analytic State Use Only E-mail address: shirley.mitchell@elpa	ttach wellbore diagram of proposed completion 24#, J55 ST & C casing at 309'. 66. Circulated 8 bbls of cement to surface. cement to pit. ge and belief. I further certify that any pit or below- lor an (attached) alternative OCD-approved plan . DATE 04/24/2006