

State of New Mexico
Energy, Minerals and Natural Resources Department

Susana Martinez
Governor

Ken McQueen
Cabinet Secretary

Matthias Sayer
Deputy Cabinet Secretary

Heather Riley, Division Director
Oil Conservation Division



Administrative Order SWD-1724
August 23, 2018

**ADMINISTRATIVE ORDER
OF THE OIL CONSERVATION DIVISION**

Pursuant to the provisions of Division Rule 19.15.26.8(B) NMAC, NGL Water Solutions Permian, LLC (the "operator") seeks an administrative order for its proposed Striker 1 SWD Well No. 1 (the "proposed well") with a location of 1015 feet from the North line and 1395 feet from the East line, Unit letter B of Section 15, Township 23 South, Range 28 East, NMPM, Eddy County, New Mexico, for the purpose of commercial disposal of produced water.

THE DIVISION DIRECTOR FINDS THAT:

The application has been duly filed under the provisions of Division Rule 19.15.26.8(B) NMAC and satisfactory information has been provided that affected parties have been notified. One objection was received but was subsequently withdrawn after the applicant relocated the proposed well. The applicant has presented satisfactory evidence that all requirements prescribed in Division Rule 19.15.26.8 NMAC have been met and the operator is in compliance with Division Rule 19.15.5.9 NMAC.

IT IS THEREFORE ORDERED THAT:

The applicant, NGL Water Solutions Permian, LLC (OGRID 372338), is hereby authorized to utilize its Striker 1 SWD Well No. 1 (API 30-015-44406) with a location of 1015 feet from the North line and 1395 feet from the East line, Unit letter B of Section 15, Township 23 South, Range 28 East, NMPM, Eddy County, for disposal of oil field produced water (UIC Class II only) through open-hole completion into an interval consisting of the Devonian and Silurian formations from approximately 13750 feet to approximately 15100 feet. Injection will occur through internally-coated, 4½-inch or smaller tubing inside the 7⅝-inch liner with a packer set within 100 feet of the top of the disposal interval.

This permit does not allow disposal into formations below the Silurian including the Montoya formation and the Ellenburger formation (lower Ordovician) or lost circulation intervals directly on top and obviously connected to these formations.

Prior to commencing disposal, the operator shall submit mudlog and geophysical logs information, to the Division's District geologist and Santa Fe Bureau Engineering office, showing evidence agreeable that only the permitted formation is open for disposal including a summary of depths (picks) for contacts of the formations which the Division shall use to amend this order for a final description of the depth for the injection interval. If significant hydrocarbon shows occur while drilling, the operator shall notify the Division's District II and the operator shall be required to receive written permission prior to commencing disposal.

If cement does not circulate on any casing string, the operator shall run a cement bond log (CBL) or other log to determine top of cement and shall notify the Artesia District with the top of cement on the emergency phone number prior to continuing with any further cement activity with the proposed well. If cement did not tie back in to next higher casing shoe, the operator shall perform remedial cement job to bring cement, at a minimum, 300 feet above the next higher casing shoe.

The operator shall run a CBL (or equivalent) across the 7⁵/₈-inch liner from 500 feet above the liner to the bottom of the liner to demonstrate placement cement across the length of the liner and the cement bond with the tie-in with the 9⁵/₈-inch casing. The operator shall notify District Office II of the top of the cement in the 7⁵/₈-inch liner. Next, the operator shall provide a copy of the CBL to the Division's District II prior to commencing disposal. Lastly, the operator shall notify District Office II of the top of the cement in the 7⁵/₈-inch liner.

IT IS FURTHER ORDERED THAT:

The operator shall take all steps necessary to ensure that the disposed water enters only the approved disposal interval and is not permitted to escape to other formations or onto the surface. This includes the completion and construction of the well as described in the application and, if necessary, as modified by the District Supervisor.

After installing tubing, the casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge or an approved leak detection device in order to determine leakage in the casing, tubing, or packer. The casing shall be pressure tested from the surface to the packer setting depth to assure casing integrity.

The well shall pass an initial mechanical integrity test ("MIT") prior to initially commencing disposal and prior to resuming disposal each time the disposal packer is unseated. All MIT procedures and schedules shall follow the requirements in Division Rule 19.15.26.11(A) NMAC. The Division Director retains the right to require at any time wireline verification of completion and packer setting depths in this well.

Without limitation on the duties of the operator as provided in Division Rules 19.15.29 and 19.15.30 NMAC, or otherwise, the operator shall immediately notify the Division's District II office of any failure of the tubing, casing or packer in the well, or of any leakage or release of water, oil or gas from around any produced or plugged and abandoned well in the area, and shall take such measures as may be timely and necessary to correct such failure or leakage.

If the disposal well fails a MIT or if there is evidence that the mechanical integrity of said well is impacting correlative rights, the public health, any underground sources of fresh water, or the environment, the Division Director shall require the well to be shut-in within 24 hours of discovery and the operator shall redirect all disposal waters to another facility. The operator shall take the necessary actions to address the impacts resulting from the mechanical integrity issues in accordance with Division Rule 19.15.26.10 NMAC, and the well shall be tested pursuant to Rule 19.15.26.11 NMAC prior to returning to injection.

The wellhead injection pressure on the well shall be limited to **no more than 2750 psi**. In addition, the disposal well or system shall be equipped with a pressure limiting device in workable condition which shall, at all times, limit surface tubing pressure to the maximum allowable pressure for this well.

The Director of the Division may authorize an increase in tubing pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the disposed fluid from the target formations. Such proper showing shall be demonstrated by sufficient evidence including but not limited to an acceptable step-rate test.

The operator shall notify the supervisor of the Division's District II office of the date and time of the installation of disposal equipment and of any MIT so that the same may be inspected and witnessed. The operator shall provide written notice of the date of commencement of disposal to the Division's District II office. The operator shall submit monthly reports of the disposal operations that includes number of days of operation, injection volume, and injection pressure on Division Form C-115, in accordance with Division Rules 19.15.26.13 and 19.15.7.24 NMAC.

The injection authority granted under this order is not transferable except upon Division approval. The Division may require the operator to demonstrate mechanical integrity of any injection well that will be transferred prior to approving transfer of authority to inject.


The Division may revoke this injection order after notice and hearing if the operator is in violation of Rule 19.15.5.9 NMAC.

The disposal authority granted herein shall terminate one (1) year after the effective date of this Order if the operator has not commenced injection operations into the subject well. One year after the last date of reported disposal into this well, the Division shall consider the well abandoned, and the authority to dispose will terminate *ipso facto*. The Division, upon written request mailed by the operator prior to the termination date, may grant an extension thereof for good cause.

Compliance with this Order does not relieve the operator of the obligation to comply with other applicable federal, state or local laws or rules, or to exercise due care for the protection of fresh water, public health and safety and the environment.

Jurisdiction is retained by the Division for the entry of such further orders as may be necessary for the prevention of waste and/or protection of correlative rights or upon failure of the operator to conduct operations (1) to protect fresh or protectable waters or (2) consistent with the

requirements in this order, whereupon the Division may, after notice and hearing, terminate the disposal authority granted herein.



HEATHER RILEY
Director


HR/prg

cc: Oil Conservation Division – Artesia District Office
Well File 30-015-44406

Attachment: Proposed well completion diagram from C-108 application

KB:	NA
BHF:	NA
GL:	NA
Spud:	NA

Casing/Tubing Information					
Label	1	2	3	4	5
Type	Surface	Intermediate	Production	Liner	Tubing
OD	20"	13-3/8"	9-5/8"	7-5/8"	5-1/2" 4-1/2"
WT	0.438"	0.480"	0.472"	0.562"	0.304" 0.250"
ID	19.124"	12.415"	8.681"	6.501"	4.892" 4.000"
Drift ID	18.936"	12.259"	8.525"	6.376"	4.767" 3.875"
COD	21.000"	14.375"	10.625"	7.625"	6.050" 5.000"
Weight	94 lb/ft	68 lb/ft	47 lb/ft	42.8 lb/ft	17 lb/ft 11.6 lb/ft
Grade	J-55 STC	L-80 STC	HCL-80 LTC	P-110 UFJ	L-80 BTC P-110 LTC
Hole Size	26"	17-1/2"	12-1/4"	8-1/2"	Varies
Depth Set	500'	2,600'	9,700'	9,400' - 13,750'	0' - 9,400' 9,400' - 13,700'
TOC	Surface (circulation)	Surface (circulation)	Surface (circulation)	9,400'	NA
Volume	1,195 sks	1,445 sks	1,855 sks	570 sks	NA



CBL

<p>AUSTIN WICHTA LONQUIST O'LEARY</p>	NGL Water Solutions Permian LLC		Striker 1 SWD No. 1	
	Country: USA	State/Province: New Mexico	County/Parish: Eddy	
	Location:	Site:	Survey/STR: Sec. 15-23S-28E	
	API No:	Field:	Well Type/Status: SWD	
	Texas License F-9147	State ID No:	Project No:	Date: 8/7/17
3345 Bee Cave Road, Suite 201 Austin, Texas 78746 Tel: 512.732.9812 Fax: 512.732.9816	Drawn: WHG	Reviewed: CBW	Approved: SLP	
	Rev No: 1	Notes:		