

District I  
1625 N. French Dr., Hobbs, NM 87240  
District II  
811 South First, Artesia, NM 87210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 South Pacheco, Santa Fe, NM 87505

OIL CONSERVATION DIVISION  
1220 South St Francis  
Santa Fe, NM 87505

WELL API NO.

30-007-20674

5. Indicate Type of Lease

STATE ☐ FEE ☒

State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:

OIL WELL ☐ GAS WELL ☒ DRY ☐ OTHER Coal Bed Methane

b. Type of Completion:

NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ OTHER ☐

2. Name of Operator

EL PASO E & P COMPANY, L.P.

3. Address of Operator

PO BOX 190, RATON, NEW MEXICO 87740

7. Lease Name or Unit Agreement Name

VPR A

8. Well No.

237

9. Pool name or Wildcat

Stubblefield Canyon Raton - Vermejo Gas

4. Well Location

Unit Letter I : 1525 Feet From The South Line and 1133 Feet From The East Line

Section 14 Township 31N Range 20E NMPM Colfax County

10. Date Spudded

03/22/2006

11. Date T.D. Reached

03/23/2006

12. Date Compl. (Ready to Prod.)

04/03/2006

13. Elevations (DF& R(B. RT, GR, etc.)

7,951'

14. Elev. Casinghead

7,951'

15. Total Depth

2,270'

16. Plug Back T.D.

2,199'

17. If Multiple Compl. How Many Zones?

18. Intervals Drilled By

Rotary Tools

0 - TD

Cable Tools

NONE

19. Producing Interval(s), of this completion - Top, Bottom, Name

1034' - 1994' Vermejo - Raton Coals

20. Was Directional Survey Made

NO

21. Type Electric and Other Logs Run

Compensated Density and Cement Bond Log / Gamma Ray

22. Was Well Cored

No

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	23	308'	11"	100 sks	None
5 1/2"	15.5	2,199'	7 7/8"	319 sks	

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN

25. TUBING RECORD

SIZE	DEPTH SET	PACKER SET
2 7/8"	2,064'	No

26. Perforation record (interval, size, and number)

1958'-1961', 1991'-1994' 24 Holes  
1813'-1816', 1878'-1881', 1890'-1893', 1903'-1906', 1915'-1920' 68 Holes  
1157'-1163' 24 Holes  
1034'-1038', 1050'-1054', 1089'-1094' 52 Holes

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
1034' - 1994'	219,900 lbs 16/30 sand

28

PRODUCTION

Date First Production

04/19/2006

Production Method (Flowing, gas lift, pumping - Size and type pump)

Pumping water up 2 7/8" tubing, pc pump.. Flowing gas up 5 1/2" Casing.

Well Status (Prod. or Shut-in)

Production

Date of Test

04/19/2006

Hours Tested

24 hrs.

Choke Size

Full 2"

Prod'n For

Test Period

Oil - Bbl

N/A

Gas - MCF

96

Water - Bbl.

209

Gas - Oil Ratio

N/A

Flow Tubing Press.

0

Casing Pressure

96

Calculated 24-Hour Rate

Oil - Bbl.

N/A

Gas - MCF

96

Water - Bbl.

209

Oil Gravity - API - (Corr.)

N/A

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

Sold, used for fuel.

Test Witnessed By:

Steven Medina

30. List Attachments

31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief.

Signature:

*Shirley Mitchell*

Printed

Shirley A. Mitchell

Title

Regulatory Analyst

Date:

05/01/2006

## INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

## Southeastern New Mexico

T. Anhy	T. Canyon
T. Salt	T. Strawn
B. Salt	T. Atoka
T. Yates	T. Miss
T. 7 Rivers	T. Devonian
T. Queen	T. Silurian
T. Grayburg	T. Montoya
T. San Andres	T. Simpson
T. Glorieta	T. McKee
T. Paddock	T. Ellenburger
T. Blinberry	T. Gr. Wash

T. Tubb	T. Delaware Sand
T. Drinkard	T. Bone Springs
T. Abo	T.
T. Wolfcamp	T.
T. Penn	T.
T. Cisco (Bough C)	T.

## Northwestern New Mexico

T. Ojo Alamo	T. Penn. "B"
T. Kirtland-Fruitland	T. Penn. "C"
T. Pictured Cliffs	T. Penn. "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzte
Base Greenhorn	T. Granite
T. Dakota	T. Raton Top <u>9'</u>
T. Morrison	T. Vermejo <u>1,815'</u>

T. Todilto	T. _____
T. Entrada	T. _____
T. Wingate	T. _____
T. Chinle	T. _____
T. Permian	T. _____
T. Penn "A"	T. _____

### OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....  
No. 2, from.....to.....  
No. 3, from.....to.....  
No. 4, from.....to.....

## IMPORTANT WATER SANDS

**Include data on rate of water inflow and elevation to which water rose in hole.**

No. 1, from.....to.....feet.....  
 No. 2, from.....to.....feet.....  
 No. 3, from.....to.....feet.....

## LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology

From	To	Thickness In Feet	Lithology