

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St Frances
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

| | | |
|--|--|---|
| SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) | | WELL API NO. 30-007-20410 |
| 1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other <input checked="" type="checkbox"/> Coalbed Methane | | 5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/> |
| 2. Name of Operator EL PASO ENERGY RATON, L.L.C. | | 6. State Oil & Gas Lease No. |
| 3. Address of Operator P.O. Box 190, Raton, NM 87740 | | 7. Lease Name or Unit Agreement Name: VPR A |
| 4. Well Location Unit Letter D : 600 feet from the North line and 1298 feet from the East line Section 21 Township 31N Range 19E NMPM Colfax County | | 8. Well No. 112 |
| 10. Elevation (Show whether DR, RKB, RT, GR, etc.) 8272' (GL) | | 9. Pool name or Wildcat |

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

05/20/03 Spud in @ 6:00 a.m. Drill 11" surface hole to 353'. Ran 9 jts of 8 5/8", J-55, 24 ppf ST&C casing to 342'. Halliburton mixed and pumped 105 sks Midcon II PP, 14 ppg, yield 1.66 at 3 bpm with 40 psi with 6% salt, .3% gilsonite, .3% versaset, and 25# flocele per sack. Circulated 5 bbls of cement to surface. WOC 8 hrs. Test surface casing to 500 psi for 30 min.

05/21/03 Drill 7 7/8" hole f/ 352' - 2540'. Reached TD at 2540'. MIRU Schlumberger & log well. Ran 12 jts of 5 1/2", J-55, and 48 jts of 5 1/2", M-50, 15.5 ppf LT &C casing to 2515'. Halliburton mixed and pump 40 bbls gel pre flush at 4 bpm at 25 psi, 363 sks Midcon II, 13.0 ppg, yield 2.04, .3% versaset, 5#/sx gilsonite, 2#/sk granulate, 6% salt and .1% Super CBL. Plug down @ 4:50 p.m. Circulated 37 bbls of cement to surface. Well shut in.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Shirley A. Mitchell TITLE Field Adm. Specialist DATE 05-24-03

Type or print name Shirley A. Mitchell Telephone No. (505) 445-6785
(This space for State use)

APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 6/19/03
Conditions of approval, if any: