Submit 3 Copies To Appropriate District Office	State of New Mexico			Form C-103
District I	Energy, Minerals and Natural Resources		WELL API NO.	Revised March 25, 1999
1625 N. French Dr., Hobbs, NM 87240 District II	OIL CONGERNATION DIVIDIONI			30-007-20363
811 South First, Artesia, NM 87210	OIL CONSERVATION DIVISION		5. Indicate Type of	
<u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St Frances		STATE [FEE W
<u>District IV</u> 2040 South Pacheco, Santa Fe, NM 87505	Santa Fe, NM 87505		6. State Oil & G	las Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			7. Lease Name or Unit Agreement Name:	
PROPOSALS.)			VPR A	
Type of Well: Oil Well				
2. Name of Operator		<u> </u>	8. Well No.	100
EL PASO ENERGY RATON, L.L.C.				
3. Address of Operator PO Box 190, RATON, NM 87740			9. Pool name or V	Wildcat on Raton-Vermejo Gas
4. Well Location			Studdicticia Carry	on Raton-vermejo Gas
Unit Letter H: 1465 feet from the North line and 1213 feet from the East line Section 36 Township 32N Range 20E NMPM Colfax County 10. Elevation (Show whether DR, RKB, RT, GR, etc.)				
7914' (GL)				
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data				
NOTICE OF INTENTION TO: SUBSEQUENT RE				
PERFORM REMEDIAL WORK	PLUG AND ABANDON 🔲	REMEDIAL WORK		ALTERING CASING L
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT		
PULL OR ALTER CASING	MULTIPLE COMPLETION	CASING TEST AN CEMENT JOB	D	
OTHER:		OTHER:		
12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.				
-02/01/03 Spud in @ 7:30 a.m. Drill 11" surface hole to 334'. Ran 10 jts of 8 5/8", J-55, 23 ppf ST&C casing to 325'. Halliburton mixed and pumped 100 sks Midcon II PP, 14 ppg, yield 1.66 at 3 bpm with 50 psi with 6% salt, 5#/sx gilsonite, .2% versaset, and .25 #/sk flocele. Circulated 8 bbls of cement to surface. WOC 8 hrs. Test surface casing to 500 psi for 30 min.				
02/02/03 Drill 7 7/8" hole f/ 334' - 2285'. Reached TD 2285'. MIRU Schlumberger & log well. Ran 12 jts of 5 ½, #17, J-55 and 41 jts of 5 ½", #15.5, J-55, LT &C casing to 1727'. Halliburton mixed and pump 40 bls gel pre flush at 3 bpm at 0 psi, 320 sks Midcon Il, 13.0 ppg, yield 2.04, with 6% salt, .3% versaset, 5#/sx gilsonite, .2% versaset, .1% super CBL and .25 #/sk flocele. Plug down @ 3:14 p.m. with 850 psi. Established circulation 60 bbls into cement. Lost circulation 5 bbls into displacement and never saw it again. Well shut in.				
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
SIGNATURE Shirly Mitchell TITLE Field Adm. Specialist DATE 02/04/03				
Type or print name Shirley A. Mitchell Telephone No. (505) 445-6785				
(This space for State use)	7///	SICTHICT CU	IDEDV/ICAL	1 / -
APPPROVED BY Conditions of approval, if any	Hoke TITLE I	DISTRICT SU	FERYIOUR	DATE 2/7/03