Submit 3 Copies To Appropriate District Office	State of New Mexico		Form C-103
District I	Energy, Minerals and Natural Resources		Revised March 25, 1999 WELL API NO.
1625 N. French Dr., Hobbs, NM 88240 District II	OH CONCEDUATION DIVICION		30-053-20014
811 South First, Artesia, NM 88210 District III	OIL CONSERVATION DIVISION 1220 South St. Francis Dr.		5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410	Santa Fe, NM 87505		STATE XX FEE
District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505	Santa Pe, Nivi 67505		6. State Oil & Gas Lease No.
	VTICES AND REPORTS ON WELLS		7. Lease Name or Unit Agreement Name:
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		Dulce Draw State #1	
1. Type of Well:	, ·		
Oil Well Gas Well	XX Other		7. Well No.
2. Name of Operator Primero Operating, Inc.			7. Well No.
3. Address of Operator			8. Pool name or Wildcat
PO box 1433, Roswell, NM 88202	2-1433		Wildcat, Atoka
4. Well Location			
Unit LetterE	feet from the _North	line and	660feet from the Westline
Section 2	Township 4S	Range 9E	NMPM Socorro County
	10. Elevation (Show whether D		
5961' GL			
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data  NOTICE OF INTENTION TO:  SUBSEQUENT REPORT OF:			
PERFORM REMEDIAL WORK	_	REMEDIAL WOR	
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DR	ILLING OPNS. X PLUG AND ABANDONMENT
PULL OR ALTER CASING	MULTIPLE  COMPLETION	CASING TEST A	
OTHER:		OTHER: Shut in	well in order to produce another
12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.			
Commenced Drilling a 17 ½" hole with air on April 22, 2001.			
Drilled 17 ½" hole to 1326', encountered no water but loss of air returns at 1140'. Ran 1283' of new 13 3/8" 54.5" J-55 casing with Texas pattern shoe, float collar and 5 centralizers. Cemented casing with 300 sx Class "C" with 2% CaCl and ¼# Celloflake.			
Displaced plug with water and pressure test casing to 600 psi, plug down at 7:30 pm 4/28/01. WOC 4 hours and ran temperature survey, found top of cement at 480' from surface. Commence drilling 12 1/4" hole at 5:00 pm on 4/29/01.			
<b>3,,</b>		<b>5</b> · · · · · · ·	F
I hereby certify that the information above is true and complete to the best of my knowledge and belief.			
SIGNATURE	TITLE	President_	DATE5-01-2001
Type or print name Phelps White	,		Telephone No. 505-622-1001
(This space for State use)			
APPPROVED BY TITLE DISTRICT SUPERVISOR DATE 5/4/2001			
Conditions of approval, if any			Ditte - / · · ·