

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.

30-007-20776

7. Indicate Type of Lease

STATE ☐ FEE ☒

7. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other Coalbed Methane

2. Name of Operator

EL PASO E & P COMPANY, L.P.

3. Address of Operator

P.O. BOX 190, RATON, NM 87740

4. Well Location

Unit Letter **B** : **275** feet from the **North** line and **2355** feet from the **East** line

Section **20** Township **29N** Range **19E** **NMPM** **Colfax** County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

7,746' (GL)

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____

Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ P AND A ☐

CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

03/12/07 Spud @ 5:30 p.m. Drill 11" surface hole to 337'. Run 11 jts. of 8 5/8", 24 #, J55 ST & C casing at 328'. Halliburton mixed and pumped 100 sx Midcon II cement, 14 ppg, yield 1.66. Circulate 5 bbls of cement to surface. WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes.

03/13/07 Drill 7 7/8" hole from 337' - 2305'. Reached TD 2305' at 10:00 p.m. MIRU Superior and log well. Logger's TD at 2286'. Run 32 jts 5 1/2", 15.5 ppg, J-55, and 8 jts 17 ppg, J-55 LT&C casing at 2222'. HES mixed and pumped 274 sks Midcon II cement. Circulated 11 bbls of cement to surface.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Shirley Mitchell TITLE Regulatory Analyst DATE 03/22/2007
Type or print name Shirley A. Mitchell E-mail address: shirley.mitchell@elpaso.com Telephone No. (505) 445-6785
For State Use Only

APPROVED BY: Ed Martin TITLE DISTRICT SUPERVISOR DATE 4-16-07
Conditions of Approval (if any):