						Staté of No Minerals &	w Mexico Form C-101 Natural Resources May 27, 2004					
District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410					Oil Conservation Division 1220 S. St. Francis Dr.				Submit to appropriate District Office			
District IV 1220 S. St. Francis Dr., Santa F <b>2093</b> APR 23 AM 11 55 anta Fe, 1										☐ AME	NDED REPORT	
APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE												
<sup>1</sup> Operator Name and Address <sup>2</sup> OGRID Number												
OXY USA Inc.									16696			
P.O. Box 50250 Midland, TX 79710-0250									<sup>3</sup> API Number 30- 021- <b>204</b> //			
<sup>4</sup> Proper 27	rty Code		Ţ	Br		<sup>5</sup> Property	Name	e Gas Unit W	6Well No. B31 01			
<u> </u>	<u> </u>	<sup>9</sup> Pro	posed Po		ravo Dome Carbon Dioxide Gas Unit 1			<sup>10</sup> Proposed Pool 2				
Bravo Dome	Bravo Dome Carbon Dioxide Gas 160 96010											
						<sup>7</sup> Surface	Loca	tion	<u> </u>		<u></u>	
UL or lot no.	Section	1	vnship	Range	Lot. Id			North/South Line	Feet from the	East/West line	County	
G		16		31 E	<u> </u>			north	0051	eust	Harding	
UL or lot no.	Section	Tov	vnship	Range	Lot, Id	n Feet from	the	North/South Line	Feet from the	East/West line	County	
L	4,,	<u> </u>		<u> </u>	A	dditional V	Vell L	ocation	<u> </u>	L	<u> </u>	
II Work Ty			12	Well Type Cod	de <sup>13</sup> Cable/Rotary R			<sup>14</sup> Lea	ase Type Code	<sup>15</sup> Ground Level Elevation 4464.3		
16 Mult	•		17	Proposed Dept	h	<sup>18</sup> Form	·	<sup>19</sup> Contractor		<sup>20</sup> Spud Date		
N				2600'	Tub				N/A	71.107		
Depth to ground	water	>100	)'		Distance	Distance from nearest fresh water well >1000'			Distance from nearest surface water >1000 '			
Pit: Liner: Syr	ithetic X	12	_ mils th	ick Clay	/□	Pit Volume _4	000	bbls Drilling Met	hod:			
Closed-La	oop System [	]								iil-based	Gas/Air 🛄	
				F	ropose	ed Casing a	nd Ce	ment Program	1	·		
Hole S	ize	<u> </u>			Casir	sing weight/foot		Setting Depth	ting Depth Sacks of Cem		ent Estimated TOC	
12-1/4"			8-5/8"		24#		<u> </u>	700'	300sx	Surface		
7-7/8"			5-1/2"		5.9	<u>5.9#FG/15.5#</u>		2600'	300sx	00sxSurfac		
L		1										
1												
<sup>22</sup> Describe the proposed program. If this application is to DEEPEN or PLUG BACK, give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.												
See Attachment												
<sup>23</sup> 1 hereby certify that the information given above is true and complete to the best of my knowledge and belief. I further certify that the drilling pit will be						OIL CONSERVATION DIVISION						
constructed according to NMOCD guidelines a general permit , or an (attached) alternative OCD-approved plan							Approved by:					
Signature: Printed name: David Stewart							Title: DISTRICT SUPERVISOR					
Title: Sr. Regulatory Analyst												
E-mail Address: david stewart@oxy.com							Approval Date: 4-23-07 Expiration Date: 4-23-08					
E-mail Address: david_stewart@oxy.com Date: Phone:							Conditions of Approval:					
4120107			432-685-5717				Attached					

ATTACHMENT C-101' BDCDGU 1831-011

PROPOSED TD: 2600' TVD

BOP PROGRAM: 0-700' None

700-2600' 8" 2M annular hydril preventer.

CASING: Surface: 8-5/8" OD 24# J55 8rd ST&C new casing set at 700' 12-1/4" hole Centralizers from TD-Surf, every fourth joint

> Production: 5-1/2" OD new casing from 0-2600' 300'-15.5# J55 8rd LTC 2300'-5.9# 10rd FG 7-7/8" hole - 5 centralizers

\*This well will have fiberglass casing from surface to the productive interval (Tubb). Steel casing will be used across the Tubb. The fiberglass casing must penetrate the Cimarron at a minimum. The optimum point for setting the fiberglass casing is at the midpoint of the Cimarron formation.

**CEMENT:** Surface - Circulate cement with 300sx Premium Plus with 2% CaCl<sub>2</sub> + .25#/sx Poly E Flake, (WT-14.8ppg, Yld-1.34cf/sx, FW-6.3g/sx)

Production - Cement with 150sx Premium Plus with 3% CaCl<sub>2</sub> + .25#/sx Poly E Flake, (WT-11.1ppg, Yld-3.27cf/sx, FW-20.47g/sx) followed by 150sx Premium Plus with 3% CaCl<sub>2</sub> + .25#/sx Poly E Flake, (WT-13.2ppg, Yld-1.86cf/sx, FW-9.93g/sx)

MUD:	0-700′	Fresh water/native mud. Wt 8.6-9.2ppg, Vis 32-36sec					
	700-2600′	Fresh water/Starch/Gel pH control as needed. Wt 9.0-9.2ppg, Vis 28-29sec					

District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 South First, Artesia, NM 88210

District III 1000 Rio Brazos Rd., Aztec, NM 87410

District IV 2040 South Pacheco, Santa Fe, NM 87505 OIL CONSERVATION DIVISION 2040 South Pacheco Santa Fe, NM 87505 Form C-102 Revised October 18, 1994 Instructions on back Submit to Appropriate District Office State Lease – 4 Copies Fee Lease – 3 Copies

## AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT												
API Number				Pool Cod	le	Pool Name						
30-07		96010			BRAVO DOME CARBON DIOXIDE GAS IC				GAS 160			
Property						perty			Well Number			
2711	1	BRAV	<u>'O DC</u>	D DOME CARBON DIOXIDE GAS L					JNIT 1831 011			
OGRID				Operator Name					Elevation			
1669	6			OXY USA INC.					4464.3			
Surface Location												
UL or lot no.	Section	Township	Range	Lot Idn.	Feet from the		North/South line Feet from the		East/West line Cou		County	
G	1	18 N	31 E		1700	1	NORTH	1700'	EAST		HARDING	
	Bottom Hole Location If Different From Surface											
UL or lot no.	Section	Township	Range	Lot Idn.	Feet from	the	North/South line	Feet from the	East/West 1	ìne	County	
Dedicated Acr	es Joint	or Infill C	onsolidatio	n Code (	Order No.	_						
160	N											
NO ALLO	WABLE						ON UNTIL ALL			EN CO	NSOLIDATED	
<b></b>			NON-SI	ANDARD	<u>UNIT HA</u>	AS BI	EEN APPROVED					
	ļ				Y	1					FICATION	
									I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.			
				H.	ļ				prote 10 1150 00		ionioage and outer	
	ļ				,001			i .				
]]	)			1	- 1 7	ł			$\sim$		-	
╟	······						- 1	En Star				
	ļ							Signature				
l.	İ			1			1700′		David Stewart Printed Name			
				NM-E NAD27				11	Sr. Regulatory Analyst			
				Lon	- 35° 49'18.47 - 103° 35'38.7			Title	Title			
1	ļ				719152.31 1755190.35	ł		· · · · · · · · · · · · · · · · · · ·	<u> </u>	0/07	۲	
[] ]]								Date				
	l			1		ļ		SURV	EYOR (	CERTI	FICATION	
											shown on this plat	
	ĺ										surveys made by the same is true	
1)	ĺ					)			o the best of n		and paint is in the	
						}		N	overbe		2006	
∦ <u></u>								Date of Surve	y /~	MEL	$\sqrt{\sqrt{2}}$	
	1							Signature and		seional Su	Geyar O g	
								Date of Surve Signature and	1991 (	<b>15</b> 079		
}	i I								13b	$\searrow$	14	
II.	í			}						J-	7/9/9001	
Į.		l		ł			Ter	SEIDNA	71			
					<u> </u>	ĺ		Certificate N1	umber 150	79		



## **BRAVO DOME 2003 DRILLING PROJECT BOP DIAGRAM**

Bravo Dome Unit Location and Pit Design Cheyenne Rig 8





•

,

3 ft

. -

.

