Submit 3 Copies To Appropriate District	State of New Mexico	Form C-103
Office District I	Energy, Minerals and Natural Res	sources May 27, 2004
1625 N. French Dr., Hobbs, NM 88240		WELL API NO.
District II 1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVI	SION 30-007-20810 7. Indicate Type of Lease
District III	1220 South St. Francis Dr	r. STATE FEE
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505	7. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM		, , state on the case season in the
87505	ICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPO	SALS TO DRILL OR TO DEEPEN OR PLUG BACI	
DIFFERENT RESERVOIR. USE "APPLI	CATION FOR PERMIT" (FORM.C-101) FOR SUCH	
PROPOSALS.)	Gas Well Other Coalbed Methane	0 W.H.Mh. 202
2. Name of Operator	das wen Z oner coance memane	9. OGRID Number
EL PASO E & P COMPANY, L.P.		
3. Address of Operator		10. Pool name or Wildcat
P.O. BOX	X 190, RATON, NM 87740	
4. Well Location		
Unit Letter <u>C</u> : <u>190</u> feet from the <u>North</u> line and <u>1629</u> feet from the <u>West</u> line		
Section 27 Towns		NMPM Colfax County
0	11. Elevation (Show whether DR, RKB, I	RT, GR, etc.)
The second secon	7,982' (GL)	
Pit or Below-grade Tank Application		
Pit typeDepth to GroundwaterDistance from nearest fresh water wellDistance from nearest surface water		
Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF IN	ITENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK 🗌		EDIAL WORK ALTERING CASING
TEMPORARILY ABANDON 🗌		MENCE DRILLING OPNS.⊠ P AND A □
PULL OR ALTER CASING	MULTIPLE COMPL	NG/CEMENT JOB
OTHER:	☐ OTHE	
		nt details, and give pertinent dates, including estimated dat
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.		
06/09/07 Spud @ 3:45 p.m. Drill 11" surface hole to 332'. Run 8 jts. of 8 5/8", 24#, J55 ST & C casing at 322'.		
Halliburton mixed and pumped 100 sks Midcon II cement. Circulated 5 bbls of cement to surface.		
WOC 8 hrs. Test sur	face 8 5/8" csg to 500 psi for 30 minutes.	
06/10/07 Drill 7 7/8" hole from	n 332' – 2185'. Reached TD at 2185' at 4	4:00 a m
MIRU Superior and log well. Logger's TD 2183'.		
Run 45 jts 5 ½ ", 15.5 ppf, J-55, and 9 jts 17 ppf, J-55 LT&C casing st 2095."		
HES mixed and pump	ed 303 sks Midcon II cement. Did not circ	culate to pit. Prep for remedial cement squeeze job.
I benches considerable the information	share is two and samulate to the heat of w	are broughed as and haliaf. I found a seriff that are sit on hiterature
		ny knowledge and belief. I further certify that any pit or below- eral permit or an (attached) alternative OCD-approved plan .
	/ l	
		atory Analyst DATE 06/19/2007
Type or print name Shirley A. M	itchell E-mail address: shirley.mit	chell@elpaso.com Telephone No. (505) 445-6785
For State Use Only	nioti	DIAT CUREBUIAAB
APPROVED BY:	Martin TITLE DISTI	RICT SUPERVISOR DATE 6/25/07
Conditions of Approval (if any):	1	