Submit 3 Copies To Appropriate District State of New Me	exico Form C-103
Office District 1 Energy, Minerals and Natur	rral Resources Revised March 25, 1999
1625 N. French Dr., Hobbs, NM 87240 District II	WELL API NO. 30-007-20385
811 South First, Artesia, NM 87210 OIL CONSERVATION	5 Indicate Type of Lease
District III 1220 South St Fr. 1000 Rio Brazos Rd., Aztec, NM 87410	ances STATE FEE
District IV 2040 South Pacheco, Santa Fe, NM 87505	6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name:
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PL	
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FO PROPOSALS.)	OR SUCH VPR D
1. Type of Well:	
Other COALBED METH	
2. Name of Operator EL PASO ENERGY RATON, L.L.C.	8. Well No. 97
3. Address of Operator	9. Pool name or Wildcat
P.O. BOX 190 RATON, NM 87740	
4. Well Location	
Unit Letter F: 2209 feet from the North line and 2019 feet from the West line	
Section 3 Township 30N Range 17E NMPM COLFAX County	
10. Elevation (Show whether DR, RKB, RT, GR, etc.)	
8511' (GR)	
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING	
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT
PULL OR ALTER CASING	CASING TEST AND
COMPLETION	CEMENT JOB
OTHER:	OTHER: COMPLETION
12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any	
proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.	
03/12/03 Halliburton ran Cement Bond Log. TOC at surface,	
03/15/03 HES perf'd 1 st stage: 1828' - 1830', 1834' - 1838' 3 SPF 16 Holes	
HES frac'd 1 st stage: Pumped fracture treatment and 112,240 lbs of 20/40 Ottawa Sand at 10.4 bpm, Final ISIP at 990 psi. HES perf'd 2 nd stage: 1728' - 1730' 3 SPF 5 Holes	
HES frac'd 2 nd stage: Pumped fracture treatment and 20.5	40 lbs of 20/40 Ottawa Sand at 8.8 bpm, Final ISIP at 1,445 psi.
HES perf'd 3 ¹¹ stage: 1594' – 1597' 3 SPF 8 Holes	
	50 lbs of 20/40 Ottawa Sand at 8.3 bpm, Final ISIP at 2,055 psi.
03/18/03 Installed rods, tubing, and pump.	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
SIGNATURE Shurley A Mitchell TITLE Field Adm Specialist DATE 05-16-03	
Type or print name: Shipley A. Mirchell Telephone No.: (505) 445-6785	
(This space for State use)	
APPPROVED BY JOHN TITLE DISTRICT SUPERVISOR DATE 5/21/03	
APPPROVED BY TITLE Conditions of approval, if any	DATE WITH DATE
v	