

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-007-20858
7. Indicate Type of Lease STATE ☐ FEE ☒
7. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		7. Lease Name or Unit Agreement Name VPR A
1. Type of Well: Oil Well ☐ Gas Well ☒ Other Coalbed Methane		8. Well Number 339
2. Name of Operator EL PASO E & P COMPANY, L.P.		9. OGRID Number
3. Address of Operator P.O. BOX 190, RATON, NM 87740		10. Pool name or Wildcat
4. Well Location Unit Letter N : 987 feet from the South line and 1790 feet from the West line Section 17 Township 31N Range 21E NMPM Colfax County		
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 7,827' (GL)		
Pit or Below-grade Tank Application ☐ or Closure ☐		
Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____		
Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____		

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☒	P AND A ☐
PULL OR ALTER CASING ☐	MULTIPLE COMPL ☐	CASING/CEMENT JOB ☐	
OTHER: ☐		OTHER: ☐	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

07/11/07 Spud @ 7:15 p.m. Drill 11" surface hole to 328'. Run 8 jts. of 8 5/8", 24#, J55 ST & C casing at 318'. Halliburton mixed and pumped 100 sks Midcon II cement. Circulated 6 bbls of cement to surface. WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes.

07/12/07 Drill 7 7/8" hole from 328' - 2135'. Reached TD at 2135' at 4:45 p.m. MIRU Superior and log well. Logger's TD 2115'. Run 44 jts 5 1/2, 15.5 ppf, J-55, and 8 jts 17 ppf, J-55 LT&C casing st 2068. HES mixed and pumped 224 sks Midcon II cement. Did not circulate to surface. Prep for remedial cement squeeze job.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Shirley Mitchell TITLE Regulatory Analyst DATE 07/18/2007
Type or print name Shirley A. Mitchell E-mail address: shirley.mitchell@elpaso.com Telephone No. (505) 445-6785
For State Use Only

APPROVED BY: Ed Martin TITLE DISTRICT SUPERVISOR DATE 7/27/07
Conditions of Approval (if any):