Office State of New Mexico	Form C-103
<u>District I</u> Energy, Minerals and Natural Resources	May 27, 2004
1625 N. French Dr., Hobbs, NM 88240	WELL API NO. 30-007-20840
District II 1301 W. Grand Ave., Artesia, NM 88210 OIL CONSERVATION DIVISION	5. Indicate Type of Lease
District III 1220 South St. Francis Dr.	STATE FEE
1000 Rio Brazos Rd., Aztec, NM 87410 District IV Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM	o. State on & Gas Boase No.
87505	
SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	N/DD A
PROPOSALS.)	VPR A
1. Type of Well: Oil Well Gas Well Other Coalbed Methane	8. Well Number 331
2. Name of Operator	9. OGRID Number 180514
EL PASO E & P COMPANY, L.P.	
3. Address of Operator	10. Pool name or Wildcat
PO BOX 190, RATON, NM 87740	Stubblefield Canyon – Vermejo Gas
4. Well Location	
Unit Letter <u>G</u> : <u>1622</u> feet from the <u>North</u> line and	1417 feet from the East line
Section 18 Township 31N Range 21E NMPM	Colfax County
11. Elevation (Show whether DR, RKB, RT, GR, etc.	
7, 746' (GL)	A SAME CONTRACTOR OF THE PARTY
Pit or Below-grade Tank Application ☐ or Closure ☐	
Pit type Depth to Groundwater Distance from nearest fresh water well Di	stance from nearest surface water
Pit Liner Thickness: mil Below-Grade Tank: Volumebbls; (Construction Material
12 Charle Appropriate Day to Indicate Nature of Natice	Papart or Other Date
12. Check Appropriate Box to Indicate Nature of Notice	, Report of Other Data
NOTICE OF INTENTION TO: SUE	SSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WOI	
	RILLING OPNS. P AND A
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN	
OAOINO/OEME	11 00B
OTHER	
OTHER: OTHER:	Completion 🖂
13. Describe proposed or completed operations. (Clearly state all pertinent details, a	nd give pertinent dates, including estimated date
13. Describe proposed or completed operations. (Clearly state all pertinent details, a	nd give pertinent dates, including estimated date
	nd give pertinent dates, including estimated date
13. Describe proposed or completed operations. (Clearly state all pertinent details, a of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion.	nd give pertinent dates, including estimated date attach wellbore diagram of proposed confection
 13. Describe proposed or completed operations. (Clearly state all pertinent details, a of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 06/30/07 Superior ran Cement Bond Log. Estimated top of cement at 340'. 	nd give pertinent dates, including estimated date attach wellbore diagram of proposed confection
 13. Describe proposed or completed operations. (Clearly state all pertinent details, a of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 06/30/07 Superior ran Cement Bond Log. Estimated top of cement at 340'. 07/12/07 HES pumped 45 bbls of cement down hole. Circulated 1 bbl to pit. 	nd give pertinent dates, including estimated date attach wellbore diagram of proposed confection
 Describe proposed or completed operations. (Clearly state all pertinent details, a of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. Superior ran Cement Bond Log. Estimated top of cement at 340'. HES pumped 45 bbls of cement down hole. Circulated 1 bbl to pit. Superior ren Cement Bond Log. Estimated top of cement to surface. 	nd give pertinent dates, including estimated date attach wellbore diagram of proposed confection
 13. Describe proposed or completed operations. (Clearly state all pertinent details, a of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 06/30/07 Superior ran Cement Bond Log. Estimated top of cement at 340'. 07/12/07 HES pumped 45 bbls of cement down hole. Circulated 1 bbl to pit. 08/14/07 Superior ren Cement Bond Log. Estimated top of cement to surface. 08/17/07 Superior Wireline perf'd 1st stage - 1745'-1749', 1810'-1814' 32 Holes HES frac'd 1st stage - Pumped 156, 720 scf 70% quality nitrogen foam with 20# 	and give pertinent dates, including estimated date attach wellbore diagram of proposed confection
 13. Describe proposed or completed operations. (Clearly state all pertinent details, a of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 06/30/07 Superior ran Cement Bond Log. Estimated top of cement at 340'. 07/12/07 HES pumped 45 bbls of cement down hole. Circulated 1 bbl to pit. 08/14/07 Superior ren Cement Bond Log. Estimated top of cement to surface. 08/17/07 Superior Wireline perf'd 1st stage - 1745'-1749', 1810'-1814' 32 Holes HES frac'd 1st stage - Pumped 156, 720 scf 70% quality nitrogen foam with 20# Perf'd 2nd stage - 1606'-1610', 1679'-1682' 28 Holes 	Ind give pertinent dates, including estimated date attach wellbore diagram of proposed confection Linear gel with 17, 689 lbs 20/40 sand.
 13. Describe proposed or completed operations. (Clearly state all pertinent details, a of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 06/30/07 Superior ran Cement Bond Log. Estimated top of cement at 340'. 07/12/07 HES pumped 45 bbls of cement down hole. Circulated 1 bbl to pit. 08/14/07 Superior ren Cement Bond Log. Estimated top of cement to surface. 08/17/07 Superior Wireline perf'd 1st stage - 1745'-1749', 1810'-1814' 32 Holes HES frac'd 1st stage - Pumped 156, 720 scf 70% quality nitrogen foam with 20# Perf'd 2nd stage - 1606'-1610', 1679'-1682' 28 Holes Frac'd 2nd stage - Pumped 122, 838 scf 70% quality nitrogen foam with 20# 	Ind give pertinent dates, including estimated date attach wellbore diagram of proposed confection Linear gel with 17, 689 lbs 20/40 sand.
13. Describe proposed or completed operations. (Clearly state all pertinent details, a of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 06/30/07 Superior ran Cement Bond Log. Estimated top of cement at 340'. 07/12/07 HES pumped 45 bbls of cement down hole. Circulated 1 bbl to pit. 08/14/07 Superior ren Cement Bond Log. Estimated top of cement to surface. 08/17/07 Superior Wireline perf'd 1 st stage - 1745'-1749', 1810'-1814' 32 Holes HES frac'd 1 st stage - Pumped 156, 720 scf 70% quality nitrogen foam with 20# Perf'd 2 nd stage - 1606'-1610', 1679'-1682' 28 Holes Frac'd 2 nd stage - Pumped 122, 838 scf 70% quality nitrogen foam with 20# Perf'd 3 rd stage - 1410'-1414', 1452'-1457', 1486'-1488' 44 Holes	Linear gel with 14, 064 lbs 20/40 sand.
13. Describe proposed or completed operations. (Clearly state all pertinent details, a of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 06/30/07 Superior ran Cement Bond Log. Estimated top of cement at 340'. 07/12/07 HES pumped 45 bbls of cement down hole. Circulated 1 bbl to pit. 08/14/07 Superior ren Cement Bond Log. Estimated top of cement to surface. 08/17/07 Superior Wireline perf'd 1 st stage - 1745'-1749', 1810'-1814' 32 Holes HES frac'd 1 st stage - Pumped 156, 720 scf 70% quality nitrogen foam with 20# Perf'd 2 nd stage - 1606'- 1610', 1679'-1682' 28 Holes Frac'd 2 nd stage - Pumped 122, 838 scf 70% quality nitrogen foam with 20# Perf'd 3 rd stage - 1410'-1414', 1452'-1457', 1486'-1488' 44 Holes Frac'd 3 rd stage - Pumped 157, 598 scf 70% quality nitrogen foam with 20#	Linear gel with 14, 064 lbs 20/40 sand.
13. Describe proposed or completed operations. (Clearly state all pertinent details, a of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 06/30/07 Superior ran Cement Bond Log. Estimated top of cement at 340'. 07/12/07 HES pumped 45 bbls of cement down hole. Circulated 1 bbl to pit. 08/14/07 Superior ren Cement Bond Log. Estimated top of cement to surface. 08/17/07 Superior Wireline perf'd 1st stage - 1745'-1749', 1810'-1814' 32 Holes HES frac'd 1st stage - Pumped 156, 720 scf 70% quality nitrogen foam with 20# Perf'd 2nd stage - 1606'-1610', 1679'-1682' 28 Holes Frac'd 2nd stage - 1606'-1610', 1679'-1682' 28 Holes Pumped 122, 838 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - 1410'-1414', 1452'-1457', 1486'-1488' 44 Holes Pumped 157, 598 scf 70% quality nitrogen foam with 20# 970'-973', 1027'-1036', 1047'-1050' 60 Holes Frac'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20#	Linear gel with 14, 064 lbs 20/40 sand. Linear gel with 21, 225 lbs 20/40 sand. Linear gel with 31, 684 lbs 20/40 sand.
13. Describe proposed or completed operations. (Clearly state all pertinent details, a of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 06/30/07 Superior ran Cement Bond Log. Estimated top of cement at 340'. 07/12/07 HES pumped 45 bbls of cement down hole. Circulated 1 bbl to pit. 08/14/07 Superior ren Cement Bond Log. Estimated top of cement to surface. 08/17/07 Superior Wireline perf'd 1st stage - 1745'-1749', 1810'-1814' 32 Holes HES frac'd 1st stage - Pumped 156, 720 scf 70% quality nitrogen foam with 20# Perf'd 2nd stage - 1606'- 1610', 1679'-1682' 28 Holes Frac'd 2nd stage - 1606'- 1610', 1679'-1682' 28 Holes Pumped 122, 838 scf 70% quality nitrogen foam with 20# Perf'd 3nd stage - 1410'-1414', 1452'-1457', 1486'-1488' 44 Holes Pumped 157, 598 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - 970'-973', 1027'-1036', 1047'-1050' 60 Holes	Linear gel with 14, 064 lbs 20/40 sand. Linear gel with 21, 225 lbs 20/40 sand. Linear gel with 31, 684 lbs 20/40 sand.
13. Describe proposed or completed operations. (Clearly state all pertinent details, a of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 06/30/07 Superior ran Cement Bond Log. Estimated top of cement at 340'. 07/12/07 HES pumped 45 bbls of cement down hole. Circulated 1 bbl to pit. 08/14/07 Superior ren Cement Bond Log. Estimated top of cement to surface. 08/17/07 Superior Wireline perf'd 1st stage - 1745'-1749', 1810'-1814' 32 Holes HES frac'd 1st stage - Pumped 156, 720 scf 70% quality nitrogen foam with 20# Perf'd 2nd stage - Pumped 156, 720 scf 70% quality nitrogen foam with 20# Perf'd 3rd stage - 1606'-1610', 1679'-1682' 28 Holes Pumped 122, 838 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 157, 598 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20#	Linear gel with 14, 064 lbs 20/40 sand. Linear gel with 21, 225 lbs 20/40 sand. Linear gel with 31, 684 lbs 20/40 sand.
13. Describe proposed or completed operations. (Clearly state all pertinent details, a of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 06/30/07 Superior ran Cement Bond Log. Estimated top of cement at 340'. 07/12/07 HES pumped 45 bbls of cement down hole. Circulated 1 bbl to pit. 08/14/07 Superior ren Cement Bond Log. Estimated top of cement to surface. 08/17/07 Superior Wireline perf'd 1st stage - 1745'-1749', 1810'-1814' 32 Holes HES frac'd 1st stage - Pumped 156, 720 scf 70% quality nitrogen foam with 20# Perf'd 2nd stage - Pumped 156, 720 scf 70% quality nitrogen foam with 20# Perf'd 3rd stage - Pumped 122, 838 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 157, 598 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# Prac'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# Pumped 246, 638 scf 70% quality nitrogen foam with 20# RIH tubing, rods and pump. Well is ready to be tested and put on product	Linear gel with 14, 064 lbs 20/40 sand. Linear gel with 21, 225 lbs 20/40 sand. Linear gel with 31, 684 lbs 20/40 sand.
13. Describe proposed or completed operations. (Clearly state all pertinent details, a of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 06/30/07 Superior ran Cement Bond Log. Estimated top of cement at 340'. 07/12/07 HES pumped 45 bbls of cement down hole. Circulated 1 bbl to pit. 08/14/07 Superior ren Cement Bond Log. Estimated top of cement to surface. 08/17/07 Superior Wireline perf'd 1st stage - 1745'-1749', 1810'-1814' 32 Holes HES frac'd 1st stage - Pumped 156, 720 scf 70% quality nitrogen foam with 20# Perf'd 2nd stage - Pumped 156, 720 scf 70% quality nitrogen foam with 20# Perf'd 3rd stage - Pumped 122, 838 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 157, 598 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 157, 598 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# 08/27/07 RIH tubing, rods and pump. Well is ready to be tested and put on product I hereby certify that the information above is true and complete to the best of my knowled	Linear gel with 14, 064 lbs 20/40 sand. Linear gel with 21, 225 lbs 20/40 sand. Linear gel with 31, 684 lbs 20/40 sand.
13. Describe proposed or completed operations. (Clearly state all pertinent details, a of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 06/30/07 Superior ran Cement Bond Log. Estimated top of cement at 340'. 07/12/07 HES pumped 45 bbls of cement down hole. Circulated 1 bbl to pit. 08/14/07 Superior ren Cement Bond Log. Estimated top of cement to surface. 08/17/07 Superior Wireline perf'd 1st stage - 1745'-1749', 1810'-1814' 32 Holes HES frac'd 1st stage - Pumped 156, 720 scf 70% quality nitrogen foam with 20# Perf'd 2nd stage - Pumped 156, 720 scf 70% quality nitrogen foam with 20# Perf'd 3rd stage - Pumped 122, 838 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 157, 598 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# Prac'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# Pumped 246, 638 scf 70% quality nitrogen foam with 20# RIH tubing, rods and pump. Well is ready to be tested and put on product	Linear gel with 14, 064 lbs 20/40 sand. Linear gel with 21, 225 lbs 20/40 sand. Linear gel with 31, 684 lbs 20/40 sand.
13. Describe proposed or completed operations. (Clearly state all pertinent details, a of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 06/30/07 Superior ran Cement Bond Log. Estimated top of cement at 340'. 07/12/07 HES pumped 45 bbls of cement down hole. Circulated 1 bbl to pit. 08/14/07 Superior ren Cement Bond Log. Estimated top of cement to surface. 08/17/07 Superior Wireline perf'd 1st stage - 1745'-1749', 1810'-1814' 32 Holes HES frac'd 1st stage - Pumped 156, 720 scf 70% quality nitrogen foam with 20# Perf'd 2nd stage - Pumped 156, 720 scf 70% quality nitrogen foam with 20# Perf'd 3rd stage - Pumped 122, 838 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 157, 598 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 157, 598 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# 08/27/07 RIH tubing, rods and pump. Well is ready to be tested and put on product I hereby certify that the information above is true and complete to the best of my knowled grade tank has been/will be constructed or closed according to NMOCD guidelines □, a general permit □	Linear gel with 14, 064 lbs 20/40 sand. Linear gel with 21, 225 lbs 20/40 sand. Linear gel with 31, 684 lbs 20/40 sand. ge and belief. I further certify that any pit or belowor an (attached) alternative OCD-approved plan .
13. Describe proposed or completed operations. (Clearly state all pertinent details, a of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 06/30/07 Superior ran Cement Bond Log. Estimated top of cement at 340'. 07/12/07 HES pumped 45 bbls of cement down hole. Circulated 1 bbl to pit. 08/14/07 Superior ren Cement Bond Log. Estimated top of cement to surface. 08/17/07 Superior Wireline perf'd 1st stage - 1745'-1749', 1810'-1814' 32 Holes HES frac'd 1st stage - Pumped 156, 720 scf 70% quality nitrogen foam with 20# Perf'd 2nd stage - 1606'-1610', 1679'-1682' 28 Holes Frac'd 3nd stage - Pumped 122, 838 scf 70% quality nitrogen foam with 20# Perf'd 3nd stage - Pumped 157, 598 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - 970'-973', 1027'-1036', 1047'-1050' 60 Holes Frac'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 246, 638 sc	Linear gel with 14, 064 lbs 20/40 sand. Linear gel with 21, 225 lbs 20/40 sand. Linear gel with 31, 684 lbs 20/40 sand. Linear gel with 31, 684 lbs 20/40 sand. Linear gel with 31, 684 lbs 20/40 sand. DATE 11/06/2007
13. Describe proposed or completed operations. (Clearly state all pertinent details, a of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 06/30/07 Superior ran Cement Bond Log. Estimated top of cement at 340'. 07/12/07 HES pumped 45 bbls of cement down hole. Circulated 1 bbl to pit. 08/14/07 Superior ren Cement Bond Log. Estimated top of cement to surface. 08/17/07 Superior Wireline perf'd 1st stage - 1745'-1749', 1810'-1814' 32 Holes HES frac'd 1st stage - Pumped 156, 720 scf 70% quality nitrogen foam with 20# Perf'd 2nd stage - Pumped 156, 720 scf 70% quality nitrogen foam with 20# Perf'd 3rd stage - Pumped 122, 838 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 157, 598 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 157, 598 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# 08/27/07 RIH tubing, rods and pump. Well is ready to be tested and put on product I hereby certify that the information above is true and complete to the best of my knowled grade tank has been/will be constructed or closed according to NMOCD guidelines □, a general permit □	Linear gel with 17, 689 lbs 20/40 sand. Linear gel with 14, 064 lbs 20/40 sand. Linear gel with 21, 225 lbs 20/40 sand. Linear gel with 31, 684 lbs 20/40 sand. ge and belief. I further certify that any pit or belowion an (attached) alternative OCD-approved plan DATE 11/06/2007
13. Describe proposed or completed operations. (Clearly state all pertinent details, a of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 06/30/07 Superior ran Cement Bond Log. Estimated top of cement at 340'. 07/12/07 HES pumped 45 bbls of cement down hole. Circulated 1 bbl to pit. 08/14/07 Superior ren Cement Bond Log. Estimated top of cement to surface. 08/17/07 Superior Wireline perf'd 1st stage - 1745'-1749', 1810'-1814' 32 Holes HES frac'd 1st stage - Pumped 156, 720 scf 70% quality nitrogen foam with 20# Perf'd 2nd stage - Pumped 122, 838 scf 70% quality nitrogen foam with 20# Perf'd 3nd stage - Pumped 157, 598 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 157, 598 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# 08/27/07 RIH tubing, rods and pump. Well is ready to be tested and put on product I hereby certify that the information above is true and complete to the best of my knowled grade tank has been/will be constructed or closed according to NMOCD guidelines □, a general permit □ SIGNATURE Shirley A Mitchell E-mail address: shirley.mitchell@elpaso.	Linear gel with 17, 689 lbs 20/40 sand. Linear gel with 14, 064 lbs 20/40 sand. Linear gel with 21, 225 lbs 20/40 sand. Linear gel with 31, 684 lbs 20/40 sand. ge and belief. I further certify that any pit or belowion an (attached) alternative OCD-approved plan DATE 11/06/2007
13. Describe proposed or completed operations. (Clearly state all pertinent details, a of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 06/30/07 Superior ran Cement Bond Log. Estimated top of cement at 340'. 07/12/07 HES pumped 45 bbls of cement down hole. Circulated 1 bbl to pit. 08/14/07 Superior ren Cement Bond Log. Estimated top of cement to surface. 08/17/07 Superior Wireline perf'd 1st stage - 1745'-1749', 1810'-1814' 32 Holes HES frac'd 1st stage - Pumped 156, 720 scf 70% quality nitrogen foam with 20# Perf'd 2nd stage - Pumped 156, 720 scf 70% quality nitrogen foam with 20# Perf'd 3rd stage - Pumped 122, 838 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 157, 598 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 157, 598 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# 08/27/07 RIH tubing, rods and pump. Well is ready to be tested and put on product 1 hereby certify that the information above is true and complete to the best of my knowled grade tank has been/will be constructed or closed according to NMOCD guidelines □, a general permit □ SIGNATURE Shirley A Mitchell □ E-mail address: shirley.mitchell@elpaso. For State Use Only	Linear gel with 14, 064 lbs 20/40 sand. Linear gel with 21, 225 lbs 20/40 sand. Linear gel with 31, 684 lbs 20/40 sand. Linear gel with 31, 684 lbs 20/40 sand. DATE 11/06/2007 Com Telephone No. (505) 445-6785
13. Describe proposed or completed operations. (Clearly state all pertinent details, a of starting any proposed work). SEE RULE 1103. For Multiple Completions: A or recompletion. 06/30/07 Superior ran Cement Bond Log. Estimated top of cement at 340'. 07/12/07 HES pumped 45 bbls of cement down hole. Circulated 1 bbl to pit. 08/14/07 Superior ren Cement Bond Log. Estimated top of cement to surface. 08/17/07 Superior Wireline perf'd 1st stage - 1745'-1749', 1810'-1814' 32 Holes HES frac'd 1st stage - Pumped 156, 720 scf 70% quality nitrogen foam with 20# Perf'd 2nd stage - Pumped 122, 838 scf 70% quality nitrogen foam with 20# Perf'd 3rd stage - Pumped 157, 598 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 157, 598 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# Perf'd 4th stage - Pumped 246, 638 scf 70% quality nitrogen foam with 20# 08/27/07 RIH tubing, rods and pump. Well is ready to be tested and put on product I hereby certify that the information above is true and complete to the best of my knowled grade tank has been/will be constructed or closed according to NMOCD guidelines □, a general permit □ SIGNATURE Shirley A Mitchell E-mail address: shirley.mitchell@elpaso.	Linear gel with 14, 064 lbs 20/40 sand. Linear gel with 21, 225 lbs 20/40 sand. Linear gel with 31, 684 lbs 20/40 sand. Linear gel with 31, 684 lbs 20/40 sand. DATE 11/06/2007 Com Telephone No. (505) 445-6785