

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis
Santa Fe, NM 87505

2007 NOV 30 PM 2 16

Form C-103
May 27, 2004

WELL API NO. 30-007-20885

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

VPR A

8. Well Number 369

9. OGRID Number 180514

10. Pool name or Wildcat
Stubblefield Canyon - Vermejo Gas

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well ☒ Other Coalbed Methane

2. Name of Operator

EL PASO E & P COMPANY, L.P.

3. Address of Operator

PO BOX 190, RATON, NM 87740

4. Well Location

Unit Letter F : 2032 feet from the North line and 1904 feet from the West line
Section 32 Township 31N Range 21E NMPM Colfax County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
8,030' (GL)

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water

Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: Completion ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

09/06/07 Superior ran Cement Bond Log. Estimated top of cement at 104'.
09/21/07 Superior Wireline perf'd 1st stage - 1920' - 1928', 1939' - 1942' 44 Holes
HES frac'd 1st stage - Pumped 194,153 scf 70% quality nitrogen foam with 20# Linear gel with 22,570 lbs 20/40 sand.
✓ Shot squeeze holes at 1710' - 1711'. Pumped 199 sks cement down hole. Circulated 3 bbls of cement to surface.
09/26/07 Ran Cement Bond Log. Estimated top of cement at surface.
10/03/07 Perf'd 2nd stage - 1162' - 1165', 1269' - 1272' 24 Holes
Frac'd 2nd stage - Pumped 152,349 scf 70% quality nitrogen foam with 20# Linear gel with 10,230 lbs 20/40 sand.
10/04/07 Perf'd 3rd stage - 1096' - 1100' 16 Holes
Frac'd 3rd stage - Pumped 124,351 scf 70% quality nitrogen foam with 20# Linear gel with 14,326 lbs 20/40 sand.
10/09/07 RIH tubing, rods and pump. Well is ready to be tested and put on production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Shirley Mitchell TITLE Regulatory Analyst DATE 11/29/2007
Type or print name Shirley A Mitchell E-mail address: shirley.mitchell@elpaso.com Telephone No. (505) 445-6785

For State Use Only

APPROVED BY: Ed Martin TITLE DISTRICT SUPERVISOR DATE 12/3/07
Conditions of Approval (if any):