

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

2008 JUL 14 PM 12 26

WELL API NO. 30-007-20878

Indicate Type of Lease

STATE ☐ FEE ☒

State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well ☒ Other Coalbed Methane

2. Name of Operator

EL PASO E & P COMPANY, L.P.

3. Address of Operator

PO BOX 190, RATON, NM 87740

4. Well Location

Unit Letter D : 1057 feet from the North line and 743 feet from the West line

Section 34 Township 31N Range 21E NMPM Colfax County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

8,017' (GL)

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water

Pit Liner Thickness: mil Below-Grade Tank: Volume bbls: Construction Material

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ P AND A ☐

CASING/CEMENT JOB ☐

OTHER: Completion ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

03/20/08 Weatherford ran Cement Bond Log. Estimated cement top at 100'.

04/17/08 Weatherford perf'd 1st stage - 1753'-1756', 1792'-1798' 36 Holes

HES frac'd 1st stage - Pumped 126,630 scf 70% quality nitrogen foam with 20# Linear gel with 16,216 lbs 20/40 sand.

Perf'd 2nd stage - 1563'-1566', 1584'-1588' 28 Holes

Frac'd 2nd stage - Pumped 106,064 scf 70% quality nitrogen foam with 20# Linear gel with 10,792 lbs 20/40 sand.

Perf'd 3rd stage - 1060'-1062', 1082'-1084', 1120'-1023', 1145'-1148' 40 Holes

Frac'd 3rd stage - Pumped 275,329 scf 70% quality nitrogen foam with 20# Linear gel with 14,621 lbs 20/40 sand.

04/25/08 RIH tubing, rods and pump. Well is ready to be tested and put on production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Shirley Mitchell TITLE Regulatory Analyst DATE 06/25/08

Type or print name Shirley A Mitchell E-mail address: shirley.mitchell@elpaso.com Telephone No. (505) 445-6785

For State Use Only

APPROVED BY: Ed Martin TITLE DISTRICT SUPERVISOR DATE 7/15/08

Conditions of Approval (if any):