Submit 3 Copies To Appropriate District	State of New Me	exico	Form C-103
Office <u>District I</u>	Energy, Minerals and Natu	ral Resources	May 27, 2004
1625 N. French Dr., Hobbs, NM 88240 District II	i e e e e e e e e e e e e e e e e e e e		WELL API NO. 30-007-20922
1201 W. G. T. L. A. C. NILLON OIL CONSERVATION DIVISION		5. Indicate Type of Lease	
<u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Fran	icis Dr. 🖒	STATE FEE S
District IV	Santa Fe, NM 8	7505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505	2008 AUG 12	PM 2 39	
SUNDRY NOTICES AND REPORTS ON WELLS		7. Lease Name or Unit Agreement Name	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A			
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		VPR A	
1. Type of Well: Oil Well	Gas Well 🛛 Other Coalbed M	lethane	8. Well Number 504
2. Name of Operator		9. OGRID Number 180514	
EL PASO E & P COMPANY, L.P. 3. Address of Operator		10. Pool name or Wildcat	
3. Address of Operator PO BOX 190, RATON, NM 87740			Stubblefield Canyon – Vermejo Gas
4. Well Location			
Unit Letter <u>H</u> : <u>2466</u> feet from the <u>North</u> line and <u>326</u> feet from the <u>East</u> line			
Section 10 Towns			Colfax County
	11. Elevation (Show whether DR		
	8,332' (G	L)	The state of the s
Pit or Below-grade Tank Application [] or			
Pit typeDepth to Groundwa	terDistance from nearest fresh v	vater well Dist	tance from nearest surface water
Pit Liner Thickness: mil	Below-Grade Tank: Volume	bbls; Co	onstruction Material
12. Check A	ppropriate Box to Indicate N	ature of Notice,	Report or Other Data
PERFORM REMEDIAL WORK		REMEDIAL WOR	SEQUENT REPORT OF: K
	CHANGE PLANS	COMMENCE DRI	_
TEIVII OTOTTICE ABATTADON	OUVITOR I EVITO	OCIVINIE IVOL DIVI	
PULL OR ALTER CASING	MULTIPLE COMPI	CASING/CEMEN	TJOB 🗆
PULL OR ALTER CASING	MULTIPLE COMPL	CASING/CEMEN	-
OTHER:	_	OTHER:	 Completion ⊠
OTHER: 13. Describe proposed or compl	eted operations. (Clearly state all	OTHER: pertinent details, and	Completion d give pertinent dates, including estimated date
OTHER: 13. Describe proposed or compl of starting any proposed wor	eted operations. (Clearly state all	OTHER: pertinent details, and	 Completion ⊠
OTHER: 13. Describe proposed or compl	eted operations. (Clearly state all rk). SEE RULE 1103. For Multip	OTHER: pertinent details, and le Completions: At	Completion d give pertinent dates, including estimated date
OTHER: 13. Describe proposed or compl of starting any proposed wor or recompletion. 02/17/08 Weatherford ran Cement Book 15/08 Weatherford perf'd 1st stage.	eted operations. (Clearly state all rk). SEE RULE 1103. For Multipond Log. Estimated top of cement at e = 2407'- 2409', 2445'- 2448', 248	OTHER: pertinent details, and le Completions: At 1850'. 66'- 2489' 32 Holes	Completion d give pertinent dates, including estimated date tach wellbore diagram of proposed completion
OTHER: 13. Describe proposed or compl of starting any proposed wor or recompletion. 02/17/08 Weatherford ran Cement Bound of the stage of the stag	eted operations. (Clearly state all rk). SEE RULE 1103. For Multip and Log. Estimated top of cement at e - 2407'- 2409', 2445'- 2448', 248 ped 115,180 scf 70% quality nitrog	OTHER: pertinent details, and le Completions: At 1850'. 66'- 2489' 32 Holes gen foam with 20# 1	Completion d give pertinent dates, including estimated date tach wellbore diagram of proposed completion Linear gel with 18,590 lbs 20/40 sand.
OTHER: 13. Describe proposed or complor of starting any proposed work or recompletion. 02/17/08 Weatherford ran Cement Bound of the stage of the s	eted operations. (Clearly state all rk). SEE RULE 1103. For Multip and Log. Estimated top of cement at e = 2407'- 2409', 2445'- 2448', 248 ped 115,180 scf 70% quality nitrogr'- 2259', 2298'- 2301', 2307'- 2311'.	OTHER: pertinent details, and le Completions: At 1850'. 16'- 2489' 32 Holes gen foam with 20# 1,2364'- 2367' 48 Ho	Completion d give pertinent dates, including estimated date tach wellbore diagram of proposed completion Linear gel with 18,590 lbs 20/40 sand. oles
OTHER: 13. Describe proposed or complof starting any proposed work or recompletion. 02/17/08 Weatherford ran Cement Bound of Starting any proposed work or recompletion. 04/15/08 Weatherford perf'd 1st stage HES frac'd 1st stage - Pum Perf'd 2nd stage - Pum Perf'd 2nd stage - Pum Perf'd 3rd stag	eted operations. (Clearly state all rk). SEE RULE 1103. For Multip and Log. Estimated top of cement at e = 2407'- 2409', 2445'- 2448', 248 ped 115,180 scf 70% quality nitrogr'- 2259', 2298'- 2301', 2307'- 2311', ped 190,153 scf 70% quality nitrogo'- 1973', 2016'- 2018', 2061'- 2064'	OTHER: pertinent details, and le Completions: At 1850'. 16'- 2489' 32 Holes gen foam with 20# 1,2364'- 2367' 48 Holes 32 Holes	Completion description descri
OTHER: 13. Describe proposed or completion of starting any proposed work or recompletion. 02/17/08 Weatherford ran Cement Bound of Starting any proposed work or recompletion. 02/17/08 Weatherford part of 1st stage HES frac'd 1st stage - Pum Perf'd 2nd stage - Pum Perf'd 3rd stage - Pum Pum Pe	eted operations. (Clearly state all rk). SEE RULE 1103. For Multip and Log. Estimated top of cement at e - 2407'-2409', 2445'-2448', 248 ped 115,180 scf 70% quality nitrogree 190,153 scf 70% quality nitrogree 1973', 2016'-2018', 2061'-2064' aped 112,009 scf 70 % quality nitrogree 112,009 scf 70	OTHER: pertinent details, and le Completions: At 1850'. 16'- 2489' 32 Holes gen foam with 20# 1,2364'- 2367' 48 Holes gen foam with 20# L 32 Holes gen foam with 20# L	Completion degive pertinent dates, including estimated date tach wellbore diagram of proposed completion Linear gel with 18,590 lbs 20/40 sand. Joles Linear gel with 34,371 lbs 20/40 sand. Linear gel with 13,127 lbs 20/40 sand.
OTHER: 13. Describe proposed or completion of starting any proposed work or recompletion. 02/17/08 Weatherford ran Cement Bound of Starting any proposed work or recompletion. 04/15/08 Weatherford perf d 1st stage HES frac'd 1st stage - Pum Perf'd 2nd stage - Pum Perf'd 3rd stage - Pum Pum Perf'd 3rd stage - Pum Pum Perf'd 3rd stage - Pum	eted operations. (Clearly state all rk). SEE RULE 1103. For Multip and Log. Estimated top of cement at e - 2407'-2409', 2445'-2448', 248 ped 115,180 scf 70% quality nitrogree 190,153 scf 70% quality nitrogree 1973', 2016'-2018', 2061'-2064' aped 112,009 scf 70 % quality nitrogree 187 sks of cement. Circu	oTHER: pertinent details, and le Completions: At 1850'. 16'- 2489' 32 Holes gen foam with 20# 1, 2364'- 2367' 48 Hogen foam with 20# L 32 Holes ogen foam with 20# L alated 9 bbls to sur	Completion degive pertinent dates, including estimated date tach wellbore diagram of proposed completion Linear gel with 18,590 lbs 20/40 sand. Joles Linear gel with 34,371 lbs 20/40 sand. Linear gel with 13,127 lbs 20/40 sand.
OTHER: 13. Describe proposed or completion of starting any proposed work or recompletion. 02/17/08 Weatherford ran Cement Boto 04/15/08 Weatherford perf'd 1st stage HES frac'd 1st stage - Pum Perf'd 2nd stage - 225' Frac'd 2nd stage - Pum Perf'd 3rd	eted operations. (Clearly state all rk). SEE RULE 1103. For Multip and Log. Estimated top of cement at e - 2407'-2409', 2445'-2448', 248 ped 115,180 scf 70% quality nitrogree 190,153 scf 70% quality nitrogree 190,153 scf 70% quality nitrogree 1973', 2016'-2018', 2061'-2064' aped 112,009 scf 70 % quality nitrogree 187 sks of cement. Circulated 187 sks of cement ant down hole. Circulated 2 bbls to set a set of the condition of th	OTHER: pertinent details, and le Completions: At 1850'. 16'-2489' 32 Holes gen foam with 20# L 32 Holes ogen foam with 20# L 32 Holes ogen foam with 20# L alated 9 bbls to surt 353'. Eurface.	Completion degive pertinent dates, including estimated date tach wellbore diagram of proposed completion Linear gel with 18,590 lbs 20/40 sand. Joles Linear gel with 34,371 lbs 20/40 sand. Linear gel with 13,127 lbs 20/40 sand.
OTHER: 13. Describe proposed or complete of starting any proposed work or recompletion. 02/17/08 Weatherford ran Cement Bound of Starting any proposed work or recompletion. 04/15/08 Weatherford perf'd 1st stage HES frac'd 1st stage - Pum Perf'd 2nd stage - Pum Perf'd 3rd	eted operations. (Clearly state all rk). SEE RULE 1103. For Multip and Log. Estimated top of cement at e - 2407'-2409', 2445'-2448', 248 ped 115,180 scf 70% quality nitrogree 190,153 scf 70% quality nitrogree 190,153 scf 70% quality nitrogree 1973', 2016'-2018', 2061'-2064' aped 112,009 scf 70% quality nitrogree 187 sks of cement. Circulated 190,153 scf 70% quality nitrogree 187 sks of cement. Circulated 2 bbls to son Log. Estimated top of cement at	oTHER: pertinent details, and le Completions: At 1850'. 16'-2489' 32 Holes gen foam with 20# L 32 Holes ogen foam with 20# L 32 Holes ogen foam with 20# L alated 9 bbls to surt 353'. Surface.	Completion degive pertinent dates, including estimated date tach wellbore diagram of proposed completion Linear gel with 18,590 lbs 20/40 sand. oles Linear gel with 34,371 lbs 20/40 sand. Linear gel with 13,127 lbs 20/40 sand. face.
OTHER: 13. Describe proposed or completion of starting any proposed work or recompletion. 02/17/08 Weatherford ran Cement Bound of Starting any proposed work or recompletion. 04/15/08 Weatherford perf'd 1st stage HES frac'd 1st stage - Pum Perf'd 2nd stage - Pum Perf'd 3rd stage - Pum Squeeze perfs 1710'- 1711'. 04/28/08 Weatherford ran Cement Bound of Solonia Weatherford ran Cement Bound of Solonia Perf'd 4th stage - 1150	eted operations. (Clearly state all rk). SEE RULE 1103. For Multip and Log. Estimated top of cement at e - 2407'-2409', 2445'-2448', 248 ped 115,180 scf 70% quality nitrogree 190,153 scf 70% quality nitrogree 1973', 2016'-2018', 2061'-2064' aped 112,009 scf 70% quality nitrogree 187 sks of cement. Circulated 190,153 scf 70% quality nitrogree 187 sks of cement. Circulated 2 bbls to som Log. Estimated top of cement at '-1153', 1168'-1172', 1185'-1187',	oTHER: pertinent details, and le Completions: At 1850'. 16'- 2489' 32 Holes gen foam with 20# L 32 Holes ogen foam with 20# L 32 Holes ogen foam with 20# L alated 9 bbls to sur t 353'. Surface. 1232'- 1237', 1260'-	Completion degive pertinent dates, including estimated date tach wellbore diagram of proposed completion Linear gel with 18,590 lbs 20/40 sand. Joles Linear gel with 34,371 lbs 20/40 sand. Linear gel with 13,127 lbs 20/40 sand. Linear gel with 13,127 lbs 20/40 sand. Linear gel with 13,127 lbs 20/40 sand.
OTHER: 13. Describe proposed or completion of starting any proposed work or recompletion. 02/17/08 Weatherford ran Cement Both 15/08 Weatherford perf'd 1st stage HES frac'd 1st stage - Pum Perf'd 2nd stage - 225 Frac'd 2nd stage - Pum Perf'd 3rd stage - Pum Perf'd 5th stage - 1150 Perf'd 4th stage - Pum Perf'd 5th sta	eted operations. (Clearly state all rk). SEE RULE 1103. For Multip and Log. Estimated top of cement at e - 2407'-2409', 2445'-2448', 248 ped 115,180 scf 70% quality nitrogor'-2259', 2298'-2301', 2307'-2311' ped 190,153 scf 70% quality nitrogor'-1973', 2016'-2018', 2061'-2064' ped 112,009 scf 70 % quality nitrogord Log. Estimated top of cement and down hole. Circulated 2 bbls to so the Log. Estimated top of cement at '-1153', 1168'-1172', 1185'-1187', ped 285,831 scf 70% quality nitrogor'-1032', 1037'-1040', 1060'-1062',	OTHER: pertinent details, and le Completions: At 1850'. 16'- 2489' 32 Holes gen foam with 20# L 32 Holes ogen foam with 20# L 32 Holes ogen foam with 20# L alated 9 bbls to sur t 353'. 10 surface. 1232'- 1237', 1260'- en foam with 20# Lin 1082'- 1086', 1098'-	Completion degive pertinent dates, including estimated date tach wellbore diagram of proposed completion Linear gel with 18,590 lbs 20/40 sand. Joles Linear gel with 34,371 lbs 20/40 sand. Linear gel with 13,127 lbs 20/40 sand. Linear gel with 60,733 lbs 20/40 sand. 1111', 1119'- 1122' 72 Holes
OTHER: 13. Describe proposed or completion of starting any proposed work or recompletion. 02/17/08 Weatherford ran Cement Both 15/08 Weatherford perf'd 1st stage HES frac'd 1st stage - Pum Perf'd 2nd stage - 225' Frac'd 2nd stage - Pum Perf'd 3rd stage - Pum Perf'd 5th sta	eted operations. (Clearly state all rk). SEE RULE 1103. For Multip and Log. Estimated top of cement at e - 2407'-2409', 2445'-2448', 248 ped 115,180 scf 70% quality nitrogor'-2259', 2298'-2301', 2307'-2311' ped 190,153 scf 70% quality nitrogor'-1973', 2016'-2018', 2061'-2064' ped 112,009 scf 70 % quality nitrogord Log. Estimated top of cement and down hole. Circulated 2 bbls to so the Log. Estimated top of cement at '-1153', 1168'-1172', 1185'-1187', ped 285,831 scf 70% quality nitrogor'-1032', 1037'-1040', 1060'-1062', ped 144,409 scf 70% quality nitrogory	OTHER: pertinent details, and le Completions: At 1850'. 16'- 2489' 32 Holes gen foam with 20# L 32 Holes ogen foam with 20# L 32 Holes ogen foam with 20# L alated 9 bbls to sur t 353'. 10 surface. 1232'- 1237', 1260'- 1082'- 1086', 1098'- 1098 ogen foam with 20# Lin 1082'- 1086', 1098'- 1099 ogen foam with 20# Lin 1082'- 1086', 1098'- 1099 ogen foam with 20# Lin 1082'- 1086', 1098'- 1099 ogen foam with 20# Lin 1082'- 1086', 1098'- 1099 ogen foam with 20# Lin 1082'- 1086', 1098'- 1099 ogen foam with 20# Lin 1082'- 1086', 1098'-	Completion degive pertinent dates, including estimated date tach wellbore diagram of proposed completion Linear gel with 18,590 lbs 20/40 sand. Joles Linear gel with 34,371 lbs 20/40 sand. Linear gel with 13,127 lbs 20/40 sand. Linear gel with 13,127 lbs 20/40 sand. Linear gel with 13,127 lbs 20/40 sand.
OTHER: 13. Describe proposed or completion of starting any proposed work or recompletion. 02/17/08 Weatherford ran Cement Both 15/08 Weatherford perf'd 1st stage HES frac'd 1st stage - Pum Perf'd 2nd stage - Pum Perf'd 3rd stage - Pum Perf'd 5rd stag	eted operations. (Clearly state all rk). SEE RULE 1103. For Multip and Log. Estimated top of cement at e - 2407'-2409', 2445'-2448', 248 ped 115,180 scf 70% quality nitrog 7'-2259', 2298'-2301', 2307'-2311' ped 190,153 scf 70% quality nitrog 0'-1973', 2016'-2018', 2061'-2064' ped 112,009 scf 70 % quality nitrog Pumped 187 sks of cement. Circulated 190,153 scf 70% quality nitrog number 187 sks of cement and down hole. Circulated 2 bbls to so n Log. Estimated top of cement at '-1153', 1168'-1172', 1185'-1187', ped 285,831 scf 70% quality nitrog 2'-1032', 1037'-1040', 1060'-1062', ped 144,409 scf 70% quality nitrog 806', 823'-825', 860'-864', 900'-9	oTHER: pertinent details, and le Completions: At 1850'. 16'-2489' 32 Holes gen foam with 20# L 32 Holes ogen foam with 20# L 32 Holes ogen foam with 20# L alated 9 bbls to sur t 353'. 10 surface. 1232'-1237', 1260'-1082'-1086', 1098'-1086', 1098'-1086', 1098'-1080', 1080',	Completion degive pertinent dates, including estimated date tach wellbore diagram of proposed completion Linear gel with 18,590 lbs 20/40 sand. oles Linear gel with 34,371 lbs 20/40 sand. Linear gel with 13,127 lbs 20/40 sand. face. 1262', 1277'- 1287' 104 Holes lear gel with 60,733 lbs 20/40 sand. 1111', 1119'- 1122' 72 Holes linear gel with 43,612 lbs 20/40 sand.
OTHER: 13. Describe proposed or completion of starting any proposed work or recompletion. 02/17/08 Weatherford ran Cement Bound of Starting any proposed work or recompletion. 02/17/08 Weatherford ran Cement Bound of Stage weatherford perf'd 1st stage was perf'd 2nd stage was perf'd 2nd stage perf'd 3rd stage pumped 53 sks of cement Bound of Stage weatherford ran Cement Bound of Stage weatherford ran Cement Bound of Stage perf'd 4th stage pumped 51 stage perf'd 5th stage pumped 5th stage pumped 5th stage perf'd 5th stage pumped 5th stage pumped 5th stage perf'd 5th stage pumped 5th stage perf'd 5th stage pumped 5th stage perf'd 5th stage perf'd 5th stage pumped 5th stage perf'd 5th stage perf'd 5th stage pumped 5th stage perf'd 5th stage perf'd 5th stage pumped 5th stage perf'd 5th stage perf'd 5th stage pumped 5th stage perf'd 5th stage pumped 5th stage perf'd 5th stage perf'd 5th stage pumped 5th stage perf'd 5th stage perf	eted operations. (Clearly state all rk). SEE RULE 1103. For Multip and Log. Estimated top of cement at e = 2407'-2409', 2445'-2448', 248 ped 115,180 scf 70% quality nitrog 7'-2259', 2298'-2301', 2307'-2311' ped 190,153 scf 70% quality nitrog 0'-1973', 2016'-2018', 2061'-2064' ped 112,009 scf 70 % quality nitrog Pumped 187 sks of cement. Circulated 187 sks of cement. Circulated 2 bbls to so n Log. Estimated top of cement at at down hole. Circulated 2 bbls to so n Log. Estimated top of cement at '-1153', 1168'-1172', 1185'-1187', ped 285,831 scf 70% quality nitroge 144,409 scf 70% quality nitroge 806', 823'-825', 860'-864', 900'-9 ped 149,325 scf 70% quality nitroge	oTHER: pertinent details, and le Completions: At 1850'. 16'-2489' 32 Holes gen foam with 20# 1,2364'-2367' 48 Hogen foam with 20# L 32 Holes ogen foam with 20# L alated 9 bbls to sur t 353'. 1017ace. 1232'-1237', 1260'-1080'-1082'-1086', 1098'-1086', 1098'-1080'-1	Completion
OTHER: 13. Describe proposed or completion of starting any proposed work or recompletion. 02/17/08 Weatherford ran Cement Bound of Starting any proposed work or recompletion. 02/17/08 Weatherford ran Cement Bound of Stage weatherford perf'd 1st stage was perf'd 2nd stage was perf'd 2nd stage perf'd 3rd stage pumped 53 sks of cement Bound of Stage weatherford ran Cement Bound of Stage weatherford ran Cement Bound of Stage perf'd 4th stage pumped 51 stage perf'd 5th stage pumped 5th stage pumped 5th stage perf'd 5th stage pumped 5th stage pumped 5th stage perf'd 5th stage pumped 5th stage perf'd 5th stage pumped 5th stage perf'd 5th stage perf'd 5th stage pumped 5th stage perf'd 5th stage perf'd 5th stage pumped 5th stage perf'd 5th stage perf'd 5th stage pumped 5th stage perf'd 5th stage perf'd 5th stage pumped 5th stage perf'd 5th stage pumped 5th stage perf'd 5th stage perf'd 5th stage pumped 5th stage perf'd 5th stage perf	eted operations. (Clearly state all rk). SEE RULE 1103. For Multip and Log. Estimated top of cement at e - 2407'-2409', 2445'-2448', 248 ped 115,180 scf 70% quality nitrog 7'-2259', 2298'-2301', 2307'-2311' ped 190,153 scf 70% quality nitrog 0'-1973', 2016'-2018', 2061'-2064' ped 112,009 scf 70 % quality nitrog Pumped 187 sks of cement. Circulated 190,153 scf 70% quality nitrog number 187 sks of cement and down hole. Circulated 2 bbls to so n Log. Estimated top of cement at '-1153', 1168'-1172', 1185'-1187', ped 285,831 scf 70% quality nitrog 2'-1032', 1037'-1040', 1060'-1062', ped 144,409 scf 70% quality nitrog 806', 823'-825', 860'-864', 900'-9	oTHER: pertinent details, and le Completions: At 1850'. 16'-2489' 32 Holes gen foam with 20# 1,2364'-2367' 48 Hogen foam with 20# L 32 Holes ogen foam with 20# L alated 9 bbls to sur t 353'. 1017ace. 1232'-1237', 1260'-1080'-1082'-1086', 1098'-1086', 1098'-1080'-1	Completion
OTHER: 13. Describe proposed or complof starting any proposed work or recompletion. 02/17/08 Weatherford ran Cement Bour of Starting any proposed work or recompletion. 02/17/08 Weatherford ran Cement Bour of Stage Weatherford perf'd 1st stage Pum Perf'd 2nd stage Pum Perf'd 3rd stage Pum Perf'd 3rd stage Pum Perf'd 3rd stage Pum Perf'd 3rd stage Pum Squeeze perfs 1710' - 1711'. 04/28/08 Squeeze perfs 1710' - 1711'. 04/28/08 Weatherford ran Cement Bour of Solo Solo Weatherford ran Cement Bour of Solo Solo Weatherford ran Cement Bour of Solo Solo Solo Solo Solo Solo Solo S	eted operations. (Clearly state all rk). SEE RULE 1103. For Multip and Log. Estimated top of cement at e = 2407'-2409', 2445'-2448', 248 ped 115,180 scf 70% quality nitrog 7'-2259', 2298'-2301', 2307'-2311' ped 190,153 scf 70% quality nitrog 0'-1973', 2016'-2018', 2061'-2064' ped 112,009 scf 70 % quality nitrog Pumped 187 sks of cement. Circulated Log. Estimated top of cement and down hole. Circulated 2 bbls to so the conduction of the cond	OTHER: pertinent details, and le Completions: At ta 1850'. 66'- 2489' 32 Holes gen foam with 20# L 32 Holes ogen foam with 20# L 32 Holes ogen foam with 20# L alated 9 bbls to sur ta 353'. surface. 1232'- 1237', 1260'-ten foam with 20# Lin 1082'- 1086', 1098'-gen foam with 20# Lin 1082'- 1086' Holes on foam with 20# Lin 1082	Completion d give pertinent dates, including estimated date tach wellbore diagram of proposed completion Linear gel with 18,590 lbs 20/40 sand. oles Linear gel with 34,371 lbs 20/40 sand. Linear gel with 13,127 lbs 20/40 sand. face. 1262', 1277'- 1287' 104 Holes lear gel with 60,733 lbs 20/40 sand. 1111', 1119'- 1122' 72 Holes linear gel with 43,612 lbs 20/40 sand. ear gel with 26,604 lbs 20/40 sand. on.
OTHER: 13. Describe proposed or complof starting any proposed work or recompletion. 02/17/08 Weatherford ran Cement Bour of Starting any proposed work or recompletion. 02/17/08 Weatherford ran Cement Bour of Stage - Pum Perf'd 2nd stage - Pum Perf'd 3rd stage - Pum Squeeze perfs 1710' - 1711'. 04/28/08 Squeeze perfs 1710' - 1711'. 04/28/08 Weatherford ran Cement Bour of Solo Solo Weatherford ran Cement Bour of Solo Solo Solo Solo Search of Stage - Pum Perf'd 4th stage - Pum Perf'd 5th stage - Pum Perf'd 6th stage - Pum Perf'd 6th stage - Pum O5/16/08 Coil Tubing clean out. 05/20/08 RIH tubing, rods and pur I hereby certify that the information as	eted operations. (Clearly state all rk). SEE RULE 1103. For Multip and Log. Estimated top of cement at e = 2407'-2409', 2445'-2448', 248 ped 115,180 scf 70% quality nitrog 7'-2259', 2298'-2301', 2307'-2311' ped 190,153 scf 70% quality nitrog 0'-1973', 2016'-2018', 2061'-2064' ped 112,009 scf 70 % quality nitrog Pumped 187 sks of cement. Circulated Log. Estimated top of cement at down hole. Circulated 2 bbls to son Log. Estimated top of cement at '-1153', 1168'-1172', 1185'-1187', ped 285,831 scf 70% quality nitrog 0'-1032', 1037'-1040', 1060'-1062', ped 144,409 scf 70% quality nitroge-806', 823'-825', 860'-864', 900'-9 ped 149,325 scf 70% quality nitrogemp. Well is ready to be tested and above is true and complete to the b	OTHER: pertinent details, and le Completions: At the 1850'. 66'- 2489' 32 Holes gen foam with 20# L 32 Holes ogen foam with 20# L 32 Holes ogen foam with 20# L 1814 1853'. Surface. 1232'- 1237', 1260'-the foam with 20# Line 1082'- 1086', 1098'-gen foam with 20# Line 1082'- 1080' 10	Completion d give pertinent dates, including estimated date tach wellbore diagram of proposed completion Linear gel with 18,590 lbs 20/40 sand. oles Linear gel with 34,371 lbs 20/40 sand. Linear gel with 13,127 lbs 20/40 sand. face. 1262', 1277'- 1287' 104 Holes lear gel with 60,733 lbs 20/40 sand. 1111', 1119'- 1122' 72 Holes linear gel with 43,612 lbs 20/40 sand. ear gel with 26,604 lbs 20/40 sand. on.
OTHER: 13. Describe proposed or complof starting any proposed work or recompletion. 02/17/08 Weatherford ran Cement Bour of Starting any proposed work or recompletion. 02/17/08 Weatherford ran Cement Bour of Stage - Pum Perf'd 2nd stage - Pum Perf'd 3rd stage - Pum Squeeze perfs 1710' - 1711'. 04/28/08 Squeeze perfs 1710' - 1711'. 04/28/08 Weatherford ran Cement Bour of Solo Solo Weatherford ran Cement Bour of Solo Solo Solo Solo Search of Stage - Pum Perf'd 4th stage - Pum Perf'd 5th stage - Pum Perf'd 6th stage - Pum Perf'd 6th stage - Pum O5/16/08 Coil Tubing clean out. 05/20/08 RIH tubing, rods and pur I hereby certify that the information as	eted operations. (Clearly state all rk). SEE RULE 1103. For Multip and Log. Estimated top of cement at e = 2407'-2409', 2445'-2448', 248 ped 115,180 scf 70% quality nitrog 7'-2259', 2298'-2301', 2307'-2311' ped 190,153 scf 70% quality nitrog 0'-1973', 2016'-2018', 2061'-2064' aped 112,009 scf 70 % quality nitrog Pumped 187 sks of cement. Circulated Log. Estimated top of cement at the down hole. Circulated 2 bbls to so and Log. Estimated top of cement at '-1153', 1168'-1172', 1185'-1187', ped 285,831 scf 70% quality nitroge 144,409 scf 70% quality nitroge 2'-1032', 1037'-1040', 1060'-1062', ped 144,409 scf 70% quality nitroge 806', 823'-825', 860'-864', 900'-9 ped 149,325 scf 70% quality nitroge mp. Well is ready to be tested and above is true and complete to the belosed according to NMOCD guidelines [school of the second of the se	OTHER: pertinent details, and le Completions: At the 1850'. 66'- 2489' 32 Holes gen foam with 20# L 32 Holes ogen foam with 20# L 32 Holes ogen foam with 20# L 1814 1853'. Surface. 1232'- 1237', 1260'-the foam with 20# Line 1082'- 1086', 1098'-gen foam with 20# Line 1082'- 1080' 10	Completion d give pertinent dates, including estimated date tach wellbore diagram of proposed completion Linear gel with 18,590 lbs 20/40 sand. oles Linear gel with 34,371 lbs 20/40 sand. Linear gel with 13,127 lbs 20/40 sand. face. 1262', 1277'- 1287' 104 Holes lear gel with 60,733 lbs 20/40 sand. 1111', 1119'- 1122' 72 Holes linear gel with 43,612 lbs 20/40 sand. ear gel with 26,604 lbs 20/40 sand. on.
OTHER: 13. Describe proposed or completion of starting any proposed work or recompletion. 02/17/08 Weatherford ran Cement Both 15/08 Weatherford perf d 1st stage HES frac'd 1st stage - Pum Perf'd 2nd stage - 225 Frac'd 2nd stage - Pum Perf'd 3rd stage - Pum Perf'd 5th stage - 1150 Frac'd 4th stage - Pum Perf'd 5th sta	eted operations. (Clearly state all rk). SEE RULE 1103. For Multip and Log. Estimated top of cement at e = 2407'-2409', 2445'-2448', 248 ped 115,180 scf 70% quality nitrogor'-2259', 2298'-2301', 2307'-2311' ped 190,153 scf 70% quality nitrogor'-1973', 2016'-2018', 2061'-2064' ped 112,009 scf 70 % quality nitrogord Log. Estimated top of cement and down hole. Circulated 2 bbls to so and Log. Estimated top of cement at '-1153', 1168'-1172', 1185'-1187', ped 285,831 scf 70% quality nitrogor'-1032', 1037'-1040', 1060'-1062', ped 144,409 scf 70% quality nitrogor'-1032', 1037'-1040', 1060'-1062', ped 144,409 scf 70% quality nitrogory-1032', 1037'-1040', 1060'-1062', ped 149,325 scf 70% quality nitrogory-1050', 1050', 1050'-1050', 1050'-1050', 1050'-1050', 1050'-1050', 1050'-1050', 1050'-1050', 1050'-1050', 1050'-1050', 1050'-1050', 1050'-1050', 1050'-1050', 1050'-1050', 1050'-1050', 1050'-1050', 1050'-1050', 1050'-1050', 1050'-1050', 1050'-1050', 1050'-1050', 1050', 1050'-1050', 1050'-1050', 1050'-1050', 1050', 1050', 1050'-1050', 10	OTHER: pertinent details, and le Completions: At the Research of the Research	Completion d give pertinent dates, including estimated date tach wellbore diagram of proposed completion Linear gel with 18,590 lbs 20/40 sand. oles Linear gel with 34,371 lbs 20/40 sand. Linear gel with 13,127 lbs 20/40 sand. face. 1262', 1277'- 1287' 104 Holes lear gel with 60,733 lbs 20/40 sand. 1111', 1119'- 1122' 72 Holes lear gel with 43,612 lbs 20/40 sand. ear gel with 26,604 lbs 20/40 sand. on. e and belief. I further certify that any pit or belowor an (attached) alternative OCD-approved plan □. Linealyst DATE 08/05/08
OTHER: 13. Describe proposed or completion of starting any proposed work or recompletion. 02/17/08 Weatherford ran Cement Both 15/08 Weatherford perf'd 1st stage HES frac'd 1st stage - Pum Perf'd 2nd stage - Pum Perf'd 3rd stage - Pum Perf'd 5rd stage - Pum Perf'd 4rd stage - Pum Perf'd 5th stage - Pum Perf'd 6th stage - Pum Perf'd 5th stag	eted operations. (Clearly state all rk). SEE RULE 1103. For Multip and Log. Estimated top of cement at e - 2407'- 2409', 2445'- 2448', 248 ped 115,180 scf 70% quality nitrogor'- 2259', 2298'- 2301', 2307'- 2311' ped 190,153 scf 70% quality nitrogor'- 1973', 2016'- 2018', 2061'- 2064' ped 112,009 scf 70 % quality nitrogord Log. Estimated top of cement and down hole. Circulated 2 bbls to so and Log. Estimated top of cement at '- 1153', 1168'- 1172', 1185'- 1187', ped 285,831 scf 70% quality nitrogor'- 1032', 1037'- 1040', 1060'- 1062', ped 144,409 scf 70% quality nitrogor'- 806', 823'- 825', 860'- 864', 900'- 9 ped 149,325 scf 70% quality nitrogor'- Well is ready to be tested and above is true and complete to the belosed according to NMOCD guidelines [OTHER: pertinent details, and le Completions: At the Research of the Research	Completion d give pertinent dates, including estimated date tach wellbore diagram of proposed completion Linear gel with 18,590 lbs 20/40 sand. oles Linear gel with 34,371 lbs 20/40 sand. Linear gel with 13,127 lbs 20/40 sand. Linear gel with 60,733 lbs 20/40 sand. 1111', 1119'- 1122' 72 Holes Linear gel with 43,612 lbs 20/40 sand. ear gel with 26,604 lbs 20/40 sand. on. e and belief. I further certify that any pit or belowor an (attached) alternative OCD-approved plan □. Linearlyst DATE 08/05/08
OTHER: 13. Describe proposed or completion of starting any proposed work or recompletion. 02/17/08 Weatherford ran Cement Both 15/08 Weatherford perf d 1st stage HES frac'd 1st stage - Pum Perf'd 2nd stage - 225 Frac'd 2nd stage - Pum Perf'd 3rd stage - Pum Perf'd 5th stage - 1150 Frac'd 4th stage - Pum Perf'd 5th sta	eted operations. (Clearly state all rk). SEE RULE 1103. For Multip and Log. Estimated top of cement at e = 2407'-2409', 2445'-2448', 248 ped 115,180 scf 70% quality nitrog 7'-2259', 2298'-2301', 2307'-2311' ped 190,153 scf 70% quality nitrog 0'-1973', 2016'-2018', 2061'-2064' ped 112,009 scf 70 % quality nitrog ond Log. Estimated top of cement and down hole. Circulated 2 bbls to son Log. Estimated top of cement at '-1153', 1168'-1172', 1185'-1187', ped 285,831 scf 70% quality nitrog 2'-1032', 1037'-1040', 1060'-1062', ped 144,409 scf 70% quality nitrog 806', 823'-825', 860'-864', 900'-9 ped 149,325 scf 70% quality nitrogemp. Well is ready to be tested and bove is true and complete to the belosed according to NMOCD guidelines [Sichell E-mail address: shirley]	oTHER: pertinent details, and le Completions: At at 1850'. 186'- 2489' 32 Holes gen foam with 20# L 32 Holes ogen foam with 20# L 32 Holes ogen foam with 20# L 31 Holes ogen foam with 20# L 11 Holes ogen foam with 20# L 11 Holes ogen foam with 20# Lind 1082'- 1086', 1098'-gen foam with 20# Lind 1082'- 1086', 1098'-gen foam with 20# Lind 103' 56 Holes of foam with 20# Lind 104 Lind 105 ogen foam with 20# Lind 105 of Holes of foam with 20# Lind 105 of foam	Completion Id give pertinent dates, including estimated date tach wellbore diagram of proposed completion Linear gel with 18,590 lbs 20/40 sand. Linear gel with 34,371 lbs 20/40 sand. Linear gel with 13,127 lbs 20/40 sand. Linear gel with 60,733 lbs 20/40 sand. 1111', 1119'- 1122' 72 Holes Inear gel with 43,612 lbs 20/40 sand. Linear gel with 26,604 lbs 20/40 sand. Linear gel with 26,604 lbs 20/40 sand. DATE 08/05/08 Linear gel with 26,608 Telephone No. (505) 445-6785
OTHER: 13. Describe proposed or completion of starting any proposed work or recompletion. 02/17/08 Weatherford ran Cement Both 15/08 Weatherford perf'd 1st stage HES frac'd 1st stage - Pum Perf'd 2nd stage - Pum Perf'd 3rd stage - Pum Perf'd 5rd stage - Pum Perf'd 4rd stage - Pum Perf'd 5th stage - Pum Perf'd 6th stage - Pum Perf'd 5th stag	eted operations. (Clearly state all rk). SEE RULE 1103. For Multip and Log. Estimated top of cement at e = 2407'-2409', 2445'-2448', 248 ped 115,180 scf 70% quality nitrog 7'-2259', 2298'-2301', 2307'-2311' ped 190,153 scf 70% quality nitrog 0'-1973', 2016'-2018', 2061'-2064' ped 112,009 scf 70 % quality nitrog ond Log. Estimated top of cement and down hole. Circulated 2 bbls to son Log. Estimated top of cement at '-1153', 1168'-1172', 1185'-1187', ped 285,831 scf 70% quality nitrog 2'-1032', 1037'-1040', 1060'-1062', ped 144,409 scf 70% quality nitrog 806', 823'-825', 860'-864', 900'-9 ped 149,325 scf 70% quality nitrogemp. Well is ready to be tested and bove is true and complete to the belosed according to NMOCD guidelines [Sichell E-mail address: shirley]	OTHER: pertinent details, and le Completions: At at 1850'. 186'- 2489' 32 Holes gen foam with 20# L 32 Holes or foam with 20# L 32 Holes or foam with 20# L 1853'. 1815'- 1237', 1260'- 1816'	Completion Id give pertinent dates, including estimated date tach wellbore diagram of proposed completion Linear gel with 18,590 lbs 20/40 sand. Linear gel with 34,371 lbs 20/40 sand. Linear gel with 13,127 lbs 20/40 sand. Linear gel with 60,733 lbs 20/40 sand. 1111', 1119'- 1122' 72 Holes Inear gel with 43,612 lbs 20/40 sand. Linear gel with 26,604 lbs 20/40 sand. Linear gel with 26,604 lbs 20/40 sand. DATE 08/05/08 Linear gel with 26,608 Telephone No. (505) 445-6785