

District I

1625 N. French Dr., Hobbs, NM 87240

District II

811 South First, Artesia, NM 87210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

1220 South St Francis

Santa Fe, NM 87505

WELL API NO.

30-007-20890

5. Indicate Type of Lease

STATE ☐ FEE ☒

State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:

OIL WELL ☐ GAS WELL ☒ DRY ☐ OTHER Coal Bed Methane

b. Type of Completion:

NEW ☒ WORK ☐ PLUG ☐ DIFF. ☐
WELL OVER ☐ DEEPEN ☐ BACK ☐ RESRV. ☐ OTHER ☐

2. Name of Operator

EL PASO E & P COMPANY, L.P.

3. Address of Operator

PO BOX 190, RATON, NEW MEXICO 87740

7. Lease Name or Unit Agreement Name

VPR A

8. Well No.

312

9. Pool name or Wildcat

Stubblefield Canyon Raton - Vermejo Gas

4. Well Location

Unit Letter P : 1273 Feet From The South Line and 1195 Feet From The East LineSection 26 Township 31N Range 20E NMPM Colfax County

10. Date Spudded

03/29/2008

11. Date T.D. Reached

03/30/2008

12. Date Compl. (Ready to Prod.)

06/27/2008

13. Elevations (DF& R(B. RT, GR, etc.)

7,993'

14. Elev. Casinghead

7,993'

15. Total Depth

2,245'

16. Plug Back T.D.

2,125'

17. If Multiple Compl. How Many Zones?

18. Intervals Drilled By

Rotary Tools

Cable Tools

0 - TD

NONE

19. Producing Interval(s), of this completion - Top, Bottom, Name

830' - 1980' Vermejo - Raton Coals

20. Was Directional Survey Made

NO

21. Type Electric and Other Logs Run

Compensated Density and Cement Bond Log

22. Was Well Cored

No

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24	323'	11"	100 sks	None
5 1/2"	15.5	2,144'	7 7/8"	285 sks	
			Top Off	68 sks	

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN

25. TUBING RECORD

SIZE	DEPTH SET	PACKER SET
2 7/8"	2,040'	No

26. Perforation record (interval, size, and number)

1895'-1897', 1941'-1944', 1958'-1961', 1974'-1980' 56 Holes

1058'-1060', 1072'-1075', 1114'-1117', 1163'-1187' 48 Holes

830'-833', 838'-841', 881'-883', 924'-927', 951'-955' 60 Holes

DEPTH INTERVAL

830'-1980'

AMOUNT AND KIND MATERIAL USED

105,015 lbs 20/40 sand

811,922 scf nitrogen foam

21 #Linear gel

28. PRODUCTION

Date First Production

08/16/2008

Production Method (Flowing, gas lift, pumping - Size and type pump)

Pumping water up 2 7/8" tubing, pc pump.. Flowing gas up 5 1/2" Casing.

Well Status (Prod. or Shut-in)

Production

Date of Test

08/16/2008

Hours Tested

24 hrs.

Choke Size

Full 2"

Prod'n For

Test Period

Oil - Bbl

N/A

Gas - MCF

65

Water - Bbl.

187

Gas - Oil Ratio

N/A

Flow Tubing Press.

Casing Pressure

65

Calculated 24-Hour Rate

Oil - Bbl.

N/A

Gas - MCF

65

Water - Bbl.

187

Oil Gravity - API - (Corr.)

N/A

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

Sold, used for fuel.

Test Witnessed By:
Vern Little

30. List Attachments

31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief.

Signature:

Shirley Mitchell

Printed

Shirley A. Mitchell

Title

Regulatory Analyst

Date:

09/05/2008

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy_____	T. Canyon_____
T. Salt_____	T. Strawn_____
B. Salt_____	T. Atoka_____
T. Yates_____	T. Miss_____
T. 7 Rivers_____	T. Devonian_____
T. Queen_____	T. Silurian_____
T. Grayburg_____	T. Montoya_____
T. San Andres_____	T. Simpson_____
T. Glorieta_____	T. McKee_____
T. Paddock_____	T. Ellenburger_____
T. Blinberry_____	T. Gr. Wash_____

T. Tubb_____	T. Delaware Sand_____
T. Drinkard_____	T. Bone Springs_____
T. Abo_____	T. _____
T. Wolfcamp_____	T. _____
T. Penn_____	T. _____
T. Cisco (Bough C)_____	T. _____

Northwestern New Mexico

T. Ojo Alamo_____	T. Penn. "B"_____
T. Kirtland-Fruitland_____	T. Penn. "C"_____
T. Pictured Cliffs_____	T. Penn. "D"_____
T. Cliff House_____	T. Leadville_____
T. Menefee_____	T. Madison_____
T. Point Lookout_____	T. Elbert_____
T. Mancos_____	T. McCracken_____
T. Gallup_____	T. Ignacio Otzte_____
Base Greenhorn_____	T. Granite_____
T. Dakota_____	T. Raton Top <u>Surface</u>
T. Morrison_____	T. Vermejo <u>1,844'</u>

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
No. 2, from.....to.....

No. 3, from.....to.....
No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology

From	To	Thickness In Feet	Lithology