Submit 3 Copies To Appropriate District State of New N	
Office Energy, Minerals and Na	
1625 N. French Dr., Hobbs, NM 87240	WELL API NO. 30-059-20505
District II 1301 W. Grand Aver, Artesia, NM 88219 - C	SN DIVISION 5 I II - T GI
1301 W. Grand Ave., Artesia, NM 88210 District III 1220 South St. F 1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM	Tallels D1.
District IV	6. State Oil & Gas Lease No.
1220 S.	L06242
SUNDRY NOTICES AND REPORTS ON W (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPER DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other CO2 Supply We	N OR PLUG BACK TO A 101) FOR SUCH Bravo Dome Carbon Dioxide Gas Unit 2233 8. Well Number 221
2. Name of Operator	9. OGRID Number
OXY USA Inc. 3. Address of Operator	16696 10. Pool name or Wildcat
P.O. Box 4294 Houston, TX 77210-4294	Bravo Dome Carbon Dioxide Gas 640
4. Well Location	
Unit Letter F: 1839 feet from the	N line and 1681 feet from the W line
Section 22 Township 22N	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4935.5' GR	
12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON	REMEDIAL WORK ALTERING CASING
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS. X P AND A
PULL OR ALTER CASING MULTIPLE COMPL	CASING/CEMENT JOB
DOWNHOLE COMMINGLE	-
DOWNTOLL COMMINGEL	
OTHER:	OTHER:
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.	
See Attachment	
Spud Date: 10/03/08 Rig Rel	ease Date: 10/08/08
Spud Date. Rig Rei	ease Date.
I hereby certify that the information above is true and complete to the	he best of my knowledge and belief.
SIGNATURE TITLE Sr. Regulatory Analyst DATE 05/12/09	
	Kimberly_Long@oxy.com
Type or print name Kimber Long E-	mail address:PHONE _713-215-7643_
For State Use Only	
APPROVED BY Martin T	TILE DISTRICT SUPERVISOR DATE 5-/19/09
Conditions of Approval (if any):	

~ Page 2 (C-103 Attachment)

Page 2 (C-103 Attachment)

SPUD 10/03/08

DRILL 12 1/4" HOLE TO 740'

RIH W/ 8 5/8" 24#J55 CSG & SET @ 727'

CEMENT W/ 400 SX PP CEMENT YIELD 1.35 @ 14.8 PPG; CIRCULATE 20 SX TO SURFACE; WOC

DRILL 7 7/8" HOLE TO 2647'

RIH W/ 5 1/2" 5.3#FG 15.5# J55 CSG & SET @ 2634'

CEMENT W/ 200 SX PP W/ 2% CACL2 @ 11.1 PPG; FOLLOWED BY 150 SX PP W/ 2% CACL2 13.2 PPG; CIRCULATE 75 SX TO SURFACE; WOC

RELEASE RIG 10/08/08