

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 South St. Frances, Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Frances
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO. 30-007-20431	
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>	
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name: VPR D	
8. Well No. 116	
9. Pool name or Wildcat	
4. Well Location Unit Letter O : 860 feet from the South line and 1910 feet from the East line Section 7 Township 30N Range 19E NMPM COLFAX County	
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 7540' (GL)	

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work).
SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

12/08/03 Spud @ 10:30 p.m. Drill 11" surface hole to 350'. Run 8 jts. of 8 5/8", J-55, 23 ppf ST&C casing to 342'. Halliburton mixed and pumped 28 bbls water, 100 sx Midcon II, 14 ppg, yield 1.66 at 4 bpm with 110 psi with 6% salt, 5#/sx gilsonite, .3% versaset, .25 #/sk flocele. Circulate 6 bbls of cement to surface. WOC 8 hrs. Test surface casing to 500 psi for 30 minutes.
12/09/03 Drill 7 7/8" hole from 350' - 1915'. Reached TD 1915' at 8:30 p.m. MIRU Schlumberger & log well. Loggers TD at 1657'.
12/10/03 Ran 48 jts. of 5 1/2", M-50, 15.5 ppf LT&C casing to 1857'. Halliburton mix and pump 73 bbls water, 40 bbls gel pre flush. Pumped 258 sx Midcon II PP, 13 ppg, yield 2.04 at 4 bpm. with 6 % salt, 2 lb/sx Granulite, 5 lb/sx Gilsonite, .3% Versaset, and .1% Super CBL. Bumped plug. Float held. Circulated 16 bbls of cement to surface. Well shut in.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Shirley A. Mitchell TITLE Senior Specialist DATE 12/11/03
Type or print name Shirley A. Mitchell Telephone No. (505) 445-6785

(This space for State use)

APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 12/22/03
Conditions of approval, if any: