

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 South St. Frances, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
1220 South St. Frances
Santa Fe, NM 87505

WELL API NO. 30-007-20466
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name: VPR D
8. Well No. 138
9. Pool name or Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Well ☐ Gas Well ☐ Other ☒ Coalbed Methane

2. Name of Operator
EL PASO ENERGY RATON, L.L.C.

3. Address of Operator
P.O. Box 190, Raton, NM 87740

4. Well Location
Unit Letter **I** : **1806** feet from the **South** line and **1123** feet from the **East** line
Section **19** Township **30N** Range **19E** NMPM COLFAX County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
7540' (GL)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work).
SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

- 12/15/03 Spud @ 11:00 p.m. Drill 11" surface hole to 360'. Run 8 jts. of 8 5/8", J-55, 23 ppf ST&C casing to 353'. Halliburton mixed and pumped 40 bbls water, 100 sx Midcon II, 14 ppg, yield 1.66 at 4 bpm with 100 psi with 6% salt, 5#/sx gilsonite, .3% versaset, .25 #/sk flocele. Circulate 7 bbls of cement to surface.
- 12/16/03 WOC 8 hrs. Test surface casing to 500 psi for 30 minutes. Drill 7 7/8" hole from 360' - 2035'. Reached TD 2035' at 9:00 p.m. MIRU Schlumberger & log well. Loggers TD at 2006'. Ran 48 jts. of 5 1/2", M-50, 15.5 ppf LT&C casing to 1965'.
- 12/17/03 Halliburton mix and pump 75 bbls water, 40 bbls gel pre flush. Pumped 270 sx Midcon II PP, 13 ppg, yield 2.04 at 4 bpm. with 6 % salt, 2 lb/sx Granulite, 5 lb/sx Gilsontite, .3% Versaset, and .1% Super CBL. Bumped plug with 1100 psi. Float held. Circulated 21 bbls of cement to surface. Well shut in.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Shirley Mitchell TITLE Senior Specialist DATE 12/30/03
Type or print name Shirley A. Mitchell Telephone No. (505) 445-6785

(This space for State use)

APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 1/12/04
Conditions of approval, if any:

RECEIVED

JAN 05 2004

OIL CONSERVATION
DIVISION