

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 South St. Frances, Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
1220 South St. Frances
Santa Fe, NM 87505

WELL API NO. 30-007-20490
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name: VPR D
8. Well No. 122
9. Pool name or Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Coalbed Methane	
2. Name of Operator EL PASO ENERGY RATON, L.L.C.	
3. Address of Operator P.O. Box 190, Raton, NM 87740	
4. Well Location Unit Letter H : 2406 feet from the North line and 1154 feet from the East line Section 11 Township 30N Range 18E NMPM COLFAX County 10. Elevation (Show whether DR, RKB, RT, GR, etc.) 7940' (GL)	

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work).
SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- 01/14/04 Spud @ 9:30 p.m. Drill 11" surface hole to 370'. Run 8 jts. of 8 5/8", J-55, 23 ppf ST&C casing to 364'. Halliburton mixed and pumped 33 bbls water, 100 sx Midcon II, 14 ppg, yield 1.66 at 4 bpm with 100 psi with 6 % salt, 5#/sx gilsonite, .3% versaset, .25 #/sk flocele. Circulated 5 bbls of cement to surface. WOC 8 hrs. Test surface casing to 500 psi for 30 minutes.
- 01/15/04 Drill 7 7/8" hole from 370' - 1705'. Reached TD 1705' at 10:30 p.m. MIRU Schlumberger & log well. Loggers TD at 1635'. Ran 39 jts. of 5 1/2", M-50, 15.5 ppf LT&C casing to 1628'.
- 01/16/04 Halliburton mix and pump 40 bbls water, 40 bbls gel pre flush. Pumped 290 sx Midcon II PP, 13 ppg, yield 2.04 at 4 bpm. with 6 % salt, 2 lb/sx Granulite, 5 lb/sx Gilsonte, .3% Versaset, and .1% Super CBL. Bumped plug with 1300 psi. Float held. Circulated 40 bbls of cement to surface. Well shut in.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Shirley A. Mitchell TITLE Senior Specialist DATE 01/22/04
Type or print name Shirley A. Mitchell Telephone No. (505) 445-6785

(This space for State use)

APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 1/23/04
Conditions of approval, if any: