

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 South St Francis, Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St Frances
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO. 30-007-20480	
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>	
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name: VPR A	
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other <input checked="" type="checkbox"/> Coalbed Methane	
2. Name of Operator EL PASO ENERGY RATON, L.L.C.	
3. Address of Operator P.O. Box 190, Raton, NM 87740	
4. Well Location Unit Letter N : 853 feet from the South line and 1392 feet from the West line Section 21 Township 32N Range 19E NMPM Colfax County	
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 8610' (GL)	

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

01/31/04 Spud in @ 3:00 p.m. Drill 11" surface hole to 365'. Ran 8 jts of 8 5/8", J-55, 24 ppf ST&C casing to 359'. Halliburton mixed and pumped 100 sks Midcon II PP, 14 ppg, yield 1.66 at 3 bpm with 110 psi with 6% salt, .3% gilsonite, .3% versaset, and 25# flocele per sack. Circulated 5 bbls of cement to surface. WOC 8 hrs. Test surface casing to 500 psi for 30 min.

02/01/04 Drill 7 7/8" hole f/ 365' - 3025'. Reached TD at 3025'. MIRU Schlumberger & log well. Logger TD at 2287'. Ran 73 jts of 5 1/2", 17#, J-55 LT & C casing to 2893'. Halliburton mixed and pump 50 bbls gel pre flush at 4 bpm at 40 psi, 504 sks Midcon II, 13.0 ppg, yield 2.04, .3% versaset, 5#/sx gilsonite, 2#/sk granulite, 6% salt and .1% Super CBL. Plug bumped w/ 1160 psi. Circulated 39 bbls of cement to surface. Well shut in.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Shirley A. Mitchell TITLE Senior Specialist DATE 02/05/04
Type or print name Shirley A. Mitchell Telephone No. (505) 445-6785

(This space for State use)

APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 2/20/04
Conditions of approval, if any: