

Submit 1 Copy To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
October 13, 2009

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-007-20980
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name
8. Well Number B-328
9. OGRID Number 180514
10. Pool name or Wildcat Van Bremmer Canyon – Vermejo Gas

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other CBM

2. Name of Operator
El Paso E&P Company, L.P.

3. Address of Operator
1001 Louisiana, Rm 2730D, Houston, Texas 77002

4. Well Location
Unit Letter I : 2383 feet from the South line and 809 feet from the East line
Section 35 Township 30N Range 18E NMPM 6th County Colfax

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
8180'

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Rig: Pense 19

CEMENT BOND LOG ENCLOSED

01/30/11: Spudded @ 2300 hrs. Drilled & set 13 3/8" conductor. Drill surface hole to 354'.

01/31/11: Ran 8 5/8", 26#, J-55, ST&C casing and set @ 343'. Mixed & pumped 100 sx 14 ppg, Trinidad surface blend cement. 7 bbls to pit.

02/01/11: Completed rig repairs. TIH 300' and tagged cement top. Drilled out cement to 354'.

02/02/11: Drilled to 2905' TD. Logged.

02/03/11: Ran 5 1/2", 15.5#, J-55, LT&C casing. Casing shoe @ 2744'. Pumped 45 bbls WFR, 20 bbls gel pill, 10 bbls WFR +32 bbls (83 sx) Trinidad Production Blend mixed @ 12.7 ppg. Displaced w/65 bbls of water. Final pressure 70 psi @ 3BPM. Bumped plug & pressure to 3000 psi and inflated ECP. Dropped bomb & SD 10 min. Opened multistage tool @ 800 psi. Pumped 10 bbls of water ahead, 40 bbls LGC gel @ 5bpm, 10 bbls of water. Mixed and pumped 100 bbls 13 ppg Trinidad blend cement. Bumped plug with 1800 psi. SI.

Spud Date:

01/30/11

Rig Release Date:

02/03/11

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Maria S. Gomez

TITLE Sr. Regulatory Analyst

DATE 03/01/11

Type or print name Maria S. Gomez E-mail address: maria.gomez@elpaso.com PHONE: 713-420-5038/832-683-0361

For State Use Only

APPROVED BY:

Ed Martin

TITLE

DISTRICT SUPERVISOR

DATE 3/4/2011

Conditions of Approval (if any):