

Submit 1 Copy To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
October 13, 2009

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-007-20965
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name
8. Well Number A-571
9. OGRID Number 180514
10. Pool name or Wildcat Stubblefield Canyon Raton-Vermejo Gas

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other CBM

2. Name of Operator
El Paso E&P Company, L.P.

3. Address of Operator
1001 Louisiana, Rm 2730D, Houston, Texas 77002

4. Well Location
Unit Letter D 568 feet from the North line and 1048 feet from the West line
Section 24 Township 31N Range 19E NMPM 6th County Colfax

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
8353'

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

02/19/11: Spudded @ 1430 hrs. Set conductor pipe. Drilled 11" surface hole to 343'. C&C hole. Ran 8 5/8", 26#, J-55 ST&C surface casing. Sett @ 343' GL. Pumped 45 bbls of water ahead @ 3BPM. Mixed and pumped 102 sx Trinidad surface blend cement. 6 bbls of cement to pit. WOC.

02/20/11: Unloaded hole with air. Drilled 7 7/8" production hole to 2695' TD. C&C hole.

02/21/11: Logged. Ram casing and landed @ 2669'. Released rig. Cement production with 84 bbls EZ-mud, 80 bbls gel, 10 bbls water, 450 sx 13# Trinidad blend. ~~Broke~~ circulation w/23 bbls disp. Lost circulation w/ 33 bbls disp. Landed plug with 550 psi.
Broke

Spud Date:

02/19/11

Rig Release Date:

02/21/11

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Maria S. Gomez TITLE Sr. Regulatory Analyst DATE 04/19/11

Type or print name Maria S. Gomez E-mail address: maria.gomez@elpaso.com PHONE: 713-420-5038/832-683-0361

For State Use Only

APPROVED BY: Ed Martin TITLE **DISTRICT SUPERVISOR** DATE 4/25/2011
Conditions of Approval (if any):



**CEMENT BOND LOG/
GAMMA RAY/CCL**

COMPANY EL PASO E & P COMPANY WELL VPR A-571 FIELD CALIENTE CNTY COLFAX STATE NM	COMPANY EL PASO E & P COMPANY WELL VPR A-571 FIELD CALIENTE COUNTY COLFAX			STATE NEW MEXICO																																																																					
	LOCATION: 568' FNL & 1048' FWL API# 30-007-20965 SEC 24 TWP 31N RGE 19E					OTHER SERVICES: NONE																																																																			
	PERM. DATUM G.L. ELEV. 8353.00 LOG MEASURED FROM G.L. FT. ABOVE PERMANENT DATUM DRILLING MEASURED FROM G.L.					ELEV.: K.B. 8358.00 D.F. 8357.0 G.L. 8353.00																																																																			
	<table style="width:100%; border-collapse: collapse;"> <tr> <td style="width:40%;">DATE</td> <td>06-APR-2011</td> <td></td> <td></td> </tr> <tr> <td>RUN NO.</td> <td>ONE</td> <td></td> <td></td> </tr> <tr> <td>DEPTH DRILLER</td> <td>2695.0</td> <td></td> <td></td> </tr> <tr> <td>DEPTH LOGGER</td> <td>2534</td> <td></td> <td></td> </tr> <tr> <td>BTM. LOG INTERVAL</td> <td>2530</td> <td></td> <td></td> </tr> <tr> <td>TOP LOG INTERVAL</td> <td>0.0</td> <td></td> <td></td> </tr> <tr> <td>OPEN HOLE SIZE</td> <td>7.875"</td> <td></td> <td></td> </tr> <tr> <td>TYPE FLUID</td> <td>WATER</td> <td></td> <td></td> </tr> <tr> <td>DENS. VISC.</td> <td>8.3 N/A</td> <td></td> <td></td> </tr> <tr> <td>MAX. REC. TEMP. °F</td> <td>111</td> <td></td> <td></td> </tr> <tr> <td>EST. CEMENT TOP</td> <td>SURFACE</td> <td></td> <td></td> </tr> <tr> <td>TIME WELL READY</td> <td>ROA</td> <td></td> <td></td> </tr> <tr> <td>TIME LOGGER ON BTM.</td> <td>1615</td> <td></td> <td></td> </tr> <tr> <td>EQUIP. NO.</td> <td>14247</td> <td></td> <td></td> </tr> <tr> <td>LOCATION</td> <td>CASPER, WY</td> <td></td> <td></td> </tr> <tr> <td>RECORDED BY</td> <td>JOHNSON</td> <td></td> <td></td> </tr> <tr> <td>WITNESSED BY</td> <td>GARRISON</td> <td></td> <td></td> </tr> </table>						DATE	06-APR-2011			RUN NO.	ONE			DEPTH DRILLER	2695.0			DEPTH LOGGER	2534			BTM. LOG INTERVAL	2530			TOP LOG INTERVAL	0.0			OPEN HOLE SIZE	7.875"			TYPE FLUID	WATER			DENS. VISC.	8.3 N/A			MAX. REC. TEMP. °F	111			EST. CEMENT TOP	SURFACE			TIME WELL READY	ROA			TIME LOGGER ON BTM.	1615			EQUIP. NO.	14247			LOCATION	CASPER, WY			RECORDED BY	JOHNSON			WITNESSED BY	GARRISON	
DATE	06-APR-2011																																																																								
RUN NO.	ONE																																																																								
DEPTH DRILLER	2695.0																																																																								
DEPTH LOGGER	2534																																																																								
BTM. LOG INTERVAL	2530																																																																								
TOP LOG INTERVAL	0.0																																																																								
OPEN HOLE SIZE	7.875"																																																																								
TYPE FLUID	WATER																																																																								
DENS. VISC.	8.3 N/A																																																																								
MAX. REC. TEMP. °F	111																																																																								
EST. CEMENT TOP	SURFACE																																																																								
TIME WELL READY	ROA																																																																								
TIME LOGGER ON BTM.	1615																																																																								
EQUIP. NO.	14247																																																																								
LOCATION	CASPER, WY																																																																								
RECORDED BY	JOHNSON																																																																								
WITNESSED BY	GARRISON																																																																								
BOREHOLE RECORD				TUBING RECORD																																																																					
RUN NO.	BIT	FROM	TO	SIZE	WGT.	FROM	TO																																																																		
1	7.875	334	T.D.																																																																						
CASING RECORD		SIZE	WT/FT	GRADE	TYPE JOINT	TOP	BOTTOM																																																																		
SURFACE STRING		8.625	24			SURF	334																																																																		
PROT. STRING																																																																									
PROD. STRING		5.50	15.5			SURF	TD																																																																		
LINER																																																																									