Office	Form C-103
District I Energy, Minerals and Natural Resources	October 13, 2009
1625 N. French Dr., Hobbs, NM 88240	WELL API NO.
District II 1301 W. Grand Ave. Artesia, NM 88210 OIL CONSERVATION DIVISION	30-007-20964
1501 W. Gland Ave., Artesia, NW 66210	5. Indicate Type of Lease
District III 1220 South St. Francis Dr. 1000 Rio Brazos Rd., Aztec, NM 87410	STATE FEE
District IV Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM	
87505	
SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	
PROPOSALS.) 1. Type of Well: Oil Well ☐ Gas Well ☒ Other CBM	8. Well Number A-570
	9. OGRID Number
2. Name of Operator	· ·
El Paso E&P Company, L.P.	180514
3. Address of Operator	10. Pool name or Wildcat
1001 Louisiana, Rm 2730D, Houston, Texas 77002	Stubblefield Canyon Raton-Vermejo Gas
4. Well Location	
Unit Letter O: 575 feet from the South line and 25	47 feet from the <u>East</u> line
Section 13 Township 31N Range 19E NMPM	
11. Elevation (Show whether DR, RKB, RT, GR, et	
8375	
12. Check Appropriate Box to Indicate Nature of Notice	Report or Other Data
12. Check rippropriate Box to mateure retained	, report of other bata
NOTICE OF INTENTION TO:	BSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WO	
	RILLING OPNS. P AND A
-	
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEME	NT JOB
DOWNHOLE COMMINGLE	·
OTHER: OTHER:	<u> </u>
12 Describe represed or completed appretions (Clearly state all partiagnt details a	
	nd give pertinent dates, including estimated date
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C	
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C	
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion.	ompletions: Attach wellbore diagram of
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. 02/21/11: Spudded @ 1800 hrs. Set conductor. Drilled to 349'. Ran 8 5/8'', 26#, J-55, 5	ompletions: Attach wellbore diagram of
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. 02/21/11: Spudded @ 1800 hrs. Set conductor. Drilled to 349'. Ran 8 5/8", 26#, J-55, \$02/22/11: Cemented surface casing with 100 sx. WOC.	ompletions: Attach wellbore diagram of ST&C casing and set @ 339.34'.
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. 02/21/11: Spudded @ 1800 hrs. Set conductor. Drilled to 349'. Ran 8 5/8", 26#, J-55, 502/22/11: Cemented surface casing with 100 sx. WOC. 02/23/11: Drilled production hole to 2755'. Estimated top of Trinidad 2445'. C&C hole	ompletions: Attach wellbore diagram of ST&C casing and set @ 339.34'. Tagged @ 2750' (5' of fill). C&C. Logged.
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. 02/21/11: Spudded @ 1800 hrs. Set conductor. Drilled to 349'. Ran 8 5/8", 26#, J-55, 502/22/11: Cemented surface casing with 100 sx. WOC. 02/23/11: Drilled production hole to 2755'. Estimated top of Trinidad 2445'. C&C hole 02/24/11: Ran 5 ½", 15.5#, J-55, LNG THD casing to 2689.72'. Tagged @ 2696'. Land	ompletions: Attach wellbore diagram of ST&C casing and set @ 339.34'. Tagged @ 2750' (5' of fill). C&C. Logged. led in WH @ 2693' KB. Released rig. Pumped
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. 02/21/11: Spudded @ 1800 hrs. Set conductor. Drilled to 349'. Ran 8 5/8", 26#, J-55, 502/22/11: Cemented surface casing with 100 sx. WOC. 02/23/11: Drilled production hole to 2755'. Estimated top of Trinidad 2445'. C&C hole 02/24/11: Ran 5 ½", 15.5#, J-55, LNG THD casing to 2689.72'. Tagged @ 2696'. Land 89 bbls fresh water with easy mud, 80 bbls gel pill with n-seal, baracarb & flocell followers.	ompletions: Attach wellbore diagram of ST&C casing and set @ 339.34'. Tagged @ 2750' (5' of fill). C&C. Logged. led in WH @ 2693' KB. Released rig. Pumped
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. 02/21/11: Spudded @ 1800 hrs. Set conductor. Drilled to 349'. Ran 8 5/8", 26#, J-55, 502/22/11: Cemented surface casing with 100 sx. WOC. 02/23/11: Drilled production hole to 2755'. Estimated top of Trinidad 2445'. C&C hole 02/24/11: Ran 5 ½", 15.5#, J-55, LNG THD casing to 2689.72'. Tagged @ 2696'. Land	ompletions: Attach wellbore diagram of ST&C casing and set @ 339.34'. Tagged @ 2750' (5' of fill). C&C. Logged. led in WH @ 2693' KB. Released rig. Pumped
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. 02/21/11: Spudded @ 1800 hrs. Set conductor. Drilled to 349'. Ran 8 5/8", 26#, J-55, 502/22/11: Cemented surface casing with 100 sx. WOC. 02/23/11: Drilled production hole to 2755'. Estimated top of Trinidad 2445'. C&C hole 02/24/11: Ran 5 ½", 15.5#, J-55, LNG THD casing to 2689.72'. Tagged @ 2696'. Land 89 bbls fresh water with easy mud, 80 bbls gel pill with n-seal, baracarb & flocell followers.	ompletions: Attach wellbore diagram of ST&C casing and set @ 339.34'. Tagged @ 2750' (5' of fill). C&C. Logged. led in WH @ 2693' KB. Released rig. Pumped
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. 02/21/11: Spudded @ 1800 hrs. Set conductor. Drilled to 349'. Ran 8 5/8", 26#, J-55, 502/22/11: Cemented surface casing with 100 sx. WOC. 02/23/11: Drilled production hole to 2755'. Estimated top of Trinidad 2445'. C&C hole 02/24/11: Ran 5 ½", 15.5#, J-55, LNG THD casing to 2689.72'. Tagged @ 2696'. Land 89 bbls fresh water with easy mud, 80 bbls gel pill with n-seal, baracarb & flocell followers.	ompletions: Attach wellbore diagram of ST&C casing and set @ 339.34'. Tagged @ 2750' (5' of fill). C&C. Logged. led in WH @ 2693' KB. Released rig. Pumped
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. 02/21/11: Spudded @ 1800 hrs. Set conductor. Drilled to 349'. Ran 8 5/8", 26#, J-55, 502/22/11: Cemented surface casing with 100 sx. WOC. 02/23/11: Drilled production hole to 2755'. Estimated top of Trinidad 2445'. C&C hole 02/24/11: Ran 5 ½", 15.5#, J-55, LNG THD casing to 2689.72'. Tagged @ 2696'. Land 89 bbls fresh water with easy mud, 80 bbls gel pill with n-seal, baracarb & flocell followers.	ompletions: Attach wellbore diagram of ST&C casing and set @ 339.34'. Tagged @ 2750' (5' of fill). C&C. Logged. led in WH @ 2693' KB. Released rig. Pumped
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. 02/21/11: Spudded @ 1800 hrs. Set conductor. Drilled to 349'. Ran 8 5/8", 26#, J-55, 502/22/11: Cemented surface casing with 100 sx. WOC. 02/23/11: Drilled production hole to 2755'. Estimated top of Trinidad 2445'. C&C hole 02/24/11: Ran 5 ½", 15.5#, J-55, LNG THD casing to 2689.72'. Tagged @ 2696'. Land 89 bbls fresh water with easy mud, 80 bbls gel pill with n-seal, baracarb & flocell followed 189 bbls Trinidad production blend cement mixed @ 13 ppg. No returns to surface.	ompletions: Attach wellbore diagram of ST&C casing and set @ 339.34'. Tagged @ 2750' (5' of fill). C&C. Logged. led in WH @ 2693' KB. Released rig. Pumped d by 10 bbls water spacer. Mixed and pumped
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. 02/21/11: Spudded @ 1800 hrs. Set conductor. Drilled to 349'. Ran 8 5/8", 26#, J-55, 502/22/11: Cemented surface casing with 100 sx. WOC. 02/23/11: Drilled production hole to 2755'. Estimated top of Trinidad 2445'. C&C hole 02/24/11: Ran 5 ½", 15.5#, J-55, LNG THD casing to 2689.72'. Tagged @ 2696'. Land 89 bbls fresh water with easy mud, 80 bbls gel pill with n-seal, baracarb & flocell followers.	ompletions: Attach wellbore diagram of ST&C casing and set @ 339.34'. Tagged @ 2750' (5' of fill). C&C. Logged. led in WH @ 2693' KB. Released rig. Pumped
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. 02/21/11: Spudded @ 1800 hrs. Set conductor. Drilled to 349'. Ran 8 5/8", 26#, J-55, 502/22/11: Cemented surface casing with 100 sx. WOC. 02/23/11: Drilled production hole to 2755'. Estimated top of Trinidad 2445'. C&C hole 02/24/11: Ran 5 ½", 15.5#, J-55, LNG THD casing to 2689.72'. Tagged @ 2696'. Land 89 bbls fresh water with easy mud, 80 bbls gel pill with n-seal, baracarb & flocell followed 189 bbls Trinidad production blend cement mixed @ 13 ppg. No returns to surface.	ompletions: Attach wellbore diagram of ST&C casing and set @ 339.34'. Tagged @ 2750' (5' of fill). C&C. Logged. led in WH @ 2693' KB. Released rig. Pumped d by 10 bbls water spacer. Mixed and pumped
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. 02/21/11: Spudded @ 1800 hrs. Set conductor. Drilled to 349'. Ran 8 5/8", 26#, J-55, 502/22/11: Cemented surface casing with 100 sx. WOC. 02/23/11: Drilled production hole to 2755'. Estimated top of Trinidad 2445'. C&C hole 02/24/11: Ran 5 ½", 15.5#, J-55, LNG THD casing to 2689.72'. Tagged @ 2696'. Land 89 bbls fresh water with easy mud, 80 bbls gel pill with n-seal, baracarb & flocell followed 189 bbls Trinidad production blend cement mixed @ 13 ppg. No returns to surface.	ompletions: Attach wellbore diagram of ST&C casing and set @ 339.34'. Tagged @ 2750' (5' of fill). C&C. Logged. led in WH @ 2693' KB. Released rig. Pumped d by 10 bbls water spacer. Mixed and pumped
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. 02/21/11: Spudded @ 1800 hrs. Set conductor. Drilled to 349'. Ran 8 5/8", 26#, J-55, \$02/22/11: Cemented surface casing with 100 sx. WOC. 02/23/11: Drilled production hole to 2755'. Estimated top of Trinidad 2445'. C&C hole 02/24/11: Ran 5 ½", 15.5#, J-55, LNG THD casing to 2689.72'. Tagged @ 2696'. Land 89 bbls fresh water with easy mud, 80 bbls gel pill with n-seal, baracarb & flocell followed 189 bbls Trinidad production blend cement mixed @ 13 ppg. No returns to surface. Spud Date: 02/21/11 Rig Release Date:	ompletions: Attach wellbore diagram of ST&C casing and set @ 339.34'. Tagged @ 2750' (5' of fill). C&C. Logged. led in WH @ 2693' KB. Released rig. Pumped d by 10 bbls water spacer. Mixed and pumped
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. 02/21/11: Spudded @ 1800 hrs. Set conductor. Drilled to 349'. Ran 8 5/8", 26#, J-55, 502/22/11: Cemented surface casing with 100 sx. WOC. 02/23/11: Drilled production hole to 2755'. Estimated top of Trinidad 2445'. C&C hole 02/24/11: Ran 5 ½", 15.5#, J-55, LNG THD casing to 2689.72'. Tagged @ 2696'. Land 89 bbls fresh water with easy mud, 80 bbls gel pill with n-seal, baracarb & flocell followed 189 bbls Trinidad production blend cement mixed @ 13 ppg. No returns to surface.	ompletions: Attach wellbore diagram of ST&C casing and set @ 339.34'. Tagged @ 2750' (5' of fill). C&C. Logged. led in WH @ 2693' KB. Released rig. Pumped d by 10 bbls water spacer. Mixed and pumped
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. 02/21/11: Spudded @ 1800 hrs. Set conductor. Drilled to 349'. Ran 8 5/8", 26#, J-55, \$02/22/11: Cemented surface casing with 100 sx. WOC. 02/23/11: Drilled production hole to 2755'. Estimated top of Trinidad 2445'. C&C hole 02/24/11: Ran 5 ½", 15.5#, J-55, LNG THD casing to 2689.72'. Tagged @ 2696'. Land 89 bbls fresh water with easy mud, 80 bbls gel pill with n-seal, baracarb & flocell followed 189 bbls Trinidad production blend cement mixed @ 13 ppg. No returns to surface. Spud Date: 02/21/11 Rig Release Date:	ompletions: Attach wellbore diagram of ST&C casing and set @ 339.34'. Tagged @ 2750' (5' of fill). C&C. Logged. led in WH @ 2693' KB. Released rig. Pumped d by 10 bbls water spacer. Mixed and pumped 02/24/11
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. 02/21/11: Spudded @ 1800 hrs. Set conductor. Drilled to 349'. Ran 8 5/8", 26#, J-55, \$02/22/11: Cemented surface casing with 100 sx. WOC. 02/23/11: Drilled production hole to 2755'. Estimated top of Trinidad 2445'. C&C hole 02/24/11: Ran 5 ½", 15.5#, J-55, LNG THD casing to 2689.72'. Tagged @ 2696'. Land 89 bbls fresh water with easy mud, 80 bbls gel pill with n-seal, baracarb & flocell followed 189 bbls Trinidad production blend cement mixed @ 13 ppg. No returns to surface. Spud Date: 02/21/11 Rig Release Date:	ompletions: Attach wellbore diagram of ST&C casing and set @ 339.34'. Tagged @ 2750' (5' of fill). C&C. Logged. led in WH @ 2693' KB. Released rig. Pumped d by 10 bbls water spacer. Mixed and pumped 02/24/11
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. 02/21/11: Spudded @ 1800 hrs. Set conductor. Drilled to 349'. Ran 8 5/8", 26#, J-55, \$02/22/11: Cemented surface casing with 100 sx. WOC. 02/23/11: Drilled production hole to 2755'. Estimated top of Trinidad 2445'. C&C hole 02/24/11: Ran 5 ½", 15.5#, J-55, LNG THD casing to 2689.72'. Tagged @ 2696'. Land 89 bbls fresh water with easy mud, 80 bbls gel pill with n-seal, baracarb & flocell followed 189 bbls Trinidad production blend cement mixed @ 13 ppg. No returns to surface. Spud Date: 02/21/11 Rig Release Date:	ompletions: Attach wellbore diagram of ST&C casing and set @ 339.34'. Tagged @ 2750' (5' of fill). C&C. Logged. led in WH @ 2693' KB. Released rig. Pumped d by 10 bbls water spacer. Mixed and pumped 02/24/11
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. 02/21/11: Spudded @ 1800 hrs. Set conductor. Drilled to 349'. Ran 8 5/8", 26#, J-55, 302/22/11: Cemented surface casing with 100 sx. WOC. 02/23/11: Drilled production hole to 2755'. Estimated top of Trinidad 2445'. C&C hole 02/24/11: Ran 5 ½", 15.5#, J-55, LNG THD casing to 2689.72'. Tagged @ 2696'. Land 89 bbls fresh water with easy mud, 80 bbls gel pill with n-seal, baracarb & flocell followed 189 bbls Trinidad production blend cement mixed @ 13 ppg. No returns to surface. Spud Date: 02/21/11 Rig Release Date: TITLE Sr. Regulatory Analy	ompletions: Attach wellbore diagram of ST&C casing and set @ 339.34'. Tagged @ 2750' (5' of fill). C&C. Logged. led in WH @ 2693' KB. Released rig. Pumped d by 10 bbls water spacer. Mixed and pumped 02/24/11 lge and belief. DATE
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. 02/21/11: Spudded @ 1800 hrs. Set conductor. Drilled to 349'. Ran 8 5/8", 26#, J-55, \$02/22/11: Cemented surface casing with 100 sx. WOC. 02/23/11: Drilled production hole to 2755'. Estimated top of Trinidad 2445'. C&C hole 02/24/11: Ran 5 ½", 15.5#, J-55, LNG THD casing to 2689.72'. Tagged @ 2696'. Land 89 bbls fresh water with easy mud, 80 bbls gel pill with n-seal, baracarb & flocell followed 189 bbls Trinidad production blend cement mixed @ 13 ppg. No returns to surface. Spud Date: 02/21/11 Rig Release Date: TITLE Sr. Regulatory Analy Type or print name Maria S. Gomez E-mail address: maria.gomez@elpaso.cc	ompletions: Attach wellbore diagram of ST&C casing and set @ 339.34'. Tagged @ 2750' (5' of fill). C&C. Logged. led in WH @ 2693' KB. Released rig. Pumped d by 10 bbls water spacer. Mixed and pumped 02/24/11
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. 02/21/11: Spudded @ 1800 hrs. Set conductor. Drilled to 349'. Ran 8 5/8", 26#, J-55, \$02/22/11: Cemented surface casing with 100 sx. WOC. 02/23/11: Drilled production hole to 2755'. Estimated top of Trinidad 2445'. C&C hole 02/24/11: Ran 5 ½", 15.5#, J-55, LNG THD casing to 2689.72'. Tagged @ 2696'. Land 89 bbls fresh water with easy mud, 80 bbls gel pill with n-seal, baracarb & flocell followed 189 bbls Trinidad production blend cement mixed @ 13 ppg. No returns to surface. Spud Date: 02/21/11 Rig Release Date: TITLE Sr. Regulatory Analy Type or print name Maria S. Gomez E-mail address: maria.gomez@elpaso.ce	ompletions: Attach wellbore diagram of ST&C casing and set @ 339.34'. Tagged @ 2750' (5' of fill). C&C. Logged. led in WH @ 2693' KB. Released rig. Pumped d by 10 bbls water spacer. Mixed and pumped 02/24/11 Ige and belief. DATE05/16/11 DM PHONE: _713-420-5038/832-683-0361
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. 02/21/11: Spudded @ 1800 hrs. Set conductor. Drilled to 349'. Ran 8 5/8", 26#, J-55, \$02/22/11: Cemented surface casing with 100 sx. WOC. 02/23/11: Drilled production hole to 2755'. Estimated top of Trinidad 2445'. C&C hole 02/24/11: Ran 5 ½", 15.5#, J-55, LNG THD casing to 2689.72'. Tagged @ 2696'. Land 89 bbls fresh water with easy mud, 80 bbls gel pill with n-seal, baracarb & flocell followed 189 bbls Trinidad production blend cement mixed @ 13 ppg. No returns to surface. Spud Date: 02/21/11 Rig Release Date: TITLE Sr. Regulatory Analy Type or print name Maria S. Gomez E-mail address: maria.gomez@elpaso.ce	ompletions: Attach wellbore diagram of ST&C casing and set @ 339.34'. Tagged @ 2750' (5' of fill). C&C. Logged. led in WH @ 2693' KB. Released rig. Pumped d by 10 bbls water spacer. Mixed and pumped 02/24/11 lge and belief. DATE
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. 02/21/11: Spudded @ 1800 hrs. Set conductor. Drilled to 349'. Ran 8 5/8", 26#, J-55, \$02/22/11: Cemented surface casing with 100 sx. WOC. 02/23/11: Drilled production hole to 2755'. Estimated top of Trinidad 2445'. C&C hole 02/24/11: Ran 5 ½", 15.5#, J-55, LNG THD casing to 2689.72'. Tagged @ 2696'. Land 89 bbls fresh water with easy mud, 80 bbls gel pill with n-seal, baracarb & flocell followed 189 bbls Trinidad production blend cement mixed @ 13 ppg. No returns to surface. Spud Date: 02/21/11 Rig Release Date: TITLE Sr. Regulatory Analy Type or print name Maria S. Gomez E-mail address: maria.gomez@elpaso.ce	ompletions: Attach wellbore diagram of ST&C casing and set @ 339.34'. Tagged @ 2750' (5' of fill). C&C. Logged. led in WH @ 2693' KB. Released rig. Pumped d by 10 bbls water spacer. Mixed and pumped 02/24/11 lge and belief. DATE
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. 02/21/11: Spudded @ 1800 hrs. Set conductor. Drilled to 349'. Ran 8 5/8", 26#, J-55, \$02/22/11: Cemented surface casing with 100 sx. WOC. 02/23/11: Drilled production hole to 2755'. Estimated top of Trinidad 2445'. C&C hole 02/24/11: Ran 5 ½", 15.5#, J-55, LNG THD casing to 2689.72'. Tagged @ 2696'. Land 89 bbls fresh water with easy mud, 80 bbls gel pill with n-seal, baracarb & flocell followed 189 bbls Trinidad production blend cement mixed @ 13 ppg. No returns to surface. Spud Date: 02/21/11 Rig Release Date: TITLE Sr. Regulatory Analy Type or print name Maria S. Gomez E-mail address: maria.gomez@elpaso.ce For State Use Only	ompletions: Attach wellbore diagram of ST&C casing and set @ 339.34'. Tagged @ 2750' (5' of fill). C&C. Logged. led in WH @ 2693' KB. Released rig. Pumped d by 10 bbls water spacer. Mixed and pumped 02/24/11 Ige and belief. DATE05/16/11 DM PHONE: _713-420-5038/832-683-0361