

Submit 1 Copy To Appropriate District Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
October 13, 2009

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-007-20970
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name
8. Well Number A-581
9. OGRID Number 180514
10. Pool name or Wildcat Stubblefield Canyon Raton-Vermejo Gas
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 8701'

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other CBM

2. Name of Operator  
El Paso E&P Company, L.P.

3. Address of Operator  
1001 Louisiana, Rm 2730D, Houston, Texas 77002

4. Well Location  
Unit Letter B : 326 feet from the North line and 2013 feet from the East line  
Section 29 Township 32N Range 19E NMPM 6<sup>th</sup> County Colfax

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☒

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

03/14/11: Spudded @ 1415 hrs. Set conductor. Drilled 11" surface hole to 334'. C&C hole. Set 8 5/8", 24#, J-55, LT&C casing @ 324'. Pumped 10 bbls fresh water, 20 bbls gel water w/LCM, floccell, baracarb and n-seal. Pumped 29 bbls (100 sx) Trinidad blend cement @ 14 ppb. Displaced. WOC.

03/15/11: WOC. Drilled 7 7/8" hole to 2695'. Estimated top of Trinidad @ 2395' (hole making water @ approx 1 BPM).

03/17/11: C&C hole. Logged. Ran 5 1/2", 15.5#, J-55, LT&C production casing. Landed @ 2620.66'. ECP from 1856' - 1867'. Marker jt 583' - 593'. Released rig. Stage 1: Pumped 20 bbls fresh water, 20 bbls gel water w/ floccell, baracarb, n-seal, 20 bbls fresh water and cement with 47 bbls (122 sx) Trinidad blend cement. Dropped plug on fly and displaced. Bumped plug with 1000 psi. Final lift of 980 psi. Returns after 56 bbls displacement pumped. Dropped bomb. Opened ECP with 2600 psi. 2nd Stage: Pumped 10 bbls fresh water, 200 bbls gel water, 120 bbls fresh water gel w/n-seal, baracarb, floccell, 10 bbls of water @ 5BPM 60 psi and 10 bbls of water. Mixed and pumped 120 bbls (332 sx) Trinidad blend cement. Dropped plug on fly and displaced. Bumped plug with 2010 psi. Final lift pressure 1250 psi. Plug bumped. Had circ through out job. 28 bbls cement to pit.

Spud Date:

03/14/11

Rig Release Date:

03/17/11

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

*Maria S. Gomez*

TITLE Sr. Regulatory Analyst

DATE 05/23/11

Type or print name Maria S. Gomez E-mail address: maria.gomez@elpaso.com PHONE: 713-420-5038/832-683-0361

For State Use Only

APPROVED BY:

*S. Martin*

TITLE

DISTRICT SUPERVISOR

DATE 5/25/2011

Conditions of Approval (if any):