

Additional Information

Received 01/10/2022

Mewbourne Oil Company

Boomerang 6 Fee SWD #1

FSP Analysis

Eddy Co., NM

Luis Canales

Lesly Carter

January 10, 2022

LONQUIST & CO. LLC

**PETROLEUM
ENGINEERS**

**ENERGY
ADVISORS**

AUSTIN • HOUSTON ↑ CALGARY • WICHITA
DENVER • COLLEGE STATION ⊕ BATON ROUGE • EDMONTON

Table of Contents

1.0	Summary	4
2.0	FSP Analysis MODEL 1 – Basement Faults - All injectors	10
3.0	FSP Analysis MODEL 2 – Basement Faults - only Boomerang SWD well.....	30
4.0	FSP Analysis MODELS 3 and 4 – Woodford Faults	40
5.0	MODEL 1 FSP Analysis Results.....	50
6.0	MODEL 2 FSP Analysis Results.....	50
7.0	MODEL 3 and 4 FSP Analysis Results.....	51
8.0	Recorded Seismicity	52
9.0	Conclusion	54
	Appendix 1 - Earthquake Backup	55

FIGURES

Figure 1 - Proposed location and FSP analysis area of interest (“AOI”).	5
Figure 2 - Injection Target: Devonian.....	6
Figure 3 - Stratigraphic column of the Delaware Basin with the proposed injection interval (Devonian section) indicated by the red arrow.....	7
Figure 4 - Cross section index map	8
Figure 5 - Structural Cross Section – Proposed injection interval in light blue.....	9
Figure 6 - FSP Analysis Injection Wells.....	11
Figure 7 - FSP injection wells input Model 1	12
Figure 8 – Basement Fault segments (8) used in FSP Analysis Models 1 and 2.....	13
Figure 9 - FSP Fault input for Models 1 and 2	14
Figure 10 - Local Stress Parameters used (Snee and Zoback, 2018) Models 1 thru 10	15
Figure 11 - FSP Stress & Reservoir depth input Models 1 thru 4.....	16
Figure 12 - Injection Interval (reservoir parameters) FSP Input Models 1 thru 4.....	16
Figure 13 - FSP Model 1 Input: 14 injectors and 8 Basement fault segments	17
Figure 14 - FSP Geomechanics Tab, Model 1 and 2	18
Figure 15 - Input for Probabilistic Geomechanics Tab	19
Figure 16 - FSP Probabilistic Geomechanics Tab, Model 1 and 2	20
Figure 17 - FSP Hydrology Tab Before Proposed Completion.....	21
Figure 18 - Model 1 FSP Hydrology Tab	22
Figure 19 - Probabilistic Hydrology tab parameters Models 1 - 4	23
Figure 20 - Model 1 Probabilistic Hydrology Tab, before completion	24
Figure 21 - Model 1 Probabilistic Hydrology Tab, 20 years after completion	25
Figure 22 - Model 1 Integrated Tab, Initial Conditions before Boomerangis completed	26
Figure 23 - Model 1 Integrated Tab, Initial Conditions	27
Figure 24 - Model 1 Integrated Tab, 20 years after completion.....	28
Figure 25 - Model 1 Integrated Tab, 20 years after completion.....	29

Figure 26 - Model 2 Injector Input	30
Figure 27 - Model 2 Inputs Tab	31
Figure 28 - Model 2 Hydrology Tab, Initial Conditions	32
Figure 29 - Model 2 Hydrology Results, 20 years after Completion	33
Figure 30 - Model 2 Probabilistic Hydrology Results Tab, Initial Conditions	34
Figure 31 - Model 2 Probabilistic Hydrology Results Tab, 20 years after completion	35
Figure 32 - Model 2 Integrated Results Tab, Initial Conditions	36
Figure 33 - Model 2 Integrated Results Tab, Initial Conditions	37
Figure 34 - Model 2 Integrated Results Tab, 20 years after completion	38
Figure 35 - Model 2 Integrated Results Tab, 20 years after completion	39
Figure 36 - FSP Fault input for Models 3 and 4	40
Figure 37 - Woodford fault segments (9) used in FSP Analysis Models 3 and 4	41
Figure 38 - FSP Model 3 Input: 14 injectors and 9 Woodford fault segments	42
Figure 39 - FSP Model 4 Input: Only injector and 9 Woodford fault segments	43
Figure 40 - FSP Geomechanics Tab, Model 3 and 4	44
Figure 41 - FSP Probabilistic Geomechanics Tab, Model 3 and 4	45
Figure 42 - Model 3 Integrated Tab, Initial Conditions	46
Figure 43 - Model 3 Integrated Tab, 20 years after completion	47
Figure 44 - Model 4 Integrated Tab, Initial Conditions	48
Figure 45 - Model 4 Integrated Tab, 20 years after completion	49
Figure 46 – USGS reported seismicity	52
Figure 47 - USGS Earthquake catalog within Boomerang 6 Fee SWD #1 FSP AOI	53

TABLES

Table 1 - Model 1 FSP Results per fault segment	50
Table 2 - Model 2 FSP Results per fault segment	50
Table 3 - Model 3 & 4 FSP Results per fault segment.	51

1.0 Summary

The location of Boomerang 6 Fee SWD #1 ("Boomerang SWD"), the 13 offsetting active and permitted injection wells, and published faults within 6 miles of the Boomerang 6 Fee SWD #1 in Eddy County, New Mexico are shown on Figure 1. The Boomerang SWD permit application is targeting the Devonian formation which is a porous dolomitic limestone at a measured depth of 13,970' to 14,855' (Figure 2). The proposed average injection rate 25,000 barrels per day is equal to an average of 760,417 barrels per month which was forecasted for this FSP analysis.

The FSP models included utilize Woodford and Basement level fault traces documented by the Texas Bureau of Economic Geology (BEG) Integrated Synthesis of the Permian Basin <http://www.beg.utexas.edu/resprog/permianbasin/gis.htm>.

Injection fluids will be confined to the Devonian formation which is approximately 650 ft above the top of the Ellenburger. **None of the FSP models run utilizing these fault traces, proposed injection interval reservoir properties, and surrounding fluid injection data demonstrated evidence these faults would slip.**




Figure 1 - Proposed location and FSP analysis area of interest ("AOI").




Figure 2 - Injection Target: Devonian

System	Series	Group/Formation	General Lithology
<i>Tertiary</i>		<i>Ogallala</i>	<i>fluvial and lacustrine clastics</i>
<i>Cretaceous</i>		<i>Fredericksburg</i>	<i>limestone sandstone</i>
		<i>Paluxy</i>	
<i>Triassic</i>		<i>Dockum</i>	<i>fluvial-deltaic and lacustrine clastics</i>
<i>Permian</i>	<i>Ochoan</i>	<i>Dewey Lake</i>	<i>sandstone</i>
		<i>Rustler</i>	<i>salt, anhydrite</i>
		<i>Salado</i>	<i>salt</i>
	<i>Guadalupian</i>	<i>Tansill</i>	<i>anhydrite</i>
		<i>Yates</i>	<i>sandstone</i>
		<i>Seven Rivers</i>	<i>anhydrite</i>
		<i>Queen</i>	<i>sandstone</i>
		<i>San Andres-Grayburg</i>	<i>dolomite-sandstone</i>
	<i>Leonardian</i>	<i>Clear Fork</i>	<i>limestone-dolomite</i>
		<i>Wichita</i>	
	<i>Wolfcampian</i>	<i>Wolfcamp</i>	<i>shelf limestones, minor shale</i>
		<i>Cisco</i>	
		<i>Canyon</i>	
<i>Pennsylvanian</i>		<i>Strawn</i>	
		<i>Atokan</i>	
		<i>Chester</i>	<i>shale</i>
<i>Mississippian</i>		<i>Mississippian Lime</i>	<i>limestone</i>
<i>Devonian</i>		<i>Woodford</i>	<i>shale</i>
		<i>Devonian</i>	<i>limestone</i>
<i>Silurian</i>		<i>Silurian</i>	<i>shale, limestone</i>
<i>Ordovician</i>		<i>Montoya</i>	<i>limestone</i>
		<i>Simpson</i>	<i>shale, limestone</i>
		<i>Ellenburger</i>	<i>dolomite</i>
<i>PRECAMBRIAN</i>			<i>igneous, metamorphic</i>

*(Bassett and Bentley, 1982)

Figure 3 - Stratigraphic column of the Delaware Basin with the proposed injection interval (Devonian section) indicated by the red arrow.




Figure 4 - Cross section index map




Figure 5 - Structural Cross Section – Proposed injection interval in light blue.

2.0 FSP Analysis MODEL 1 – Basement Faults - All injectors

SCITS software (v 2.0) was used for the Fault Slip Potential (FSP) analysis.

Analysis includes:

- Fluid injection history from DrillingInfo within the 6 miles AOI.
- Proposed average injection rate (25,000 bpd) for Boomerang 6 Fee SWD #1.
- Proposed injection interval reservoir parameters and average depth.
- Local stress information and pressure gradients.
- Known fault locations within AOI with faults segmented to a maximum length of 3 km.

Two FSP models were run, including year-end analysis 20 years into the future.

- Model #1: includes permitted injection wells in the AOI plus the proposed injection interval (14 wells total).
- Model #2: includes only the proposed injection interval.

In summary, the proposed fluid injection does not significantly increase the risk that these faults will slip.

Figure 6 shows the location of existing fluid injection wells and the proposed Boomerang 6 Fee SWD #1 in relation to faults documented within the AOI. The Basement fault traces utilized on this models are shown on **Figure 8**.




Figure 6 - FSP Analysis Injection Wells

Partial View of 14 Wells

Injection Wells

☐ Enter Wells Manually

☒ Load Wells Complete .csv

Number of file header lines:

1

Load .csv File

	UniqueID/Name	Easting (km)	Northing (km)	Year	Month (1-12)	InjectionVolume (bbl/month)
458	26142	175.7554163	132.0064069	2020	3	605056
459	26142	175.7554163	132.0064069	2020	4	705128
460	26142	175.7554163	132.0064069	2020	5	228405
461	26142	175.7554163	132.0064069	2020	6	682317
462	26142	175.7554163	132.0064069	2020	7	723647
463	26142	175.7554163	132.0064069	2020	8	744187
464	26142	175.7554163	132.0064069	2020	9	517499
465	26142	175.7554163	132.0064069	2020	10	533143
466	26142	175.7554163	132.0064069	2020	11	310449
467	26142	175.7554163	132.0064069	2020	12	645604
468	26142	175.7554163	132.0064069	2021	1	494273
469	26142	175.7554163	132.0064069	2021	2	330596
470	26142	175.7554163	132.0064069	2021	3	358650
471	26142	175.7554163	132.0064069	2021	4	528597
472	26142	175.7554163	132.0064069	2021	5	491293
473	26142	175.7554163	132.0064069	2021	6	662251
474	26142	175.7554163	132.0064069	2021	7	648776
475	26142	175.7554163	132.0064069	2021	8	424252
476	26142	175.7554163	132.0064069	2021	9	315604
477	26142	175.7554163	132.0064069	2021	10	329167
478	26142	175.7554163	132.0064069	2021	11	547500
479	48530	178.3816949	121.9962875	2022	5	760417
480	BOOMERANG	172.0071994	128.5265359	2022	8	760417

File Format Help

Extrapolate Injection? ☒

Accepts up to 100 wells

OK

Figure 7 - FSP injection wells input Model 1




Figure 8 – Basement Fault segments (8) used in FSP Analysis Models 1 and 2

Basement Fault Segments

Fault Data

-
□
✕

Number of faults (max 500) 8

Friction Coefficient mu 0.58

☐ Random Faults
☒ Enter Faults

	X [East km]	Y [North km]	Strike [Deg]	Dip [Deg]	Length [km]
1	164.5413	132.6269	136.2000	70	2.3800
2	166.2662	130.7977	137.2000	70	2.6500
3	167.8479	129.0865	137.1000	70	2.0100
4	169.4308	127.3741	137.1000	70	2.6600
5	171.1152	125.5518	137.3000	70	2.3100
6	172.5891	123.9438	138	70	2.0600
7	174.0144	122.3659	138	70	2.2000
8	175.5025	120.7109	138	70	2.2500


Load File
Help

OK

Figure 9 - FSP Fault input for Models 1 and 2

State of stress in the Permian Basin, Texas and New Mexico: Implications for induced seismicity

Jens-Erik Lund Snee¹ and Mark D. Zoback¹ February 2018 THE LEADING EDGE



"The A_ϕ parameter describes the ratio between the principal stress magnitudes using a single, readily interpolated value that ranges smoothly from 0 (the most extensional possible condition of radial normal faulting) to 3 (the most compressive possible condition of radial reverse faulting)." (Snee & Zoback)

Shmax azimuth direction ($N35^\circ E$) is taken from the mapped Area 3 corresponding to this FSP analysis published by Snee and Zoback. The maximum horizontal stress gradient is derived from the A_ϕ parameter (0.52) also for Area 3

Figure 10 - Local Stress Parameters used (Snee and Zoback, 2018) Models 1 thru 10

Shmax azimuth direction ($N035^\circ E$) is taken from the mapped Area 3 corresponding to this FSP analysis published by Snee and Zoback (Figure 10). The maximum horizontal stress gradient is derived from the A_ϕ parameter (0.52) also for Area 3. The same stress parameters are used for all models (1 thru 4).

Stress Data

☐ Specify All Three Stress Gradients [psi/ft]

☒ Use A-Phi Model

Vertical Stress Gradient [psi/ft]

A-Phi Parameter

☐ Min Horiz Stress Grad Available [psi/ft]

Max Hor Stress Direction [deg N CW]

Initial Res. Pressure Gradient [psi/ft]

Reference Depth for Calculations [ft]

OK

Figure 11 - FSP Stress & Reservoir depth input Models 1 thru 4

The following reservoir parameters were utilized for the AOI as input to FSP models 1 thru 4.

Hydrology and well parameters data was provided by Mewbourne Oil Company.

Hydrology Data

☒ Enter Hydrologic Parameters

☐ Load External Hydrologic Model

Aquifer Thickness [ft]

Porosity [%]

Permeability [mD]

OK

Figure 12 - Injection Interval (reservoir parameters) FSP Input Models 1 thru 4.

Model 1 – Basement




Figure 13 - FSP Model 1 Input: 14 injectors and 8 Basement fault segments

Model 1 & 2




Figure 14 - FSP Geomechanics Tab, Model 1 and 2

Demonstrates pore pressure to slip (psi) for each fault segment, direction of S_{Hmax} , and a Mohr diagram with frictional slip line shown in red. Faults are colored according to the color scale.

A-Phi stress model is being used

	Plus/Minus
Vertical Stress Grad [1.1 psi/ft]	0.1
Initial PP Grad [0.44 psi/ft]	0.052
Strike Angles [varying, degrees]	5
Dip Angles [70 degrees]	7
Max Horiz. Stress Dir [35 degrees]	3.5
Friction Coeff Mu [0.58]	0.058
A Phi Parameter [0.52]	0.052

OK

Figure 15 - Input for Probabilistic Geomechanics Tab

The FSP program performs a probabilistic Monte Carlo analysis based on user specified variability of input parameters for both Geomechanical and Hydrology calculations.

Model 1 & 2




Figure 16 - FSP Probabilistic Geomechanics Tab, Model 1 and 2

The software propagates the relative uncertainties through the model, producing a distribution of pore pressures to slip.

Model 1 – Initial conditions before Boomerang SWD well is completed




Figure 17 - FSP Hydrology Tab Before Proposed Completion

The software demonstrates pressure change as a function of distance from each of the 14 injection wells in Model #1.

Model 1 - Conditions in 2042 after Boomerang SWD well is completed




Figure 18 - Model 1 FSP Hydrology Tab

The software projects pressure changes away from each injector 20 years after completion.

Probabilistic analysis input utilized for this internal radial flow-based model

Uniform Distribution bounds

☒ Probabilistic Hydrology
☐ Deterministic Hydrology

	Plus/Minus:
Aquifer Thickness [910 ft]	109.2
Porosity [6 %]	0.72
Perm [150 mD]	18
fluid density [1000 kg/(m ³)]	100
dynamic viscosity [0.0008 Pa.s]	0
Fluid Compressibility [3.6e-10 Pa ⁻¹]	0
Rock Compressibility [1.08e-09 Pa ⁻¹]	0
Change Computations?	
#Hydrologic Iterations=200, change?	200

OK

Figure 19 - Probabilistic Hydrology tab parameters Models 1 - 4

Model 1 – Initial Conditions before Boomerang SWD well is completed




Figure 20 - Model 1 Probabilistic Hydrology Tab, before completion

The Probabilistic Hydrology tabs combine hydrology with the Probabilistic Geomechanical cumulative distribution function (CDF) of the pore pressure to slip.

Model 1 – Conditions in 2042 after Boomerang SWD well is completed




Figure 21 - Model 1 Probabilistic Hydrology Tab, 20 years after completion

The following integrated tabs show the combined results of probabilistic geomechanics and hydrology models run for all 8 Basement fault segments.

Model 1 – Initial Conditions before Boomerang SWD well is completed




Figure 22 - Model 1 Integrated Tab, Initial Conditions before Boomerang is completed

Pore Pressure change (psi) is posted for each fault segment.

Model 1 – Initial Conditions before Boomerang SWD well is completed




Figure 23 - Model 1 Integrated Tab, Initial Conditions

Fault Slip Potential for each fault segment is posted as a percentage likelihood.

Model 1 – Conditions in 2042 after Boomerang SWD well is completed




Figure 24 - Model 1 Integrated Tab, 20 years after completion

Pore Pressure change (psi) is posted for each fault segment.

Model 1 – Conditions in 2042 after Boomerang SWD well is completed




Figure 25 - Model 1 Integrated Tab, 20 years after completion

Fault Slip Potential for each fault segment is posted as a percentage likelihood.

3.0 FSP Analysis MODEL 2 – Basement Faults - only Boomerang SWD well

Model #2 only incorporates the proposed Boomerang 6 Fee SWD #1 well with proposed injection rate of 25,000 barrels per day, or an average of 760,417 barrels per month.

All other parameters remain consistent as Model #1 such as faults, stress regime, reservoir, and probabilistic parameters. Below is the only change regarding Model #1 with respect to injector data.

Injection Wells

☐ Enter Wells Manually

☒ Load Wells Complete .csv

Number of file header lines:

	UniqueID/Name	Easting (km)	Northing (km)	Year	Month (1-12)	InjectionVolume (bbl/month)
1	BOOMERANG	172.0071994	128.5265359	2022	8	760417

Extrapolate Injection? ☒ Accepts up to 100 wells

Figure 26 - Model 2 Injector Input

Model 2 - Basement




Figure 27 - Model 2 Inputs Tab

The following FSP result tabs are for the second model which includes only the proposed injection well.

Model 2 – Initial conditions before Boomerang SWD well is completed




Figure 28 - Model 2 Hydrology Tab, Initial Conditions

Model 2 - Conditions in 2042 after Boomerang SWD well is completed.




Figure 29 - Model 2 Hydrology Results, 20 years after Completion

Model 2 – Initial Conditions before Boomerang SWD well is completed




Figure 30 - Model 2 Probabilistic Hydrology Results Tab, Initial Conditions

Model 2 – Conditions in 2042 after Boomerang SWD well is completed




Figure 31 - Model 2 Probabilistic Hydrology Results Tab, 20 years after completion

Only includes proposed injector, held constant at the permitted rate.

Model 2 – Initial Conditions before Boomerang SWD well is completed




Figure 32 - Model 2 Integrated Results Tab, Initial Conditions

Pore Pressure change (psi) is posted for each fault segment.

Model 2 – Initial Conditions before Boomerang SWD well is completed




Figure 33 - Model 2 Integrated Results Tab, Initial Conditions

Fault Slip Potential for each fault segment is posted as a percentage likelihood.

Model 2 – Conditions in 2042 after Boomerang SWD well is completed




Figure 34 - Model 2 Integrated Results Tab, 20 years after completion

Pore Pressure change (psi) is posted for each fault segment.

Model 2 – Conditions in 2042 after Boomerang SWD well is completed




Figure 35 - Model 2 Integrated Results Tab, 20 years after completion

Fault Slip Potential for each fault segment is posted as a percentage likelihood.

4.0 FSP Analysis MODELS 3 and 4 – Woodford Faults

Models #3 and #4 analyze Woodford fault traces within the AOI which utilize the same methodology as previous models. Input parameters for stress regime, reservoir, and probabilistic ranges are consistent with Models 1 & 2. Therefore, the following figures (36 to 45) illustrate the Precambrian fault traces used as input, and the FSP results tabs.

Model #3 incorporates all 14 injection wells, whereas Model #4 only uses the planned Boomerang 6 Fee SWD #1 completion with proposed average injection rate of 25,000 barrels per day, or an average of 760,417 barrels per month.

Fault Data

Number of faults (max 500)

Friction Coefficient mu

☐ Random Faults

☒ Enter Faults

	X [East km]	Y [North km]	Strike [Deg]	Dip [Deg]	Length [km]
1	163.9619	131.9552	137.7000	70	1.9900
2	165.5193	130.2271	138.3000	70	2.6600
3	167.1233	128.4506	137.5000	70	2.1300
4	168.7543	126.7632	134.6000	70	2.5700
5	170.3176	125.2160	134.8000	70	1.8300
6	171.4297	124.0941	135.9000	70	1.3300
7	172.5659	122.8073	140.3000	70	2.1100
8	173.8664	121.2480	140.1000	70	1.9600
9	174.9183	119.9868	140.1000	70	1.3300

Figure 36 - FSP Fault input for Models 3 and 4




Figure 37 - Woodford fault segments (9) used in FSP Analysis Models 3 and 4

Model 3 - Woodford




Figure 38 - FSP Model 3 Input: 14 injectors and 9 Woodford fault segments

Model 4 - Woodford




Figure 39 - FSP Model 4 Input: Only injector and 9 Woodford fault segments

Model 3 and 4




Figure 40 - FSP Geomechanics Tab, Model 3 and 4

Demonstrates pore pressure to slip (psi) for each fault segment, direction of SHmax, and a Mohr diagram with frictional slip line shown in red. Faults are colored according to the color scale.

Model 3 and 4




Figure 41 - FSP Probabilistic Geomechanics Tab, Model 3 and 4

Propagates the relative uncertainties through the model producing a distribution of pore pressures to slip.

The following page shows the integrated tabs which combined results of probabilistic geomechanics and hydrology models run for all 9 Woodford fault segments.

Model 3 – Initial Conditions before Boomerang SWD well is completed




Figure 42 - Model 3 Integrated Tab, Initial Conditions

Pore Pressure change (psi) is posted for each fault segment.

Model 3 – Conditions in 2042 after Boomerang SWD well is completed




Figure 43 - Model 3 Integrated Tab, 20 years after completion.

Pore Pressure change (psi) is posted for each fault segment.

Model 4 – Initial Conditions before Boomerang SWD well is completed




Figure 44 - Model 4 Integrated Tab, Initial Conditions

Pore Pressure change (psi) is posted for each fault segment.

Model 4 – Conditions in 2042 after Boomerang SWD well is completed




Figure 45 - Model 4 Integrated Tab, 20 years after completion

Pore Pressure change (psi) is posted for each fault segment.

5.0 MODEL 1 FSP Analysis Results

Model 1 13 Injection Wells, Boomerang SWD & Basement faults					
Fault	Pore Pressure to Slip	PP Change 2022	FSP 2022	PP Change 2042	FSP 2042
1	4521	3	0.00	78	0.00
2	4448	5	0.00	98	0.00
3	4455	9	0.00	117	0.00
4	4455	16	0.00	133	0.00
5	4440	28	0.00	145	0.00
6	4387	40	0.00	149	0.00
7	4387	41	0.00	145	0.00
8	4387	34	0.00	135	0.00

Table 1 - Model 1 FSP Results per fault segment

6.0 MODEL 2 FSP Analysis Results

Model 2 Boomerang SWD & Basement faults					
Fault	Pore Pressure to Slip	PP Change 2022	FSP 2022	PP Change 2042	FSP 2042
1	4521	0	0.00	13	0.00
2	4448	0	0.00	19	0.00
3	4455	0	0.00	27	0.00
4	4440	0	0.00	34	0.00
5	4387	0	0.00	32	0.00
6	4387	0	0.00	25	0.00
7	4387	0	0.00	18	0.00
8	4387	0	0.00	13	0.00

Table 2 - Model 2 FSP Results per fault segment

7.0 MODEL 3 and 4 FSP Analysis Results

Model 3					
13 Injection Wells, Boomerang SWD & Woodford faults					
Fault	Pore Pressure to Slip	PP Change 2022	FSP 2022	PP Change 2042	FSP 2042
1	4410	2	0.00	65	0.00
2	4364	4	0.00	83	0.00
3	4425	8	0.00	105	0.00
4	4629	15	0.00	129	0.00
5	4616	26	0.00	148	0.00
6	4542	34	0.00	157	0.00
7	4200	39	0.00	160	0.00
8	4217	38	0.00	154	0.00
9	4217	35	0.00	145	0.00

Model 4					
Boomerang SWD & Woodford faults					
Fault	Pore Pressure to Slip	PP Change 2022	FSP 2022	PP Change 2042	FSP 2042
1	4410	0	0.00	13	0.00
2	4364	0	0.00	18	0.00
3	4425	0	0.00	24	0.00
4	4629	0	0.00	29	0.00
5	4616	0	0.00	29	0.00
6	4542	0	0.00	25	0.00
7	4200	0	0.00	21	0.00
8	4217	0	0.00	16	0.00
9	4217	0	0.00	12	0.00

Table 3 - Model 3 & 4 FSP Results per fault segment.

8.0 Recorded Seismicity

Between 1/1/1900 and 1/06/2021 **0 earthquakes** with magnitudes 2 or greater were recorded by **USGS** within the Boomerang 6 Fee SWD #1 FSP AOI (6 miles).




Figure 46 – USGS reported seismicity

0 Earthquakes with magnitude of 2 or greater inside the the Boomerang 6 Fee SWD #1 FSP ANALYSIS AREA




Figure 47 - USGS Earthquake catalog within Boomerang 6 Fee SWD #1 FSP AOI

9.0 Conclusion

Four (4) FSP models were run within Boomerang SWD AOI analyzing the following fault traces.

- Precambrian
- Woodford

Two models were run for each set of fault traces, the first included all currently active injectors and select permitted injectors within the 6-mile AOI (including the proposed Boomerang 6 Fee SWD #1 location), and the second model per fault set only includes the proposed SWD well. The reservoir and stress parameters for the proposed injection interval do not increase the potential for the faults analyzed to slip.

In our opinion the proposed BOOMERANG6 FEE SWD #1 injection well does not pose a risk of increasing seismicity within this FSP AOI.

Appendix 1 - Earthquake Backup

USGS
Earthquake Hazards Program

Search Earthquake Catalog

Search results are limited to 20,000 events. To get URLs for a search, click the search button, then copy the URL from the browser address bar.

- [FAQ](#)
- [USGS Comprehensive Earthquake Catalog \(ComCat\) Documentation](#)
- [Researcher's Guide - A library of functions and services for the MNC's ComCat data](#)
- [USGS Search Earthquake Catalog](#)

Basic Options

Magnitude

☐ 2.0+
☐ 4.0+
☒ Custom

Minimum:
Maximum:

Date & Time

☐ Past 7 Days
☐ Past 30 Days
☒ Custom

Start (UTC):
End (UTC):

Geographic Region

☒ World
☐ Conterminous U.S.¹
☐ Custom

Worldwide:

Search

BOOMERANG 6 FEE SWD #1
ELEV.: 3060'
LAT: 32.1592532° N (NAD83)
LONG: 104.1269550° W (NAD83)

Circle

Center Latitude:
Center Longitude:
Outer Radius (km):

0 Earthquakes with magnitude of 2 or greater inside the Boomerang 6 Fee SWD #1 FSP ANALYSIS AREA

USGS

Search Results

0 of 0 earthquakes in map area.

☒ Only List Earthquakes Shown on Map

Format: Sort:


Didn't find what you were looking for?

- Check your [Settings](#).
- [Which earthquakes are included on the map and list?](#)
- [Felt something not shown - report it here.](#)

Modify Search?

Your search has zero results, you can view realtime data instead or modify your search.

Mewbourne Oil Company FSP ANALYSIS



USGS
Earthquake Research Program

Search Earthquake Catalog

Search results are limited to 20,000 events. To get URLs for a search, click the search button, then copy the URL from the browser address bar.

- Help
- USGS Comprehensive Earthquake Catalog / Open-File Documentation
- Developer's Corner: Library of functions and services for use with the USGS's Open-File data
- Download Earthquake Archives

Basic Options

Magnitude

☐ 2.5+

☐ 4.5+

☒ Custom

Minimum:

Maximum:

Date & Time

☐ Past 7 Days

☐ Past 30 Days

☒ Custom

Start (UTC):

End (UTC):

Geographic Region

☒ World


☐ Conterminous U.S.

☐ Custom

Worldwide:

☐ Advanced Options

One USGS earthquake within 20 km of the Boomerang 6 Fee SWD #1



Circle

Center Latitude


32.1592532

Center Longitude

-104.126955

Outer Radius (km)

20



M 3.9 - 5 km WNW of Loving, New Mexico

1974-11-28 03:35:20 (UTC) | 32.311°N 104.143°W | 5.0 km depth

Origin

[View all origin products \(1 total\)](#)

Contributed by [US¹](#) last updated 2014-11-06 23:21:27 (UTC)

- ✓ The data below are the most preferred data available
- ✓ The data below have been reviewed by a scientist

Details	Phases	Magnitudes
Magnitude	3.9 mb	
Location	32.311°N 104.143°W	
Depth uncertainty	5.0 km	
Origin Time	1974-11-28 03:35:20.500 UTC	

LONQUIST & CO.

PETROLEUM
ENGINEERS

ENERGY
ADVISORS

AUSTIN • HOUSTON • CALGARY • WISCONSIN
DENVER • COLLEGE STATION • BAYTOWN • HOUSTON

Boomerang 6 Fee SWD #1

The closest earthquake is 1974-11-28 03:35:20, Lat 32.3108793, Long - 104.1425000, Mag 3.9 and it's 16.9 km (10.5 miles) away from Boomerang 6 Fee SWD #1

