

1R - 2498

# REPORTS

DATE:

12-3-12

# Rice Environmental Consulting & Safety

P.O. Box 5630 Hobbs, NM 88241  
Phone 575.393.4411 Fax 575.393.0293

RECEIVED OCD

2012 DEC -6 P 1:35

CERTIFIED MAIL

RETURN RECEIPT NO. 7008 1140 0001 3073 0582

**December 3<sup>rd</sup>, 2012**

**Mr. Edward Hansen**

New Mexico Energy, Minerals, & Natural Resources  
Oil Conservation Division, Environmental Bureau  
1220 S. St. Francis Drive  
Santa Fe, New Mexico 87505

**RE: CAP Report for Groundwater  
Apache Corporation  
Walter Lynch Tank Battery (1R-2498): UL/F sec. 1 T22S R37E**

Mr. Hansen:

Apache Corporation, Inc. (Apache) has retained Rice Environmental Consulting and Safety (RECS) to address potential environmental concerns at the above-referenced site.

## **Background and Previous Work**

This site is located approximately 2.5 miles south-east of Eunice, New Mexico at UL/F sec. 1 T22S R37E as shown on the Site Location Map (Figure 1). Monitor wells at the site indicate groundwater will be encountered at 54 +/- feet.

On August 26<sup>th</sup>, 2009, four soil bores were advanced at the site. Each soil bore was sampled every five feet and all samples were taken to a commercial laboratory for field test confirmation. SB-1 was drilled to a depth of 65 ft bgs and had laboratory chloride readings ranging from a high of 1,424 mg/kg at 35 ft bgs to a low of 96 mg/kg at 30 ft bgs. SB-2 was drilled to 65 ft bgs and had laboratory chloride readings ranging from a high of 1,860 mg/kg at 40 ft bgs to a low of 96 mg/kg at 55 ft bgs. SB-3 was drilled to a depth of 56 ft bgs and had laboratory chloride readings ranging from a high of 1,230 mg/kg at 25 ft bgs to a low of non-detect at 5 ft bgs. Finally, SB-4 was drilled to 56 ft bgs and had laboratory chloride readings ranging from a high of 672 mg/kg at 55 ft bgs to a low of 16 mg/kg at 5 ft bgs. BTEX, GRO, and DRO were all non-detect throughout all the bores and at all depths. All four soil bores were plugged and abandoned (P&A) on August 27<sup>th</sup>, 2009 in conformance with NMOCD Rules and Regulations.

On December 8-9<sup>th</sup>, 2009, three monitor wells were installed at the site. Two soil samples from each monitor well installation were sent to a commercial laboratory for verification of field numbers. From MW-1, samples from 10 ft bgs and 60 ft bgs were taken. The laboratory chloride reading from the 10 ft bgs sample was non-detect and from 60 ft bgs sample was 64 mg/kg. From MW-2, the 10 ft bgs and 60 ft bgs samples were taken for laboratory analysis. The chloride reading for 10 ft bgs sample was non-detect and the reading from 60 ft bgs sample was 96 mg/kg. From MW-3, the 10 ft bgs and 57 ft bgs

samples were taken for laboratory analysis. The chloride reading for the 10 ft bgs sample was 16 mg/kg and the chloride reading for 57 ft bgs sample was 96 mg/kg. BTEX, GRO, and DRO were non-detect in the soil samples for all the wells.

On January 20<sup>th</sup>, 2010, Apache submitted a Notice of Groundwater Impact to the NMOCD District 1 office.

On February 10<sup>th</sup>, 2010, Apache submitted a Remediation Proposal to the NMOCD District 1 office. In that report, Apache agreed that it would excavate the entire area to 4 ft bgs. The sidewalls would be excavated to whatever distance necessary to achieve chloride numbers at or below 250 mg/kg. Once the site was excavated, a 20 mil-polyethylene liner would be installed along the bottom and up the sidewalls to inhibit chloride migration through the vadose zone to groundwater. The site would then be backfilled to bring the excavation to surface level and seeded. The remediation proposal was approved by NMOCD and the soil work was subsequently completed.

On September 2<sup>nd</sup>, 2011, MW-2 was plugged and abandoned per NMOCD requirements with a 1 – 3% bentonite slurry and a 3 foot concrete cap. It was replaced with a 4 inch recovery well (RW-1) located approximately 7 ft northwest of the former MW-2.

The Walter Lynch Tank Battery site is located within a regionally impacted groundwater area. The up gradient monitor well (MW-1) shows chloride impacted water (570 mg/L) coming onto the site. However, it is apparent that although the up gradient groundwater is impaired before it moves across the site, it has also been affected by prior downward migration of residual soil chlorides from the vadose zone. The down gradient well (RW-1) showed evidence of these prior residual soil chlorides from the site with a laboratory chloride reading of 1,220 mg/L (Figure 2 and Appendix A). However, since Apache installed a 20 mil-polyethylene liner, the subsequent effects to groundwater from the vadose zone will have become negligible. The liner will have virtually stopped the downward migration of water and thus the downward movement of chlorides. Therefore, only the chloride mass in the groundwater has been taken into account.

As part of the Corrective Action Plan submitted to NMOCD of October 11<sup>th</sup>, 2011 and approved on October 18<sup>th</sup>, 2011, Apache proposed to remove a total chloride mass of 1,256 kg. Groundwater source removal at the site began on April 9<sup>th</sup>, 2012 and continued until October 25<sup>th</sup>, 2012, when the pump was shut in for winter. During the 2012 season, a total of 2,778 barrels of water were removed from the site. Given the most recent chloride concentration of 1,220 mg/L, this equates to 538 kgs of chloride removed from the site. As weather conditions have change and become more intemperate, Apache shut in the groundwater removal system at the site until the spring thaw. Once the weather is again conducive for pumping, Apache will begin the groundwater source removal for the year 2013.

Pumping activities will continue at the site until the calculated amount of chlorides is removed or until a significant reduction in chloride concentrations in the groundwater is achieved, whichever occurs later.

RECS appreciates the opportunity to work with you on this project. Please call Hack Conder at (575) 393-9174 or Natalie Gladden (Apache) (575) 390-4186 if you have any questions or wish to discuss the site.


Sincerely,

A handwritten signature in black ink, appearing to read 'L.W.', followed by a long, horizontal, sweeping flourish.

Lara Weinheimer  
Project Scientist  
RECS  
(575) 441-0431

Attachments


- Figure 1 – Site Location Map
- Figure 2 – MW Sampling Data Map
- Appendix A – MW Sampling Data Lab



# Figures

**RICE Environmental Consulting and Safety (RECS)**  
P.O. Box 5630 Hobbs, NM 88241  
Phone 575.393.4411 Fax 575.393.0293

# Site Map




## Apache Walter Lynch Tank Battery

Legals: UL/F sec. 1  
T22S R37E

NMOCD Case #: 1R-2498


## Figure 1



Drawing date: 2-9-10  
Drafted by: L. Weinheimer

# MW Sampling Data


MW	Depth to Water	Volume Purged	Sample Date	Cl
1	55.5	10	3/5/2012	600
	55.49	10	6/20/2012	590
	55.64	10	9/25/2012	570
MW	Depth to Water	Volume Purged	Sample Date	Cl
RW-1	56.85	90	3/5/2012	1200
	XXX	Pumping	6/20/2012	1220
	XXX	Pumping	9/25/2012	1220
MW	Depth to Water	Volume Purged	Sample Date	Cl
3	54.83	10	3/5/2012	630
	54.86	10	6/20/2012	600
	55.02	10	9/25/2012	640




## APACHE WALTER LYNCH TANK BATTERY AREA

Legals: UL's C,D,E,F sec. 1  
 T-22-S R-37-E  
 NMOCD Case #: 1R-2498

### Figure 2





# Appendix A

MW Sampling Data Lab

**RICE Environmental Consulting and Safety (RECS)**  
P.O. Box 5630 Hobbs, NM 88241  
Phone 575.393.4411 Fax 575.393.0293

October 02, 2012

NATALIE GLADDEN

APACHE - EUNICE

P. O. BOX 1849

EUNICE, NM 88231

RE: APACHE WALTER LYNCH TANK BATTERY

Enclosed are the results of analyses for samples received by the laboratory on 09/28/12 15:03.

Cardinal Laboratories is accredited through Texas NELAP under certificate number T104704398-11-3. Accreditation applies to drinking water, non-potable water and solid and chemical materials. All accredited analytes are denoted by an asterisk (\*). For a complete list of accredited analytes and matrices visit the TCEQ website at [www.tceq.texas.gov/field/ga/lab\\_accred\\_certif.html](http://www.tceq.texas.gov/field/ga/lab_accred_certif.html).

Cardinal Laboratories is accredited through the State of Colorado Department of Public Health and Environment for:

Method EPA 552.2	Haloacetic Acids (HAA-5)
Method EPA 524.2	Total Trihalomethanes (TTHM)
Method EPA 524.4	Regulated VOCs (V1, V2, V3)

Accreditation applies to public drinking water matrices.

This report meets NELAP requirements and is made up of a cover page, analytical results, and a copy of the original chain-of-custody. If you have any questions concerning this report, please feel free to contact me.

Sincerely,



Celey D. Keene

Lab Director/Quality Manager

**Analytical Results For:**

 APACHE - EUNICE  
 NATALIE GLADDEN  
 P. O. BOX 1849  
 EUNICE NM, 88231  
 Fax To: 394-2425

Received:	09/28/2012	Sampling Date:	09/25/2012
Reported:	10/02/2012	Sampling Type:	Water
Project Name:	APACHE WALTER LYNCH TANK BATTERY	Sampling Condition:	Cool & Intact
Project Number:	NONE GIVEN	Sample Received By:	Amanda Ponce
Project Location:	T22S-R37E-SEC1 UL/F-LEA CTY., NM		

**Sample ID: MONITOR WELL #1 (H202376-01)**

Chloride, SM4500Cl-B	mg/L	Analyzed By: AP							
Analyte	Result	Reporting Limit	Analyzed	Method Blank	BS	% Recovery	True Value QC	RPD	Qualifier
Chloride*	570	4.00	10/02/2012	ND	100	100	100	0.00	

**Sample ID: MONITOR WELL #3 (H202376-02)**

Chloride, SM4500Cl-B	mg/L	Analyzed By: AP							
Analyte	Result	Reporting Limit	Analyzed	Method Blank	BS	% Recovery	True Value QC	RPD	Qualifier
Chloride*	640	4.00	10/02/2012	ND	100	100	100	0.00	


**Sample ID: RECOVERY WELL #1 (H202376-03)**

Chloride, SM4500Cl-B	mg/L	Analyzed By: AP							
Analyte	Result	Reporting Limit	Analyzed	Method Blank	BS	% Recovery	True Value QC	RPD	Qualifier
Chloride*	1220	4.00	10/02/2012	ND	100	100	100	0.00	

Cardinal Laboratories

\*=Accredited Analyte

PLEASE NOTE: Liability and Damages. Cardinal's liability and client's exclusive remedy for any claim arising, whether based in contract or tort, shall be limited to the amount paid by client for analyses. All claims, including those for negligence and any other cause whatsoever shall be deemed waived unless made in writing and received by Cardinal within thirty (30) days after completion of the applicable service. In no event shall Cardinal be liable for incidental or consequential damages, including, without limitation, business interruptions, loss of use, or loss of profits incurred by client, its subsidiaries, affiliates or successors arising out of or related to the performance of the services hereunder by Cardinal, regardless of whether such claim is based upon any of the above stated reasons or otherwise. Results relate only to the samples identified above. This report shall not be reproduced except in full with written approval of Cardinal Laboratories.



Celey D. Keene, Lab Director/Quality Manager

**Notes and Definitions**


- ND Analyte NOT DETECTED at or above the reporting limit
- RPD Relative Percent Difference
- \*\* Samples not received at proper temperature of 6°C or below.
- \*\*\* Insufficient time to reach temperature.
- Chloride by SM4500Cl-B does not require samples be received at or below 6°C  
Samples reported on an as received basis (wet) unless otherwise noted on report

---

Cardinal Laboratories

\*=Accredited Analyte

PLEASE NOTE: Liability and Damages. Cardinal's liability and client's exclusive remedy for any claim arising, whether based in contract or tort, shall be limited to the amount paid by client for analyses. All claims, including those for negligence and any other cause whatsoever shall be deemed waived unless made in writing and received by Cardinal within thirty (30) days after completion of the applicable service. In no event shall Cardinal be liable for incidental or consequential damages, including, without limitation, business interruptions, loss of use, or loss of profits incurred by client, its subsidiaries, affiliates or successors arising out of or related to the performance of the services hereunder by Cardinal, regardless of whether such claim is based upon any of the above stated reasons or otherwise. Results relate only to the samples identified above. This report shall not be reproduced except in full with written approval of Cardinal Laboratories.



---

Celey D. Keene, Lab Director/Quality Manager

