MM OIL CONSERVATION ARTESIA DISTRICT

District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

APR 1 0 2017

Form C-141 Revised August 8, 2011

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Release Notification and Corrective Action

NABI710234614 OPERATOR X Initial Report Final Report				
OPERATOR	X	Initial Report	Final Report	
Contact: Johnny Titsworth				
Telephone No. (432) 425-2891				
Facility Type: well				
	Contact: Johnny Titsworth Telephone No. (432) 425-2891	Contact: Johnny Titsworth Telephone No. (432) 425-2891	Contact: Johnny Titsworth Telephone No. (432) 425-2891	

······		
Surface Owner:	BLM	Mineral Owner: BLM

API No. 30-015-21386

RECEIVED opy to appropriate District Office in accordance with 19.15.29 NMAC.

LOCATION OF RELEASE

Unit Letter N	Section 13	Township 17S	Range 30E	Feet from the 660	North/South Line FSL	Feet from the 1980	East/West Line FWL	County Eddy

Latitude: 32.84957 Longitude: -103.92321

NATURE OF RELEASE

Type of Release: produced water	Volume of Release: 5	Volume Recovered: 0
Source of Release: steel flow line	Date and Hour of Occurrence:	Date and Hour of Discovery
	4/8/17 9:00 am	4/8/17 9:30 am
Was Immediate Notice Given?	If YES, To Whom?	
🗌 Yes 🔲 No 🔲 Not Required		
By Whom? Johnny Titsworth	Date and Hour 4/10/17	
Was a Watercourse Reached?	If YES, Volume Impacting the Wa	atercourse.
Yes X No		
If a Watercourse was Impacted, Describe Fully.*		
Describe Cause of Problem and Remedial Action Taken.*		
steel flowline corroded and release fluid into the pasture area approx. 165	' to the West of the Jackson B 55 we	ll location.
		1
Describe Area Affected and Cleanup Action Taken.*		
The release impacted an area approx. 60'x5'		
I hereby certify that the information given above is true and complete to t	he hest of my knowledge and underst	and that nursuant to NMOCD rules and
regulations all operators are required to report and/or file certain release n	otifications and perform corrective a	ctions for releases which may endanger
public health or the environment. The acceptance of a C-141 report by th		
should their operations have failed to adequately investigate and remediat		
should then operations have raned to adequately investigate and remediat	e contamination that pose a threat to	ground water, surface water, numan near
or the environment. In addition, NMOCD acceptance of a C-141 report d	loes not relieve the operator of respon	isibility for compliance with any other
federal, state, or local laws and/or regulations.		
	<u>OIL CONSER</u>	VATION DIVISION
Signature:	Signed De	Alla Kan
	Approved by Environmental Special	in Prance Late
Printed Name Johnny Titsworth		· · · · · · · · · · · · · · · · · · ·
	Alulin	
Title: HSE Coordinator	Approval Date:	Expiration Date: NHT
E-mail Address: jtitsworth@burnettoil.com	Conditions of Approval:	A
		Attached M
Date: 4/10/17 Phone: (432) 425-2891	CHE WITT	X//N/X
Attach Additional Sheets If Necessary		
Autori Austronal Shotis II Nocossaly		120-416
		LIVIA

Operator/Responsible Party,

The OCD has received the form C-141 you provided on $\frac{4/10/17}{1000}$ regarding an unauthorized release. The information contained on that form has been entered into our incident database and remediation case number where the provided on the provided o

It is the Division's obligation under both the Oil & Gas Act and Water Quality Act to provide for the protection of public health and the environment. Our regulations (19.15.29.11 NMAC) state the following,

The responsible person shall complete <u>division-approved corrective action</u> for releases that endanger public health or the environment. The responsible person shall address releases in accordance with a remediation plan submitted to and approved by the division or with an abatement plan submitted in accordance with 19.15.30 NMAC. [emphasis added]

Release characterization is the first phase of corrective action unless the release is ongoing or is of limited volume and all impacts can be immediately addressed. Proper and cost-effective remediation typically cannot occur without adequate characterization of the impacts of any release. Furthermore, the Division has the ability to impose reasonable conditions upon the efforts it oversees. As such, the Division is requiring a workplan for the characterization of impacts associated with this release be submitted to the OCD District $\frac{2}{2}$ office in <u>ARTESIA</u> on or before <u>5/10/17</u>. If and when the release characterization workplan is approved, there will be an associated deadline for submittal of the resultant investigation report. Modest extensions of time to these deadlines may be granted, but only with acceptable justification.

The goals of a characterization effort are: 1) determination of the lateral and vertical extents along with the magnitude of soil contamination. 2) determine if groundwater or surface waters have been impacted. 3) If groundwater or surface waters have been impacted, what are the extents and magnitude of that impact. 4) The characterization of any other adverse impacts that may have occurred (examples: impacts on vegetation, impacts on wildlife, air quality, loss of use of property, etc.). To meet these goals as quickly as possible, the following items must, at a minimum, be addressed in the release characterization workplan and subsequent reporting:

• Horizontal delineation of soil impacts in each of the four cardinal compass directions. Adsorbed soil contamination must be characterized for the following constituents using the associated laboratory methods: benzene, toluene, ethylbenzene, and total xylenes by either Method 8260 or 8021, total petroleum hydrocarbons by Method 8015 extended range (GRO+DRO+MRO; C₆ thru C₃₆), and for chloride by Method 300. This is not an exclusive list of potential contaminants. Analyzed parameters should be modified based on the nature of the released substance(s). Soil sampling must be both within the impacted area and beyond.

• Vertical delineation of soil impacts. Adsorbed soil contamination must be characterized for the following constituents using the associated laboratory methods: benzene, toluene, ethylbenzene, and total xylenes by either Method 8260 or 8021, total petroleum hydrocarbons by Method 8015 extended range (GRO+DRO+MRO; C₆ thru C₃₆), and for chloride by Method 300. As above, this is not an exclusive list of potential contaminants and can be modified. Vertical characterization samples should be taken at depth intervals no greater than five feet apart. Lithologic description of encountered soils must also be provided. At least ten vertical feet of soils with contaminant concentrations at or below these values must be demonstrated as existing above the water table.

• Nominal detection limits for field and laboratory analyses must be provided.

• Composite sampling is not generally allowed.

• Field screening and assessment techniques are acceptable (headspace, titration, EC [include algorithm for validation purposes], EM, etc.), but the sampling and assay procedures must be clearly defined. Copies of field notes are highly desirable. A statistically significant set of split samples must be submitted for confirmatory laboratory analysis, including the laterally farthest and vertically deepest sets of soil samples. Make sure there are at least two soil samples submitted

for laboratory analysis from each borehole or test pit (highest observed contamination and deepest depth investigated). Copies of the actual laboratory results must be provided including chain of custody documentation.

•Probable depth to shallowest protectable groundwater and lateral distance to nearest surface water. If there is an estimate of groundwater depth, the information used to arrive at that estimate must be provided. If there is a reasonable assumption that the depth to protectable water is 50 feet or less, the responsible party should anticipate the need for at least one groundwater monitoring well to be installed in the area of likely maximum contamination.

• If groundwater contamination is encountered, an additional investigation workplan may be required to determine the extents of that contamination. Groundwater and/or surface water samples, if any, must be analyzed by a competent laboratory for volatile organic hydrocarbons (typically Method 8260 full list), total dissolved solids, pH, major anions and cations including chloride and sulfate, dissolved iron, and dissolved manganese. The investigation workplan must provide the groundwater sampling method(s) and sample handling protocols. To the fullest extent possible, aqueous analyses must be undertaken using nominal method detection limits. As with the soil analyses, copies of the actual laboratory results must be provided including chain of custody documentation.

• Accurately scaled and well-drafted site maps must be provided providing the location of borings, test pits, monitoring wells, potentially impacted areas, and significant surface features including roads and site infrastructure that might limit either the release characterization or remedial efforts. Field sketches may be included in subsequent reporting, but should not be considered stand-alone documentation of the site's layout. Digital photographic documentation of the location and fieldwork is recommended, especially if unusual circumstances are encountered.

Nothing herein should be interpreted to preclude emergency response actions or to imply immediate remediation by removal cannot proceed as warranted. Nonetheless, characterization of impacts and confirmation of the effectiveness of remedial efforts must still be provided to the OCD before any release incident will be closed.

Jim Griswold OCD Environmental Bureau Chief 1220 South St. Francis Drive Santa Fe, New Mexico 87505 505-476-3465 jim.griswold@state.nm.us

Bratcher, Mike, EMNRD

From:	Johnny Titsworth <jtitsworth@burnettoil.com></jtitsworth@burnettoil.com>
Sent:	Monday, April 10, 2017 2:51 PM
То:	Tucker, Shelly; Bratcher, Mike, EMNRD; Weaver, Crystal, EMNRD
Cc:	Kyle Adams; Leslie Garvis
Subject:	Jackson B 30 WIW release
Attachments:	JB 30 initial C-141 4.8.17.pdf

All

We had a release on the Jackson B 30 WIW flowline. The release was approx. 5 bbls of produced water. The release was in the pasture 165' to the west of the Jackson B 55 well location, in the pipeline ROW. The area will be sampled and a work plan will be submitted. If there are any questions or concerns, feel free to contact us. Thanks.

Johnny Titsworth HSE COORDINATOR

BURNETT OIL CO., INC. P.O. Box 188 CR 220 North Loco Hills, NM 88255 MOBILE: (432)-425-2891 EMAIL: jtitsworth@burnettoil.com

This message is intended only for the person(s) to which it is addressed and may contain privileged, confidential and/or insider information. If you have received this communication in error, please notify us immediately by replying to the message and deleting it from your computer. Any disclosure, copying, distribution, or the taking of any action concerning the contents of this message and any attachment(s) by anyone other than the named recipient(s) is strictly prohibited.