District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505 State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Tracking # Pit, Below-Grade	Tank, or	
Proposed Alternative Method Permit or Closure Plan Application		
Printik Type of action: Below grade tank registration Permit of a pit or proposed alternative in Closure of a pit, below-grade tank, or p Modification to an existing permit/or re Closure plan only submitted for an existing or proposed alternative method	nethod roposed alternative method gistration ting permitted or non-permitted pit, CER 2018	
Instructions: Please submit one application (Form C-144) per ind	lividual pit, below-grade tank or alternative request	
Please be advised that approval of this request does not relieve the operator of liability should environment. Nor does approval relieve the operator of its responsibility to comply with any	d operations result in pollution of surface water, ground water or the other applicable governmental authority's rules, regulations or ordinances.	
1. Operator: Enterprise Products Operating, LLC	OGRID #:	
Address: P.O. Box 4324, Houston, TX 77210		
Facility or well name: Non-permitted Earthen Pit		
API Number: OCD Perm	it Number:	
U/L or Qtr/Qtr <u>K</u> Section <u>7</u> Township <u>28N</u> R	ange <u>8W</u> County: <u>San Juan</u>	
Center of Proposed Design: Latitude <u>36.673407°</u> Longi	tude <u>-107.723131°</u> NAD: □1927 ⊠ 1983	
Surface Owner: 🛛 Federal 🗌 State 🗋 Private 🗋 Tribal Trust or Indian Allotment		
Pit: Subsection F, G or J of 19.15.17.11 NMAC Temporary: Drilling Workover Buriel Decs Not meet He Requirements . Image: Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other In Line Drip Pit String-Reinforced . Liner Seams: Welded Factory Other		
3. Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume: Gal Type of fluid: Tank Construction material:		
 4. Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. 		
 5. Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary) Chain link, six feet in height, two strands of barbed wire at top (Required if located institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four Alternate. Please specify	pits, and below-grade tanks) I within 1000 feet of a permanent residence, school, hospital, `eet	

Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)

Screen Netting Other_

7

Monthly inspections (If netting or screening is not physically feasible)

Signs: Subsection C of 19.15.17.11 NMAC

12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers

Signed in compliance with 19.15.16.8 NMAC

Variances and Exceptions:

Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.

Please check a box if one or more of the following is requested, if not leave blank:

- Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.
- Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC

Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.

General siting		
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank □ NM Office of the State Engineer - iWATERS database search; □ USGS; □ Data obtained from nearby wells		
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells		
 Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality 		
 Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	Yes No	
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society: Topographic map 	Yes No	
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map		
Below Grade Tanks		
 Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	Yes No	
 Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	Yes No	
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)		
 Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No	
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	🗌 Yes 🗌 No	
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image		
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search: Visual inspection (certification) of the proposed site	Yes No	

4 J		
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No	
Temporary Pit Non-low chloride drilling fluid		
 Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 		
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 		
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 		
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 		
Permanent Pit or Multi-Well Fluid Management Pit		
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa		
 lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 		
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 		
 Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 		
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 		
10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.10 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC null 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:		
11. Multi Wall Fluid Management Bit Checklist, Subsection P of 10.15.17.0 NMAC		
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do	cuments are	
attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	.15.17.9 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:		

5 4		
12. <u>Permanent Pits Permit Application Checklist</u> : Subsection B of 19.15.17.9 NMAC <i>Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the a</i> <i>attached.</i>	locuments are	
 Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment 		
 Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC 		
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Ouality Control/Ouality Assurance Construction and Installation Plan		
 Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC 		
 Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization 		
Monitoring and Inspection Plan Erosion Control Plan		
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC		
 <u>Proposed Closure</u>: 19.15.17.13 NMAC <i>Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.</i> 		
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Fl	uid Management Pit	
Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only)		
On-site Closure Method (Only for temporary pits and closed-loop systems)		
14. Waste Excavation and Removal Closure Plan Checklist: (19 15 17 13 NMAC) Instructions: Each of the following items must be of	attached to the	
waste Excavation and Removal Closure Fian Checkist: (19.15.17.13 NMAC) Instructions: Each of the following tiems must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC		
15.		
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. Please refer to 19.15.17.10 NMAC for guidance.		
 Ground water is less than 25 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	⊠ Yes □ No □ NA	
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells		
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells		
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark) Topographic map; Visual inspection (certification) of the proposed site		
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Ye - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Ye		
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site		
Written confirmation or verification from the municipality; Written approval obtained from the municipality Xes 🗌		
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site		
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance		

 Written confirmation or verification from the municipality; Written approval obtained from the municipality 		
 Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 		
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological 		
Within a 100-year floodplain.	Yes No	
- FEMA map		
 16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.11 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 		
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed.	ief.	
Name (Print): Jon E. Fields Title: Director, Field Environmental		
Signature: \underline{N} . tube Date: $\frac{2}{12}/\frac{2}{19}$		
e-mail address: <u>snolan@eprod.com</u> Telephone: <u>713-381-6595</u>		
18. OCD Approval: Permit Application (including closure plan) Olosure Plan (only) OCD Conditions (see attachment) OCD Representative Signature:	26/18	
 18. OCD Approval: Permit Application (including closure plan) for closure Plan (only) for OCD Conditions (see attachment) OCD Representative Signature: Approval Date: Title: Falsi constraint Spec OCD Permit Number: (6 / 88) 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed	the closure report.	
18. OCD Approval: Permit Application (ocluding closure plan) Closure Plan (only) OCD Conditions (see alwachment) OCD Representative Signature:	the closure report. complete this	

Operator Closure Certification:		
I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.		
Name (Print):	Title:	
Signature:	Date:	
e-mail address:	Telephone:	

Non-Permitted Earthen Pit Closure Plan

On November 13, 2017, the New Mexico Oil Conservation Division (NMOCD) notified Enterprise Products Operating, LLC (Enterprise) via email, that during inspections in the area, an inspector found an earthen pit near an Enterprise pipeline. Enterprise confirmed it was the operator of the earthen pit and that it was an out of service in-line drip previously used to remove produced water and condensate from the adjacent pipeline. During subsequent email correspondence with NMOCD, Enterprise was instructed to submit a closure plan for approval prior to implementation of closure activities.

The following Closure Plan Packet including the C-144 form accordance with the NMOCD Pit Rules per 19.15.17 NMAC for the non-permitted earthen pit is located UL K Township 28 North Rage 8 West; 36.673407, -107.723131. Enterprise will not commence closure activities without first obtaining approval of the closure plan pursuant to 19.15.17.13 NMAC.

1.0 Closure Criteria

Due the proximity and elevation difference from the non-permitted earthen pit and Largo Wash, groundwater is estimated to be less than fifty feet below ground surface (bgs). According to the NMOCD Pit Rules soil closure criteria in Table I of 19.15.17.13 NMAC, soil contaminant concentrations shall meet the following:

Table 1: Closure Criteria			
Constituent	Method	Limit	
Chloride	EPA Method 300.0	600 mg/kg	
TPH	EPA Method 8015 DRO/GRO/MRO	100 mg.kg	
BTEX	EPA Method 8021B	50 mg/kg	
Benzene	EPA Method 8021B	10 mg/kg	

2.0 Closure Methods

Enterprise may close this non-permitted earthen pit by the following methods:

Method 1: In Place Closure

Enterprise shall conduct a subsurface investigation by installing five soil borings utilizing a hand auger. Soil boring placement is illustrated in in Figure 1, Site Map. One soil boring will be placed in the center of the earthen pit. The other four soil borings will be placed in each cardinal direction just outside of the berm of the earthen pit. Each soil boring advanced to a maximum of five feet bgs. Composite soil samples will be collected at one foot intervals. Each soil sample will be field screened for volatile organic compounds utilizing a calibrated photo-ionization detector (PID). Soil samples that exhibited the highest observed field screening PID result will be collected and submitted for laboratory analysis. Soil samples will be analyzed for constituents in the above referenced Table 1.

If laboratory sample results meet contaminant concentrations in Table 1, Enterprise will request in place closure and perform the site reclamation and re-vegetation activities outlined in Section 3.

Method 2: Waste Excavation and Removal

If laboratory analysis from the subsurface investigation indicates contaminant concentrations exceed the closure limits in the above referenced Table 1, Enterprise will implement closure activities by waste excavation and removal. All excavation activities will be overseen by a third party environmental contractor. The third party environmental contractor will conduct field screening (headspace analysis) with a calibrated PID to guide the excavation activities. When field screening results indicate contaminant concentrations are compliant with the NMOCD site specific remediation standard, soil samples will be collected for laboratory analysis from the excavation. All soil samples will be analyzed for constituents in Table 1. Enterprise will notify NMOCD twenty four hours (24) prior to the collection final (closure) soil samples.

The excavation will remain open until receipt of laboratory analysis and confirmation that contaminants meet the site specific NMOCD remediation standard. Upon confirmation that contaminant concentrations comply with the applicable NMOCD remediation standard, the laboratory analytical reports will be emailed to the NMOCD for prompt review. After approval from NMOCD, the excavation will be backfilled with non-land farm soils. All hydrocarbon impacted soils generated during excavation activities will be loaded onto tandem trucks for transport to Envirotech, Inc. land farm, a NMOCD approved land farm facility, for proper disposal.

3.0 Site Reclamation and Re-vegetation Plans

A. In Place Closure

If in place closure is determined suitable, Enterprise will remove the fence and level the earthen berms. Enterprise will perform these activities so that there is minimal impact to the surrounding land surface and the existing vegetation.

B. Waste Excavation and Removal

If closure by waste excavation and removal was the chosen strategy, Enterprise will backfill the excavation with non-land farm soils. The ground surface will be recontoured as much as practical to the existing grade prior to disturbance. The disturbed area will be re-seeding with a Bureau of Land Management Farmington Field Office approved seed mixture during the next favorable growing season.

CLOSURE REQUIREMENTS

Enterprise shall not commence closure without first obtaining approval of the closure plan submitted with the permit application or registration pursuant to 19.15.17.13 NMAC.

CLOSURE NOTIFICATION

Enterprise shall notify the appropriate division district office verbally, and in writing, at least 72 hours, but not more than one week, prior to any closure operation. The notice shall include the Enterprise name and the location to be closed, including the unit letter, section, township, and range. Enterprise shall notify the surface owner by certified mail (return receipt requested) that Enterprise plans closure operations at least 72 hours, but not more than one week, prior to any closure operation. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records is sufficient to demonstrate compliance with this requirement per 19.15.17.13.E

RECLAMATION AND RE-VEGETATION/ RECLAMATION OF AREAS NO LONGER IN USE

- 1.0 If in place closure is determined suitable, Enterprise will remove the fence and level the earthen berms. Enterprise will perform these activities so that there is minimal impact to the surrounding land surface and the existing vegetation.
- 2.0 If excavation is required, all areas disturbed, except areas reasonably needed for production operations or for subsequent drilling operations, shall be reclaimed as early and as nearly as practicable to their original condition or their final land use and shall be maintained to control dust and minimize erosion to the extent practicable. Enterprise shall replace topsoils and subsoils to their original relative positions and shall be contoured to achieve erosion control, long-term stability and preservation of surface water flow patterns. The disturbed area then shall be reseeded per BLM requirements per 19.15.17.13.H in the first favorable growing season following closure of the pit.

Reclamation of all disturbed areas no longer in use shall be considered complete when all ground surface disturbing activities at the site have been completed, and a uniform vegetative cover has been established that reflects a life-form ratio of plus or minus fifty percent (50%) of pre-disturbance levels and a total percent plant cover of at least seventy percent (70%) of pre-disturbance levels, excluding noxious weeds.

OTHER REGULATORY REQUIREMENTS

The re-vegetation and reclamation obligations imposed by other applicable federal or tribal agencies on lands managed by those agencies shall supersede these provisions

and govern the obligations of any operations subject to those provisions, provided the other requirements provide equal or better protection of fresh water, human health and the environment. Enterprise shall notify the division when reclamation and re-vegetation are complete.

BURIAL MARKER

Enterprise shall install a burial a marker approximately three feet below ground surface instead of installing an above ground burial marker as that it poses a safety risk on an active right-of-way. This burial marker at approximately three feet below ground surface will satisfied NMAC 19.15.17.13.F.

CLOSURE REPORT

Within 60 days of closure completion, Enterprise shall submit a closure report on form C-144, with necessary attachments to document all closure activities including sampling results, information required by 19.15.17 NMAC, and details on back-filling, capping and covering, where applicable. In the closure report, Enterprise shall certify that all information in the report and attachments is correct and that Enterprise has complied with all applicable closure requirements and conditions specified in the approved closure plan.



LEGEND:

- EARTHEN PIT

- PROPOSED SOIL BORING LOCATION

40

80

APPROXIMATE SCALE: 1"=80'

DRAWN BY: TJLONG CHECKED BY: BSTONE APPROVED BY: BSTONE

DRIPPIT

PROJ. ID:

160

ENTERPRISE PRODUCTS OPERATING, LLC UL K TOWNSHIP 28 NORTH RANGE 8 WEST 36.673407, -107.723131 SAN JUAN COUNTY, NEW MEXICO

~1"=80'

COUNTY, NEW MEXICO			Proc	
	DATE: 11-2	0-2017		
	DATE: 11-2	0-2017		
	DATE: 11-2	0-2017		
SCALE		DRAWING N	I IMBER.	

1

Enterprise Products