GW - 134

GENERAL CORRESPONDENCE

YEAR(S): 2008 - 2010

Bill Richardson

Cabinet Secretary, who was a supplied a process of the control of the Reese Fullerton Deputy Cabinet Secretary

Joanna Prukope was the second of the second Division Director
Oil Conservation Division



Taging 1815

N. 9341311 1

CAN THE THE PROPERTY OF THE ACTION OF THE ACTION OF May 19, 2008

मान्ये एक एक माना र जावले १९४० में लिये ने वाकिन संदर्भन के अवस्था के महत्व के महत्व के स्वतान के जो

THE SHEET OF SELECTION SECURITY

Mr. David Bays First in historical strain a grider of the war remarkets a subjective a rower Williams Four Corners, DLC and the available to the second series of the 188 Road 4900

Bloomfield, New Mexico 87413

Re: NOTICE OF DEFICENCY

Williams Four Corners Compressor Stations San Juan Basin facilities

METAL THE METAL IN WEST AND A STORY OF A STORY OF THE STORY OF THE STORY

करें कि में निकासकी होते हैं की निकास प्रान्त का निवास के निवास के अधिक है। असी है

Dear Mr. Bays:

kalikali kalikali da kara kalikali kara kalika k The Oil Conservation Division has performed 26 inspections of Williams Four Corners compressor station located in the San Juan Basin. The following stations have been inspected:

e.;	1(GW-108).	30-5#1	14 mar	.,(GW-273)	Moore (Idle)
	2. (GW-111).	32-8 #2	15	.,(GW-271)	Kernaghan
	3. GW-117) 3	2-7-#1	7 mg - mg/14 16	. (GW-272)	Kernaghan B-8 (Idle)
	4. (GW-287)	Snow Shoe	17	. (GW-136)	29-7 CDP
	5. (GW-122)	29-6 # 4		: (GW-307)	Laguna Seca
					Bancos CDP
	7. (GW-121)-2	29-6 #2 CDP	Agram, $\gamma_{ij} \sim \lambda 20$.:(GW-365)	Eul CDP
		31-6 CDP			30 – 8 CDP (Ídle)
	9. (GW-120) I	Pipkin	on of - Justin ,22	. (GW-116)	$32 - 8 \text{ CDP}_{\text{CDP}}$
	10. (GW-129) (Crouch Mesa	23	. (GW-292)	Rosa # 1 CDP
	11. (GW-208) I	Hart Mountain (Idle)	24	. (GW-306)	Trunk N
	12. (GW-091) 3	32-9 CDP	25	. (GW-134)	Decker Junction (Idle)
	13. (GW-087) (Cedar Hills	26	. (GW-250)	Coyote Springs

The OCD has observed several areas of concern after inspecting these sites. They are as follows:

- 1. Condition 6. Waste Disposal and Storage: "The owner/operator shall not store oil field" waste on-site for more than 180 days unless approved by the OCD." Williams Four Corners? has renewed their permits for 5 of the 26 facilities that are "non-operational". These facilities have been non-operational for more than one year and a few still contain waste material on site, i.e. landfarm soil, solid waste and liquids. Williams Four Corners shall properly dispose of their remaining waste for these facilities.
- 2. Condition 7. Drum Storage: "The owner/operator must store all drums, including empty drums, containing materials other than fresh water on an impermeable pad with curbing. Must store empty drums on their sides with the bungs in place and lined up on a horizontal



- plane. Must store chemicals in other containers, such as tote tanks, sacks, or buckets on an impermeable pad with curbing." OCD has witness several stations with improper storage of barrels and fluids.
- Condition 10. Labeling: "The owner/operator shall clearly label all tanks, drums, and containers to identify their contents and other emergency notification information. The owner/operator may use a tank code numbering system, which is incorporated into their emergency response plans". Several containers were not labeled.
- Condition 11. A: "Small sumps or depressions in secondary containment systems used to facilitate fluid removal are exempt from these requirements if fluids are removed within 72 hours." Several secondary containers were holding a large amount of liquids assumed greater then 72 hours. Williams Four Corners must remove all fluids from secondary containers within 72 hours.
- 5. Condition 8. Process, Maintenance and Yard areas. "The owner/operator shall either pave and curb or have some type of spill collection device incorporated into the design at all process, maintenance, and yard areas which show evidence that water contaminants from releases, leaks and spills have reached the ground surface." Secondary containers are present at these facilities but best management practices are not followed. The OCD has witnessed the majority of the stations to have hydrocarbon staining within its facility grounds with the majority near the compressor engines. Williams Four Corners shall prevent any discharging of hydrocarbons directly on to the ground. If a discharge does occur it shall be addressed immediately and not allowed to accumulate. Placing clean gravel over the contamination is not an allowable practice

The OCD would like to point out these deficiencies. Please correct as soon as possible and provide the OCD a progress report within 90 days from the date of this letter. These conditions are assumed by the OCD to be present at all of Williams Four Corners 70 + compressor stations that have a discharge permit. Please reflect these concerns to all of the permitted compressor stations and gas plants owned by Williams Four Corners, LLC. NMSA 1978, Section 70-2-31 (A) authorizes penalties of up to one thousand dollars (\$1000.00) per day per violation for any knowing and willful violation of any provision of the Oil and Gas Act or any rule adopted pursuant to the Act.

If there are any questions regarding this matter, please do not hesitate to contact me at (505) 476 Co. (Significant) (Marketing). When 3492 or leonard.lowe@state.nm.us. white members will rest edit with

to contribute to the recommendation of the tribute and makes a mention of the city for the little

STATE PRODUCTION OF THE PROPERTY OF THE PROPER the manufactured is a supply

LESS CONTRACTOR OF THE WARREST WELL OF THE WORLD BY CONTRACTOR WAS A SECTION OF THE CONTRACTOR OF THE and the control of th

MUSELLE CONTROL THE TRADE CONTROL AND MOTOR OF THE PROPERTY AND STATE OF THE PROPERTY AND STATE OF THE PARTY OF THE PARTY

William Francisco

Strainsk rush

Sincerely, the posterior of the second of th

Legrard Lower of the surregion was all appropriate the design and the second

Environmental Engineer W. W. Charles and a server against the rest was a server of the server of the and a large transfer of the last of his flow of the appropriate from the contract of the first of the contract of

xe: Daniel Sanchez, Enforcement and Compliance Manager Wayne Price, Environmental Bureau Chief

医化丁香二甲酰甲基丁烯醇的 银矿

WALL SUMMERS

Brandon Powell, District III Environmental Specialist

AFFIDAVIT OF PUBLICATION

Ad No. 539117

STATE OF NEW MEXICO County of San Juan:

BOB WALLER, being duly sworn says: That he is the CLASSIFIED MANAGER of THE DAILY TIMES, a daily newspaper of general circulation published in English at Farmington, said county and state, and that the hereto attached Legal Notice was published in a regular and entire issue of the said DAILY TIMES, a daily newspaper duly qualified for the purpose within the meaning of Chapter 167 of the 1937 Session Laws of the State of New Mexico for publication and appeared in the Internet at The Daily Times web site on the following day(s):

Wednesday, January 23, 2008

cost of the publication is \$525.37

Bob Waller appeared before me whom I know personally to be the person who signed the above document.

My-Commission Expires The state of the s

RECEIVED

2008 JAN 31 PM 1 32

COPY OF PUBLICATION

de desecho aceitoso del equipo se ומעמון ע מעניין, זי איניין אינייין איניין איניין איניין איניין איניין איניין איניין איניין אינייין איניין איניין אינייין איניין אינייין איניין איניין איניין איניין איניין איניין איניין איניין אינייי alación permitida por la agencia Se espera que la profundidad de El plan de descarga se dirige como las caídas, los agujeros, y otras descargas casuales a la superficie serán manejados. Los materiales típicos gen erados o usados en la instalación incluyén el echar agua condensado/producir de gas natural, el petróleo de lubricación nuevo y usado, echar agua dores equipados con la contención secundaria. La basura transportó offsite agua subterránea estimada en el sitio esté en la variedad de 50-200 pies. El total se disolvió se espera que la concentración de sólidos del agua subterránea de área esté en la variedad de 200-2,000 partes por millón una instalación permitida por la estatal, federal, o tribal recibir tal basura. dispuesto o reciclado en

a de instalación para futuros avisos por ponerse en contac-Lowe en el Nuevo México OCD en 1220 Sur San. Francis Teléfono (505) 476-3492. El OCD to con Leonard L Drive, Santa Fe, presentar

Decker Junction Central Delivery Point Compressor Station localel NE/4, SE/4 de la Sección 19, Municipio 32 Norte, Recorren 10 han presentado una aplicación de renovación en el diciembre de 2007 a la New Mexico Energy, Minerals and Natural Resources Department, Oil Conservation Division para la descarga antes aprobada planean (GW-134 para su Decker Junction Central Delivery Point Compressor Station local-Oeste en San Juan County, New Mexico. La instalación, noroeste de aproximadamente 3 millas localizado de Cedar Hill, proporciona servicios de acondicionamiento y compresión de gas naturales. izada en

expects to submit a renewal application in December

glycol. The quantity of wastewater generated is 100-5000 gallons per year per engine. The facility does not discharge to surface or subsurface applicable. All wastes generated will be temporarily stored in tanks or containers equipped with secondary containment. Waste shipped offor tribal agency to receive such waste. The estimated ground water depth at the site is expected to be in the range of 50-200 feet. The total dissolved solids concentration of area ground water is expected to be in the range of 200-2,000 parts per million. new and used lube oil, oily waste water from equipment wash down, and and therefore the quantity and quality of the discharges is not discharges to the surface will be managed. Typical materials generated or used at the facility include natural gas condensate/produced water. recycled at a facility permitted by state, federal, discharge plan addresses how spills, leaks, and other harges to the surface will be managed. Typical materials containers equipped with secondary containment. site will be disposed or recycled at a facility permitt waters,

Any interested person or persons may obtain information, submit comments or request to be placed on a facility-specific mailing list for future notices by contacting Leonard Lowe at the New Mexico OCD at 1220 South St. Francis Drive, Santa Fe, New Mexico 87505, Telephone (505) 476-3492. The OCD will accept comments and statements of interest regarding the renewal and will create a facility-specific mailing list for persons who wish to receive future notices. notices by contacting South St. Francis Drive

PUBLIC NOTICE

Department, Oil Conservation Division for the previously approved discharge plan IGW-434 for their Decker Junction Central Delivery Point charge plan (GW-434 for their Decker Junction Central Delivery Point Compressor Station located in the NE/4, SE/4 of Section 19, Township 32 North, Range 10 West in San Juan County, New Mexico. The facility, located approximately 3 miles northwest of Cedar Hill, provides natural gas compression and conditioning services. to the



PO Box 450 Farmington, NM 87499

Date: 02/07/08

NM ENERGY, MINERALS & NATURA

NM ENERGY, MINERALS & NA 1220 SOUTH ST. FRANCIS DR. SANTA FE, NM 87505 (505) 476-3400

Ad#	Publication	Class	Start	Stop	Times	AS/400 Acct
1000906792	FARMINGTO:	0152 - Legal Notices	02/04/2008	02/04/2008	1	780352
1000906792	FARMINGTO:	0152 - Legal Notices	02/04/2008	02/04/2008	1	780352

Total Cost:

\$313.54

Payment:

\$0.00

Balance Due:

\$313.54

TEXT:

NOTICE OF PUBLICATIONSTATE OF NEW MEXICOENERGY, MINERALS AND NAT

AFFIDAVIT OF PUBLICATION

Ad No. 59700

STATE OF NEW MEXICO County of San Juan:

he is the CLASSIFIED MANAGER of THE DAILY TIMES, a daily newspaper of general circulation published in English at Farmington, said county and state, and that the hereto attached Legal Notice was published in a regular and entire issue of the said DAILY TIMES, a daily newspaper duly qualified for the purpose within the meaning of Chapter 167 of the 1937 Session Laws of the State of New Mexico for publication and appeared in the Internet at The Daily Times web site on the following day(s):

Monday, February 4, 2008

h					
1/					
ON	2/08/08	ВО	B WALL	_ER appe	eared
before	e me, who	ள் I knov	w persoi	nally to b	e the
perso	who sign	ed the a	above do	ocument.	

And the cost of the publication is \$313.54

COPY OF PUBLICATION

NOTICE OF PUBLICATION

STATE OF NEW MEXICO ENERGY, MINERALS AND NATURAL RESOURCES DEPARTMENT OIL CONSERVATION DIVISION

Notice is hereby given that pursuant to New Mexico Water Quality Control? Commission Regulations (20.6.2.3106 NMAC), the following discharge permit application(s) has been submitted to the Director of the New Mexico Oil Conservation Division ("NMOCD") 1220 S. Saint Francis Drive, Santa Fe' New Mexico 87505, Telephone (505) 476-3440.

(GW-045) Williams Four Corners, Mr. David Bays, Senior Environmental Specialist, 188 County Road 4900, Bloomfield, N.M. 87413, has submitted a renewal application for the previously approved discharge plan for their Kutz Canyon Gas Plant/Keblah Compressor Station, located in the NW/4 NW/4 of Section 13 and SW/4 of Section 12, Township 28 North, Range 11 West, NMPM, San Juan County, New Mexico, approximately 3 miles south of Bloomfield, New Mexico. The gas plant removes Ethane and higher hydrocarbons from field gas. The compressor station provides metering and compression to various producers for the gathering of natural gas for treatment and delivery. Approximately 1 — 1.5 million gal/year of waste water, 1000 = 5000 gal/month of used oil; 2000-8000 bbl/year of produced/natural gas water and 40,000 = 100,000 gal/month of condensate/natural gas water and 40,000 = 100,000 gal/month of condensate/natural gas water and abermed area prior to disposal at an NMOCD approved facility. Groundwater most likely to be affected by a spill, leak or accident rotal discharge is at a depth of approximately 200-500 feet, with a total dissolved solids concentration of approximately 200-2000 mg/l. The discharge plan addresses how oilfield products and waste will be properly handled, stored, and disposed of, including how spills, leaks, and other accidental discharges to the surface will be managed in order to protect fresh water.

(GW-133) Williams Four Corners, Mr. David Bays, Senior Environ mental Specialist, 188 County Road 4900, Bloomfield, N.M., 87413, has submitted a renewal application for the previously approved discharge plan for their 30-8 CDP Compressor Station, located in the SW/4 SE/4 of Section 32, Township 31 North, Range 8 West, NMPM, San Juan County, New Mexico, approximately 17miles east of Axtec, New Mexico. The station provides metering, compression, and dehydration services to various producers for the gathering of natural gas for treatment and delivery. Approximately 2000-8000 bbl/year of produced water/natural gas condensate; 100-5000 gal/year/unit of waste water and stored in OCD approved containers onsite within a bermed area prior to disposal at an NMOCD approved facility. Groundwater most likely to be affected by a spill, leak or accidental discharge is at a depth of approximately 200-500 feet, with a total dissolved solids concentration of approximately 200 - 2000 mg/l. The discharge plan addresses how oilfield products and waste will be property handled, stored, and disposed of, including how spills, leaks, and other accidental discharges to the surface will be man aged in order to protect fresh water.

(GW-134) Williams Four Corners, Mr. David Bays, Senior Environ mental Specialist, 188 County Road 4900, Bloomfield, N.M. 87413, has submitted a renewal application for the previously approved discharge plan for their Decker Junction CDP Compressor Station, located in the NE/4 5E/4 of Section 19, Township 32 North, Range 10 West, NMPM, San Juan County, New Mexico, approximately 3 miles northwest of Cedar Hill, New Mexico. The station provides metering, compression, and dehydration services to various producers for the gathering of natural gas for freatment and delivery. Approximately 2000-8000 bbl/year of produced water/natural gas condensate, 100-5000 gal/year/unit of waste water and 500-2000 gal/year/engine of used engine oil are generated and stored in OCD approved containers onsite within a berned area prior to disposal at an NMOCD approved hacility. Groundwater most likely to be affected by a spill, leak or accidental discharge is at a depth of approximately 50-200 feet, with a total dissolved solids concentration of approximately 200 - 2000 mg/l. The discharge plan addresses how oilfield products and waste will be property handled, stored, and disposed of, including how spills, leaks, and other accidental discharges to the surface will be managed in order to protect fresh water.

(GW-136) Williams Four Corners, Mr. David Bays, Senior Environmental Specialist, 188 County Road 4900, Bloomfield, N.M. 87413, has submitted a renewal application for the previously approved discharge plan for their 29-7 # 1. Compressor Station, located in the NE/4 SE/4 of Section 15, Township 29 North, Range 7. West, NMPM, San Juan County, New Mexico, approximately 24 miles east of Bloomfield New Mexico. The station provides metering, compression, and dehydration services to various producers for the gathering of natural gas for treatment and delivery. Approximately 2000-8000 bbl/year/onf produced water/natural gas condensate; 100-5000 gal/year/unit of waste water and 500-2000 gal/year/engine of used engine oil are generated and stored in OCD approved containers onsite within a bermed area prior to disposal at an NMOCD approved facility. Groundwater most likely to be affected by a spill, leak or accidental discharge is at a depth of approximately 50-200 feet, with a total dissolved so lids concentration of approximately 200 e 2000 mg/l. The discharge plan addresses how oilfield products and waste will be properly handled, stored, and disposed of including how spills, leaks, and other accidental discharges to the surface will be man aged in order to protect fresh water.

(GW-374) Nalco Chemical Company, 1902 Black Gold Road, Lev elland, Texas, 79336 has submitted an application for a new discharge plan for their Nalco Oil and Gas Service Company, 13 County Road, 3535 Flora Vista, N.M.; located in the NE/4 NW/4 of Section 22, Township 30 North, Range 12 West, NMPM, San Juan County, New Mexico. Approximately 72 bils of Acid/Caustics, 52 bils of Biocides, 1600 gallons of methanol, and 14,000 gallons of Corrosion inhibitors will be stored onsite in a closed top steel tank within a bermed area prior to disposal at an NMOCD approved facility. Groundwater most likely to be affected by a spill, leak or accidental discharge is at a depth of approximately 1000 ppm. The discharge plan addresses how oilfield products and waste will be properly handled, stored, and disposed of, in cluding how spills, leaks, and other accidental discharges to the surface will be managed in order to protect fresh water.

The NMOCD has determined that the application is administratively complete and has prepared a draft permit. The NMOCD will accept comments and statements of interest regarding this application and will create a facility-specific mailing list for persons who wish to receive future notices. Persons interested in obtaining further information, submitting comments or requesting to be on a facility-specific mailing list for future notices may contact the Environmental Bureau Chief of the Oil Conservation Division at the address given above. The administrative completeness determination and draft permit may be viewed at the above address between 8:00 arm and 4:00 p.m., Monday through firiday for may also be viewed at the NMOCD website http://www.ennrd.state.nm.us/ocd/. Persons interested in obtaining a copy of the application and draft permit may contact the NMOCD at the address given above. Prior to ruling on any proposed discharge permit or major modification, the Director shall allow a period of at least thirty (30) days after the date of publication of this no fice during which interested persons may submit comments or request that NMOCD hold a public hearing. Requests far a public hearing shall set forth the reasons why a hearing should be held. A hearing will be held if the Director determines that there is significant public interests.

If no public hearing is held, the Director will approve or disapprove the proposed permit based on information available, including all comments received if a public hearing is held, the director will approve or disapprove the proposed permit based on information in the permit application and information submitted at the hearing.

Para obtener más informacion sobre esta solicitud en espan?ol, sir vase comunicarse por tavor. New Mexico Energy, Minerals and Natural Resources Department (Depto Del Energia, Minerals y Recursos Naturales de Nuevo Mexico), Oil Conservation Division (Depto Conservacion Del Petroleo), 1220 South St. Francis Drive, Santa Fe, New Mexico (Contacto: Dorothy Phillips, 505-476-3461)

GIVEN under the Seal of New Mexico Oil Conservation Commission at Santa Fe, New Mexico, on this 30th day of January, 2008.

STATE OF NEW MEXICO OIL CONSERVATION DIVISION Mark Fesmire, Director

SEAL,

Legal No. 59700 published in The Daily Times, Farmigton, New Mexico on Manday February 04, 2008

THE SANTA FE NEW MEXICAN Founded 1849

NM EMNRD OIL CONSERV 1220 S ST FRANCIS DR SANTA FE NM 87505

ALTERNATE ACCOUNT: 56689

AD NUMBER: 00245365 ACCOUNT: 00002212

LEGAL NO: 82256

P.O. #: 52100-00000075

925 LINES 1 TIME(S)

#. 52100-0000007. 805.28

AFFIDAVIT:

7.00

TAX:

64.47

TOTAL:

876.75

AFFIDAVIT OF PUBLICATION

STATE OF NEW MEXICO COUNTY OF SANTA FE

I, T. Valencia, being first duly sworn declare and say that I am Legal Advertising Representative of THE SANTA FE NEW MEXICAN, a daily newspaper published in the English language, and having a general circulation in the Counties of Santa Fe and Los Alamos, State of New Mexico and being a newspaper duly qualified to publish legal notices and advertisements under the provisions of Chapter 167 on Session Laws of 1937; that the publication #82256 a copy of which is hereto attached was published in said newspaper 1 day(s) between 02/06/2008 and 02/06/2008 and that the notice was published in the newspaper proper and not in any supplement; the first date of publication being on the 6th day of February, 2008 and that the undersigned has personal knowledge of the matter and things set forth in this affidavit.

П

181 T Valence

LEGAL ADVERTISEMENT REPRESENTATIVE

Subscribed and sworn to before me on this 6th day of February, 2008

Notary

Commission Expires:__

May 31, 2011

OFFICIAL SEAL

Pamela Anne Beach

NOTARY PUBLIC

STATE OF NEW MEXICO

My Commission Expires: 5-3/-//

jected into the Salado Formation at a depth New Mexico, 1500 tainers onsite within oil are generated and 30th day of January, of 1,350 feet and 450 Broadway. Place, a bermed area prior stored in 0CD approved containers on the provides sand brine water is extracted through a basting and painting cility. Groundwater of oil filed equipment. The feeted by a spill, leak solved solids (TDS) 100 lb sacks of sand charge is at a depth likely to be affected. of 1,350 feet and 450 Broadway Place, a bermed area prior barrels per day of brine water is extracted through a 2,200 foot fiberglass tubing with total dissolved solids (TDS) to los lasting and painting concentration of approximately 300,000 mg/L for use in the oil paint are stored onsided by a spill, leak or accidental dissected by a spill, leak or accidental disconcentration of approximately fected by a spill, leak or accidental disconcentration of approximately to be affected by a spill, leak or accidental disconcentration of approximately fected by a spill, leak or accidental disconcentration of approximately fected by a spill, leak or accidental disconcentration of approximately fected by a spill, leak of approximately fected by a spill, leak of accidental disconcentration of approximately 200-2000 feet, with a total disconcentration of approximately 70 feet with a total disconcentration of approximately 70 feet, with a total disconcentration of approximately 70 feet, with a total disconcentration of approximately 1,100 mg/L. The discharge blan addresses how oilfield products and waste will be properly within a TDS of approximately 50 feet, with a total disconcentration of approximately 1,100 mg/L. The discharge blan addresses how oilfield products and waste will be properly disposed of, including how spills. leaks, and mately 1,100 mg/L.
The discharge permit
addresses well construction, operation,
monitoring of the monitoring of the well, associated surwell, associated sur-face facilities, and died stored and dis-provides a contin-gency plan in the event of accidental other accidental disspills, leaks and other accidental discharges in order to protect fresh water.

(BW-030) Liquid Re-Mr. David Pyeatt, 1819 Transportation Inc., N. Turner, Suite B, P.O. Box 1898, Carls-Hobbs, New Mexico 88240 has submitted an application for the renewal of a diethat pursuant to New source Services, LLC., Mexico Water Quality Mr. David Pyeatt, 1819

solved solids concent handled, stored, and tration of approximately 500 mg/l. The how spills, leaks, and discharge plan ad other accidental discresses how oilfield charges to the surproducts, and waste face will be managed charges to the sur-face will be managed in order to protect fresh water.

(GW-362) Mr. Clifford Stewart of Riverside

in order to protect fresh water.

(GW-133) Williams Four Corners., Mr. David Bays, Senior En-vironmental Specialist, 188 County Road 4900, Bloomfield, N.M. 87413, has submitted a renewal application for the previously ap-proved discharge plan for their 30-8 CDP Compressor Station, located in the SW/4 SE/4 of Section 32, Township 31 North, Range 8 West, NMPM,

likely to be affected S by a spill, leak or accidental discharge is at Mark Fesmire. a depth of approxi-mately 50-200 feet, with a total dissolved Pub Feb. 6, 2008 with a total dissolved solids concentration of approximately 200 2000 mg/L. The discharge plan addresses how ollfield products and waste will be properly handled, stored, and disposed of including how spills, leaks, and other accidental discharges to the surface will be managed in order to protect fresh water.

(GW-374) (GW-374) Naico Chemical Company, 1902 Black Gold Road; Levelland, Texas, 79336 has submitted an application for a new discharge plan for their Nalco Oil and Gas Service Company, 13 County
Road, 3535 Flora
Vista, N.M., located in the NE/4 NW/4 of Section 22, Township 30 North, Range, 12 West, NMPM, San Juan County, New Mexico, Approximately 72 bbls of Acid/Caustics, 52 bbls of Biocides, 1600 gallons of methanol, and 14,000 gallons of Corrosion inhibitors will be stored onsite in a closed top steel Gas Service Company, Regulations (20.6.2.3106 NMAC), the following discharge permit application for the charge permit application for the submitted to the Director of the New Mexico Oil Conservation Division Division Division Francis Drive Santa Fe, New Mexico Santa Fe, New Mexico (505) 476-3440:

(Short Santa Fe, New Mexico Section 29, Township Section 29, Township 30, 114 miles Service Ms. Sherry Glass, 11413 US Hwy. Glass and the renewal of a distribution of the renewal of a distribution of

Έ

NOTICE OF PUBLICATION

NEW MEXICO ENERGY, MINERALS AND NATURAL RESOURCES DEPARTMENT OIL CONSERVATION DIVISION

Notice is hereby given Mexico Water Quality Control Commission Regulations NMAC), (20.6.2.3106

brine well "State 24 of the back was and turn right will No. 001" (APH# in the habbs, water is interesting the back) was a section 24, Township jected into the Salado religion to the Salado religion to the Salado religion of a proximately 14 miles of 1.700 feet and 580 fity county, New Mexico. Drine water is ex- stewell is located approximately and miles on Hagerman fer most likely to be east of Artesia, New Concentration of approximately and turn south 6 miles on Hagerman fer most likely to be maker is injected into the Salado Formation of a proximately and publication of a proximately and solids (TDS) and turn south 6 miles on the salado formation of a proximately be been at a depth of 456 feet with a total discharge to the surfacted by a spill leak, or accidental discharge to the surfacted by a spill leak, or accidental discharge to the surfacted by a spill leak, or accidental discharge to the surfacted by a spill leak, or accidental discharge to the surfacted by a spill leak or accidental discharge to the surfacted by a spill leak and other free discharge to the surfacted by a spill leak of a proximately concentration of a provides a continer of approximately and publication of a proximately dresses well consideratel discharges bermit and effect for a proximately and sponsorial and despendent of the surface facilities, and spendent of the surface facilities, and spendent of the surface facilities, and spendent of seeding of the browning of the least of the surface facilities, and spendent of seeding of the browning of the least of the surface facilities, and spendent of seeding of the browning of the least of the surface facilities, and spendent of seeding of the browning of the least of the surface facilities, and seeding of the provided in order to protect discharge seeding of s Define we have been made and m

pression, sweetening and sulfur recovery, dehydration, cryoethane (8W-019) Key Energy Services, Inc., Mr. T. Louis Sanchez, 6 De- Rata Drive, Suite 4400, LMIdland, Texas 79705, Inas submitted an application for the renewell "City of Carlsbad Well No. 001" (API# p. 30-015-21842) located ain the SE/4, NE/4 of Section 36, Township p. 22. South, Range 26 extraction NMPM proximatel East,

Cellity, A00 bags of 50lb government of the facility. And bags of 50lb government of the facility benefits and will be stored to disposal at an NMOCD lisposal at an obstance of disposal at an obstance of the facility. By a spill, leak or accin a dental discharge is at a dental discharge is at a depth of approximately 85 feet, with a concentration of approximately 85 feet, with a concentration of approximately 855 mg/l. The dissolved solids of field products and waste will be properly proximately solids of the surface will be managed in order to protect.

GW-372) Mr. Edward D. Philley, EnvironMey Energy Services of Exery Services of LLC., 6 Desta Drive, 8 Sulte 4400, Midland at TX 79705 has submitTX 79705 cility. Groundwater of most likely to be af-verteed by a spill, leak for accidental dis-charge is at a depth of and heavier

by a spill, leak or actification of approximately are proved containers.on-approximately 35 stored in OCD apportant approximately 35 stored or actification of approximately 35 stored and area prior to disposal area area prior to disposal area prior to disposal area prior to disposal area properly han adeption and area properly han area products and waste area products and waste disposal area products and waste area products and products and

Four Comers, Man tion and will creat build be a build build be a build be a build build be a build b (GW-134)

garding this application and will create a
facility-specific mailing list for persons
who wish to receive
future notices. Persons interested in obtaining further information, submitting
comments or requesting to be on a
facility-specific mailing list for future notices may contact the
future may contact the
future may contact the
future for future notices may contact the
future for future notices and contact the
future and conservation Division at
the address given
above. The administrative completeness
determination and
diraft permit may be
viewed at the above
address between 8:00
a.m. and 4:00 p.m.
Monday through Friday, or may also be
viewed at the NMOCD

south cot Carlsbad. New Mexico, and 0.5 mile east on Hwy. 62/180. Fresh water is injected into the Salado Formation at a depth of 710 feet and 650 barrels per day of brine water is ex-tracted with a total dissolved solids (TDS) concentration of ap-proximately 300,000 mg/L for use in the oil industry. Groundwa-ter most likely to be deficited by a spill, leak, or accidental discharge to the surface is at a depth of approximately 150 feet with a TDS of approximately 1,800 mg/L. The discharge permit addresses well construction. operation, monitoring of the well, associated surface facilities, and provides a contin-gency plan in the event of accidental spills, leaks and other accidental discharges in order to protect fresh water.

(BW-028) Key Energy Services, Inc., Mr. Louis Sanchez, 6 Desta Drive, Suite 4400, Midland, Texas 79705 has submitted an application for the re-newal of a discharge permit for the brine well "State Well No. well No. (API# 30-025-33547) located in the SW/4, NW/4 of Section 15; Township 21 South, Range 37 East, NMPM, Lea County, New Mexico. The brine extraction well is located anwell is located approximately 2.5 miles north of Eunice, New Mexico on Hwy. 18, east on CR-207 0.1

nave no intentional liquid discharges and disposes of wastewater and acid gass in a permitted Class II Woolworth Estate disposal well (API# 30-025-27081), which will be replaced by a similar well about 200 ft. east of the existing well. The new dis-posal well will inject in addition to past waste disposal, acid gas (H2S) into the San Andres Formation (4,350 - 5,200 ft.). A hydrogen sulfide con-tingency plan has tingency plan has been incorporated into the discharge permit. Groundwater most likely to be affected by a spill, leak or accidental dis-charge is at a depth of approximately 90 feet, with a total dissolved solids concentration of approximately 2,200 mg/l.
The discharge permit addresses remedia-tion of soil and ground water and of, including how in order to protect

solved solids concentration of approximately 1,010 mg/l. The discharge plan addresses how oil-field products and waste will be properly handled, stored, and disposed of, including how spills, leaks, and other accidental discharges to the surcharges to the sur-face will be managed in order to protect fresh water.

(GW-045) Williams Four Corners, Mr. David Bays, Senior En-vironmental Special-ist, 188 County Road 4900, Bloomfield, N.M. 87413, has submitted a renewal application for the previously ap-proved discharge plan for their Kutz Canyon Gas Plant/Keplan for their Kutz Canyon Gas Plant/Keblah Compressor Station, located in the NW/4 NW/4 of Section 10 and SW/4 of Section 12 Township 28 North, Range 11 West, NMPM, San Juan County, New Mexico, approximately 3 miles south of Bloomfield, New Mexico, approximately 3 miles south of Bloomfield, New Mexico, The gas Incompressor Station, plant removes Ethane and higher hydrocarbons from field gas. The compressor Station provides metering and compression to various producers for the gathering of natural gas for treatment and delivery. how oilfield products Mexico, approxi-and waste will be mately 3 miles south properly handled, of Bloomfield, New stored, and disposed Mexico. The gas spills, leaks, and and higher hydrocar-other accidental dis-charges to the sur-face will be managed in order to protect ing and compression to various producers for the gathering of (GW-319) Robert Strasner of R&R Service Company Inc., P.O. Approximately, 1 - 1.5 Box 1409, Hobbs, N.M. million gal/year of 88241-1409, has submitted a renewal application for the previously approved discharge plan for their Oil and Gas Service water, and 40,000 -Approximately 1 - 1.5 hydration services to million gal/year of various producers for waste water; 1000 - the gathering of natused oil; 2000-8000 bbl/year of produced/natural gas bbl/year of produced/natural gas bbl/year of produced water and 40.000 produced/natural gas bbi/year of produced/natural gas water and 40,000 water/natural gas 100,000 gal/month of condensate; 100-5000 GIVEN under the Seal condensate/natural gal/year/unit of New Mexico Oil waste water and Conservation Compression at Santa Fe,

will be properly han: dled, stored, and dis-posed of, including how spills, leaks, and other accidental dis-

north of Eunice, New Oil and Gas Service water and 40,000 - water/natural gas company, located in 100,000 gal/month of east on CR-207 0.1 the NE/4 SW/4 of Section 100,000 gal/month of gas/year/unit of New Mexico Oil miles into the facility. The New Mexico Oil gas of New Mexico Oil water is in- South, Range 38 East, ated and stored in 500-2000 gal/year/en- mission at Santa Fe,

reet, with a total dis- proved containers on- fication, the Director solved solids concen- site within a permed shall allow a period of proved containers onsite within a bermed
area prior to disposal
at an NMOCD approved facility.
Groundwater most
likely to be affected
by a spill, leak or accidental discharge is at
a depth of approximately 50 200 feet,
with a total dissolved
solids concentration
if cation, the Director
shall allow a period of
at least thirty (30)
at least thirty (30)
days affer the date of
publication of this notice, during which interested persons may
submit comments or
request that NMOCD
Requests for a public
hearing shall set forth
solids concentration solids concentration the reasons why a of approximately 200- hearing should be 2000 mg/l. The discharge plan adheld if the Director dresses how oilfield determines that there products and waste is significant public interest. interest.

> If no public hearing is held, the Director will now spills, leaks, and held, the Director will other accidental discharges to the surprove or disapprove or disapp

> > vation (Depto. cio n Del Petróleo), 1220 South St. Francis Drive, Santa Fe, New México (Contacto: Dorothy Phillips,