Submit 3 Copies To Appropriate District Office District I 1625 N. French Dr., Hobbs, NM 87240 District II 1301 W. Grand Ave, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505 SUNDEY MOTICES AND REPORTS ON WELLS	ON 30-015-22818 5. Indicate Type of Lease STATE FEE 6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BAD DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCPROPOSALS.) 1. Type of Well: Oil Well Gas Well Other	
2. Name of Operator BP America Production Company 3. Address of Operator P.O. Box 1089, Eunice NM 88231 4. Well Location	9. OGRID Number 00778 10. Pool name or Wildcat EMPIRE ABO
Unit Letter <u>B</u> : <u>959</u> feet from the <u>N</u> lin Section <u>35</u> Township <u>178</u> Range	ne and 2400 feet from the E line 28E NMPM County EDDY
11. Elevation (Show whether DR, RKB, I	
Pit or Below-grade Tank Application or Closure	
Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water	
Pit Liner Thickness: mil Below-Grade Tank: Volumebbls;	Construction Material
_	SUBSEQUENT REPORT OF: L WORK ALTERING CASING COMMENT CE DRILLING OPNS. PLUG AND ABANDONMENT EST AND ABANDONMENT
OTHER:	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 10/21/08: RU PU. 10/22/08: NU BOP AND RIG FLOOR. PICKUP 199 JTS OF TBG AT TAG PLUG WITH 10' OF JOINT 200. PICKUP TO NEXT COLLAR. PUMP 140 BBLS OF MUD AROUND. 10/23/08: PUMP 25 SX PLUG AT 6227'. POH WITH 82 JTS AND SPOT PLUG AT 3913'. PUMP 25 SX PLUG AT 3913'. POH WITH 10 JOINT AND 10 STANDS. WOC. RIH AND TAG PLUG AT 3639'. POH AND LAYDOWN TBG TO 3162' AND SPOT 25 SX PLUG. SPOT 25 SX PLUG AT 3162'. POH WITH 30 JNT OF TUBING. 10/24/08: POH W/ TBG TO 913'. SPOT IN WATER TRUCKS AND PUMP 35 SX OF CEMENT AT 913'. DISPLACE CEMENT. POH W/ TBG 10 JNT ON RACK AND STOOD BACK 9 STANDS. OOH W/ TBG. WOC. Continued on page 2.	
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines, a general permit or an (attached) alternative OCD-approved plan	
SIGNATURE TITLE Area Operations Team Lead DATE 10/31/08	
Type or print name Barry C. Price E-mail address: barry.price@bp.com Approved for plugging of well bore only the property of	
TO THE STATE OF TH	Fix under bond is retained pending receipt 103 (Subsequent Report of Well Plugging)
APPROVED BY NMOCD // TITLE which	n may be found at OCD Web Page under
Conditions of Approval, if any:	s, www.emnrd.state.nm.us/ncds.

Form C-103 Empire Abo Unit E-392 30-015-22818 Continued from Page 1

10/25/08: RIH WITH TUBING AND TAG UP AT 567. POH AND LAYDOWN TUBING. ND BOP. PICKUP 2 JOINT (60') AND SPOT IN ALL CEMENT EQUIPMENT AND VAC TRUCKS AND GET READY TO PUMP. PUMP 60' PLUG AND LAYDOWN TUBING. RIG DOWN.

10/30/08: DIG OUT AND CUT OFF WELLHEAD, WELD IN PLATE, 1" NIPPLE & VALVE, DRY HOLE MARKER, DIG OUT AND CUT OFF ALL ANCHORS, BACK FILL AND LEVEL LOCATION.