



New Mexico Energy, Minerals and Natural Resources Department

**Susana Martinez**  
Governor

**Brett F. Woods, Ph.D.**  
Acting Cabinet Secretary

**J. Daniel Sanchez**  
Acting Division Director  
Oil Conservation Division



Administrative Order SWD-1265  
February 21, 2011

**ADMINISTRATIVE ORDER  
OF THE OIL CONSERVATION DIVISION**

Under the provisions of Division Rule 26.8B., Golden Oil Holding Corp. seeks an administrative order to utilize its Jicarilla 70 Well No. 7 (API 30-039-21827), located 1850 feet from the South line and 790 feet from the East line, Unit Letter I of Section 27, Township 24 North, Range 4 West, NMPM, Rio Arriba County, New Mexico, for produced water disposal purposes.

**THE DIVISION DIRECTOR FINDS THAT:**

The application has been duly filed under the provisions of Division Rule 26.8B. Satisfactory information has been provided that affected parties as defined in Rule 26.8B.(2) have been notified and no objections have been received within the prescribed waiting period. The applicant has presented satisfactory evidence that all requirements prescribed in Rule 26.8 will be met and the operator is in compliance with Division Rule 5.9.

**IT IS THEREFORE ORDERED THAT:**

The applicant, Golden Oil Holding Corp., is hereby authorized to utilize its Jicarilla 70 Well No. 7 (API 30-039-21827), located 1850 feet from the South line and 790 feet from the East line, Unit Letter I of Section 27, Township 24 North, Range 4 West, NMPM, Rio Arriba County, New Mexico, for disposal of oil field produced water through perforations in the Point Lookout member of the Mesaverde Formation from 4760 feet to 5256 feet, and through lined tubing and a packer set within 100 feet of the permitted disposal interval.

**Prior to commencing disposal, the operator shall:**

- a. Ensure the well is plugged back internally to within approximately 200 feet of the bottom of the permitted disposal interval – or as allowed by the US Bureau of Land Management.
- b. Swab test the disposal interval for productive potential and obtain insitu water samples.

The operator shall report these swab test results and also results of the insitu water analysis to the Division in Aztec.



IT IS FURTHER ORDERED THAT:

The operator shall take all steps necessary to ensure that the disposed water enters only the proposed disposal interval and is not permitted to escape to other formations or onto the surface.

After installing tubing, the casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge or an approved leak detection device in order to determine leakage in the casing, tubing, or packer. The casing shall be pressure tested from the surface to the packer setting depth to assure casing integrity.

The wellhead injection pressure on the well shall be limited to **no more than 952 psi**. In addition, the disposal well or system shall be equipped with a pressure limiting device in workable condition which shall, at all times, limit surface tubing pressure to the maximum allowable pressure for this well.

The Director of the Division may authorize an increase in tubing pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the disposed fluid from the target formation. Such proper showing shall be demonstrated by sufficient evidence including but not limited to an acceptable Step-Rate-Test.

The operator shall notify the supervisor of the Division's district office of the date and time of the installation of disposal equipment and of any mechanical integrity test so that the same may be inspected and witnessed. The operator shall provide written notice of the date of commencement of disposal to the Division's district office. The operator shall submit monthly reports of the disposal operations on Division Form C-115, in accordance with Division Rules 26.13 and 7.24.

Without limitation on the duties of the operator as provided in Division Rules 30 and 29, or otherwise, the operator shall immediately notify the Division's district office of any failure of the tubing, casing or packer in the well, or of any leakage or release of water, oil or gas from around any produced or plugged and abandoned well in the area, and shall take such measures as may be timely and necessary to correct such failure or leakage.

The injection authority granted under this order is not transferable except upon division approval. The division may require the operator to demonstrate mechanical integrity of any injection well that will be transferred prior to approving transfer of authority to inject.

The division may revoke this injection permit after notice and hearing if the operator is in violation of 19.15.5.9 NMAC.

In accordance with Division Rule No 26.12.C., the disposal authority granted herein shall terminate one year after the effective date of this order if the operator has not commenced injection operations into the subject well, provided however, the Division, upon written request, mailed by the operator prior to the termination date, may grant an extension thereof for good

cause. One year after disposal into the well has ceased, the authority to dispose will terminate *ipso facto*.

Compliance with this order does not relieve the operator of the obligation to comply with other applicable federal, state or local laws or rules, or to exercise due care for the protection of fresh water, public health and safety and the environment.

Jurisdiction is retained by the Division for the entry of such further orders as may be necessary for the prevention of waste and/or protection of correlative rights or upon failure of the operator to conduct operations (1) to protect fresh or protectable waters or (2) consistent with the requirements in this order, whereupon the Division may, after notice and hearing, terminate the disposal authority granted herein.



J. DANIEL SANCHEZ  
Acting Director

JDS/wvjj

cc: Oil Conservation Division – Aztec  
Bureau of Land Management - Farmington