STATE OF NEW MEXICO

ENERGY, MINERALS AND NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION



POST OFFICE BOX 2088 STATE LAND OFFICE BUILDING SANTA FE, NEW MEXICO 87504 (505) 827-5800

AMENDED ADMINISTRATIVE ORDER NO. WFX 607

APPLICATION OF GREENHILL PETROLEUM CORPORATION TO EXPAND ITS WATERFLOOD PROJECT IN THE LOVINGTON PADDOCK POOL IN LEA COUNTY, NEW MEXICO

ADMINISTRATIVE ORDER OF THE OIL CONSERVATION DIVISION

Under the provisions of Division Order No. R-3124, Greenhill Petroleum Corporation has made application to the Division on May 24, 1991, for permission to expand its Lovington Paddock Unit Waterflood Project in the Lovington Paddock Pool in Lea County, New Mexico.

NOW, on this 15th day of August, 1991, the Division Director finds that:

- (1) The application has been filed in due form.
- (2) Satisfactory information has been provided that all offset operators have been duly notified of the application.
- (3) No objection has been received within the waiting period as prescribed by Rule 701(B).
- (4) The proposed injection wells are eligible for conversion to water injection under the terms of Rule 701.
- (5) The proposed expansion of the above-referenced waterflood project will not cause waste nor impair correlative rights.
 - (6) The application should be approved.

Administrative Order WFX-607 Greenhill Petroleum Corporation August 14, 1991 Page 2

IT IS THEREFORE ORDERED THAT:

The applicant, Greenhill Petroleum Corporation, be and the same is hereby authorized to inject water into the Paddock formation at approximately 6044 feet to approximately 6286 feet through 2 3/8 inch plastic lined tubing set in a packer located within 100 feet of the uppermost injection perforations in the wells shown on Exhibit "A" attached hereto for purposes of secondary recovery:

IT IS FURTHER ORDERED THAT:

The operator shall take all steps necessary to ensure that the injected water enters only the proposed injection interval and is not permitted to escape to other formations or onto the surface.

Prior to commencing injection operations into the wells, the casing in each well shall be pressure tested from the surface to the packer setting depth to assure the integrity of said casing.

The casing-tubing annulus in each well shall be loaded with an inert fluid and equipped with a pressure gauge at the surface or left open to the atmosphere to facilitate detection of leakage in the casing, tubing or packer.

The injection wells or system shall be equipped with a pressure limiting device which will limit the wellhead pressure on the injection well to no more than 0.2 psi/ft. of depth to the uppermost perforation as shown on Exhibit "A".

The Director of the Division may authorize an increase in injection pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the injected fluid from the Paddock formation. Such proper showing shall consist of a valid step-rate test run in accordance with and acceptable to this office.

The operator shall notify the supervisor of the Hobbs district office of the Division of the date and time of the installation of injection equipment and of the mechanical integrity tests so that the same may be inspected and witnessed.

The operator shall immediately notify the supervisor of the Hobbs district office of the Division of the failure of the tubing, casing or packer in said wells and shall take such steps as may be timely and necessary to correct such failure or leakage.

Administrative Order WFX-607 Greenhill Petroleum Corporation August 14, 1991 Page 3

The subject well shall be governed by all provisions of Division Order No. R-3124 and Rules 701-708 of the Division Rules and Regulations not inconsistent herewith.

PROVIDED FURTHER THAT, jurisdiction of this cause is hereby retained by the Division for the entry of such further order or orders as may be deemed necessary or convenient for the prevention of waste and/or protection of correlative rights; upon failure of the operator to conduct operations in a manner which will ensure the protection of fresh water or in a manner inconsistent with the requirements set forth in this order, the Division may, after notice and hearing, terminate the injection authority granted herein.

The operator shall submit monthly progress reports of the project in accordance with Rules 706 and 1115 of the Division Rules and Regulations.

Approved at Santa Fe, New Mexico, on this 14th day of August, 1991.

STATE OF NEW MEXICO OIL CONSERVATION DIVISION

WILLIAM J. LEMA

Director

cc: OCD - Hobbs

SEAL

EXHIBIT "A" DIVISION ORDER NO. AMENDED WFX-607 APPROVED INJECTION WELLS LOVINGTON PADDOCK UNIT

1232 PSIG	2-3/8"	6100'	6160' - 6279'	1-17S-36E	p	660' FSL & 660' FEL	LPU NO. 71
1227 PSIG	2-3/8"	6100'	6136' - 6286'	6-17S-37E	L	2310' FSL & 660' FWL	LPU NO. 67
1213 PSIG	2-3/8"	6000'	6065' - 6235'	1-17S-36E	Н	1980' FNL & 560' FEL	LPU NO. 58
1220 PSIG	2-3/8"	6000'	6100' - 6256'	6-17S-37E	T	1650' FNL & 1733' FWL	LPU NO. 56
1209 PSIG	2-3/8"	6000'	6044' - 6260'	36-16S-36E	Z	810' FSL & 2130' FWL	LPU NO. 41
1211 PSIG	2-3/8"	6000'	6054' - 6250'	31-16S-37E	Z	330' FSL & 2290' FWL	LPU NO. 37
1216 PSIG	2-3/8"	6000'	6082' - 6275'	35-16S-36E	H	2310' FNL & 330' FEL	LPU NO. 18
1215 PSIG	2-3/8"	6000'	6075' - 6280'	36-16S-36E	D	660' FNL & 660' FWL	LPU NO. 16
1217 PSIG	2-3/8"	60007	6085' - 6260'	25-16S-36E	P	330' FSL & 330' FEL	LPU NO. 7
1220 PSIG	2-3/8"	6000'	6100' - 6281'	25-16S-36E	Z	660' FSL & 1980' FWL	LPU NO. 5
Injection Pressure	Tubing Size	Packer Depth	Injection Interval	S-T-R	Unit	Location	Well Number