### STATE OF NEW MEXICO

# ENERGY, MINERALS AND NATURAL RESOURCES DEPARTMENT



BRUCE KING

GOVERNOR

OIL CONSERVATION DIVISION

POST OFFICE BOX 2088 STATE LAND OFFICE BUILDING SANTA FE, NEW MEXICO 87504 (505) 827-5800

## ADMINISTRATIVE ORDER NO. WFX 608

APPLICATION OF TEXACO PRODUCING, INC. TO EXPAND ITS WATERFLOOD PROJECT IN THE DOLLARHIDE TUBB DRINKARD POOL IN LEA COUNTY, NEW MEXICO

# ADMINISTRATIVE ORDER OF THE OIL CONSERVATION DIVISION

Under the provisions of Division Order No. R-3768, Texaco Producing, Inc. has made application to the Division on May 20, 1991, for permission to expand its West Dollarhide Drinkard Unit Waterflood Project in the Dollarhide Tubb Drinkard Pool in Lea County, New Mexico.

# THE DIVISION DIRECTOR FINDS THAT:

- (1) The application has been filed in due form.
- (2) Satisfactory information has been provided that all offset operators have been duly notified of the application.
- (3) No objection has been received within the waiting period as prescribed by Rule 701(B).
- (4) The proposed injection wells are eligible for conversion to water injection under the terms of Rule 701.
- (5) The proposed expansion of the above referenced Waterflood Project will not cause waste nor impair correlative rights.
  - (6) The application should be approved.

Administrative Order WFX-608 Texaco Producing, Inc. July 19, 1991 Page 2

## IT IS THEREFORE ORDERED THAT:

The applicant, Texaco Producing, Inc., be and the same is hereby authorized to inject water into the Tubb-Drinkard formation at approximately 6400 feet to approximately 6586 feet through 2 3/8 inch plastic lined tubing set in a packer located within 100 feet of the uppermost injection perforations in the wells shown on Exhibit "A" attached hereto for purposes of secondary recovery to wit:

# IT IS FURTHER ORDERED THAT:

The operator shall take all steps necessary to ensure that the injected water enters only the proposed injection interval and is not permitted to escape to other formations or onto the surface.

Prior to commencing injection operations into the wells, the casing in each well shall be pressure tested from the surface to the packer setting depth to assure the integrity of said casing.

The casing-tubing annulus in each well shall be loaded with an inert fluid and equipped with a pressure gauge at the surface or left open to the atmosphere to facilitate detection of leakage in the casing, tubing or packer.

The injection wells or system shall be equipped with a pressure limiting device which will limit the wellhead pressure on the injection well to no more than 0.2 psi/ft. of depth to the uppermost perforation as shown on Exhibit "A".

The Director of the Division may authorize an increase in injection pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the injected fluid from the Tubb-Drinkard formation. Such proper showing shall consist of a valid step-rate test run in accordance with and acceptable to this office.

The operator shall notify the supervisor of the Hobbs district office of the Division of the date and time of the installation of injection equipment and of the mechanical integrity tests so that the same may be inspected and witnessed.

The operator shall immediately notify the supervisor of the Hobbs district office of the Division of the failure of the tubing, casing or packer in said wells and shall take such steps as may be timely and necessary to correct such failure or leakage.

Administrative Order WFX-608 Texaco Producing, Inc. July 19, 1991 Page 3

The subject well shall be governed by all provisions of Division Order No. R-3768 and Rules 702-706 of the Division Rules and Regulations not inconsistent herewith.

PROVIDED FURTHER THAT, jurisdiction of this cause is hereby retained by the Division for the entry of such further order or orders as may be deemed necessary or convenient for the prevention of waste and/or protection of correlative rights; upon failure of the operator to conduct operations in a manner which will ensure the protection of fresh water or in a manner inconsistent with the requirements set forth in this order, the Division may, after notice and hearing, terminate the injection authority granted herein.

The operator shall submit monthly progress reports of the project in accordance with Rules 706 and 1115 of the Division Rules and Regulations.

DONE at Santa Fe, New Mexico, on this 18th day of July, 1991.

STATE OF NEW MEXICO OIL CONSERVATION DIVISION

WILLIAM J. LEMAY

Director

cc: OCD - Hobbs

WJL/DC/jc

SEAL

# EXHIBIT "A" DIVISION ORDER NO. WFX-608 WEST DOLLARHIDE DRINKARD UNIT APPROVED INJECTION WELLS

1280 PSIG	2-3/8"	6350'	6400' - 6490'	32-24S-38E	K	1980' FSL & 1980' FWL	WDDU NO. 62
1290 PSIG	2-3/8"	6400'	6449' - 6586'	32-24S-38E		2130' FSL & 510' FEL	WDDU NO. 60
1284 PSIG	2-3/8"	6375'	6418' - 6499'	31-24S-38E	A	990' FNL & 330' FEL	WDDU NO. 46
1300 PSIG	2-3/8"	6450'	6503' - 6586'	30-24S-38E		1650' FSL & 660' FEL	WDDU NO. 28
Injection Pressure	Tubing Size	Packer Depth	Injection Intervals	S-T-R	Unit	Location	Well Number