

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-025-34488

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

023608

7. Lease Name or Unit Agreement Name:

Fern Guye

8. Well No.

1

9. Pool name or Wildcat

South Tatum Wildcat Upper Penn

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other

2. Name of Operator Greka Energy

Saba Energy of Tx

3. Address of Operator Greka Energy, Suite 220, Houston, Tx 77042

4. Well Location

Unit Letter M 400 feet from the S line and 990 feet from the W line

Section 5

Township 13S

Range 36E

NMPM

County Lea

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
4003' (GL)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

See attached well bore schematic.

Pump 25sx cmt plug @ 10854' on top of existing RBP. (10510' - 10854')

Will attempt to recover 5 1/2" csg @ TOC ~7600'. If successful will pump 25sx cmt plug @ stub. (7470' - 7600')

If unsuccessful will pump 25sx cmt plug @ 7600' in cased hole: (7256' - 7600')

Pump 25sx cmt plug @ 8 5/8" csg shoe @ 4530'. (4443' - 4580')

If first attempt to recover 5 1/2" csg unsuccessful then cut @ 4580'. POH. Pump 25sx cmt plug @ stub. (4443' - 4580')

Pump 25sx cmt plug @ 2230' @ salt zone.

Pump 25sx cmt plug @ 13 3/8" csg shoe @ 438'. (351' - 438')

Pump 12 1/2sx cmt plug @ surf. (0' - 65')

Cut off wellhead and install deadman marker.

THE COMMISSION MUST BE NOTIFIED 24
HOURS PRIOR TO THE BEGINNING OF
OPERATIONS FOR THE C-103.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

DATE

Type or print name Tracy Headstream

(This space for State use)

APPROVED BY

TITLE

Conditions of approval, if any:

ORIGINAL SIGNED BY
PAUL F. KAUTZ
PETROLEUM ENGINEER

Telephone No.

917-769-5154
(505) 390-7482

FEB 12 2002

Before the OCD
Case 13363
OCD Ex. 22

PLUGGING & ABANDONMENT WORKSHEET

(3 STRING CSNG)

OPERATOR

GREEK ENERGY

LEASENAME

FERN GUYE

SECT

TVN

WELL #

135 RNG 36E

36E

FROM

NS/L

990 ENVL

EWL

TD:

11230

FORMATION

CANYON

PBTD:

11220

FORMATION

ID **ADLTYPE**

	SIZE	SET @	TOC	TOC DETERMINED BY	
SURFACE	13 1/2	438	SURK	CIRC CHIT	
INTMED 1	8 1/2	4530	SURF	CIRC	
INTMED 2					
PROD	5 1/2	11220	7675	CIRC	
	SIZE	TOP	BOT	TOC	DETERMINED BY
LINER 1					
LINER 2					
	CUT & PULL @			TOP - BOTTOM	
INTMED 1			PERFS	10692 - 10702	
INTMED 2			OPENHOLE	4530 - 7600	
PROD	7600'				

• REQUIRED PLUGS DISTRICT 1

HUNTLEY (ANNEY)	
YATES	
QUEEN	
GRAYBURG	
HAN ANDRES	
CARLOAN BEEF	
DELAWARE	
BELL CANYON	
CHERRY CANYON	
BROOKY CANYON	
STONE SPRING	
CLONETA	
ELLSWICK	
TEBB	
FOREKARD	
ABO	
WOC	
PEASE	
STRAWN	
ATOKA	
LACROW	
SAW	
DEVORMAN	

[illegible]

Hand-drawn stratigraphic column with labels and calculations:

- 12 SX
- 25 SX
- 13 7/8
- ② 438
- TOC SURF
- 25 SX
- 25 SX
- 8 5/8
- ② 4530'
- TOC SURF
- TOC' ±7675'
- 25 SX
- 25 SX
- 10692-702
- 10932-950
- 11096-128 5/2
- ② 11220
- TOC 7675'
- TD 11230