

State of New Mexico
Energy, Minerals and Natural Resources Department

Susana Martinez
Governor

David Martin
Cabinet Secretary

Brett F. Woods, Ph.D.
Deputy Cabinet Secretary

Jami Bailey, Division Director
Oil Conservation Division



Administrative Order PMX-273
November 7, 2014

**ADMINISTRATIVE ORDER
OF THE OIL CONSERVATION DIVISION**

Under the provisions of Division Order R-4430, as amended, Cross Timbers Energy, LLC, (OGRID No. 298299) has made application to the Division for permission to add six (6) additional injection wells to its North Vacuum-Abo Unit Pressure Maintenance Project located within the Vacuum; Abo, North Pool (Pool code 61760) in Lea County, New Mexico. These wells are being proposed for infill of injection points within the Project area. The six wells are currently production wells that are proposed for conversion using existing perforation intervals within the Unitized formation.

THE DIVISION DIRECTOR FINDS THAT:

The application has been duly filed under the provisions of Division Rule 19.15.26.8B NMAC and satisfactory information has been provided that affected parties as defined in said rule have been notified and no objections remain outstanding. The proposed wells are eligible for conversion to injection under the terms of that rule. The applicant has presented satisfactory evidence that all requirements prescribed in Division Rule 19.15.26.8 NMAC have been met and the operator is in compliance with Division Rule 19.15.5.9 NMAC.

The proposed expansion of the above-referenced pressure maintenance project, will prevent waste, is in the best interests of conservation, will not impair correlative rights, and should be approved.

IT IS THEREFORE ORDERED THAT:

Cross Timbers Energy, LLC, as operator, is hereby authorized to inject water into the following well for the purpose of enhanced recovery through plastic or fiberglass lined tubing set into a packer:

API	Well No.	Unit	Sec	Twp	Rng	Footage N/S	Footage E/W	Approved Injection Interval (in feet)	Maximum Surface Injection Pressure
30-025-28315	North Vacuum-Abo Unit Well No. 235	K	24	17 S	34 E	1880 FSL	2000 FWL	8474 to 8515	1695 psi
30-025-28601	North Vacuum-Abo Unit Well No. 241	K	26	17 S	34 E	1882 FSL	2001 FWL	8462 to 8666	1692 psi
30-025-28919	North Vacuum-Abo Unit Well No. 269	A	15	17 S	34 E	660 FNL	660 FEL	8664 to 8704	1733 psi
30-025-29233	North Vacuum-Abo Unit Well No. 276	I	27	17 S	34 E	2050 FNL	652 FEL	8544 to 8706	1709 psi
30-025-29238	North Vacuum-Abo Unit Well No. 281	A	23	17 S	34 E	800 FNL	550 FEL	8484 to 8543	1697 psi
30-025-29610	North Vacuum-Abo Unit Well No. 300	K	10	17 S	34 E	1980 FSL	1980 FWL	8748 to 8783	1750 psi

The approved injection intervals shall be established using existing perforations at the time of application and listed in the summary table. The approved maximum surface tubing injection pressure shall be determined by the administrative pressure gradient of 0.2 pounds per square inch (psi) per foot and shall be no more than the pressure listed for each well. The operator shall set the injection packer no more than 100 feet above the top perforation.

IT IS FURTHER ORDERED THAT:

The operator shall take all steps necessary to ensure that the injected fluid enters only the approved injection interval and is not permitted to escape to other formations or onto the surface.

After installing tubing, the casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge or an approved leak detection device in order to determine leakage in the casing, tubing, or packer. The casing shall be pressure tested from the surface to the packer setting depth to assure casing integrity.

The wells shall pass an initial mechanical integrity test ("MIT") prior to initially commencing injection and prior to resuming injection each time any injection packer is unseated. All MIT procedures and schedules shall follow the requirements in Division Rule 19.15.26.11A. NMAC. The Division Director retains the right to require at any time wireline verification of completion and packer setting depths in the wells.

The wellhead injection pressure on each well shall be limited to the approved maximum surface tubing injection pressure listed above. In addition, the injection well or header system shall be equipped with a pressure limiting device in workable condition which shall, at all times, limit surface tubing pressures to the maximum allowable pressures for these wells.

Subject to the limitations within the hearing order permitting this project, the Division Director may authorize an increase in tubing pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the injected fluids from the approved injection interval. Such proper showing shall be demonstrated by sufficient evidence

including but not limited to an acceptable Step-Rate Test.

The operator shall notify the supervisor of the Division's District I office of the date and time of the installation of injection equipment and of any MIT so that the same may be inspected and witnessed. The operator shall provide written notice of the date of commencement of injection to the Division's District office. The operator shall submit monthly reports of the disposal operations on Division Form C-115, in accordance with Division Rules 19.15.26.13 and 19.15.7.24 NMAC.

Without limitation on the duties of the operator as provided in Division Rules 19.15.29 and 19.15.30 NMAC, or otherwise, the operator shall immediately notify the Division's District I office of any failure of the tubing, casing or packer in the approved injection wells, or of any leakage or release of water, oil or gas from around any produced or plugged and abandoned well in the area, and shall take such measures as may be timely and necessary to correct such failure or leakage.


The injection authority granted under this Order is not transferable except upon Division approval. The Division may require the operator to demonstrate mechanical integrity of any injection well that will be transferred prior to approving transfer of authority to inject.

The Division may revoke this injection permit after notice and hearing if the operator is in violation of Division Rule 19.15.5.9 NMAC.

Compliance with this Order does not relieve the operator of the obligation to comply with other applicable federal, state or local laws or rules, or to exercise due care for the protection of fresh water, public health and safety and the environment.

The subject wells shall be governed by all provisions of Division Order No. R-4430, as amended, and Division Rules 19.15.26.9 NMAC through 19.15.26.13 NMAC not inconsistent herewith.

Jurisdiction is retained by the Division for the entry of such further orders as may be necessary for the prevention of waste and/or protection of correlative rights or upon failure of the operator to conduct operations (1) to protect fresh or protectable waters or (2) consistent with the requirements in this order, whereupon the Division may, after notice and hearing, terminate the disposal authority granted herein.



JAMI BAILEY
Director

JB/prg

cc: Oil Conservation Division – Hobbs District Office
State Land Office - Oil, Gas and Minerals Division
Case No. 4831