

FORM	TOP																																													
			Davis N #5 P & A WELLBORE DIAGRAM Phillips Petroleum																																											
	8 5/8" Csg @ 614' Cmt w/ 400 sx. Circ.		Sec.Twp.Rng 7N-T8S, R33E 660' FSL 1980' FWL API #: 30-005-20847 POOL: Chaveroo CO, ST: Chaves, NM STATUS: P & A DIAGRAM REVISED:																																											
	Sqz hole @664' Sqz. Cmt to Surf.		LOG ELEVATION: GROUND ELEVATION: 4439'																																											
	TOC @ 1260' TS		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="4">CASING</th> </tr> </thead> <tbody> <tr> <td>Csg</td> <td>8 5/8"</td> <td>614'</td> <td>400 sx</td> </tr> <tr> <td>Csg</td> <td>4 1/2"</td> <td>4579'</td> <td>1245 sx</td> </tr> <tr> <td>Csg</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Csg</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	CASING				Csg	8 5/8"	614'	400 sx	Csg	4 1/2"	4579'	1245 sx	Csg				Csg																										
CASING																																														
Csg	8 5/8"		614'	400 sx																																										
Csg	4 1/2"		4579'	1245 sx																																										
Csg																																														
Csg																																														
	20 sx cmt 1593-1793		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="4">LOGS</th> </tr> </thead> <tbody> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> </tbody> </table>	LOGS																																										
LOGS																																														
	CIBP 4200' w/ 20 sx cmt 4000-4200' 20 sx cmt 3410-3610' 20 sx cmt 2668-2868" 20 sx cmt 1593-1793 Perf 4 1/2" Csg 664', Cmt w/ 250 sx. Circ	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td colspan="2"> Spud Date: 1/28/1982 Comp. Date: 3/22/1982 First Perforated Interval: 4268-4498 Acid Job: NA Gal. Frac: </td> </tr> <tr> <td colspan="2"> IP: 20 BOPD 17 MCF 116 BWPD </td> </tr> <tr> <td colspan="2" style="height: 100px;"> NOTES: </td> </tr> <tr> <td colspan="2"> COMMENTS P & A 11/92 CIBP 4200' w/ 20 sx cmt 4000-4200' 20 sx cmt 3410-3610' 20 sx cmt 2668-2868" 20 sx cmt 1593-1793 Perf 4 1/2" Csg 664', Cmt w/ 250 sx. Circ </td> </tr> </table>	Spud Date: 1/28/1982 Comp. Date: 3/22/1982 First Perforated Interval: 4268-4498 Acid Job: NA Gal. Frac:		IP: 20 BOPD 17 MCF 116 BWPD		NOTES:		COMMENTS P & A 11/92 CIBP 4200' w/ 20 sx cmt 4000-4200' 20 sx cmt 3410-3610' 20 sx cmt 2668-2868" 20 sx cmt 1593-1793 Perf 4 1/2" Csg 664', Cmt w/ 250 sx. Circ																																					
Spud Date: 1/28/1982 Comp. Date: 3/22/1982 First Perforated Interval: 4268-4498 Acid Job: NA Gal. Frac:																																														
IP: 20 BOPD 17 MCF 116 BWPD																																														
NOTES:																																														
COMMENTS P & A 11/92 CIBP 4200' w/ 20 sx cmt 4000-4200' 20 sx cmt 3410-3610' 20 sx cmt 2668-2868" 20 sx cmt 1593-1793 Perf 4 1/2" Csg 664', Cmt w/ 250 sx. Circ																																														
	20 sx cmt 2668-2868"																																													
	20 sx cmt 3410-3610'																																													
	CIBP 4200' w/ 20 sx cmt 4000-4200' SELECT PERFS: 4268-4498'																																													
	4 1/2" Csg @ 4579' Cmt w/ 1245 sx. TOC @ 1260' TS																																													
	PBTD=4527' TD=4600'																																													