

WELLS IN THE AREA OF REVIEW

WELL NAME	OPERATOR	TYPE	SPUD	COMPL (IP)	T.D.	PROD. ZONE	PERFS.	COMPLETION INFORMATION	T O C		
Conoco 7 St. #5 F 07 19S 29E	SDX Resources	Prod.	02/02/82	03/17/82	2571'	Grayburg	2038-50' (Sqz d) 2054-68' 2140-79'	12-1/4" hole, 372' 8-5/8" 24# cmtd w/800 sxs 7-7/8" 2571', 4-1/2" 9.5# cmtd w/850 sxs.	4500 g. acid, 28,000 g. & 60,000# sd frac.	Surf 50% Circ	Calc
Conoco 7 St. #7 G 07 19S 29E	SDX Resources	Prod.	01/16/82	03/4/82	2576'	Grayburg	2069-2107' 2137-87'	12-1/4" hole, 399', 8-5/8" 23# cmtd w/300 sxs. 7-7/8" hole, 2568' 4-1/2" 9.5# cmtd w/1000 sxs.	4000 g. acid, 28000 g. & 60,000# sd frac.	Surf Circ	Circ
Conoco 7 St. #3 E 07 19S 29E	SDX Resources	Prod.	03/21/81	07/17/81	3599'	Grayburg	3523-54' CIBP 3423' 2730-74' CIBP 2700' 2142-2239'	12-1/4" hole, 432' 8-5/8" 24# cmtd w/400 sxs. 7-7/8" hole, 3599' 4-1/2" 9.5# cmtd w/1250 sxs.	2000 g. acid, 28000 g. & 60,000# sd frac.	Surf Circ	Calc 0.75
Conoco 7 St. #2 L 07 19S 29E	SDX Resources	Prod.	03/14/81	07/21/81	3792'	Grayburg	1854-2054 (Sqz d) 2122-2216'	12-1/4" hole, 450', 8-5/8" 23# cmtd w/600 sxs. 7-7/8" hole, 3792' 4-1/2" 9.5# cmtd w/1085 sxs.	4000 g. acid, 28000 g. & 60,000# sd frac.	Surf Circ	Circ
Conoco 7 St. #13 J 07 19S 29E	SDX Resources	Prod.	01/05/86	02/25/86	2765'	Grayburg	1202-1307' (sqz d) 2412-2642' CIBP 2402' 2224-2358'	12-1/4" hole, 354', 8-5/8" 24# cmtd w/248 sxs. 7-7/8" hole, 2765' 5-1/2" 15.5# cmtd w/675 sxs.	3700 g. acid, 68000 g. & 83,000# sd frac.	Surf Circ	Calc 0.75
Conoco 7 St. #12 K 07 19S 29E	SDX Resources	Prod.	04/27/85	10/29/85	2800'	Grayburg	1993-2100' (sqz d) 2638-96' CIBP 2625' 2112-2590'	12-1/4" hole, 378' 8-5/8" 24# cmtd w/275 sxs. 7-7/8" hole, 2800' 4-1/2" 9.5-10.5# cmtd w/930 sxs.	15,300 g. acid, 84,900 g. & 212,434# sd frac.	Surf Circ	Calc
Conoco 7 St. #11 H 07 19S 29E	SDX Resources	Prod.	05/04/82	06/22/82	2505'	Grayburg	2150-60' (Sqz d) 2149-54'	12-1/4" hole, 369', 8-5/8" 23# cmtd w/185 sxs. 7-7/8" hole, 2505' 4-1/2" 9.5-10.5# cmtd w/575 sxs.	3,000 g. acid, 14,000 g. & 30,000# sd frac.	Surf Circ	Calc (50 eff)
Conoco 7 St. #9 A 07 19S 29E	SDX Resources	Prod.	12/19/81	04/05/82	2449'	Grayburg	2076-2111' (Sqz d) 2115-25'	12-1/4" hole, 370', 8-5/8" 23# cmtd w/250 sxs. 7-7/8" hole, 2449' 4-1/2" 10.5# cmtd w/1000 sxs.	2,500 g. acid, 14,000 g. & 30,000# sd frac.	Surf Circ	Calc (50 eff)
Conoco 7 St. #8 B 07 19S 29E	SDX Resources	Prod.	02/13/82	03/31/82	2549'	Grayburg	2110-20' (Sqz d) 2351-2508' CIBP 2340' 2199-2323'	12-1/4" hole, 379', 8-5/8" 23# cmtd w/400 sxs. 7-7/8" hole, 2549' 4-1/2" 11.6-9.5# cmtd w/950 sxs.	1325 g. acid, 39000 g. & 52200# sd frac.	Surf Circ	Circ (75)
Conoco 7 St. #4 D 07 19S 29E	SDX Resources	Prod.	11/11/81	02/21/82	2587'	Grayburg	2163-98' 2214-40'	12-1/4" hole, 384', 8-5/8" 24# cmtd w/400 sxs. 7-7/8" hole, 2587' 4-1/2" 9.5# cmtd w/875 sxs.	4000 g. acid, 28000 g. & 60000# sd frac.	Surf Circ	Calc 0.75
Conoco 7 St. #6 C 07 19S 29E	SDX Resources	Prod.	11/30/81	02/21/82	2853'	Grayburg	2165-86' 2214-38'	12-1/4" 385', 8-5/8" 24# cmtd w/400 sxs. 7-7/8" hole, 2553' 4-1/2" 9.5# cmtd w/884 sxs.	4000 g. acid, 28000 g. & 60000# sd frac.	Surf Circ	Calc (0.50)
Conoco 7 St. #1 J 07 19S 29E	Stanley Jones	P&A 4/24/60	04/09/52	NA	2832'	NA	NA	12", 10-3/4" 300' set & pld. 10" hole 8-5/8" 2000' set & pld. See wellbore diagram for P&A details.		NA	NA
Conoco 7 St. #1 N 07 19S 29E	Mitchell Energy Corp.	Prod.	02/12/80	05/08/80	11610'	Morrow	11036-11050'	17-1/2" hole, 13-3/8" 48# 400', cmtd w/550 sxs Cl C 11" hole, 8-5/8" 24-32# 2690' cmtd w/ 1100 sxs Lite & 200 sxs C, 7-7/8" hole, 5-1/2" 17# 11264' cmtd w/1025 sxs 2-7/8" tbg & pkr @ 10942'.		NA	RediMix Temp Calc 5678 (75%)
Conoco 7 St. #10 F 07 19S 29E	Mitchell Energy Corp.	Prod.	11/04/81	01/07/82	11550'	Morrow	11138-166', pkr plug @ 11078' New Perfs 10986-11044'	17-1/2" hole, 13-3/8" 54.5-61# 377' cmtd w/375 sxs Cl C 12-1/4" hole, 8-5/8" 24-32# 3020' cmtd w/ 580sxs Pozmix, 200 sxs Cl C, 7-7/8" 5-1/2" 17-20# @ 11533' cmtd w/785 Pozmix, 2-3/8" tbg & pkr @ 10925'		Surf Circ	Circ 10 sxs Circ 10 sxs Temp
Elizabeth Dundas #1 M 07 19S 29E	John A. Yates	P&A 01/14/67	08/10/61	09/11/61	2227'	NA	2092-96' 1773-96'	11" hole, 8-5/8" @ 283', cmtd w/50 sxs, 6" hole, 4-1/2" @ 2163', cmtd w/125 sxs. See wellbore for P&A details.		8995 144 1530	Temp Assumed Assumed
Elizabeth Dundas #2 N 07 19S 29E	John A. Yates	P&A 12/28/66	12/30/61	01/31/62	2348'	NA	2101-2096' 2087-2080'	11" hole, 8-5/8" @ 283', cmtd w/50 sxs, 6" hole, 4-1/2" 9.5# @ 2192' cmtd w/100 sxs. See wellbore for P&A details.		162 1441	Assumed Assumed

P:\LUNDS\WELLAREA\WK1 FORM

WELLS IN THE AREA OF REVIEW

WELL NAME	OPERATOR	TYPE	SPUD	COMPL. (IP)	T.D.	PROD. ZONE	PERFS.	COMPLETION INFORMATION	T O C			
State N&C #1 M 06 19S 29E	M. Yates II	P&A	10/18/65	07/14/66	2844' PB 2658	San Andres	2776-78' (Sqz'd) 2676-82' (Sqz'd) 2621-25' (Sqz'd) 2612-16'	12-1/4" hole, 433' 8-5/8" 24# cmtd w/50 sx 2795 5-1/2", cmtd w/300 sx, assume 7-7/8"	7000 g. acid SWF: 39,480 & 58000#	353' 1652'	50% calc 50% calc	
Nix & Curtis St #1 K 06 19S 29E	Collins, Davis, Nix & Curtis	P&A	09/15/62	03/22/63	2626' PB 1987	Grayburg (TA) Pentose	2188-98', 2208-18' CIBP 1987, 1924-28' 1930-32', 1940-44' 1950-55'	12-1/4" hole, 282' 8-5/8", cmtd w/75 sx 7-7/8" hole, 2329' 4-1/2", cmtd w/200 sx	500 g. mud acid 500 g. acid SF 40000 & 66000#	122' 727'	50% calc assumed (cut)	
Heyco S St #1 K 6 19S 29E	Heyco	Prod	08/13/77	12/11/77	11,500'	Bone Spring	8424', 8246'	17-1/2" hole, 13-3/8" @ 418' w/400 "C" 12-1/4" hole, 9-5/8" @ 3665' w/2150 "C" lite 8-3/4" hole 5-1/2" @ 11500' w/1700 "H" lite Cut off & spliced back @ 2894'. Original Amoco State ER #2 Com	A: 3000 gal 5% HCL F: 19000 gals & 30000# 20/40	circ circ NA	calc calc	
New Mexico Z St #1 A 12 19S 28E	Frostman	Prod.	07/06/82	09/29/82	2922' PB 2252	San Andres QN/GRB	2592-2632' New Perfs: 2382-98' 2280-94', 2056-88' 2106-16', 2158-74' 2196-2220'	412' 9-5/8", cmtd w/250 sx 2922 5-1/2", cmtd w/1475 sx	12000 g. acid SWF: 80000 & 139750#		circ circ	
New Mexico O St #1 G 12 19S 28E	Bass Enterprises	Prod.	01/16/83	01/26/84	11485' PB 9511	Cisco Wolfcamp	10802-804, 10886-890 10903-915, 10932-941 10316-324, 9756-60 9789-99, 9534-46 CIBP 9680' New Perf: 9468-87	365' 13-3/8", cmtd w/450 sx 12-1/4" hole, 3000' 8-5/8", cmtd w/2000 sx 11465' 5-1/2", cmtd w/1680 sx	11400 g. total acid		circ circ	
Bass #2 H 12 19S 28E	S&J Co	Prod	01/07/64	03/28/64	2278'	Grayburg	2167-69', 2190-94' 2234-36'	12-1/4" hole, 405' 8-5/8", cmtd w/50 sx 1894' 7" cmt NA, 2260' 4-1/2", cmtd w/75 sx	SF: 25000 & 25000#	325' 1683'	50% calc 50% calc	
E. Millman Tr 3 #1 I 12 19S 28E	S&J Co	WI	08/11/63 Converted 08/01/81	10/10/63	2318' PB 2272	QN/GRB	2148-56', 2225-35' New Perf: 1718-2136'	12-1/4" hole, 401' 8-5/8", cmtd w/50 sx 8" hole 2318' 4-1/2", cmtd w/100 sx, Tbg 2248' 2-3/8"	5850 g. acid SF: 700 & 25000#	321' 1875' 2041'	50% calc 75% calc 50% calc	