

ULF - b66w 1.1.1.

7"- 2295 SX - 12,130'

9 5/8" - 1800SX - 4273
Circ 5805X

13 ³/₈ - 300 SX - 39.
Circ 100 SX

CONDOLTOR CIE 1

SET SURFACE PLUS 30' to SURFACE.

CONDUCTOR (IF USED)

PERF 13 7/8 @ 393' success emt 50' out
50' inside.

CMT P146 FROM 2320' - 2450'

Top of CMT 7" 3170'
by TEMP. SURVEY.

Perforate 7" @ 4273' Square Cmt 50' out
50' inside

2230' T. 4NN.

2370' T. 346

2850' T. Yates:

4130' SAN ANDR.

9 5/8 @ 4273

5550' - T. Glacier

CMT PLUG-6950-7050

7700' T. 480

8985 - T. Permo Pen.

9639' T. OF BOUGH

11606' - T. M. 55

12/28 - T. Devonian

TDA 12137'

100' CMT PLUG @ 8950
9050

9050

BEFORE EXAMINER SIGNATURE

OIL COMPANY (TYPE & NUMBER)

OCD

LABOR NO. 4

CASE NO. 11901

Set CIP @ 12,000' - 35' CMT ON TOP
7" set @ 14130