

NE SE 14 T16S R35E

Schlumberger		SIDEWALL NEUTRON POROSITY LOG	
COMPANY: PUBCO PETROLEUM CORPORATION			
WELL: SKELLY STATE #1			
FIELD: WILDCAT			
COUNTY: LEA		STATE: NEW MEXICO	
Location: 1980' FSL & 660' FEL		Other Services:	
Sec. 14 Twp. 16-S Rge. 35-E		DIL, ML	
Permanent Datum: G.L. 3970		Elev. K.B. 3970	
Log Measured From: K.B. 37 ft Above Perm. Datum		D.F. 3970	
Drilling Measured From: K.B.		G.L. 3970	
Date: 1-25-73	Run No: ONE		
Depth - Driller: 13200	Depth - Logger: 13189		
Bit Log Interval: 13188	Top Log Interval: 0		
Casing - Driller: 9 5/8" 4810	Casing - Logger: 4804		
Bit Size: 8 3/4"	Bit Type: 2 1/2"		
Type Fluid in Hole: LULL	Fluid Level: 2.2 74		
Dens. Visc. pH Fluid Log: 4.2	Source of Sample: PIT		
Run in Meas. Temp: 1.82 in 62 °F	Run in Meas. Temp: 1.67 in 66 °F		
Run in Meas. Temp: 2.53 in 66 °F	Source Rec. 18 in 1 M		
Run in Meas. Temp: 62 in 181 °F	Time Since Core: 10 HOURS		
Max Rec Temp: 181 °F	Max Rec Temp: 181 °F		
Equip. Location: 3241 IHUBDS	Recorded By: WALLS, YEMPER		
Witnessed By: JOHNSON, CA SEY			

Atoka Lime

Atoka Clastics

Spud: 11/17/72

Comp: 3/24/73

Wolfcamp 10,456-474 F 334 BOPD

Atoka (Morrow) 11864-884 F CAOF 1.9 MM CFFPD

DST 11,750-900

GTS 2 hr 420 MCF GPD

rec 480' VHG# SC CM

485' SGT MCWB

3 hr 34' ISIP 4849

3 hr FSIP 4756

Atoka "Brunson" Sand

Morrow Lime

Perf 11,864-884

A/3250

F 557 MCF GPD, 17 BC/12 hr.

Perf 12036-43 Chester

A/3500

F 30 MCF GPD

NEW MEXICO
OIL CONSERVATION DIVISION

EXHIBIT C

CASE NO.

