BURLINGTON RESOURCES

MID-CONTINENT DIVISION

October 15, 1998

Application for the Unitization of the Corbin Delaware Unit Lea County, New Mexico

State of New Mexico Energy, Minerals and Natural Resources Department Oil Conservation Division 2040 South Pacheco Santa Fe, NM 87505-5472

85°61

Attention: Mr. David Catanach

Dear Mr. Catanach:

Pursuant to your request for additional data related to the unitization of the Corbin Delaware Unit, attached for your review are wellbore diagrams for wells that have been plugged and abandoned, which are located within one-half mile of the proposed injector wells for the Corbin Delaware Unit. Also enclosed for your review are upper and lower member hydrocarbon pore volume maps for the Upper "YZ" Sand.

Should you need additional information or data, please contact the undersigned at (915) 688-9044.

Sincerely

Rick Gallegos Senior Landman

Encl.

WEST CORBIN FEDERAL #3

WEST CORBIN FIELD 660' FNL and 660' FEL T18S, R33E, Section 18 Lea County, New Mexico Current Completion – Well plugged 2/14/77

10 sx cement plug at surface. KB 3,866' GL 3,856' 12-1/4" hole 8-5/8" 24# K-55 Casing set at 332'. Cemented with 275 sx. Top of Cement at surface (Circ). 50 sx cement plug 155' to 332' (Shoe) 50 sx cement plug 1203' to 1380' (Top Salt) 50 sx cement plug 2523' to 2700' (Base Salt) 50 sx cement plug 3118' to 3295' (Yates) 50 sx cement plug 3913' to 4090' (Queen) 50 sx cement plug 4623' to 4800' (San Andres) -----[;] 7-7/8" hole to 5177'.

TD 5,177'.

FEDERAL #1

TD 4,500'.

1980' FNL and 1980' FWL T18S, R33E, Section 17 Lea County, New Mexico

Current Completion - Well plugged 1/12/61

	5 sx cement plug at surface.	KB 3,887' GL 3,877'
	12-1/4" hole 8-5/8" 24# Casing set at 246'. Cemented with 150 sx. Top of Cement at surface (Circ).	
	30 sx cement plug 1370' to 1470'	
	30 sx cement plug 2700' to 2800'	
	30 sx cement plug 3100' to 3200'	
	7-7/8" hole to 4,500'.	