

THE OHIO OIL COMPANY
 BERTHA BARBER-NO. 9
 MONUMENT FIELD
 LEA COUNTY, NEW MEXICO

20000 to dual
 127000 to drill separate
 mon-Pad well

13 ³/₈" O. D., 48#, H-40
 Casing set at 267'
 Cem. w/250 sxs

Top of cement
 2355' by temp. survey

8 ⁵/₈" O. D., 32#, J-55
 Casing set at 2801'
 Cem. W/1200 sxs.

2 ¹/₁₆" O. D., 3.4#, J-55
 Hydril "CS" tubing
 Hung at 5275'

← offset GOR
 712-1

2 ¹/₁₆" O. D., 3.4#, J-55,
 Hydril "CS" tubing
 Hung at 5600'

Monument-Paddock
 Perforations approx.
 5200'-5223'

5 ¹/₂" O. D., 15.5#, J-55
 Casing set at 5752'
 Cem. W/ 515 sxs
 Top of cem. 2355'
 By temp. survey

Baker Model "D" production
 Packer at 5540' ✓

Monument-Blinebry
 Perforations 5570'-5600'

PB. TD. 5721'
 TD. 5755'

BEFORE THE
 OIL CONSERVATION COMMISSION
 SANTA FE, NEW MEXICO
 Ohio EXHIBIT No. 3
 CASE 1340

six feet
 GOR
 aug 57

