Form 9-831 a		Budget Bureau No. 42-R358.4. Approval expires 12-31-60.	
(Feb. 1951)	(SUBMIT IN TRIPLICATE)	Land Office	Las Cruces
		Lease No.	029415(b)
	UNITED STATES	Unit	F
	DEPARTMENT OF THE INTERIOR		
	GEOLOGICAL SURVEY		

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL NOTICE OF INTENTION TO CHANGE PLANS NOTICE OF INTENTION TO TEST WATER SHUT-OFF NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDIZE NOTICE OF INTENTION TO PULL OR ALTER CASING NOTICE OF INTENTION TO ABANDON WELL		
	 ure of report, notice, or other data) September 12	<u>1960</u>

ruckett D					
Well No. 19 is locate	d 2615 ft.	from $\begin{bmatrix} N \\ S \end{bmatrix}$ line	and <u>2615</u> ft. fro	m $\left\{ \begin{matrix} \mathbf{E} \mathbf{X} \\ \mathbf{W} \end{matrix} \right\}$ line of	sec. <u>25</u>
SE/NW Sec. 25 (% Sec. and Sec. No.)	17S	31E	NMPM		
(1/4 Eec. and Sec. No.)	(Twp.)	(Range)	(Meridian)		
Wildcat		Eddy	New	Mexico	
(Field)	(C	ounty or Subdivision)		(State or Territory)	

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show siz	s, weights, and lengths of proposed casings; indicate mudding jobs, cement- ther important proposed work)

We propose to drill a test to the Abo formation at a depth of approximately 8000 feet. Surface casing will be 13 3/8" set at about 300 feet and cement will be circulated to the surface. Approximately 4100 feet of 8 5/8" casing will be set and cemented to at least the top of the salt. A $5\frac{1}{2}$ " liner will be used for production string and cemented into the 8 5/8", or a complete string of $5\frac{1}{2}$ " will be used and cemented to 1000 feet above the shoe. Pipe will be set through the Abo pay.

l understa	nd that this plan of work must receive approval in	n writing by the Geological Survey before operations may be commenced.
Company	William A. & Edward R.	Hudson
Address	1810 Electric Building	
	Fort Worth, Texas	By By and he we It we
		Title Joint Operator
