## Markham, Cone & Redfern Eubanks No. 3 NE SW Sec. 14, T-21-S, R-37-E. Lea County, New Mexico Diagrammatic Sketch of Down-hole Equipment For Dual Completion Blinebry Oil and Drinkard Pools

Blinebry Oil and Drinkard Pools		
Blinebry Oil	<del>                                      </del>	Drinkard Oil 13-3/8" csg cem @ 249' w/ 200 sx. Circ. 8-5/8" csg cem @ 2857' w/ 1600 sx. Circ.
		Parallel strings 2-1/16" OD FJ tubing (top 2000 feet of both strings to be internally plastic coated for paraffin control.
OCC Blinebry		
Marker 5630		5645 New Blinebry Gas zone perforations.
		PSI Model S-3 side door with separation sleeve at 5665
		(for annular unloading and controlled gas entry).
		5670 PSI seating nipple with standing valve cage only.
		5675 Baker Model K double grip snap set retrievable packer
		(with full bore for long string & 1.53" bore for short string)
		5705-5790 Approximate gross new Blinebry Oil perforations.
		5775 Approximate bottom short tubing string (with perforations and blank bull plug on bottom).
		6315 PSI Model S-3 side door.
		O)1) ISI Model S=) Side dool:
		6320 Baker Model FA retainer production packer.
Top Drinkard 6443		6448-6500 Approximate new Drinkard perforations.
	<del>,  </del>     <del> </del>	The state of the s
ON ON		6520 PSI Model S-2 Side door.
1: = V.		
] <b>3</b> ₹ 0		6525 Baker Model F retainer production packer
R NUT		(to separate high and low pressure zones in Drinkard).
EXAMINER NUT		6544-6636 Present gross Drinkard perforations.
	<b>√</b>	The second se
AA E E W		6620 PSI seating nipple with standing valve complete.
	₹ <b>₽</b>	6625 Approximate bottom long tubing string
ORE EXAM CONSERVATION PLO EXHIBIT	·	(with perforations and tapped bull plug on bottom)
BEFORE OL CONS		6732 Baker Model D-5 retainer production packer now in well
B 000		(to be blocked with expendable plug)
		6852 5-1/2" 15.5 lb casing cemented with 600 sacks.
	7-3/4" open hole	
	1 11 . 45000	7342 PBTD