

Schlumberger

SIMULTANEOUS

# COMPENSATED NEUTRON- FORMATION DENSITY

COMPANY EXXONWELL NEW MEXICO STATE "AB" #4

FIELD \_\_\_\_\_

COUNTY LEA STATE NEW MEXICOLOCATION 660' FNL & 660' FEL

Other Services:

DLL/GR

API SERIAL NO.

SEC.

TWP.

RANGE

1624537EPermanent Datum: G.L.; Elev.: 3222Log Measured From KB, 13 Ft. Above Perm. DatumDrilling Measured From K.B.Elev.: K.B. 3225'D.F. 3222'G.L. 3222'

Date	<u>13 APR 79</u>					
Run No.	<u>ONE</u>					
Depth-Driller	<u>5204</u>					
Depth-Logger	<u>5298</u>					
Btm. Log Interval	<u>5292</u>					
Top Log Interval	<u>SURF</u>					
Casing-Driller	<u>103 1/4 @ 1110'</u>			@	@	@
Casing-Logger	<u>1103</u>					
Bit Size	<u>7.875</u>					
Type Fluid in Hole	<u>SALT MUD</u>					
Dens.	Visc.	<u>10.1</u> <u>40</u>				
pH	Fluid Loss	<u>9.5</u> <u>10</u> ml		ml	ml	ml
Source of Sample	<u>PLT</u>					
Rm @ Meas. Temp.	<u>.077 @ 60 °F</u>	@	°F	@	°F	@ °F
Rmf @ Meas. Temp.	<u>.06 @ 60 °F</u>	@	°F	@	°F	@ °F
Rmc @ Meas. Temp.	<u>- @ - °F</u>	@	°F	@	°F	@ °F
Source: Rmf	Rmc	<u>C</u> <u>-</u>				
Rm @ BHT	<u>.04 @ 120 °F</u>	@	°F	@	°F	@ °F
Circulation Stopped	<u>-</u>					
Logger on Bottom	<u>1300</u>					
Max. Rec. Temp.	<u>120</u> °F		°F		°F	°F
Equip.	Location	<u>2064 HOBBS</u>				
Recorded By	<u>DANIEL</u>					
Witnessed By Mr.	<u>CLARK</u>					

The well name, location and borehole reference data were furnished by the customer.

FOLD HERE