


Exhibits 1 through 9
Complete Set



- OIL WELL
- ★ P&A OIL WELL
- ▲ INJECTOR
- ✱ GAS WELL
- ✱ P&A GAS WELL
- ✱ OIL & GAS WELL
- ✱ P&A OIL & GAS WELL
- ◇ O&A
- LOCATION


BEFORE EXAMINER CATANACH
OIL CONSERVATION DIVISION


TEXACO EXHIBIT NO. 1

CASE NO. 10572 AND 10573



TEXACO INC.		
HOBBS	NH	U.S.A.
RHODES YATES WATERFLOOD 80 ACRE 5 SPOT PATTERN LEA COUNTY, NEW MEXICO		
SCALE 1" = 1000'	C. E. SADLER	22-APR-61





LEGEND

- OIL WELL
- ✱ P&A OIL WELL
- ▲ INJECTOR
- ✱ GAS WELL
- ✱ P&A GAS WELL
- ✱ OIL & GAS WELL
- ✱ P&A OIL & GAS WELL
- ◇ D&A
- LOCATION

BEFORE EXAMINER CATALOG
OIL CONSERVATION DIVISION

TEXACO EXHIBIT NO. 3

CASE NO. 10572 AND 10573


TEXACO INC.

HOBBS NM

U.S.A.

RHODES YATES WATERFLOOD AREA
STRUCTURE TOP OF YATES
LEA COUNTY, NEW MEXICO

Scale 1"=1000' C. E. SADLER 28-MAR-81



PHASE 1 (1992)

- OIL WELL
- ▲ P&A OIL WELL
- △ INJECTOR
- ★ GAS WELL
- ✱ P&A GAS WELL
- ✱ OIL & GAS WELL
- ✱ P&A OIL & GAS WELL
- ◇ D&A
- LOCATION

● INFILL DRLG.

● CONVERSION

● INJ. MODIFICATION


BEFORE EXAMINER CATANACH
OIL CONSERVATION DIVISION

TEXACO EXHIBIT NO. 4

CASE NO. 10572 AND 10573

STATUTE MILES 0 1 2 3 4 5
FEET 0 1000 2000 3000 4000 5000

TEXACO INC.		
HOBBS	NM	U.S.A.
RHODES YATES WATERFLOOD LEA COUNTY, NEW MEXICO		
Scale 1"=1000'	Drawn C. E. SODLER	Date 26-MAR-91



LEGEND

- OIL WELL
- P&A OIL WELL
- ▲ INJECTOR
- ★ GAS WELL
- ★ P&A GAS WELL
- ★ OIL & GAS WELL
- ★ P&A OIL & GAS WELL
- ◇ D&A
- LOCATION

BEFORE EXAMINER CATANACH
OIL CONSERVATION DIVISION

TEXACO EXHIBIT NO. 5

CASE NO. 10572 AND 10573

FEET 0 1000 2000 3000 4000 5000
STATUTE MILES 0 .1 .2 .3 .4 .5 .6 .7 .8 .9 1.0 STATUTE MILES

TEXACO INC.

HOBBS

NH

U.S.A.

RHODES YATES WATERFLOOD
40 ACRE LINE DRIVE
WITH LEASE LINE WELLS
LEA COUNTY, NEW MEXICO

11/1/1988

C. E. BRIDLER

2-DEC-91



August 25, 1992

New Mexico Oil Conservation Commission
P. O. Box 2088
Santa Fe, New Mexico 87504-2088

Attention: Ben Stone

Re: Application for Expansion of Waterflood;
Orders R-2748/48A, 3889, 4521/22 & WFX-454
Texaco Exploration and Production Inc.
Rhodes Yates Unit, Rhodes B Fed NCT-1 - Rhodes Yates 7R
T-26-S, R-37-E, Lea County, New Mexico

Gentlemen:

Texaco Exploration and Production Inc. respectfully requests administrative approval for the expansion of the Rhodes Yates Unit and Rhodes B Fed NCT-1 (CO-OP). Two oil wells in the Unit and two oil wells on the Rhodes B NCT-1 will be converted to water injection. This work will help maintain reservoir pressure and recover additional oil reserves that would otherwise be left in place. This work will be done in conjunction with a workover program to develop additional Yates reserves. Five infill oil wells will also be drilled.

Texaco E&P Inc. respectfully requests that the Rhodes Yates Unit and the Rhodes B NCT-1 be expanded to include the conversion of four producing wells to water injection. Administration approval is requested so that the necessary operations can be advanced in a prudent manner.

Yours very truly,

Terry L. Frazier
Hobbs Area Manager

TLF:rtm

attachments

BEFORE EXAMINER CATANACH	
OIL CONSERVATION DIVISION	
TEXACO	EXHIBIT NO. 6
CASE NO. 10572 AND 10573	

APPLICATION FOR AUTHORIZATION TO INJECT

I. Purpose: ☒ Secondary Recovery ☐ Pressure Maintenance ☐ Disposal ☐ Storage
Application qualifies for administrative approval? ☐ yes ☐ no

II. Operator: Texaco Exploration & Production Inc.

Address: P.O. Box 730, Hobbs, New Mexico 88240

Contact party: Terry L. Frazier, Area Manager Phone: 505 - 397 - 0411

III. Well data: Complete the data required on the reverse side of this form for each well proposed for injection. Additional sheets may be attached if necessary.

IV. Is this an expansion of an existing project? ☒ yes ☐ no R-2748, 2748 A, 3889,
If yes, give the Division order number authorizing the project 4521, WFX-454, R-4522

V. Attach a map that identifies all wells and leases within two miles of any proposed injection well with a one-half mile radius circle drawn around each proposed injection well. This circle identifies the well's area of review.

* VI. Attach a tabulation of data on all wells of public record within the area of review which penetrate the proposed injection zone. Such data shall include a description of each well's type, construction, date drilled, location, depth, record of completion, and a schematic of any plugged well illustrating all plugging detail.

VII. Attach data on the proposed operation, including:

1. Proposed average and maximum daily rate and volume of fluids to be injected;
2. Whether the system is open or closed;
3. Proposed average and maximum injection pressure;
4. Sources and an appropriate analysis of injection fluid and compatibility with the receiving formation if other than reinjected produced water; and
5. If injection is for disposal purposes into a zone not productive of oil or gas at or within one mile of the proposed well, attach a chemical analysis of the disposal zone formation water (may be measured or inferred from existing literature, studies, nearby wells, etc.).

*VIII. Attach appropriate geological data on the injection zone including appropriate lithologic detail, geological name, thickness, and depth. Give the geologic name, and depth to bottom of all underground sources of drinking water (aquifers containing waters with total dissolved solids concentrations of 10,000 mg/l or less) overlying the proposed injection zone as well as any such source known to be immediately underlying the injection interval.

IX. Describe the proposed stimulation program, if any.

* X. Attach appropriate logging and test data on the well. (If well logs have been filed with the Division they need not be resubmitted.)

* XI. Attach a chemical analysis of fresh water from two or more fresh water wells (if available and producing) within one mile of any injection or disposal well showing location of wells and dates samples were taken.

XII. Applicants for disposal wells must make an affirmative statement that they have examined available geologic and engineering data and find no evidence of open faults or any other hydrologic connection between the disposal zone and any underground source of drinking water.

XIII. Applicants must complete the "Proof of Notice" section on the reverse side of this form.

XIV. Certification

I hereby certify that the information submitted with this application is true and correct to the best of my knowledge and belief.

Name: Terry L. Frazier Title Area Manager

Signature: *Terry L. Frazier* Date: 8/25/92

* If the information required under Sections VI, VIII, X, and XI above has been previously submitted, it need not be duplicated and resubmitted. Please show the date and circumstance of the earlier submittal. R-2748, 6-29-74; 2748A, 12-3-69; 3889, 12-2-69; 4521, 5-17-73;

R-4522, 5-17-73 and WFX-454, 8-2-77, Examiner Hearings and administrative applications.

DISTRIBUTION: Original and one copy to Santa Fe with one copy to the appropriate Division

III. WELL DATA

- A. The following well data must be submitted for each injection well covered by this application. The data must be both in tabular and schematic form and shall include:

- (1) Lease name; Well No.; location by Section, Township, and Range; and footage location within the section.
- (2) Each casing string used with its size, setting depth, sacks of cement used, hole size, top of cement, and how such top was determined.
- (3) A description of the tubing to be used including its size, lining material, and setting depth.
- (4) The name, model, and setting depth of the packer used or a description of any other seal system or assembly used.

Division District offices have supplies of Well Data Sheets which may be used or which may be used as models for this purpose. Applicants for several identical wells may submit a "typical data sheet" rather than submitting the data for each well.

- B. The following must be submitted for each injection well covered by this application. All items must be addressed for the initial well. Responses for additional wells need be shown only when different. Information shown on schematics need not be repeated.

- (1) The name of the injection formation and, if applicable, the field or pool name.
- (2) The injection interval and whether it is perforated or open-hole.
- (3) State if the well was drilled for injection or, if not, the original purpose of the well.
- (4) Give the depths of any other perforated intervals and detail on the sacks of cement or bridge plugs used to seal off such perforations.
- (5) Give the depth to and name of the next higher and next lower oil or gas zone in the area of the well, if any.

XIV. PROOF OF NOTICE

All applicants must furnish proof that a copy of the application has been furnished, by certified or registered mail, to the owner of the surface of the land on which the well is to be located and to each leasehold operator within one-half mile of the well location.

Where an application is subject to administrative approval, a proof of publication must be submitted. Such proof shall consist of a copy of the legal advertisement which was published in the county in which the well is located. The contents of such advertisement must include:

- (1) The name, address, phone number, and contact party for the applicant;
- (2) the intended purpose of the injection well; with the exact location of single wells or the section, township, and range location of multiple wells;
- (3) the formation name and depth with expected maximum injection rates and pressures; and
- (4) a notation that interested parties must file objections or requests for hearing with the Oil Conservation Division, P. O. Box 2088, Santa Fe, New Mexico 87501 within 15 days.

NO ACTION WILL BE TAKEN ON THE APPLICATION UNTIL PROPER PROOF OF NOTICE HAS BEEN SUBMITTED.

NOTICE: Surface owners or offset operators must file any objections or requests for hearing of administrative applications within 15 days from the date this application was mailed to them.

NEW MEXICO OIL CONSERVATION DIVISION - Form C-108, cont'd

Summary of Details for Conversion of Wells to Water Injection

Rhodes Yates Unit - Rhodes Yates Seven Rivers8 - Unit Letter E, 1875 FNL & 765 FWL, Section 27, T26S, R37E13 - Unit Letter M, 660 FSL & 660 FWL, Section 27, T26S, R37EW.H. Rhodes B Fed NCT-1 - Rhodes Yates Seven Rivers6 - Unit Letter I, 1980 FSL & 660 FEL, Section 27, T26S, R37E13 - Unit Letter O, 990 FSL & 1650 FEL, Section 27, T26S, R37E

III. All pertinent well data is included on the well schematic sheets. Additional wells will eventually be converted as part of later phases of infill drilling. A braden head survey was run in April, 1991, on all unit and Co-op wells within the area of review. Survey sheets for the referenced wells are attached.

V. A Lease map of wells within a 2 mile radius is attached. A 1/2 mile radius circle is drawn around the subject wells.

VI. Data for sections VI, VIII, X and XI have been previously submitted under NMOCD Order R-2748 dated 6/29/64, R-2748A on 12/3/69, R-3889 on 12/2/69, R-4521 and 4522 on 5/17/73. Additional information was supplied on July 18, 1977 as part of the 1978 waterflood expansion application (WFX-454).

Rhodes Yates Unit #13 was drilled in 1978 and was the last well drilled in the area of review. Texaco will drill 5 infill wells in the last quarter of 1992. Two will be in the Co-op and three will be on the unit. The full plan of development has been discussed with the NMOCD in Hobbs and the BLM in Roswell, and both have given their approval. Construction details for the five infill wells are attached. However, the applications to drill have not been filed yet.

Four wells have been plugged within the leasehold area. Three were plugged before 1960 and information on these has previously been submitted in prior applications. Meridian Oil Inc's State UTP #1 was plugged 3-27-92 and a final plugging report is attached. Texaco E&P Inc's W.H. Rhodes B NCT-1 #2 will be plugged as soon as partner and Federal approval have been granted. The intent to plug is also attached.


NEW MEXICO OIL CONSERVATION DIVISION - Form C-108, cont'd

Summary of Details for Conversion of Wells to Injection Status

Rhodes Yates Unit, Rhodes B NCT-1 - Rhodes Yates Seven Rivers

- VII. Proposed average daily injection rate per well is 500 Bbls per day and anticipated maximum rate is 750 Bbls per day. Maximum pressure will not exceed 2000 psi system working pressure. The average injection pressure will not exceed 600 psi until a step rate test establishes a higher limit. The system will be closed.
- IX. As part of the overall infill drilling project, a workover program will be aimed at developing the middle Yates zone. Both producers and injectors will have some upper pay zones opened and stimulated. Net additional pay will average about 60' and will be hydraulically fracture treated. The injection well work will be centered around diverting a substantial part of the water into the middle zones that have not been developed across the leasehold.
- XII. Based on current geological and engineering data, there is no evidence of natural or artificially induced open faults within the unitized interval or above. There is no communication from the injection zone to any subsurface source of drinking water.
- XIII.A notarized copy of a "Proof of Notice" is included.

LEA COUNTY, NEW MEXICO




1" = 3000'

Proposed Injection Conversion

OPERATOR: Texaco Exploration & Production Inc. Lease: Rhodes Yates Unit #8
 FOOTAGE LOCATION: 1875 FNL X 765 FWL Sec./Twn/Rng: Unit E, Sec 27, T-26-S, R-37-E
Former Amerada Petroleum Corp. State 'AJ' #2 Lea County, New Mexico

SCHEMATIC



TABULAR DATA

Surface Casing: Set at 679'
 Size 9-5/8, 36# Cemented with 150 sx.
 TOC 114 ' determined by calculated
 Hole Size 12-1/4" Comp. Date 8-27-43
Intermediate casing: Set at _____
 Size NONE Cemented with _____ sx.
 TOC _____ ' determined by _____
 Hole Size _____
Production Casing: Set at 3126'
 Size 7", 24# Cemented with 250 sx.
 TOC 1454 ' determined by calculated
 Hole Size 8-3/4"

Tops:

Salt 1307'-2810'
 Yates 2955'
 Seven Rivers NR

Injection Interval:

3092' to 3320' through: OH, Perforations
 Tubing: 2-3/8", 4.7#, J-55, IPC 2000# WP

Proposed Injection Conversion

FOOTAGE LOCATION: 660 FSL X 660 FWL **Sec./Twn/Rng:** Unit M, Sec 27, T-26-S, R-37-E

Lea County, New Mexico

SCHEMATIC

TABULAR DATA

Surface Casing: Set at 654'

Size 8-5/8", 24# Cemented with 700 sx.

TOC surface , determined by circulated

Hole Size 12-1/4" Comp. Date 2-15-78

Intermediate casing: Set at _____

Size NONE Cemented with sx.

TOC _____, determined by _____

Hole Size

Production Casing: Set at 3450'

Size 5-1/2", 14# Cemented with 950 sx.


TOC surface, determined by circulated

Hole Size 7-7/8"

Injection Interval:

3167 , to 3349 , through: Perforations

Tubing: 2-3/8", 4.7#, J-55, IPC 2000# WP




Top:

Salt	1215'-2878'
Yates	3045'
Seven Rivers	3362'

Proposed Injection Conversion

OPERATOR: Texaco Exploration & Production Inc. Lease: Rhodes B Fed NCT-1 #6
 FOOTAGE LOCATION: 1980 FSL X 660 FEL Sec./Twn/Rng: Unit I, Sec 27, T-26-S, R-37-E
Former Texaco Rhodes 'B' #6 Lea County, New Mexico

SCHEMATIC



TABULAR DATA

Surface Casing: Set at 1212'
 Size 8-5/8, 32# Cemented with 200 sx.
 TOC 40 ' determined by calculated
 Hole Size 11" Comp. Date 8-11-44
Intermediate casing: Set at _____
 Size NONE Cemented with _____ sx.
 TOC _____ ' determined by _____
 Hole Size (Perfs to be added: 3048'-3150')
Production Casing: Set at 3162'
 Size 5-1/2", 14# Cemented with 300 sx.
 TOC 1660 ' determined by calculated
 Hole Size 7-1/2", 4-3/4" open hole

Injection Interval:

3048' to 3300' through: OH, Perforations
 Tubing: 2-3/8", 4.7#, J-55, IPC 2000# WP

Tops:

Salt 1262'-2780'
 Yates 2922'
 Seven Rivers NR

PO-108
(8/92)

Proposed Injection Conversion

OPERATOR: Texaco Exploration & Production Inc. Lease: Rhodes B Fed NCT-1 #13

FOOTAGE LOCATION: 990 FSL X 1650 FEL Sec./Twn/Rng: Unit O, Sec 27, T-26-S, R-37-E

Former Texas Company W. H. Rhodes 'B' #13 Lea County, New Mexico

SCHEMATIC

TABULAR DATA

Surface Casing: Set at 1212'

Size 8-5/8, 28# Cemented with 350 sx.

TOC surface ' determined by calculated

Hole Size 11" Comp. Date 7-26-45

Intermediate casing: Set at

Size NONE Cemented with sx.

TOC ' determined by

Hole Size (Perfs to be added; 3050'-3150')

Production Casing: Set at 3167'

Size 5-1/2", 14# Cemented with 300 sx.


TOC 1530 ' determined by calculated

Hole Size 7-7/8", 4-3/4" open hole

Injection Interval:

3050' to 3327' through: OH, Perforations

Tubing: 2-3/8", 4.7#, J-55, IPC 2000# WP



Tops:

Salt 1255'-2828'
Yates 2950'
Seven Rivers NR

P 369 428 057



**Receipt for
Certified Mail**

No Insurance Coverage Provided

Sea Sand Oil Co.
P.O. Box 101777
Ft. Worth, Texas 76185

PS Form 3800, June 1991

Postage	\$.75
Certified Fee	1.00
Special Delivery Fee	
Restricted Delivery Fee	
Return Receipt Showing to Whom & Date Delivered	1.00
Return Receipt Showing to Whom, Date, and Addressee's Address	
TOTAL Postage and Fees	\$ 2.75
Postmark or Date	AUG 27 1992 USPO

P 365 085 108

RECEIPT FOR CERTIFIED MAIL

NO INSURANCE COVERAGE PROVIDED
NOT FOR INTERNATIONAL MAIL

Mack Energy Corp.
P.O. Box 276
Artesia, NM 88211

PS Form 3800, June 1985

Postage	\$.75
Certified Fee	1.00
Special Delivery Fee	1.00
Restricted Delivery Fee	
Return Receipt showing to whom and Date Delivered	1.00
Return Receipt showing to whom, Date, and Addressee's Address	
TOTAL Postage and Fees	\$ 2.75
Postmark or Date	AUG 27 1992 USPO

P 365 085 107

RECEIPT FOR CERTIFIED MAIL

NO INSURANCE COVERAGE PROVIDED
NOT FOR INTERNATIONAL MAIL
(See Reverse)

U.S.G.P.O. 1985-234-555

PS Form 3800, June 1985

Sent to	Tom & Evelyn Linclay
Street and No.	802 S. Main
P.O. State and ZIP Code	Midland, TX 79701
Postage	\$.75
Certified Fee	1.00
Special Delivery Fee	
Restricted Delivery Fee	
Return Receipt showing to whom and Date Delivered	1.00
Return Receipt showing to whom, Date, and Addressee's Address	
TOTAL Postage and Fees	\$ 2.75
Postmark or Date	AUG 27 1992 USPO

P 369 428 058



**Receipt for
Certified Mail**

No Insurance Coverage Provided

Doyle Hartman
P.O. Box 10426
Midland, Texas 79702

PS Form 3800, June 1991

Postage	\$.75
Certified Fee	1.00
Special Delivery Fee	
Restricted Delivery Fee	
Return Receipt Showing to Whom & Date Delivered	1.00
Return Receipt Showing to Whom, Date, and Addressee's Address	
TOTAL Postage and Fees	\$ 2.75
Postmark or Date	AUG 27 1992 USPO

P 369 428 059


**Receipt for
Certified Mail**

No Insurance Coverage Provided

Meridian Oil, Inc
P.O. Box 51810
Midland, Texas 79710

Postage	\$ 1.75
Certified Fee	1.00
Special Delivery Fee	
Restricted Delivery Fee	
Return Receipt Showing to Whom & Date Delivered	1.00
Return Receipt Showing to Whom, Date, and Addressee's Address	
TOTAL Postage & Fees	\$ 2.75
Postmark or Date	

PS Form 3800, June 1991

P 365 085 111

RECEIPT FOR CERTIFIED MAIL

 NO INSURANCE COVERAGE PROVIDED
NOT FOR INTERNATIONAL MAIL

Koch Industries
P.O. Box 2256
Wichita, Kansas 67201

Postage	\$ 1.75
Certified Fee	1.00
Special Delivery Fee	
Restricted Delivery Fee	
Return Receipt showing to whom and Date Delivered	1.00
Return Receipt showing to whom, Date, and Address of Delivery	
TOTAL Postage and Fees	\$ 2.75
Postmark or Date	

PS Form 3800, June 1985

P 369 428 082


**Receipt for
Certified Mail**

No Insurance Coverage Provided

Smith & Marrs, Inc.
1110 N Big Spring
Midland, Texas 79701

Postage	\$ 1.75
Certified Fee	1.00
Special Delivery Fee	
Restricted Delivery Fee	
Return Receipt Showing to Whom & Date Delivered	1.00
Return Receipt Showing to Whom, Date, and Addressee's Address	
TOTAL Postage & Fees	\$ 2.75
Postmark or Date	

PS Form 3800, June 1991

P 369 428 056


**Receipt for
Certified Mail**


No Insurance Coverage Provided

Marathon Oil Co.
P.O. Box 552
Midland, Texas 79702

Postage	\$ 1.75
Certified Fee	1.00
Special Delivery Fee	
Restricted Delivery Fee	
Return Receipt Showing to Whom & Date Delivered	1.00
Return Receipt Showing to Whom, Date, and Addressee's Address	
TOTAL Postage & Fees	\$ 2.75
Postmark or Date	

PS Form 3800, June 1991

W.H. RHODES "A" FEDERAL # 3



BEFORE EXAMINER CATANACH
OIL CONSERVATION DIVISION
TEXACO EXHIBIT NO. 7
PAGE NO. 10572 AND 10573

THIS WELL WAS SHOT WITH
170 Gals. Nitro 2-19-1944.

F.M.R.
1-25-77

CHO/1-10-81

LEASE: W.H. RHODES 'R' NCT 1

WELL NO. 1

1650' FNL, 1650' FEL

Unit G, Sec. 27, 26-S, 37-E

Rhodes B Fed.

NCT-1 #1

8" 8 RD

KR 15'

13" 40' GR SET AT 196'
CMT CIRC. 180 SX

95/8" 36" GR SET @ 1910'
CMT CIRC. 450 SX

TOC at surf. assuming
12 1/2" hole and 79% fill

REF 2 JS @ 1580' SD w/ 600 SX CMT
7-11-79 CIRC.

7" 24" GR SET @ 3071

TOC @ 2144 BY PMAU 106.

JULY 79 REF @ 1580' SD w/

600 SX CMT CIRC.

JULY 79 REF @ 2580' SD w/

600 SX TOC 1784 BY TEMA

REF 2 JS @ 2580' SD w/ 600 SX CMT
7-10-79 TOC 1784' BY TEMA

CIBP set at 2975'; 4-05-90 : TA

3071

3071

RHODES YARDS

ASSUMED SHOT HOLE

CLEAN OUT TO
3160 8/16/83

6 1/8" .65 BIT; 4800 x 1 5/16 ID x 1.44 LONG
BH SUB: 3800 x 1 3/4 ID x 1.23 LONG x 0.016

P870 3280
TD 3280

3280

LEGAL 1650' NL 1650' EL

3280

SECT 27 26-S 37-E G

Date 2-19-81

KDB = 11.5'

Casing Size 8 5/8
Weight 28
Grade H-40
Set @ 1197
Hole Size 11"
Cement 350 SX - CEMENT
CIRCULATED

Pull 9 wire down hole running equipment.
Set Kelly Casing @ 3000' Run 100' in hole
Press. Test Casing to 5000' depth. Circulate hole
with filtered water 1/4 down 100'. (200)

3-24-84

3041

Casing Size 5 1/2
Weight 14
Grade J-55, H-40
Set @ 3128
Hole Size 7 7/8
Cement 300 SX

CEMENT TOP CALL @ 1735'

GRAVEL PACKING

Hole Size when drilled 4 3/4

Shot with 120 grs. NITRO

LINER 4" 11.38" 3-4" slots


SET @ 3255

TOP @ 3041

PBTD @ 3255
TO @ 3325


W. H. RHODES "B" (NCT-1) #14

KOB
T
10



F.M.R

8-8-79




WELL DATA SHEET

OPERATOR: Texaco Exploration & Production Inc. Lease: W.H. Rhodes B Fed NCT-2 #3

FOOTAGE LOCATION: 1980 FSL X 660 FEL Sec./Twn/Rng: Unit I, Sec 28, T-26-S, R-37-E

Lea County, New Mexico

SCHEMATIC



TABULAR DATA

Surface Casing: Set at 608'

Size 8-5/8, 32# Cemented with 200 sx.

TOC surface ' determined by circulation

Hole Size ? Comp. Date 6-21-43

Intermediate casing: Set at

Size NONE Cemented with sx.

TOC ' determined by

Hole Size

Production Casing: Set at 3185'

Size 5-1/2", 15# Cemented with 300 sx.

TOC 1066 ' determined by calculation

Hole Size 6-3/4" ? (assumed 50% fill)

Open Hole Interval:

3185 ' to 3300 ' Size 4-3/4", nitro shot

4-1/2", 16.6# slotted liner 3195'- 3330'

Estimated Tops:

Salt 1200'-2850'

Yates 3014'

Seven Rivers 3340'

Queen NR

W.H. Rhodes' B" (NET-2) #4

14'

12 1/4" HOLE

7 7/8" HOLE

8 5/8" 24" Csg. set @ 655'
500 SX - Cmt CIRC.

TOC at 1150'

15' 560 Ht. MA-SN - 102 JTS 2 7/8" BHA TBg. LAID @ 3204' (2 1/2" x 1 1/2" x 20' pump w/ 8' 9 1/8" 1 3/16" Rcm)

Top-3289'

YATES

Bottom-3318'

RBP 4+3282

Perf: w/ 1 SPF: 3122, 23, 32, 37, 59'
44, 59, 69, 71, 74, 76, 78, 80, 84, 90'
95, 98, 3201, 03, 11, 18, 25, 31, 35, 37, 41,
Perf w/ 2 JSP: @ 3289-3294 - 53, 59, 65'
3300-3307-3312-3318'
(12 Holes)

P8TD 3433'

TD 3460'

5 1/2" 14" K55 Csg set @ 3460'
750 SX - Top Cmt @ 1150' by Temp Survey

F.M.R

2-21-78


RTM

WELL NAME: SHAW'S FAIRY LAULIE
 - WELL No 4
 DATE: 12-28-83
 DATE OF COMP: 12-16-76

31-7/8 90-7/8

- 1- 1 3/4" DE MUD ANCHOR 278
 - 2- 2 7/8" SA
 - 3- 1 1/2" JTS 2 7/8" J-SS TOL
- CHINA MA @ 2131'

KINGS VATES



8 3/4" 28.5" X-SS JTC SA 670'
 CEMENT LOSS CIRC 12 1/4" H.S

REL 1300' BY TEMP

5 1/2" 14" X-SS SA 3350'
 CEMENT LOSS CIRC 12 1/4" H.S

NOTE: INITIAL COMP 3215 TO 3246
 NEW PADS 3246 TO 3312 3740 LBS - JSPF
 SET CMT RT @ 3246 138 WOULD NOT TEST
 SET 63 DRILL CMT RT @ 3176 502 ALL PADS W/
 200SS CMT. REL 3116 DRILL CMT TO 3176
 PADS W/ 1.150E @ 3116, 1.150 32.41, 46.52, 62
 (12182)

NEW PADS: 3116, 18.30, 1.150E
 32.41, 46.52, 62, 1.150E
 OLD PADS 3246 OFF 2 JSPF 3246 TO 3272 3740 LBS
 3215 TO 3246

TD 3350'

WELL NE4 NE4 28 285 376 WLA

WUT INFO:


LAU (LMAU)

SCHEMATIC

Seven Rivers na
Queen na

WELL NAME & No. Rhodes 1/4 & Unit # 11

DATE _____



PBTD 3327'
TD 3327'


WELL DATA SHEET

OPERATOR: Anderson-Pritchard Oil Corporation Lease: State 28 "A" #2

FOOTAGE LOCATION: 1980 FNL X 1980 FEL Sec./Twn/Rng: Unit G, Sec 28, T-26-S, R-37-E

Drilled and abandoned August, 1943. Lea County, New Mexico

SCHEMATIC



TABULAR DATA

Surface Casing: Set at 587'

Size 8-5/8", 28# Cemented with 188 sx.

TOC surface ' determined by calculation

Hole Size 11" Comp. Date 8-11-43

Intermediate casing: Set at

Size NONE Cemented with sx.

TOC ' determined by

Hole Size Hole filled with 10-1/2# mud

Production Casing: Set at 3157'

Size 5-1/2", 15# Cemented with 650 sx.

TOC 2169 ' determined by free point

Hole Size 7-7/8"

Open Hole Interval:

3157' to 3350' size: 4-3/4" ?

Nitro shot 70 qts L.N.G., 3247'-3284'.

Tops:

Salt 1285'-2840'
Tansil 2840'
Yates 2988'
Seven Rivers 3285'


WELL DATA SHEET

OPERATOR: Sea Sand Oil Co. Lease: Wills Federal #8

FOOTAGE LOCATION: 330 FNL X 330 FEL Sec./Twn/Rng: Unit A, Sec 33, T-26-S, R-37-E

Lea County, New Mexico

SCHEMATIC



TABULAR DATA

Surface Casing: Set at 84'

Size 8-5/8", 32# Cemented with 40 sx.

TOC surface ' determined by circulation

Hole Size 12-1/4" Comp. Date 4-12-88

Intermediate casing: Set at

Size NONE Cemented with sx.

TOC ' determined by

Hole Size

Production Casing: Set at 3440'

Size 5-1/2", 15.5# Cemented with 150 sx.

TOC 2350' ' determined by calculation

Hole Size 7-1/4", assumed 75% fill

Completion Interval:

3130' to 3255' : 4 spf, 100 perforations

Tops:

Salt not recorded

Tansil


Yates 3130'

Seven Rivers 3235'

WELL DATA SHEET

OPERATOR: Marathon Oil Co. Lease: Wills Federal #1
 FOOTAGE LOCATION: 330 FNL X 330 FWL Sec./Twn/Rng: Unit D, Sec 34, T-26-S, R-37-E
Temporarily abandoned 3-14-84; casing tested to 500 psi. Lea County, New Mexico

SCHEMATIC



TABULAR DATA
Surface Casing: Set at 1198'
 Size 8-5/8", 24# Cemented with 525 sx.
 TOC surface ' determined by circulation
 Hole Size 11" Comp. Date 3-12-84
Intermediate casing: Set at _____
 Size NONE Cemented with _____ sx.
 TOC _____ ' determined by _____
 Hole Size _____
Production Casing: Set at 3500'
 Size 5-1/2", 15.5# Cemented with 1100 sx.
 TOC surface ' determined by calculation
 Hole Size 7-7/8", assumed 47% fill

Completion Interval:

3221' to 3367' : 1 spf, 42 perforations


Tops:

Salt not recorded
 Tansil
 Yates 3060'
 Seven Rivers 3408'

WELL DATA SHEET

OPERATOR: Koch Exploration Co. Lease: Mary E Wills Fed A #3
 FOOTAGE LOCATION: 660 FNL X 660 FEL Sec./Twn/Rng: Unit A, Sec 34, T-26-S, R-37-E
 Former operators: The Ohio Oil Company, Rock Island O&R Lea County, New Mexico

SCHEMATIC



TABULAR DATA

Surface Casing: Set at 1233'
 Size 8-5/8", 30# Cemented with 350 sx.
 TOC surface , determined by calculation
 Hole Size 11" Comp. Date 4-27-45
 Intermediate casing: Set at _____
 Size NONE Cemented with _____sx.
 TOC _____ , determined by _____
 Hole Size _____
 Production Casing: Set at 3165'
 Size 5-1/2", 17# Cemented with 325 sx.
 TOC 950' , determined by calculation
 Hole Size 7-3/8" , assumed 75% fill

Open hole interval:

3165' to 3337' : 4-3/4" ? ns
Shot with 80 Qts Nitro, 3280'-3321'

Tops:

Salt 1468'-2860'
 Tansil
 Yates 2990'
 Seven Rivers na

PO-113
(5/91)

WELL DATA SHEET

OPERATOR: Koch Exploration Co. Lease: Mary E Wills Fed A #9

FOOTAGE LOCATION: 1135 FSL X 20 FWL Sec./Twn/Rng: Unit D, Sec 35, T-26-S, R-37-E

Former Wood River O&R, plugged 8-27-81: collapsed casing. Lea County, New Mexico

SCHEMATIC

TABULAR DATA

Surface Casing: Set at 608'

Size 8-5/8", 24# Cemented with 300 sx.

TOC surface ' determined by circulation

Hole Size 11" ? Comp. Date 10-04-59

Intermediate casing: Set at

Size NONE Cemented with sx.

TOC ' determined by

Hole Size

Production Casing: Set at 3369'

Size 5-1/2", 14# Cemented with 150 sx.


TOC 2570' ' determined by calculation

Hole Size 7-7/8" ?, assumed 75% fill

Completion Interval:

3290' to 3342' : ? spf, 88 perforations

Drilled as water injection well; R-1352



Tops:

Salt 1215'-2891'
Tansil 2844'
Yates 2996'
Seven Rivers 3271'


WELL DATA SHEET

OPERATOR: Koch Exploration Co. Lease: Mary E Wills Fed A #10

FOOTAGE LOCATION: 1135 FSL X 20 FWL Sec./Twn/Rng: Unit D, Sec 35, T-26-S, R-37-E

Former Wood River O&R, plugged 9-2-81 - collapsed casing. Lea County, New Mexico

SCHEMATIC



TABULAR DATA

Surface Casing: Set at 609'

Size 8-5/8", 24# Cemented with 275 sx.

TOC surface ' determined by circulation

Hole Size 11" ? Comp. Date 4-08-60

Intermediate casing: Set at

Size NONE Cemented with sx.

TOC ' determined by

Hole Size

Production Casing: Set at 3354'

Size 5-1/2", 14# Cemented with 150 sx.

TOC 2560' ' determined by calculation

Hole Size 7-7/8" ? , assumed 75% fill

Completion Interval:

3260' to 3326' : ? spf, 104 perforations

Drilled as water injection well; R-1352

Tops:

Salt 1205'-2818'

Tansil

Yates 2974'

Seven Rivers 3250'

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: September 30, 1990

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
Texaco Exploration & Production Inc.

3. Address and Telephone No.
P.O. Box 730, Hobbs, NM 88241-0730 (505) 393-7191

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
2970 FNL, 2310 FEL
Unit J, Sec. 27, T-26-S, R-37-E

5. Lease Designation and Serial No.
LC-030174 b

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.
W.H. Rhodes B NCT-1 #2

9. API Well No.
30 - 025 - 12060

10. Field and Pool, or Exploratory Area
Rhodes Yates

11. County or Parish, State
Lea County, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION	
☒ Notice of Intent	☒ Abandonment	☐ Change of Plans
☐ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment Notice	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut-Off
	☐ Altering Casing	☐ Conversion to Injection
	☐ Other	

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- 1) Inform BLM 24 hours prior to commencement of plugging.
- 2) MIRU, Install BOP. Run bit and casing scraper and clean hole to TD. T. CIBP. POH. Run 5-1/2" packer and test CIBP for possible leak. POH.
- 3) If necessary, set 2nd CIBP by wireline. Perf 2 squeeze holes at 1284'
- 4) TIH w/ work string and tag CIBP. Load hole with salt gel mud; 10# bri and 25# gel/ Bbl. Pump 100', 15 sx class 'C' cement on top of CIBP.
- 5) Establish circulation through squeeze perfs and circulate annulus with 110 sx class 'C'. Adjust volumes if needed. Fill casing from 1284'-110 with 24 sx cement. WOC. Tag plug. Spot 12 sx from 100'-surface.
- 6) POH. Fill annulus and casing from surface with 1" tubing if necessary
- 7) Cut off wellhead and install marker. Clean location.
- 8) Restore surface as per Federal requirements.

14. I hereby certify that the foregoing is true and correct

DEPT. OF THE INTERIOR
OIL CONSERVATION DIVISION

TEXACO EXHIBIT NO. 8

CASE NO. 10572 AND 10573

Production Engineer

Date 8-20-92

Date _____

Do not make to any department or agency of the United States any false, fictitious or fraudulent statement


Attention on Reverse Side

WELL DATA SHEET

PO-113
(5/91)

OPERATOR: Texaco Exploration & Production Inc. Lease: W.H. Rhodes B Fed NCT-1 #2
 FOOTAGE LOCATION: 2970 FNL X 2310 FEL Sec./Twn/Rng: Unit J, Sec 27, T-26-S, R-37-E
Classified TA on 4-12-84; CIBP set at 3000'. Lea County, New Mexico

SCHEMATIC



Tops:

Salt 1155'-2850'
 Yates 2960'
 Seven Rivers 3183'
 Queen NR

TABULAR DATA


Surface Casing: Set at 1234'
 Size 7-5/8, 26.4# Cemented with 450 sx.
 TOC surface ' determined by circulation
 Hole Size 9-5/8" Comp. Date 8-23-40
 Intermediate casing: Set at
 Size NONE Cemented with sx.
 TOC ' determined by
 Hole Size
 Production Casing: Set at 3077'
 Size 5-1/2", 14# Cemented with 125 sx.
 TOC 2936 ' determined by Temp log
 Hole Size 6-3/4"
 Open Hole Interval:
 3077 ' to 3275 ' Size ???
 Nitro Shot 500 Ots SOWE #1, 3130' - 3275'

PLUG AND ABANDON DATA

PO-113
(5/91)

OPERATOR: Texaco Exploration & Production Inc. Lease: W.H. Rhodes B Fed NCT-1 #2
 FOOTAGE LOCATION: 2970 FNL X 2310 FEL Sec./Twn/Rng: Unit J, Sec 27, T-26-S, R-37-E
Failed MIT on 4-25-91, 70 psig on casing. Lea County, New Mexico

SCHEMATIC



PLUGGING DATA

Surface Plug:
 Size 100'-surf. Cemented with 12 sx.
 Squeeze annulus with 110 sx to surface.
 Class 'C' Cement, 1.32 cu ft/ sx
 Intermediate Plug(s):
 Size 1284'-1105' Cemented with 24 sx.
 Class 'C' cement, 1.32 cu ft/ sx
 Intermediate plug covers t/ salt and shoe.
 Lower plug covers b/ salt and open hole.
 Producing Zone Plugs:
 Size CIBP, 100' Cemented with 15 sx.


WELL DATA SHEET

OPERATOR: Koch Exploration Co. Lease: Mary E Wills Fed A #9

FOOTAGE LOCATION: 1135 FSL X 20 FWL Sec./Twn/Rng: Unit D, Sec 35, T-26-S, R-37-E

Former Wood River O&R, plugged 8-27-81: collapsed casing. Lea County, New Mexico

SCHEMATIC



TABULAR DATA

Surface Casing: Set at 608'
Size 8-5/8", 24# Cemented with 300 sx.
TOC surface ' determined by circulation
Hole Size 11" ? Comp. Date 10-04-59
Intermediate casing: Set at _____
Size NONE Cemented with _____ sx.
TOC _____ ' determined by _____
Hole Size _____
Production Casing: Set at 3369'
Size 5-1/2", 14# Cemented with 150 sx.
TOC 2570' ' determined by calculation
Hole Size 7-7/8" ?, assumed 75% fill

Completion Interval:

3290' to 3342' : ? spf, 88 perforations
Drilled as water injection well; R-1352

Tops:

Salt 1215'-2891'
Tansil 2844'
Yates 2996'
Seven Rivers 3271'

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other **Water Inj. well**

2. NAME OF OPERATOR
Koch Exploration Co. Div. of Koch Ind., Inc.

3. ADDRESS OF OPERATOR
P.O. Box 2256, Wichita, Kansas 67201

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: **1135' FSL & 20' FWL**
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF ☐	☐
FRACTURE TREAT ☐	☐
SHOOT OR ACIDIZE ☐	☐
REPAIR WELL ☐	☐
PULL OR ALTER CASING ☐	☐
MULTIPLE COMPLETE ☐	☐
CHANGE ZONES ☐	☐
ABANDON ☒ Plug and abandon	☒
(other)	

5. LEASE
LC-050107(a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
N/A

7. UNIT AGREEMENT NAME
N/A

8. FARM OR LEASE NAME
Mary E. Wills "A"

9. WELL NO.

10. FIELD OR WILDCAT NAME
Rhodes

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 35-26S-37E

12. COUNTY OR PARISH
N/A Lea

13. STATE
New Mexico

14. API NO.
N/A


15. ELEVATIONS (SHOW DF, KDB, AND WD)
GR 2979.28

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8-24-81 Set 20 sxs @3290' tagged @3050'
8-25-81 Set 35 sxs @1730'
8-25-81 Set 50 sxs @1200' tagged @1088'
8-25-81 Set 50 sxs @650' tagged @510'
8-27-81 Set 5 sxs and dry hole marker

Plugs set thru tubing
Hole loaded with 10# mud laden fluid



OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED **Peter W. Chester** TITLE **Mayo Marts Casing Pulling Inc.** DATE **9-8-81**

APPROVED

(This space for Federal or State office use)

(Orig. S.L.) **PETER W. CHESTER**

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

MAR 8 1983

FOR


JAMES A. GILHAM
DISTRICT SUPERVISOR

*See Instructions on Reverse Side

WELL DATA SHEET

OPERATOR: Koch Exploration Co. Lease: Mary E Wills Fed A #10
 FOOTAGE LOCATION: 1135 FSL X 20 FWL Sec./Twn/Rng: Unit D, Sec 35, T-26-S, R-37-E
Former Wood River O&R, plugged 9-2-81 - collapsed casing. Lea County, New Mexico

SCHEMATIC



TABULAR DATA
Surface Casing: Set at 609'
 Size 8-5/8", 24# Cemented with 275 sx.
 TOC surface ' determined by circulation
 Hole Size 11" ? Comp. Date 4-08-60
Intermediate casing: Set at _____
 Size NONE Cemented with _____ sx.
 TOC _____ ' determined by _____
 Hole Size _____
Production Casing: Set at 3354'
 Size 5-1/2", 14# Cemented with 150 sx.
 TOC 2560' ' determined by calculation
 Hole Size 7-7/8" ?, assumed 75% fill

Completion Interval:

3260' to 3326' : ? spf, 104 perforations
Drilled as water injection well; R-1352

Tops:

Salt 1205'-2818'
 Tansil
 Yates 2974'
 Seven Rivers 3250'

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other Water Inj. Well
2. NAME OF OPERATOR
Koch Expl. Co., Div. of Koch Ind., Inc.
3. ADDRESS OF OPERATOR
P.O. Box 2256, Wichita, Kansas 67201
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 20' FNL & 20' SWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☒

(other) Plug & abandon

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☒


5. LEASE
LC-050107(a)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
N/A
7. UNIT AGREEMENT NAME
N/A
8. FARM OR LEASE NAME
Mary E. Wills "A" *Federal*
9. WELL NO.
10
10. FIELD OR WILDCAT NAME
Rhodes
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 35-26S-37E
12. COUNTY OR PARISH
Lea
13. STATE
New Mexico
14. API NO.
N/A
15. ELEVATIONS (SHOW DF, KDB, AND WD)
GR 2984'

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8-29-81 Set 20 sxs @3200' tagged @3020'
8-31-81 Set 35 sxs @1700'
8-31-81 Set 50 sxs @ 1200' tagged @1092'
9-1-81 Set 50 sxs @660' tagged @490'
9-2-81 Set 5 sxs and dry hole marker

All plugs set thry tubing
Hole loaded with 10# mud laden fluid

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Mayo Marrs TITLE Casing Pulling Inc. DATE 9-8-81

(This space for Federal or State office use)


APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

MERIDIAN OIL

STATE UTP NO. 1
RHODES (OIL) FIELD
LEA COUNTY, NEW MEXICO

PROPOSED CONDITION AFTER P&A



Submit 3 Copies
Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Box DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-25492
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. B-7606
7. Lease Name or Unit Agreement Name State "UTP"
8. Well No. 1
9. Pool name or Wildcat Rhodes (Yates, 7 Rivers)

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL ☒ GAS WELL ☐ OTHER ☐	
2. Name of Operator Meridian Oil Inc	
3. Address of Operator P.O. Box 51810, Midland, TX 79710-1810	
4. Well Location Unit Letter <u>G</u> : <u>1650</u> Feet From The <u>North</u> Line and <u>1650</u> Feet From The <u>East</u> Line Section <u>28</u> Township <u>26S</u> Range <u>37E</u> NMPM Lea County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 2966' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
PLUG AND ABANDON ☐	ALTERING CASING ☐
TEARFULLY ABANDON ☐	COMMENCE DRILLING OPNS. ☐
PULL OR ALTER CASING ☐	PLUG AND ABANDONMENT ☒
OTHER: ☐	CASING TEST AND CEMENT JOB ☐
	OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3/27/92 RIH to CIBP @ 3087'. MIRU Halliburton. Mix & circ well w/ 9# brine w/ salt gel., spot 25 sxs cmt plug @ 3087', 25 sxs @ 1440', 60 sxs @ 660' and 5 sxs @ surface (105 sxs premium plus w/ 2% caci). LD workstring. RDMOPU. Cut off wellhead & place p&a marker on well.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Roxann Scholz TITLE Production Asst DATE 04/06/92

TYPE OR PRINT NAME Roxann Scholz TELEPHONE NO. (915)688-

(This space for State Use)

APPROVED BY Charles P. ... TITLE OIL & GAS INSPECTOR DATE APR 28 '92

CONDITIONS OF APPROVAL, IF ANY:


WELL DATA SHEET

OPERATOR: Anderson-Pritchard Oil Corporation Lease: State 28 "A" #2

FOOTAGE LOCATION: 1980 FNL X 1980 FEL Sec./Twn/Rng: Unit G, Sec 28, T-26-S, R-37-E

Drilled and abandoned August, 1943. Lea County, New Mexico

SCHEMATIC



TABULAR DATA


Surface Casing: Set at 587'
 Size 8-5/8", 28# Cemented with 188 sx.
 TOC surface ' determined by calculation
 Hole Size 11" Comp. Date 8-11-43
Intermediate casing: Set at _____
 Size NONE Cemented with _____sx.
 TOC _____ ' determined by _____
 Hole Size Hole filled with 10-1/2# mud
Production Casing: Set at 3157'
 Size 5-1/2", 15# Cemented with 650 sx.
 TOC 2169 ' determined by free point
 Hole Size 7-7/8"

Open Hole Interval:

3157' to 3350' size: 4-3/4" ?
Nitro shot 70 qts L.N.G., 3247'-3284'.

Tops:

Salt 1285'-2840'
 Tansil 2840'
 Yates 2988'
 Seven Rivers 3285'

PLUG AND ABANDON DATAPO-113
(5/91)OPERATOR: Texaco Exploration & Production Inc. Lease: W.H. Rhodes B Fed NCT-1 #2FOOTAGE LOCATION: 2970 FNL X 2310 FEL Sec./Twn/Rng: Unit J, Sec 27, T-26-S, R-37-EFailed MIT on 4-25-91, 70 psig on casing. Isla County, New MexicoSCHEMATICSurface Plug:PLUGGING DATASize 100'-surf. Cemented with 12 sx.

Squeeze annulus with 110 sx to surface.

Class 'C' Cement, 1.32 cu ft/ sx

Intermediate Plug(s):Size 1284'-1105' Cemented with 24 sx.Class 'C' cement, 1.32 cu ft/ sx
Intermediate plug covers t/ salt and shoe.
Lower plug covers b/ salt and open hole.Producing Zone Plugs:Size CIBP, 100' Cemented with 15 sx.

BEFORE EXAMINER CATTANACH

OIL CONSERVATION DIVISION

TEXACO EXHIBIT NO. 9DATE NO. 10572 AND 10573