

Submit 1 Copy To Appropriate District Office
 District I - (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II - (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III - (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV - (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

EMNRD-OCD ARTESIA
 REC'D: 6/02/2020
 Form C-103
 Revised July 18, 2013

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

WELL API NO. 30-015-27970
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No. 18195
7. Lease Name or Unit Agreement Name Higgins Trust "1"
8. Well Number 1
9. OGRID Number 151416
10. Pool name or Wildcat Atoka; Penn

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well Other

2. Name of Operator
Fasken Oil and Ranch, Ltd.

3. Address of Operator
6101 Holiday Hill Road, Midland, TX 79707

4. Well Location
 Unit Letter D : 990 feet from the North line and 990 feet from the West line
 Section 1 Township 18S Range 26E NMPM County Eddy

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3287' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	P AND A <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPL <input type="checkbox"/>	CASING/CEMENT JOB <input type="checkbox"/>	
DOWNHOLE COMMINGLE <input type="checkbox"/>			
CLOSED-LOOP SYSTEM <input type="checkbox"/>			
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Fasken Oil and Ranch, Ltd. Plan to plug the above well. Attached is our current and proposed WBD and our procedure.

Notify OCD 24 hrs. prior to any work done

SEE CHANGES TO PROCEDURE

Spud Date:

Rig Release Date:

****SEE ATTACHED COA'S****

MUST BE PLUGGED BY 6/10/2021

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Attn Guelker TITLE Regulatory Analyst DATE 3/31/20

Type or print name Addison Guelker E-mail address: addisong@forl.com PHONE: 432-687-1777
For State Use Only

APPROVED BY: Gilbert Cordero TITLE Staff Manager DATE 6/10/2020
 Conditions of Approval (if any):

**Higgins Trust "1" No. 1
990' FNL & 990' FWL
Sec 1, T18S R26E**

OBJECTIVE:	Plug and Abandon
WELL DATA:	
API Number:	30-015-27970
30" conductor:	Set at 78' w 300 sx "C", Circ 50 sx, TOC surf.
20" 133#/ft J55 conductor:	St at 111.5' w/275sx "C", Circ 127 sx, TOC surf.
13-3/8" 54.5# J55 Surface casing:	Set at 1359.80' KB w/800 sx Howco Lite (12.6ppg+2.00Cuft/sk) + 200sx "C" w/2% CaCl2 (14.8ppg+1.32Cuft/sk). Circ 120 sx, TOC surf.
8-5/8" 24#/ft J-55 Interm casing:	Set at 1914.82' KB, Cmt w/450sx "C" w/2% CaCl2 (14.8ppg+1.32Cuft/sk). TOC 620' by Temp survey.
4-1/2" 11.6# N80, K55 casing:	Set at 9070.86' Cmt w/800 sx HLH (12.7ppg, 1.84cuft/ft)+400sx "H" 50/50 Poz (12.7ppg, 1.84cuft/ft). TOC 4800' by temp survey. K55 543.16'-7518.04' (jts 26-195). Marker Jt: 8,853.81'-8,860.55' (6.74')
Perfs:	Morrow 8,882'-90' (17 holes), 9-2-1994
Tubing (9-2-94 orig compl):	2-3/8" EUE 8RD SN w/cplg on btm (1.10'), 1-jt 2-3/8" EUE 8rd N-80 tubing (31.45'), 2-3/8" EUE 8rd perf sub (3.96'), 4.5"x2-3/8" Arrowset I 10k pkr w/1.81" "F" profile/TOSSD (7.83'), 278jts 2-3/8" EUE 8rd N-80 tbg (8714.20'. EOT 8,767.54' KB
TD:	9,075'
PBTD:	9,030' (FC)
Top of PKR:	8,723.20' KB

1. Test mast anchors.
2. RUPU.
3. Set pipe racks. Receive 6 jts 2-3/8" EUE 8rd 4.7#/ft N-80 workstring tubing. Set flowback tank.
4. RU pump truck and kill well w/ 30 bbls fresh water.
5. NDWH. NU BOP.
6. Release Watson Arrowset I 10k packer at 8,723.20' KB and POW with 278 joints 2-3/8" EUE 8rd 4.7#/ft N-80 tubing (8714.20'), 1-4-1/2" x 2-3/8" Watson Arrowset I pkr w/TOSSD w/1.81" F" PN (7.83'), 1-2-3.8" x 4' perf sub (3.96'), 1jt 2-3/8" EUE 8rd N-80 tbg (31.45'), 2-3/8"x1-25/32" SN w/cplg (1.10').
7. RIW testing tubing to 6000 psi above slips with 4-1/2" 11.6# CIBP with setting tool, 2-3/8" drain nipple, 4' perforated sub, 2-3/8 EUE 8rd 4.7#/ft N-80 tubing, and set CIBP at +/-8,832' (minimum 50' above top perforation at 8,882').
8. **Plug #1:** RU cement pump and spot 25 sx class "H" cement (1.17 cuft/sk yield) above CIBP 8,832 for a PBTD of 8496'. Displace cement with fresh water. POW 10 stands and WOC 4 hours and tag plug at +/-8,496'.
9. RU pump truck and displace well from +/-8,496' with 75 bbls 9.5 ppg gel laden mud.
10. POW laying down +/-2,300' of /2-3/8" EUE 8rd 4.7#/ft N-80 tubing to +/-6,200'.
11. **Plug #2:** RU cement pump and spot 25 sx class "C" cement (1.32 cuft/sk yield) at **6,200'** for a PBTD of 5,820'. Displace cement with 9.5 ppg gel laden mud. POW 10 stands and WOC 4 hours and tag plug at +/-5,820'.

Must tag at 5774' - 50' above top of Wolfcamp

12. POW w/2-3/8" EUE 8rd 4.7#/ft N-80 tubing, PS, drain nipple, and setting tool, laying down +/- 1,500' of tubing.
13. RIW with 4-1/2" AD-1 tension packer, SN, 2-3/8" EUE 8rd N80 tubing and set packer at +/-4,300'.
14. RUWL and 3000 psi lubricator. RIW with 1-11/16" strip gun and perforate 4 squeeze holes at 4,700'. RDWL.
15. **Plug #3:** Open 4-1/2" x 8-5/8" casing to flowback tank. Squeeze perfs at 4,700' with 45 sx Class "C" cement, displacing cement with 9.5 ppg gel laden mud to 4,553' or above. WOC 4 hours. Release packer RIW with tubing and TAG cement plug @ or above 4,553' and notify Midland Office and BLM of the results.
OCD 4500' - T of Abo
16. Release AD-1 packer and POW laying down +/-3,000' tubing. Set 4-1/2" AD-1 packer at +/-1,700'.
Spot 25 sx cmt @ 2860 - WOC and Tag at 2480' - T of Glorieta
17. RUWL and 3000 psi lubricator. RIW with 1-11/16" strip gun and perforate 4 squeeze holes at 1,965'. RDWL.
18. **Plug #4:** (8-5/8" shoe plug): Open 4-1/2" x 8-5/8" casing to pit. Squeeze perfs at 1,965' with 30 sx Class "C" cement, displacing cement with 9.5 ppg gel laden mud to 1,845' or above. WOC 4 hours. Release packer RIW with tubing and TAG cement plug @ or above 1,845' and notify Midland Office and BLM of the results.
19. Release AD-1 packer and POW laying down +/-900' tubing. Set 4-1/2" AD-1 packer at +/-1,100'.
20. RUWL and 3000 psi lubricator. RIW with 1-11/16" strip gun and perforate 4 squeeze holes at 1,401'. RDWL.
21. **Plug #5:** Open 4-1/2" x 8-5/8" casing to pit. Squeeze perfs at 1,401' with 40 sx Class "C" cement, displacing cement with 9.5 ppg gel laden mud to 1,208' or above. WOC 4 hours. Release packer RIW with tubing and TAG cement plug @ or above 1,208' and notify Midland Office and BLM of the results.
22. Release AD-1 packer and POW laying down +/-500' tubing. Set 4-1/2" AD-1 packer at +/-200'.
23. RUWL and 3000 psi lubricator. RIW with 1-11/16" strip gun and perforate 4 squeeze holes at 450'. RDWL.
24. **Plug #6:** Open 4-1/2" x 8-5/8" casing to pit. Squeeze perfs at 450' with 34 sx Class "C" cement, displacing cement with 9.5 ppg gel laden mud to 340' or above. WOC 4 hours. Release packer RIW with tubing and TAG cement plug @ or above 340' and notify Midland Office and BLM of the results.
25. POW laying down remainder of tubing. Set 4-1/2" AD-1 packer at 10'.
26. RUWL and 3000 psi lubricator. RIW with 1-11/16" strip gun and perforate 4 squeeze holes at 160'. RDWL.
27. **Plug #7** (20" shoe plug): Open 4-1/2" x 8-5/8" casing to pit. Squeeze perfs at 160' with 40 sx Class "C" cement, displacing cement with 9.5 ppg gel laden mud to surface.
28. Dig out wellheads and cut-off below "A" section.
29. ~~Weld plate onto casing with~~ marker joint with the following information:

INFORMATION MUST BE WELDED ONTO THE DHM - CANNOT USE PLATE - SEE ATTACHED COA'S

Fasken Oil & Ranch Ltd.,
 Higgins Trust "1" #1
 Unit D, Section 1, T18S, R26E, 990' FNL and 990' FWL.

VALVE NOT REQUIRED

3

Install 1" 2000 psi valve welded into top of marker joint. Remove valve handle and close valve.

30. Send wellheads to Downing Wellhead in Midland. Clean location, RDPUs and release all rental equipment.

Higgins Trust "1" No. 1

Current as of 9-2-94

Operator: **Fasken Oil and Ranch, Ltd.** *Tops*
 Location: 990' FNL and 990' FWL
 Sec 1, T18S, R26E
 Eddy County, NM
 Compl.: 8-31-94 released rig
 API #: 30-015-27970 *San Andres 1080'*
 TD: 9075'
 PBTD: 9030' (FC)

Casing: **30" Conductor @ 78' w/300sx "C"**, TOC surf.
20" 133# J55 csg @ 111.47' KB w/275 sx "C" TOC surf.
13-3/8" 54.5# J55 @ 1350.80' KB
 w/800 sx Howco Lite (12.6ppg+2.00Cuft/sk) +
 200sx "C" w/2% CaCl2 (14.8ppg+1.32Cuft/sk)
 TOC surf, circ 120sx
8-5/8" 24# J-55 @ 1914.82' KB *Glorieta 2538'*
 w/450sx "C" w/2% CaCl2 (14.8ppg+1.32Cuft/sk)
 TOC 620' by Temp Survey *Yeso*
4-1/2" 11.6# N80, K55 LT&C @ 9070.86' KB
 Marker Jt: 8,853.81'-8,860.55' (6.74') *Tubb 3875'*
 w/800 sx HLH (12.7ppg, 1.84cuft/ft)+400sx "H" 50/50
 Poz (12.7ppg, 1.84cuft/ft) TOC 4800' by Temp

Tubing: *Abo 4559'*

9/2/1994 2-3/8" EUE 8RD SN w/cplg on btm	1.10
1-jt 2-3/8" EUE 8rd N-80 tubing	31.45
2-3/8" EUE 8rd perf sub	3.96
4.5"x2-3/8" Arrowset I 10k pkr	7.83
w/1.81" "F" profile/TOSSD <i>Wolfcamp 5824'</i>	<u>8714.20</u>
278 jts 2-3/8" EUE 8rd N-80 tubing-	8758.54
Below KB	13.00
Less compression	-4.00
Total EOT	8767.54

Strawn 8100'


Atok 8540'

Perfs: Morrow
 9/2/1994 8,882'-90' (2SPF w/1-11/16" strip gun)

Morrow 8753'

Miss 9048'


Hole Sizes 36" 0'-80', 26" 80-114', 17-1/2" 114'-1349',
 12-1/4" 1349'-2010', 7-7/8" 2010'-9075'



Higgins Trust "1" No. 1

Proposed P&A 3-25-20

Operator: **Fasken Oil and Ranch, Ltd.** *Tops*
 Location: 990' FNL and 990' FWL
 Sec 1, T18S, R26E
 Eddy County, NM
 Compl.: 8-31-94 released rig
 API #: 30-015-27970
 TD: 9075' *San Andres 1080'*
 PBTD: 9030' (FC)
 Casing: **30" Conductor @ 78'** w/300sx "C", TOC surf
20" 133# J55 csg @ 111.47' KB w/275 sx "C" TOC surf
13-3/8" 54.5# J55 @ 1350.80' KB
 w/800 sx Howco Lite (12.6ppg+2.00Cuft/sk) +
 200sx "C" w/2% CaCl2 (14.8ppg+1.32Cuft/sk)
 TOC surf, circ 120sx
8-5/8" 24# J-55 @ 1914.82' KB
 w/450sx "C" w/2% CaCl2 (14.8ppg+1.32Cuft/sk)
 TOC 620' by Temp Survey *Glorieta 2538'*
4-1/2" 11.6# N80, K55 LT&C @ 9070.86' KB
 Marker Jt. 8,853.81'-8,860.55' (6.74') *Tubb 3875'*
 w/800 sx HLH (12.7ppg, 1.84cuft/ft)+400sx "H" 50/50
 Poz (12.7ppg, 1.84cuft/ft) TOC 4800' by Temp
Abo 4559'



Proposed P&A - 3-25-2020 *Wolfcamp 5824'*
 40sx"C" 0'-160' Plg #7 Surface
 34sx"C" 340'-450', Tag Plg #6, Perf & Sqz, TAG
 40sx"C" 1208'-1401', Tz Plg #5, Perf & Sqz, TAG
 30sx"C" 1845'-1965', Tz Plg #4, Perf & Sqz, TAG
 45sx"C" 4553'-4700', Tz Plg #3, Perf & Sqz, Tag
 25sx"C" 5820'-6200', Tz Plg #2, tag
 25sx "H" 8496'-8832', Tz Plg #1, Tag
 CIBP: 8,832'

Perfs: Morrow *Atok 8540'*
 9/2/1994 8,882'-90' (2SPF w/1-11/16" strip gun)

Morrow 8753'
Miss. 9048'

Hole Sizes 36" 0'-80', 26" 80-114', 17-1/2" 114'-1349',
 12-1/4" 1349'-2010', 7-7/8" 2010'-9075'

GL 3286.9" KB 3301.9'
 30" csg @ 78' w/300 sx "C" TOC surf
Plg7 40sx "C" 0'-160', Tag
 20" 133# K55 csg @ 111.5" w/275 sx "C" TOC surf
Plg6 34sx "C" 340'-450', Tag
Plg5 40sx "C" 1208'-1401', Tag
 13-3/8" 54.5# J55 @ 1350.80' KB
 TOC surf, circ 120sx
Pl4 30sx "C" 1845'-1965', Tag
 8-5/8" 24# J-55 @ 1914.82' KB
 TOC 620' by Temp Survey
Plg3 45sx "C" 4553'-4700', Tag
 TOC 4800' by Temp
 4-1/2" K55 543.16'-7518.04'
Plg2 25sx "C" 5820'-6200', Tag
Plg1 25sx "H" 8496'-8832', Tag
CIBP 8,832'
 Marker Jt. 8,853.81'-8,860.55' (6.74')
 8,882'-90'
 PBTD 9030' (FC)
 TD 9075'
 4-1/2" 11.6# N80, K55 LT&C @ 9070.86' KB
 TOC 4800' by Temp

CONDITIONS FOR PLUGGING AND ABANDONMENT

OCD - Southern District

The following is a guide or checklist in preparation of a plugging program, this is not all inclusive and care must be exercised in establishing special plugging programs in unique and unusual cases, **Notify NMOCD District Office II at (575)-748-1283 at least 24 hours before beginning work. After MIRU rig will remain on well until it is plugged to surface. OCD is to be notified before rig down. Company representative will be on location during plugging procedures.**

1. A notice of intent to plug and abandon a wellbore is required to be approved before plugging operations are conducted. A cement evaluation tool is required in order to ensure isolation of producing formations, protection of water and correlative rights. A cement bond log or other accepted cement evaluation tool is to be provided to the division for evaluation if one has not been previously run or if the well did not have cement circulated to surface during the original casing cementing job or subsequent cementing jobs. Insure all bradenheads have been exposed, identified and valves are operational prior to rig up.
2. Closed loop system is to be used for entire plugging operation. Upon completion, contents of steel pits are to be hauled to a permitted disposal location.
3. Trucking companies being used to haul oilfield waste fluids to a disposal – commercial or private – shall have an approved NMOCD C-133 permit. A copy of this permit shall be available in each truck used to haul waste products. It is the responsibility of the operator as well as the contractor, to verify that this permit is in place prior to performing work. Drivers shall be able to produce a copy upon request of an NMOCD Field inspector.
4. Filing a subsequent C-103 will serve as notification that the well has been plugged.
5. A final C-103 shall be filed (and a site inspection by NMOCD Inspector to determine if the location is satisfactorily cleaned, all equipment, electric poles and trash has been removed to Meet NMOCD standards) before bonding can be released.
6. If work has not begun within 1 Year of the approval of this procedure, an extension request must be file stating the reason the well has not been plugged.
7. Squeeze pressures are not to exceed 500 psi, unless approval is given by NMOCD.
8. Produced water **will not** be used during any part of the plugging operation.
9. Mud laden fluids must be placed between all cement plugs mixed at 25 sacks per 100 bbls of water.
10. All cement plugs will be a minimum of 100' in length or a minimum of 25 sacks of cement, whichever is greater. 50' of calculated cement excess required for inside casing plugs and 100% calculated cement excess required on outside casing plugs.
11. Class 'C' cement will be used above 7500 feet.
12. Class 'H' cement will be used below 7500 feet.
13. A cement plug is required to be set 50' above and 50' below, casing stubs, DV tools, attempted casing cut offs, cement tops outside casing, salt sections and anywhere the casing is perforated, these plugs require a 4 hour WOC and then will be tagged
14. All Casing Shoes Will Be Perforated 50' below shoe depth and Attempted to be Squeezed, cement needs to be 50' above and 50' Below Casing Shoe inside the Production Casing.

16. When setting the top out cement plug in production, intermediate and surface casing, wellbores should remain full at least 30 minutes after plugs are set
17. A CIBP is to be set within 100' of production perforations, capped with 100' of cement, WOC 4 hours and tag.
18. A CIBP with 35' of cement may be used in lieu of the 100' plug if set with a bailer. This plug will be placed within 100' of the top perforation, (WOC 4 hrs and tag).
19. No more than 3000' is allowed between cement plugs in cased hole and 2000' in open hole.
20. Some of the Formations to be isolated with cement plugs are: These plugs to be set to isolate formation tops
 - A) Fusselman
 - B) Devonian
 - C) Morrow
 - D) Wolfcamp
 - E) Bone Springs
 - F) Delaware
 - G) Any salt sections
 - H) Abo
 - I) Glorieta
 - J) Yates.
 - K) **Potash---** (In the R-111-P Area (Potash Mine Area), a solid cement plug must be set across the salt section. Fluid used to mix the cement shall be saturated with the salts that are common to the section penetrated and in suitable proportions, not more than 3% calcium chloride (by weight of cement) will be considered the desired mixture whenever possible, WOC 4 hours and tag, this plug will be 50' below the bottom and 50' above the top of the Formation.
21. If cement does not exist behind casing strings at recommended formation depths, the casing can be cut and pulled with plugs set at recommended depths. If casing is not pulled, perforations will be shot and cement squeezed behind casing, WOC and tagged. These plugs will be set 50' below formation bottom to 50' above formation top inside the casing

DRY HOLE MARKER REQUIREMENTS

The operator shall mark the exact location of the plugged and abandoned well with a steel marker not less than four inches in diameter, 3' below ground level with a plate of at least ¼" welded to the top of the casing and the dry hole marker welded on the plate with the following information welded on the dry hole marker:

1. Operator name 2. Lease and Well Number 3. API Number 4. Unit Letter 5. Quarter Section (feet from the North, South, East or West) 6. Section, Township and Range 7. Plugging Date 8. County (SPECIAL CASES)-----AGRICULTURE OR PRARIE CHICKEN BREEDING AREAS

In these areas, a below ground marker is required with all pertinent information mentioned above on a plate, set 3' below ground level, a picture of the plate will be supplied to NMOCD for record, the exact location of the marker (longitude and latitude by GPS) will be provided to NMOCD (We typically require a current survey to verify the GPS)

SITE REMEDIATION DUE WITHIN ONE YEAR OF WELL PLUGGING COMPLETION