

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-70

NO. OF COPIES RETURNED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.P.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State For

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL GAS WELL CO2 OTHER

2. Name of Operator
Amoco Production Company

3. Address of Operator
P. O. Box 68 Hobbs, NM 88240

4. Location of Well
UNIT LETTER J 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 10 TOWNSHIP 20-N RANGE 34-E RMPM.

5. Elevation (Show whether DF, RT, GR, etc.)
4810' GL

6. 12. County
Union

7. Unit Agreement Name

8. Farm or Lease Name
Kerr

9. Well No.
1

10. Field and Pool, or WHdect
Und. Tubb

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

11. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On 3-1-81 Moran Brothers (Rig #52) spudded a 12-1/4" hole at 12:01 p.m. Drilled to a TD of 710' and ran 5-1/2" casing set at 710'. Cemented with 500 SX Class H cement. Plugged down 5:00 p.m. 3-2-81. Circulated 272 SX. WOC 18 hrs. Tested casing with 800# for 30 min. Reduced hole to 7-7/8" and resumed drilling. Drilled to a TD of 1772' and spotted 200 SX Class H cement. Drilled to a TD of 2298' and stuck drill pipe. Backed off at 1160'. Ran wash pipe to 1256'. Stuck wash pipe. Top of wash pipe 1106'. Propose to P X A. Plugged and abandoned per the following: Spotted 250 SX Class H cement 1106'-600'. WOC 4 hrs. Tagged cement at 710'. Spot 35 SX Class H cement 710'-391'. Spot 20 SX surface plug. Propose to skid rig 100' west and spud Kerr #1X.

0+2-NMOCD, SF 1-Hou 1-Susp 1-BD

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Bob Davis TITLE Admin. Analyst DATE 4-2-81

APPROVED BY Carl Whrog TITLE SENIOR PETROLEUM GEOLOGIST DATE 4/6/81

CONDITIONS OF APPROVAL, IF ANY